

KVM Quick Specifications



THE POSSIBILITIES ARE INFINITE

Description			Mechanical				Power			Users		Targets	Virtual Media	Network 10/100/1000	USB (Local)	PS/2 (Local)	Video Max Resolution	Tiering		Max (Supported) Servers/Devices	Security	
Part No.	Model	Technology	H (mm)	W (mm)	D (mm)	W (kg)	Volts (VAC)	Freq (Hz)	Input (W)	Local	Remote							Port	Levels		Local	LDAP
S26361-F2293-E621/L621	s3-1621	Digital	43.7	431.8	279.8	3.3	100-240	50-60 Auto	40 max	1	2	16	Y	1	4*	Y	1280 x 1024 @ 75	0	2	256**	64	Y
S26361-F2293-E411/L411	s2-0411	Digital	43.7	431.8	203.2	2.6	100-240	50-60 Auto	40 max	1	1	4	Y	1	-	Y	1280 x 1024 @ 75	0	2	64**	64	Y
S26361-F2293-E602/L602	s2-1602	Analog	43.7	431.8	165.1	3.6	100-240	50-60 Auto	40 max	2	-	16	N	-	-	Y	1280 x 1024 @ 75	1	2	256**	64	N
S26361-F2293-E801/L801	s2-0801	Analog	43.7	431.8	203.2	2.6	100-240	50-60 Auto	40 max	1	-	8	N	-	-	Y	1280 x 1024 @ 75	1	2	128**	64	N

Video Resolution (See also Adapter Module Notes)

640 x 480 @ 60 Hz (Local Port and Remote Port Minimum)
 800 x 600 @ 75 Hz
 960 x 700 @ 75 Hz
 1024 x 768 @ 75 Hz
 1280 x 1024 @ 75 Hz (Remote Port Maximum using a KVM-IA)

Ambient Atmospheric Condition Ratings

Temperature 0° to 50° Celsius (32° to 122° Fahrenheit) operating
 -20° to 60° Celsius (-4° to 140° Fahrenheit) non operating
 Humidity 20 to 80% non condensing operating
 5 to 95% non condensing non operating

Safety and EMC Approvals and Markings

s3-1621 & s2-0411
 UL, FCC, cUL, ICES, CE, N, GS, IRAM, GOST, VCCI, MIC, C-Tick
 s2-1602 & s2-0801
 EN55022 Class A, EN55024, EN61000-3-3, FCC15 Class A, VCCI Class A, IEC950
 EN60950, UL 1950/60950 third edition, CSA C22.2 No. 60950

Series3 - Adapter Module

Part No.	Model	Description
S26361-F2293-E203/L203	USB2	KVM-IA s3 Adapter USB2-VGA Virtual Media

Series2 - Adapter Module

Part No.	Model	Description
D:GPRAC-AN30	SUN	s2 Interface Adapter (SUN)
S26361-F2293-E202/L202	USB	s2 Interface Adapter (USB 1.0)
S26361-F2293-E201/L201	PS/2	s2 Interface Adapter

Adapter Module Notes

Maximum Cable Length	1280 x 1024 @ 85 Hz	1024 x 768 @ 85 Hz	800 x 600 @ 85 Hz
3 meters (9.8 feet)	Supported	Supported	Supported
15 meters (49 feet)	Supported	Supported	Supported
30 meters (98.5 feet)	-	-	Supported

PRODUCT VIEWS

s3-1621



s3 USB2



s2-0411



SUN



s2-1602



PS/2



s2-0801



S2 USB 1.0



CONTACT

<http://fujitsu.avocent.com>

KVM over IP...being there without going there.