

Data Sheet

Fujitsu CELSIUS H770 Workstations

Mobile Workstation Meets Security

If you are looking for workstation power on-the-go packed in a 39.6 cm (15.6-inch) stylish form factor, then the FUJITSU CELSIUS H770 mobile workstation is the right choice. Its port replicator is compatible with seven LIFEBOOK devices and thus ideal for a shared desk environment. Maximum data security is guaranteed by the unique PalmSecure™ technology.

Mobile Workstation Meets Security

When true workstation performance meets the elegant style of a laptop

- Choose between Intel® Core™ processors or powerful Intel® Xeon processor® E3-1500M family supporting ECC memory
- Support of Windows 10 Pro
- UHD/4k and Full HD LED anti-glare displays
- Up to 64 GB DDR4 2400 MHz memory (ECC optional)
- M.2 SSDs PCIe NVMe technology supports quick loading of core applications

Full connectivity and worry-free docking experience

No compromise in terms of port connectivities, regardless of whether you are away, in a meeting or at your desk

- USB Type-C™ connector offering more speed (40 Gbps), more protocols (including Thunderbolt 3) and charging capabilities (power delivery of 15W)
- Full monitor connectivity support: 1x VGA and 1x DisplayPort (full size)
- 1 port replicator shared across 8 mobile devices: Notebooks, Ultrabook™, 2 in 1 and mobile workstations

Maximum Security

Data security and peace of mind

- Optional PalmSecure™, a leading-edge highly secure authentication system using biometric technology that authenticates users through vein pattern recognition
- Optional fingerprint sensor
- Integrated SmartCard reader
- TPM 2.0 and Advanced Theft Protection



Components

Base unit	CELSIUS H770
Operating system preinstalled	
Operating system pre-installed	Windows 10 Pro
Operating system compatible	Windows 10 Pro
Operating system notes	Certified for SUSE Enterprise Desktop
	Intel® Xeon® processor E3-1535M v6 (3.1 GHz, up to 4.2 GHz, 8 MB, Intel® HD Graphics P630)
	Intel® Xeon® processor E3-1505M v6 (3.0 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics P630)
	Intel® Core™ i7-7920HQ processor (3.1 GHz, up to 4.1 GHz, 8 GB, Intel® HD Graphics 630)
	Intel® Core™ i7-7820HQ processor (2.9 GHz, up to 3.9 GHz, 8 GB, Intel® HD Graphics 630)
	Intel® Core™ i7-7700HQ processor (2.8 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630)
Memory modules	8 GB (2 module(s) 4 GB) DDR4, 2,400 MT/s, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, 2,400 MT/s, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, ECC, 2,400 MT/s, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, 2,400 MT/s, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, ECC, 2,400 MT/s, SO DIMM
Hard disk drives (internal)	SSD SATA III, 1024 GB, 2.5-inch, SED
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	SSD SATA III, 5,400 rpm, 1000 GB
	SSD SATA III, 5,400 rpm, 500 GB
	PCIe-SSD, 512 GB, M.2 module, SED
Hard disk drives (internal)	PCIe-SSD, 256 GB, M.2 module, SED
	SSD SATA, 1024 GB, M.2 module, SED
Hard disk drives (internal)	SSD SATA, 512 GB, M.2 module, SED
	SSD SATA, 256 GB, M.2 module, SED
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software.
Modular bay options	2nd battery
	Blu-ray Disc™ Triple Writer
	DVD Super Multi
	Weight saver
Interface add on cards/components (optional)	
	Sierra Wireless AirPrime® EM7305 LTE/HSPA+ (LTE/UMTS module)
WLAN (optional)	Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2
	Import and usage according to country-specific regulations.
	2 Dual Band WLAN antennas, 2 UMTS antennas
Display	39.6 cm (15.6-inch),LED backlit,(UHD/4K),Anti-glare IPS display,magnesium,3,840 x 2,160 pixel,min. 700:1,typ. 300 cd/m ² , 85/85/85
	39.6 cm (15.6-inch),LED backlit,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,min. 700:1,typ. 300 cd/m ² , 85/85/85
	39.6 cm (15.6-inch),LED backlit,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel
Camera	Optional: Built-in webcam, 2.0 megapixel
Microphone	2x digital (optional)

Base unit

Base unit	CELSIUS H770
Mainboard	
Chipset	Intel® QM175 or CM238 (depending on CPU)
Supported capacity RAM (min.)	8 GB
Supported capacity RAM (max.)	64 GB
Memory slots	4 SO DIMM (DDR4, 2133 MHz)
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS features	InsydeH20 Bios
Audio type	On board
Audio codec	Realtek ALC255 with MaxxAudio
Audio features	Stereo speakers, 2 digital microphones
MIL-STD tested	Yes, selected MIL-STD-810G tests passed. MIL-STD-810G test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.

Display	
Display notes	ISO 9241-307 - Pixel class II - anti-glare level UHD - Viewing angle: Left/Right/Top/Bottom 80°min.; Color Gammut: 72%; Brightness: 300cd/m ² ; Contrast Ratio: 700 typ. FHD premium - Viewing angle: Left/Right/Top/Bottom 80°min.; Color Gammut: 72%; Brightness: 300cd/m ² ; Contrast Ratio: 700 typ. FHD - Viewing angle: Left/Right/Top/Bottom 80°min.; Color Gammut: 45%; Brightness: 250cd/m ² ; Contrast Ratio: 700 typ.

Graphics	
Base unit	CELSIUS H770
Graphics brand name	NVIDIA® Quadro® M2200, NVIDIA® Quadro® M1200, NVIDIA® Quadro® M620
Graphics features	NVIDIA® Quadro® M2200: 4GB (1024 CUDA Cores) NVIDIA® Quadro® M1200: 4GB (640 CUDA Cores) NVIDIA® Quadro® M620: 2GB (512 CUDA Cores)

S26391-K463-V100 CELSIUS H770

DC-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Internal microphones	2 digital array microphones
USB 2.0 total	1
USB 3.1 Gen1 (USB 3.0) total	2
USB Type-C	1 (USB 3.1 Gen2 (10 Gbps), Thunderbolt 3 (20/40Gbps), Power Delivery (15W), DP 1.2)
VGA	1
DisplayPort	1
Ethernet (RJ-45)	1
SmartCard slot	1
SIM card slot	1
Multicardreader	1 (SD/SDHC) SD/microSD = 2GB, SDHC/micro SDHC = 32GB, SDXC = 64GB
Interface Module notes	1x Kensington Lock support, 1x Docking connector

Port Replicator interfaces (optional)	
DC-in	1 (19V)
Power on switch	1
Audio: headphone	1
Audio: microphone	1

Port Replicator interfaces (optional)

USB 3.1 Gen1 (USB 3.0) total	4
DisplayPort	2 - 1 DP (next to DVI) is shared with DVI, works when DVI not connected
VGA	1
DVI	1 - shared with DP (next to DVI) - works when DP (next to DVI) not connected
Kensington Lock support	1 (Portrep & System)
eSATA	1
Notes	Port replicator supports 0-Watts functionality

Keyboard

Touchpad with three mouse buttons

Input devices (optional)

TouchStick

Fast IDE/Ultra DMA-100

SATA RAID support 0,1

AC Adapter

AC adapter	19 V / 150 W (7.89 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
Runtime 1st battery	up to 11 hours
Runtime 1st + 2nd battery	up to 14 hours

Dimension with stand (W x D x H)

Dimensions (W x D x H) 380.0 x 257.0 x 24.8-31.9 mm w/o bump / with rubber feet 35.0 mm
14.96 x 10.12 x 0.98-1.26 inch w/o bump / with rubber feet 1.38 inch

Weight	2.75 kg
Weight (lbs)	6.1 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 80 % (relative humidity, non-condensing)

Product	CELSIUS H770
Europe	CE Marking
USA/Canada	cULus FCC Class B part 15C/E + 22 + 24 (depending on wireless configuration)
Global	RoHS (EU & China) Medical EMC standard IEC60601-1-2 in combination with medical kit ENERGY STAR® 6.1 (dedicated regions)

Compliance link <https://sp.ts.fujitsu.com/sites/certificates>**Additional Software**

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Fujitsu Display Manager EasyGuide online user documentation Power Saving Utility ShockSensor Utility SmartAccess Fujitsu Plugfree Network (network management utility) Intel® SBA (manageability suite for local administration) DTS® Sound Enhance Software Fujitsu Application Button Utility Fujitsu DeskUpdate (driver and utility tool) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
------------------------------------	---


Additional software (optional) Drivers & Utilities DVD (DUDVD)
LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS)


Manageability


Security	
Physical Security	Kensington Lock support
System and BIOS Security	Advanced Theft Protection Computrace® enabled BIOS EraseDisk (optional) Write protect option for the Flash EPROM Trusted Platform Module (TPM 2.0)
User Security	Embedded fingerprint sensor (optional) Embedded PalmSecure™ sensor (optional) Separate SmartCard slot Hard disk password User and supervisor BIOS password Preboot Authentication with SystemLock 3


Warranty	
Warranty period	3 years (depending on country)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life

Recommended Accessories

Port Replicator for LIFEBOOK T7, E5, E7 Series and CELSIUS H730, H760		Flexibility, expandability, desktop replacement, investment protection – to name just a few benefits of Fujitsu docking options.	Order Code: S26391-F1337-L109
--	---	--	----------------------------------

Port Replicator for LIFEBOOK T7, E5, E7 Series and CELSIUS H730, H760		Flexibility, expandability, desktop replacement, investment protection – to name just a few benefits of Fujitsu docking options.	Order Code: S26391-F1337-L110
--	---	--	----------------------------------

Prestige Trolley 17		The FUJITSU Prestige Trolley 17 protects and transports notebooks with up to 17 inch screens, along with clothes and toiletries. It is the perfect companion in a city environment or for overnight stays with four spacious compartments. Smooth running wheels and a telescopic handle ensure convenience, while the central section protects your notebook with shock-absorbing foam.	Order Code: S26391-F1194-L130
----------------------------	---	--	----------------------------------

Display P27-8 TS Pro		If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P27-8 TS Pro Display is the perfect choice. The display provides outstanding picture performance thanks to cutting-edge panel technology and 3.7 Mio pixels. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and USB support during standby.	Order Code: S26361-K1594-V160
-----------------------------	---	---	----------------------------------

Display B34-9 UE



The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1642-V140

Blue LED Mouse GL9000



Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:
S26381-K438-L100

SpaceMouse™ Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

More information

In addition to Fujitsu CELSIUS H770, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS H770, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com>

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: [www.fujitsu.com/\[country\]](http://www.fujitsu.com/[country])
2019-12-04 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions