

Fujitsu recommends Windows 11 Pro.

# Data Sheet

## FUJITSU Workstation CELSIUS J5010

### Space-saving design that packs a workstation-sized punch

No need to choose between size and performance in a Small Form Factor (SFF). FUJITSU CELSIUS J5010 offers high-end performance in a compact 8.3 liter design. Ideally suited for 2D and 3D CAD, this small yet powerful computer is a great match for space-constrained workplaces that need workstation-class performance and reliability.



#### Breakthrough performance

Power through demanding workflows with unparalleled ease

- 10th generation Intel® Core™ and Intel® Xeon® W-1200 processors
- Support of Windows 11 Pro
- Up to 128 GB DDR4 2,933 MHz memory (incl. ECC)
- Full-height graphics cards
- Support of 24/7 operation with reliable high-endurance and business critical drives

#### Space-saving design – taking the small form factor to next level

No compromise between performance, design and space

- Compact housing (8.3 liter) which is 17% smaller than the previous generation system
- Extremely quiet workstation with NVIDIA® Quadro® P2200 graphics card

#### Whisper-quiet design

Pleasant working environment that helps you focus on what matters most

- Innovative thermal design for optimized thermal management and cooling
- Lowest-noise emission in its category – helps you realize a silent workplace and enhanced productivity

#### Ultimate usability

Easy access, upgrade and use of the system

- Tool-less access to components, easy change and screw-less add on cards
- High reliability – built for 24/7 operations
- Software compatibility – ISV certifications for leading software applications

#### Applicable in a wide range of usage scenarios

Ideal for CAD, design, multimedia, visualization and manufacturing; great choice for multi-monitoring in control rooms, surveillance and trading floors with limited space

- Supports graphics-accelerated applications
- Advanced CPUs in combination with flash storage for best application performance
- Up to 8 monitors with the NVIDIA® Mosaic™ technology



# Components

|                                    |   |
|------------------------------------|---|
| <b>Processor</b>                   | Intel® Xeon® processor W-1290 (10 Cores / 20 Threads, 3.20 GHz, up to 5.1 GHz, Intel® UHD Graphics P630)  |
|                                    | Intel® Xeon® processor W-1270 (8 Cores / 16 Threads, 3.40 GHz, up to 5.0 GHz, Intel® UHD Graphics P630)   |
|                                    | Intel® Xeon® processor W-1250 (6 Cores / 12 Threads, 3.30 GHz, up to 4.7 GHz, Intel® UHD Graphics P630)   |
|                                    | Intel® Core™ i9-10900 processor (10 Cores / 20 Threads, 2.80 GHz, 20 MB, Intel® UHD Graphics 630) **  |
|                                    | Intel® Core™ i7-10700 processor (8 Cores / 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) **   |
|                                    | Intel® Core™ i5-10600 processor (6 Cores / 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) *  |
|                                    | Intel® Core™ i5-10500 processor (6 Cores / 12 Threads, 3.10 GHz, 12 MB, Intel® UHD Graphics 630) *  |
|                                    | Intel® Core™ i3-10100 processor (4 Cores / 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) *  |
|                                    | Intel® vPro® Platform with all Intel® Xeon® processors<br>Intel® vPro® Platform Logo with Intel® Core™ i5, Intel® Core™ i7 and Intel® Core™ i9 processors<br>*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables)  |
| <b>Operating systems</b>           |   |
| Operating system pre-installed     | Windows 10 Pro for Workstations<br>Windows 10 Pro<br>Windows 10 Home  |
| Operating system compatible        | Windows 11<br>Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business.<br>FREE Upgrade to Windows 11 when available.<br>The Windows 11 upgrade will be delivered to qualifying devices late 2021 into 2022. Timing varies by device. Certain features require specific hardware (see <a href="https://www.microsoft.com/windows/windows-11-specifications">https://www.microsoft.com/windows/windows-11-specifications</a> ).  |
| Operating system notes             | For some configurations third party drivers are currently not available or configuration restrictions may apply.<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> . |
| <b>Memory modules</b>              | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, ECC, 2,933 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, ECC, 2,933 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM<br>32 GB (1 module(s) 32 GB) DDR4, unbuffered, ECC, 2,933 MT/s, UDIMM<br>32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM  |
| <b>Graphics</b>                    | Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP<br>Entry 3D: NVIDIA® Quadro® P620 LP, 2 GB, PCIe x16, 4 x miniDP<br>Entry 3D: NVIDIA® Quadro® P400 LP, 2 GB, PCIe x16, 3 x miniDP<br>Entry 3D: NVIDIA® T400, 2 GB, PCIe x16, 3 x miniDP<br>Others: MiniDP to DP Adapter Cable   |
| <b>Mass storage 2.5 inch size</b>  | SSD SATA III, 512 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch  |
| <b>Mass Storage M.2 technology</b> | SSD PCIe, 2048 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 128 GB M.2 NVMe module<br>RAID1 Bundle 2x512GB M.2 NVMe Highend<br>RAID1 Bundle 2x256GB M.2 NVMe Highend   |

|  |   |
|--|---|
| Mass storage 3.5 inch size                   | HDD SATA III, 7,200 rpm, 8000 GB, 3.5-inch, business critical   |
|  | HDD SATA III, 7,200 rpm, 4000 GB, 3.5-inch, business critical   |
|  | HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch, business critical   |
|  | HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch  |
| Mass storage 2.5 inch size                   | HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical  |
| Mass storage 3.5 inch size                   | HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch  |
| Mass storage 2.5 inch size                   | HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch   |
|  | SSD SATA III, 960 GB High Endurance, 1DWDP, 2.5-inch  |
|  | SSD SATA III, 480 GB High Endurance, 1DWDP, 2.5-inch  |
|  | SSD SATA III, 240 GB High Endurance, 1DWDP, 2.5-inch  |
| Hard disk notes                              | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.<br>24/7 ready (business critical HDDs required)<br>SED (Self-Encrypting Drive)<br>SSD (Solid State Disk) |
| Drives (optional)                            | BD Triple Writer SATA ultra slim (tray)   |
|  | DVD Super Multi ultra slim (tray)   |
|  | SD Card reader  |
| Interface add on cards/components (optional) | Intel® WI-FI 6 AX200 and Bluetooth 5.1 vPro, SRD 5.8GHz (dedicated regions only)  |
|  | Dual serial card PCIe x1 LP   |

## Base unit

|                                |  |
|--------------------------------|--|
| Base unit                      | CELSIUS J5010  |
| <b>Mainboard</b>               |  |
| Mainboard type                 | D3828  |
| Formfactor                     | proprietary  |
| Chipset                        | Intel® W480  |
| Processor socket               | LGA 1200   |
| Processor quantity maximum     | 1  |
| Supported capacity RAM (max.)  | 128 GB   |
| Memory slots                   | 4 DIMM (DDR4) ECC/non-ECC  |
| Memory frequency               | 2,933 MT/s   |
| Memory notes                   | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.<br>2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration |
| LAN                            | 10/100/1,000 MBit/s Intel® I219LM  |
| Integrated WLAN                | optional; Intel® Wi-Fi 6 AX200 (2x2/160) Gig+ and Bluetooth 5.1  |
| BIOS version                   | AMI Aptio V<br>UEFI Specification 2.6  |
| BIOS features                  | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)   |
| Audio type                     | On board   |
| Audio codec                    | Realtek ALC623   |
| Audio features                 | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound   |
| <b>I/O controller on board</b> |  |
| Serial ATA total               | 4  |
| thereof SATA III               | 4  |

**I/O controller on board**

|                      |   |
|----------------------|---|
| Controller functions | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI<br>RAID 0/1/5/10 |
|----------------------|---|

**Interfaces**

|                              |  |
|------------------------------|--|
| Audio: line-in               | 1  |
| Audio: line-out              | 1  |
| Front audio: headset         | 1  |
| Internal speakers            | 1  |
| USB 2.0 total                | 4  |
| USB 3.2 Gen1 (5 Gbps) total  | 3  |
| USB 3.2 Gen2 (10 Gbps) total | 5 and 1 optional   |
| USB front                    | 2x USB 2.0; 2x USB 3.2 Gen 2; 1x USB 3.2 Gen 2 Type-C (supports up to 15W)   |
| USB rear                     | 2x USB 2.0; 2x USB 3.2 Gen 1; 2x USB 3.2 Gen 2; optional: additional 1x USB 3.2 Gen 2 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot) |
| USB internal                 | 1x USB 2.0 or 1x USB 3.2 Gen 1 Type A  |
| VGA                          | optional   |
| DisplayPort                  | 2  |
| DVI                          | optional (DVI-D)   |
| Serial (RS-232)              | 1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible))  |
| Mouse / Keyboard (PS/2)      | 2 (optional)   |
| Ethernet (RJ-45)             | 1  |
| Parallel                     | 1 (optional) (25pin with EPP and ECP)  |
| Interface Module notes       | Anytime USB charge functionality   |

**Input device / components**

|                          |                   |
|--------------------------|-------------------|
| Input devices (optional) | Keyboard<br>Mouse |
|--------------------------|-------------------|

**Drive bays**

|                         |   |
|-------------------------|---|
| Drive bays total        | 3   |
| 2.5-inch internal bays  | 1   |
| 5.25-inch external bays | 1   |
| Drive bay notes         | 1x internal 3.5" bay optional (screwless), can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only; |
| M.2-2280                | 2 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s)   |

**Slots**

|                                |  |
|--------------------------------|--|
| PCI-Express 3.0 x4 (mech. x16) | 1 x (150 mm / 5.91 inch)   |
| PCI-Express 3.0 x16            | 1 x (210 mm / 8.27 inch) Low profile or full height (via Riser card), optional |
| M.2-2230                       | on mainboard for WLAN/Bluetooth module   |

**Graphics on board**

|                              |   |
|------------------------------|---|
| Graphics brand name          | Intel® UHD Graphics P630, Intel® UHD Graphics 630 |
| Shared video memory          | Up to half size of total system memory            |
| TFT resolution (VGA)         | Up to 1,920 x 1,080 pixel                         |
| TFT resolution (DVI)         | up to 1,920 x 1,200 pixel                         |
| TFT resolution (DisplayPort) | Up to 4,096 x 2,304 pixel                         |
| TFT resolution (HDMI)        | Up to 4,096 x 2,160 pixel (30 Hz)                 |

**Graphics on board**

|                   |  |
|-------------------|--|
| Graphics features | <p>Support for up to three independent displays</p> <p>DirectX® 12</p> <p>HDCP support</p> <p>OpenCL™ 2.1</p> <p>OpenGL® 4.5</p> <p>For multi monitoring mode, graphics card and integrated graphics run in parallel</p> <p>DisplayPort interface supports Ver. 1.4 incl. Multi-Stream</p> <p>Digital audio formats are supported, including Dolby Digital Plus (7.1 channels)</p> <p>DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included)</p> <p>Additional I/O connectors configurable, choice of</p> <p>DVI-D</p> <p>HDMI™</p> <p>VGA</p> <p>USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)</p> <p>USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCIe x16 slot)</p> |
| Graphics notes    | <p>up to 1 GB dedicated video memory (main memory owned and locked for graphics use)</p> <p>Tested resolutions, depending on display type additional resolutions and frequencies possible</p> <p>Shared memory depending on main memory size and operating system</p> <p>Resolution (color depth up to 32 Bit/pixel)</p> <p>For TFT we recommend using 60Hz</p>  |

**Electrical values**

|                                      |   |
|--------------------------------------|---|
| Power efficiency note                | <p>Power supply efficiency in % at 10% / 20% / 50% / 100% load</p> <p>80Plus PLATINUM</p> <p>for 230V ; 88/92/94/93</p> <p>for 115V ; 87/91/92/91</p> |
| Rated voltage range                  | 100 V - 240 V   |
| Rated frequency range                | 50 Hz - 60 Hz   |
| Operating voltage range              | 90 V - 264 V  |
| Operating line frequency range       | 47 Hz - 63 Hz   |
| Max. output of single power supply   | 300 W   |
| Power factor correction/active power | active  |
| Monitor outlet                       | Switched  |

**Noise emission**

|  |  |
|--|--|
| Related Processors for noise                           | Intel® Xeon™ W-1290 processor  |
| Standard noise emission                                | <p>HDD, M.2</p> <p>NVIDIA® Quadro® P1000</p> <p>16 GB, ODD, Windows 10</p> <p>According to ISO 7779:2010, ECMA-74</p>                |
| Standard noise notes / description                     | A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)) |
| Standard noise operation mode: CPU 50% load            | 3.3 B / 20 dB(A) Bystander; 21 dB(A) Operator position (HDD+M.2)   |
| Standard noise operation mode: HDD load                | 3.5 B / 22 dB(A) Bystander; 26 dB(A) Operator position (HDD+M.2)   |
| Standard noise operation mode: Idle mode               | 3.2 B / 19 dB(A) Bystander; 21 dB(A) Operator position (HDD+M.2)   |
| Standard noise operation mode: ODD load                | 4.5 B / 31 dB(A) Bystander; 37 dB(A) Operator position (HDD+M.2)   |
| Standard noise operation mode: Office applications 2.0 | 3.2 B / 20 dB(A) Bystander; 21 dB(A) Operator position (HDD+M.2)   |

**Dimensions / Weight / Environmental**

|                        |   |
|------------------------|---|
| Dimensions (W x D x H) | <p>314 x 296 x 89 mm</p> <p>12.36 x 11.65 x 3.51 inch</p> |
| Operating position     | horizontal / vertical (optional, feet needed)             |
| Weight                 | approx. 8 kg  |
| Weight (lbs)           | approx. 17.64 lbs   |

**Dimensions / Weight / Environmental**

|                               |   |
|-------------------------------|---|
| Weight notes                  | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F)                           |
| Operating relative humidity   | 5 - 85 % (relative humidity)                      |

**Compliance**

|                 |   |
|-----------------|---|
| Product         | CELSIUS J5010   |
| Model           | DTG   |
| Germany         | TÜV GS  |
| Europe          | CE  |
| USA/Canada      | FCC Class B<br>cTUVus   |
| Global          | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>Microsoft Secured-core PC certification (for selected configurations)<br>ENERGY STAR® 8.0, depending on configuration<br>TCO Certified 8.0 (depending on configuration)<br>EPEAT® Silver (dedicated regions), depending on configuration<br>ENERGY STAR® compliance is an order option. Non ENERGY STAR/ TCO/ EPEAT compliant products are marked at brand name with additional suffix "n". |
| Compliance link | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |

**Additional Software**

|                                    |   |
|------------------------------------|---|
| Additional software (preinstalled) | McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)<br>Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)   |
| Additional software (optional)     | Recovery DVD for Windows®<br>Drivers & Utilities DVD (DUDVD)<br>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)<br>CyberLink PowerDVD DVD (playback software for DVD)<br>Nero Essentials XL<br>Microsoft® Office Professional 2019<br>Microsoft® Office Home and Business 2019<br>(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |

**Security**

|                          |  |
|--------------------------|--|
| Physical Security        | Kensington Lock support<br>Eye for padlock<br>Cable Cover (optional; covers and secures the ports and cables on rear side)   |
| System and BIOS Security | Embedded security (TPM 2.0)<br>EraseDisk<br>Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVMe)<br>Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards)<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces |
| User Security            | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>AuthConductor Client Basic (secure authentication solution)   |

**Manageability**

|                          |   |
|--------------------------|---|
| Manageability technology | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode)<br>Intrusion switch (optional)<br>WoL (Wake on LAN)<br>iAMT 14.0 (depending on processor) |
|--------------------------|---|

**Manageability**

|                        |  |
|------------------------|--|
| Manageability software | DeskView Client<br>DeskView Instant BIOS Management  |
| DeskView components    | BIOS Management incl. Security<br>Inventory Management<br>Driver Management<br>Alarm Management  |
| Supported standards    | DMI (Desktop Management Interface)<br>SMBIOS (System Management BIOS)<br>PXE (Preboot Execution Environment)<br>WMI (Windows Management Instrumentation)<br>WBEM (Web Based Enterprise Management)<br>CIM (Common Information Model) |
| Manageability link     | <a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>  |

**Miscellaneous**

|  |   |
|--|---|
|  | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management<br>Extended lifetime 24/7 (limited configurations) |
|--|---|

**Packaging information**

|                 |  |
|-----------------|--|
| Packaging notes | printed user documentation is bleached in chlorine free process;<br>Bulk packaging for projects (optional) |
|-----------------|--|

**Warranty**

|                             |  |
|-----------------------------|--|
| Warranty period             | 3 years (depending on country)   |
| Warranty type               | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)   |
| Warranty Terms & Conditions | <a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>  |
| Digital bug fixes           | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a> free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. |

**Product Support Services - the perfect extension**

|                          |   |
|--------------------------|---|
| Recommended Service      | 9x5, Onsite Response Time: Next Business Day  |
| Spare Parts availability | 5 years after end of product life   |
| Service Weblink          | <a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a> |

## Recommended Accessories

|                     |   |  |  |
|---------------------|---|--|--|
| Blue LED Mouse M960 |  | The Blue LED Mouse M960 comes in a slim design with proven Fujitsu engineering quality. The track on glass Blue LED sensor enables ultra precise switchable resolution at 1,000, 1,600 and 2,000 dpi. Blue LED Mouse M960 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.                        | Order Code:<br>S26381-K470-L100                      |
| SpaceMouse Pro      |  | Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit. | Order Code:<br>S26381-K459-L100                      |
| Keyboard KB955      |  | The KB955 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB955 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.                       | S26381-K955-L4** (**:<br>Country specific variation) |

## More information

### Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS J5010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about the FUJITSU Workstation CELSIUS J5010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/CELSIUS](http://www.fujitsu.com/emeia/CELSIUS)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2020 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2022-01-25 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2020 Fujitsu Technology Solutions GmbH