

Data Sheet

Fujitsu CELSIUS R940

Breaking all Barriers

Fujitsu's CELSIUS R940 desktop workstation is designed to surpass all expectations. Achieving first-class benchmark results, this reliable, high-end dual processor desktop workstation is individually configurable and optimized for extremely demanding and memory intensive multi-threaded applications. CELSIUS workstations offer you an "IT made in Germany" quality in which you can trust.

Unleash the power

Achieve the optimum out of any demanding application

- Intel® Xeon® processor E5-2600 v4 family up to 2 x 22 cores
- Support of Windows 10 Pro
- Maximum of 1024 GB of DDR4 ECC memory
- Fujitsu SSD PCIe card (up to 2 x 1 TB)

Maximum expandability

Broad selection and configurability options

- Broad choice of ISV certified professional graphics cards from AMD and Nvidia
- Up to two ultra-high-end, three high-end 3D or four mid-range graphic cards for simulation or photorealistic renderings
- Compute graphics cards of up to NVIDIA® Tesla® M60
- Support for eight hard disk drives

Work around the clock

Certain components can be configured to support an extended lifetime usage

- Selection of top-quality components and comprehensive testing in certified in-house laboratories
- Full support for ISV applications and easy integration into existing IT environments
- Server capabilities: SAS RAID controller, Windows® Server 2012, Dual 10 Gigabit Ethernet PCIe x8

Made in Germany

Design, engineering, product management, support and production - located at the Augsburg factory in Germany

- Optimized air flow and dedicated triple "Air Tunnel" flow results in reduced noise emissions even under full system load

We are (VR) ready

Enjoy a fully immersive and real-time Virtual Reality experience with low latency at high frame rates

- Powered by the NVIDIA® Quadro® P4000, P5000 and P6000 VR-ready graphics cards



Components

Processor	Intel® Xeon® processor E5-2699v4 (22 cores, 2.20 GHz, 55 MB)	
	Intel® Xeon® processor E5-2697v4 (18 cores, 2.30 GHz, 45 MB)	
	Intel® Xeon® processor E5-2697Av4 (16 cores, 2.60 GHz, 40 MB)	
	Intel® Xeon® processor E5-2690v4 (14 cores, 2.60 GHz, 35 MB)	
	Intel® Xeon® processor E5-2680v4 (14 cores, 2.40 GHz, 35 MB)	
	Intel® Xeon® processor E5-2650v4 (12 cores, 2.20 GHz, 30 MB)	
	Intel® Xeon® processor E5-2643v4 (6 Cores, 3.40 GHz, 20 MB)	
	Intel® Xeon® processor E5-2640v4 (10 Cores, 2.40 GHz, 25 MB)	
	Intel® Xeon® processor E5-2637v4 (4 Cores, 3.50 GHz, 15 MB)	
	Intel® Xeon® processor E5-2630v4 (10 Cores, 2.20 GHz, 25 MB)	
	Intel® Xeon® processor E5-2623v4 (4 Cores, 2.60 GHz, 10 MB)	
	Intel® Xeon® processor E5-2620v4 (8 Cores, 2.10 GHz, 20 MB)	
	Intel® Xeon® processor E5-2609v4 (8 Cores, 1.70 GHz, 20 MB)	
	Intel® Xeon® processor E5-2603v4 (6 Cores, 1.70 GHz, 15 MB)	
Operating system preinstalled		
Operating system pre-installed	Windows 10 Pro Windows 7 Professional (available through downgrade rights from Windows 10 Pro)	Windows 10 Pro Windows 7 Professional (available through downgrade rights from Windows 10 Pro)
Operating system compatible	Windows 8.1 Pro 64-bit (available through downgrade rights from Windows 10 Pro) Windows® Server 2012 Linux	Windows 8.1 Pro 64-bit (available through downgrade rights from Windows 10 Pro) Windows® Server 2012 Linux
Operating system notes	Certified for Red Hat© Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server	Certified for Red Hat© Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server
Memory modules	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,400 MT/s	
	16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,400 MT/s	
	32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,400 MT/s	
	64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,400 MT/s	
Graphics	Ultra-high-end 3D: NVIDIA® Quadro® P6000, 24 GB, PCIe x16, 1 x Dual Link DVI-D, 4 x DisplayPort	
	Ultra-high-end 3D: NVIDIA® Quadro® P5000, 16 GB, PCIe x16, 1 x Dual Link DVI-D, 4 x DisplayPort	
	High-end 3D: AMD FirePro™ W7100, 8 GB, PCIe x16, 4 x DisplayPort	
	High-end 3D: NVIDIA® Quadro® P4000, 8 GB, PCIe x16, 4 x DisplayPort	
	Midrange 3D: NVIDIA® Quadro® P2000, 5 GB, PCIe x16, 4 x DisplayPort	
	Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP	
	Entry 3D: NVIDIA® Quadro® P600, 2 GB, PCIe x16, 4 x miniDP	
Graphics	Entry 3D: NVIDIA® Quadro® P400, 2 GB, PCIe x16, 3 x miniDP	
	Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4 x miniDP, 4 x miniDP/DP Adapter	
Graphics	Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2 x miniDP, PCoIP	
	Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1 x LFH59 (max. 2 x DP or 2 x DVI-I)	
	Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4 x miniDP, PCoIP	
	Others: DP to DVI-D (single link) Adapter Cable	
	Others: MiniDP to DP Adapter Cable	
Personal Supercomputing	Coprocesor: NVIDIA® Tesla® M60, 16 GB, 4096 cores, PCIe x16	
Hard disk drives (internal)	SSD SATA III, 960 GB High Endurance, 3DWPD, 2.5-inch	
	SSD SATA III, 480 GB High Endurance, 3DWPD, 2.5-inch	
	SSD SATA III, 240 GB High Endurance, 3DWPD, 2.5-inch	

Hard disk drives (internal)	SSD PCIe, 2x 1024 GB M.2 NVMe Highend card
	SSD PCIe, 2x 512 GB M.2 NVMe Highend card
	SSD PCIe, 2x 256 GB M.2 NVMe Highend card
	SSD PCIe, 1x1024 GB M.2 NVMe Highend card
	SSD PCIe, 1x 512 GB M.2 NVMe Highend card
	SSD PCIe, 1x 256 GB M.2 NVMe Highend card
	SSD PCIe, 2x 1024 GB M.2 NVMe card
	SSD PCIe, 2x 512 GB M.2 NVMe card
	SSD PCIe, 2x 256 GB M.2 NVMe card
	SSD PCIe, 1x 1024 GB M.2 NVMe card
	SSD PCIe, 1x 512 GB M.2 NVMe card
	SSD PCIe, 1x 256 GB M.2 NVMe card
	SSD SATA III, 1024 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	HDD SAS, 10,000 rpm, 1800 GB, 2.5-inch
	HDD SAS, 10,000 rpm, 1200 GB, 2.5-inch
	HDD SAS, 10,000 rpm, 900 GB, 2.5-inch
Hard disk drives (internal)	HDD SAS, 10,000 rpm, 600 GB, 2.5-inch
	HDD SATA III, 10,000 rpm, 500 GB, 2.5-inch, business critical
Hard disk drives (internal)	HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1000 GB, 2.5-inch, enhanced availability
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
Hard disk notes	<p>*Disk imaging software of the customer must be 4k sector size / advanced format ready One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (Business Critical HDDs or SAS HDDs or High Endurance SSDs required) Up to 20 GB of HDD space is reserved for system recovery SSHHD (Solid State Hard Disk, Hybrid drive) SED (Self-Encrypting Drive) SSD (Solid State Disk)</p>
Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD-ROM
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 24in1 USB 2.0 3.5"
SCSI / SAS Controller	LSI RAID Ctrl SAS 1GB (D3216) RAID 5/6 Ctrl. 12 Gbit/s 8 ports int.
	LSI RAID Ctrl SAS (D3327) RAID 0/1 Ctrl. 12 Gbit/s 8 ports int.
	Flash Backup Unit (FBU + TFM) For RAID controller D3216

**Interface add on cards/components
(optional)**

WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)
WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)
PLAN EP X550-T2 2x10GBASE-T
Intel 2x1Gb Ethernet Adapter I350-T2
Gigabit Ethernet PCIe x1
eSATA Interface
Dual serial card PCIe x1
Dual 10 Gigabit Ethernet PCIe x8

Base unit	CELSIUS R940 (S26361-K1449-V355)	CELSIUS R940power (S26361-K1449-V455)
------------------	----------------------------------	---------------------------------------

Mainboard

Mainboard type	D3358-A2x
Formfactor	proprietary
Chipset	Intel® C612
Processor socket	Socket R3
Processor quantity maximum	2
Supported capacity RAM (max.)	1,024 GB
Memory slots	16 (8 per processor) DIMM (DDR4) ECC
LAN	10/100/1,000 MBit/s Intel® I217LM and Intel® I210
BIOS version	AMI Aptio V
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	High Definition Audio

I/O controller on board

Serial ATA total	10
thereof SATA III	10
Controller functions	Serial ATA III (6 Gbit) AHCI RAID 0/1/5/10

S26361-K1449-V355 CELSIUS R940

Audio: in (rear)	1
Audio: out (rear)	1
Audio: in	1
Audio: out	1
Internal speakers	1
USB 2.0 total	9
USB 3.1 Gen1 (USB 3.0) total	4
USB front	4 (2x USB 3.0)
USB rear	6
USB internal	3, thereof 1 type A
Ethernet (RJ-45)	2
Interface Module notes	Anytime USB charge functionality

Input device / components

Optical USB wheel mouse

Input device / components

Input devices (optional)	Keyboard Optical USB tilt wheel mouse Optical USB wheel mouse
--------------------------	---

Drive bays

Drive bays total	12
2.5-inch internal bays	8
3.5-inch internal bays	4
3.5-inch external bays	2
5.25-inch external bays	1
Drive bay notes	Up to 8x 2.5-inch HDDs (cold plug) and 1x 2.5-inch SSD or Up to 4x 3.5-inch HDDs (cold plug) and 1x 2.5-inch SSD or Up to 2x 2.5-inch and 2x 3.5-inch HDDs (cold plug) and 1x 2.5-inch SSD

Slots

PCI-Express 3.0 x8	1 x (200 mm) Full height
PCI-Express 3.0 x16	4 x (340 mm / 13.39 inch) Full height (2x PCIe 3.0x16 per processor)
PCI-Express 2.0 x4 (mech. x16)	1 x (340 mm / 13.39 inch) Full height
PCI-Express 2.0 x1 (mech. x8)	1 x (340 mm / 13.39 inch) Full height
PCI-Express 3.0 x8 (internal)	1 x (170 mm / 6.69 inch) Full height (available with 2nd CPU)

Electrical values

Power consumption note	500 W depending on configuration	650 W depending on configuration
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz
Max. output of single power supply	1000 W up to 90% efficiency	1300 W up to 90% efficiency for an input voltage above 115 V
Power factor correction/active power	active	active
Power supply output	2 graphics power rails (8pin connector / 18.5A@12V)	1000 W for an input voltage below 115 V 3 graphics power rails (8pin connector / 18.5A@12V)

Noise for standard configuration (HDD, ODD)

Related Processors for noise	Intel® Xeon® E5-2643v4 w/ NVIDIA® Quadro®M2000	Intel® Xeon® E5-2643v4 w/ NVIDIA® Quadro®M2000
Standard noise emission	8x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	8x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A))	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A))
Standard noise operation mode: CPU 50% load	4.0 B / 23 dB(A) Bystander position	4.0 B / 23 dB(A) Bystander position
Standard noise operation mode: CPU 90% load	4.4 B / 26 dB(A) Bystander position	4.3 B / 26 dB(A) Bystander position
Standard noise operation mode: HDD load	3.9 B / 23 dB(A) Bystander position	4.0 B / 23 dB(A) Bystander position
Standard noise operation mode: Idle mode	3.8 B / 22 dB(A) Bystander position	3.9 B / 22 dB(A) Bystander position
Standard noise operation mode: ODD load	4.6 B / 29 dB(A) Bystander position	4.6 B / 29 dB(A) Bystander position
Standard noise operation mode: Office applications 2.0	3.8 B / 22 dB(A) Bystander position	3.9 B / 22 dB(A) Bystander position

Dimension with stand (W x D x H)

Dimensions (W x D x H)	186 x 618 x 430 mm 7.32 x 24.3 x 16.9 inch
------------------------	---

Operating position	Vertical / horizontal
--------------------	-----------------------

Weight	approx. 20 kg
Weight (lbs)	approx. 44.8 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)
Product	CELSIUS R940
Model	ETNA-L
Germany	GS depending on configuration
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (EU & China) Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment) Energy Star® 6.1 (dedicated regions, depending on configuration) EPEAT® Silver (dedicated regions)
Compliance notes	Product Name maybe followed by suffixes
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Windows® 8 and Windows® 7

Security

Physical Security	Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional)	Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional)
System and BIOS Security	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of all USB interfaces Trusted Platform Module (TPM 2.0) EraseDisk	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of all USB interfaces Trusted Platform Module (TPM 2.0) EraseDisk
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) SystemLock 3 SmartCard Security (optional): BIOS based pre-boot/ two-factor authentication for high level of access protection	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) SystemLock 3 SmartCard Security (optional): BIOS based pre-boot/ two-factor authentication for high level of access protection

Manageability

Miscellaneous

	Rack mountable (5U)	Rack mountable (5U)
Spare part availability	5 years	5 years

Packaging information

Packaging dimension (mm)	394 x 730 x 578 mm
Packaging dimension (inch)	15.51 x 28.74 x 22.76 inch
Max. quantity / pallet	11
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life 5 years

Recommended Accessories

Blue LED Mouse GL9000

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:
S26381-K438-L100

SpaceMouse™ Pro

Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KB900

The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

More information

In addition to Fujitsu CELSIUS R940, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS R940, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com>

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: [www.fujitsu.com/\[country\]](http://www.fujitsu.com/[country])
2019-08-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions