

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Workstation CELSIUS W550 Long Lifecycle

### Long Lifecycle CELSIUS W550

Do you require a minimum lifecycle of 36 months? Then the FUJITSU CELSIUS W550 power Long Lifecycle desktop workstation is the ideal choice, especially for video editing, MCAD/electrical CAD or Architecture, Engineering and Construction applications. Enjoy best-in-class low noise emissions of only 18 dB(A) for a quiet and efficient working environment.



#### Abundant performance at an affordable price

Enjoy impressive professional graphics and storage capacity at an affordable price

- Choose between the energy-efficient Intel® Core™ processors or the powerful Intel® Xeon® E3-1200 v5 processor family
- Support of Windows 10 Pro
- Support of Windows 7 Professional 64-bit
- Broad choice of graphics cards, starting from the cost-effective integrated Intel graphic card, up to professional 2D and even high-end 3D graphic cards from AMD and NVIDIA
- Boost your storage performance with super-fast PCIe SSDs to provide a quick loading of core applications and reliable high-endurance and business critical drives designed for long-term operation

#### Maximum lifecycle, expandability and scalability

Long lifecycle, maximum graphical and storage performance

- Minimum lifecycle of 36 months
- 500W power supply for maximum graphic card configurability: up to the high-end 3D AMD FirePro™ W7100 series as well as the NVIDIA® Quadro® M4000 graphics cards
- The system will accommodate a total of five storage drives which can add up to an impressive capacity of 27.5 TB

#### Whisper quiet design Made in Germany

Fujitsu's desktop workstations are designed, engineered and manufactured in the heart of Europe

- Optimized thermal management and cooling solutions
- NVIDIA® NVS™ 315 fanless graphic card

#### Multi-monitor experience

Enjoy maximum viewing capabilities and increase your productivity

- Support 4 monitors when choosing AMD Eyefinity™ or NVIDIA® Mosaic™ technologies
- Up to 8 monitors when selecting Nvidia's professional 2D graphics



RADEON PRO WX



# Components

<b>Processor</b>	Intel® Xeon® processor E3-1275v5 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics P530) *, **
	Intel® Xeon® processor E3-1225v5 (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 8 MB, Intel® HD Graphics P530) *, **
	Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **
	Intel® vPro™ with all Intel® Xeon® processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
<b>Operating systems</b>	
<b>Operating system pre-installed</b>	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
<b>Operating system compatible</b>	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Windows 7 Professional 64-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Linux
<b>Operating system notes</b>	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server For some configurations third party drivers are currently not available or configuration restrictions may apply. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .
<b>Memory modules</b>	
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, ECC, 2,133 MHz, UDIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, ECC, 2,133 MHz, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
<b>Graphics</b>	
	High-end 3D: AMD FirePro™ W7100, 8 GB, PCIe x16, 4 x DisplayPort
	High-end 3D: AMD Radeon™ Pro WX 7100 , 8 GB, PCIe x16, 4 x DisplayPort
	High-end 3D: NVIDIA® Quadro® P4000, 8 GB, PCIe x16, 4 x DisplayPort
	Midrange 3D: NVIDIA® Quadro® P2000, 5 GB, PCIe x16, 4 x DisplayPort
	Midrange 3D: AMD Radeon™ Pro WX 5100, 8 GB, 320 stream processors, PCIe x16, 4 x DisplayPort
	Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4x miniDP
	Entry 3D: AMD Radeon™ Pro WX 3100, 4 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP
	Professional 2D: NVIDIA® NVS™ 315 fanless, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Entry 3D: AMD Radeon™ Pro WX 2100, 2 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP
	Entry 3D: NVIDIA® Quadro® P620, 2 GB, PCIe x16, 4x miniDP
	Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP
	Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP
	Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP
	Others: DP to DVI-D (single link) Adapter Cable
	Others: VGA Extension Card

<b>Hard disk drives (internal)</b>	SSD SATA III, 960 GB High Endurance, 1DWDP, 2.5-inch
	SSD SATA III, 480 GB High Endurance, 1DWDP, 2.5-inch
	SSD SATA III, 240 GB High Endurance, 1DWDP, 2.5-inch
	SSD PCIe, 2048 GB M.2 NVMe Highend module
	SSD PCIe, 1024 GB M.2 NVMe Highend module
	SSD PCIe, 512 GB M.2 NVMe Highend module
	SSD PCIe, 256 GB M.2 NVMe Highend module
	SSD PCIe, 1x 2048 GB M.2 NVMe Highend card
	SSD PCIe, 1x1024 GB M.2 NVMe Highend card
	SSD PCIe, 1x 512 GB M.2 NVMe Highend card
	SSD PCIe, 1x 256 GB M.2 NVMe Highend card
	SSD SATA III, 1024 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1000 GB, 2.5-inch, enhanced availability
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch	
HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch	
<b>Hard disk notes</b>	<p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p> <p>24/7 ready (business critical HDDs required)</p> <p>Up to 20 GB of HDD space is reserved for system recovery</p> <p>SSHD (Solid State Hard Disk, Hybrid drive)</p> <p>SED (Self-Encrypting Drive)</p> <p>SSD (Solid State Disk)</p>
<b>Drives (optional)</b>	BD Triple Writer SATA ultra slim (tray)
	DVD-ROM
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 24in1 USB 2.0 3.5"
<b>Interface add on cards/components (optional)</b>	WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)
	WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)
	Parallel Interface
	Gigabit Ethernet PCIe x1
	eSATA Interface
	Dual serial card PCIe x1
<b>Base unit</b>	CELSIUS W550power-L
<b>Mainboard</b>	
<b>Mainboard type</b>	D3417

**Mainboard**

Formfactor	µATX
Chipset	Intel® C236
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	4 DIMM (DDR4) ECC/non-ECC
Memory frequency	2,133 MHz
Memory notes	Dual channel support For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS version	AMI Aptio V
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound

**I/O controller on board**

Serial ATA total	6
thereof SATA III	6
thereof eSATA	2 (optional)
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10

**Interfaces**

Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
Internal speakers	1
USB 2.0 total	6
USB 3.1 Gen1 (USB 3.0) total	7
USB front	2x USB 2.0; 2x USB 3.0
USB rear	2x USB 2.0; 4x USB 3.0
USB internal	2x USB 2.0 + 1x USB 3.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

**Input device / components**

<b>Input devices (optional)</b>	Keyboard Mouse KBPC PX ECO Mouse M440 ECO Space Explorer USB
---------------------------------	--

**Drive bays**

<b>Drive bays total</b>	9
<b>2.5-inch internal bays</b>	1
<b>3.5-inch internal bays</b>	4
<b>3.5-inch external bays</b>	2
<b>5.25-inch external bays</b>	2
<b>Drive bay notes</b>	Up to 1x 2.5-inch HDDs and up to 4x 2.5/3.5-inch HDDs
<b>M.2-2280</b>	1 x on mainboard (for PCIe SSD modules)

**Slots**

<b>PCI-Express 3.0 x1</b>	2 x (340 mm / 170 mm / 13.39 inch / 6.69 inch) Full height
<b>PCI-Express 3.0 x4 (mech. x16)</b>	1 x (170 mm / 6.69 inch) Full height
<b>PCI-Express 3.0 x16</b>	1 x (340 mm / 13.39 inch) Full height

**Graphics on board**

<b>Graphics brand name</b>	Intel® HD Graphics P530, Intel® HD Graphics 530
----------------------------	---

<b>Shared video memory</b>	up to 1,782 MB
----------------------------	----------------

<b>TFT resolution (VGA)</b>	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
-----------------------------	--

<b>TFT resolution (DVI)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
-----------------------------	---

<b>TFT resolution (DisplayPort)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
-------------------------------------	---

<b>Graphics features</b>	Support for up to three independent displays DirectX® 12 HDCP support OpenCL® 2.0 OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
--------------------------	---

**Graphics on board**

<b>Graphics notes</b>	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
-----------------------	--

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 84% / 91% / 93% / 91%
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	500 W
<b>Power factor correction/active power</b>	active
<b>Power supply output</b>	1 graphics power rail (6pin connector / 17A@12V)

**Noise for standard configuration (HDD, ODD)**

<b>Noise emission</b>	According to ISO9296
<b>Related Processors for noise</b>	Intel® Xeon® E3-1275v5
<b>Standard noise emission</b>	4x8 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
<b>Standard noise notes / description</b>	A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)) (depending on configuration)
<b>Standard noise operation mode: CPU 50% load</b>	3.5 B / 21 dB(A) Bystander position
<b>Standard noise operation mode: CPU 90% load</b>	3.5 B / 22 dB(A) Bystander position
<b>Standard noise operation mode: HDD load</b>	3.5 B / 21 dB(A) Bystander position
<b>Standard noise operation mode: Idle mode</b>	3.4 B / 21 dB(A) Bystander position
<b>Standard noise operation mode: ODD load</b>	4.4 B / 29 dB(A) Bystander position
<b>Standard noise operation mode: Office applications 2.0</b>	3.4 B / 21 dB(A) Bystander position
<b>Blue angel noise emission according certification</b>	According to ISO 7779:2010, ECMA-74 for max. possible configuration
<b>Blue angel noise notes / description</b>	A-weighted sound power level L <sub>wad</sub> (in B); 1B = 10dB
<b>Blue angel noise operation mode: HDD load</b>	3.9 B = 44 dB (A)
<b>Blue angel noise operation mode: Idle mode</b>	3.9 B = 44 dB (A)
<b>Blue angel noise operation mode: ODD load</b>	4.4 B = 44 dB (A)

**Dimensions / Weight / Environmental**

<b>Dimensions (W x D x H)</b>	175 x 419 x 395 mm 6.89 x 16.5 x 15.56 inch
<b>Operating position</b>	Vertical
<b>Weight</b>	approx. 14 kg
<b>Weight (lbs)</b>	approx. 30.86 lbs
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Operating ambient temperature</b>	10 - 35 °C (50 - 95 °F)
<b>Operating relative humidity</b>	5 - 85 % (relative humidity)

**Compliance**

<b>Product</b>	CELSIUS W550power-L
<b>Model</b>	M15W
<b>Europe</b>	CE
<b>USA/Canada</b>	FCC Class B cCSAus
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)
<b>China</b>	CCC (planned) China RoHS
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

**Additional Software**

<b>Additional software (preinstalled)</b>	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)

**Security**

<b>Physical Security</b>	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
<b>System and BIOS Security</b>	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
<b>User Security</b>	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
<b>Workplace Embedded Tools</b>	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)

**Manageability**

<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 11.0 (depending on processor)
<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management

**Manageability**

<b>DeskView components</b>	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
----------------------------	--

<b>Supported standards</b>	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
----------------------------	--

<b>Manageability link</b>	<a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>
---------------------------	---

**Miscellaneous**

Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime 24/7 (limited configurations)
--

**Packaging information**

<b>Packaging dimension (mm)</b>	516 x 278 x 562 mm
<b>Packaging dimension (inch)</b>	20.31 x 10.94 x 22.13 inch
<b>Max. quantity / pallet</b>	24
<b>Material - Weight (g) Carton</b>	1280 g
<b>Material - Weight (lbs) Carton</b>	2.82 lbs
<b>Material - Weight (g) EPS / PS</b>	190 g
<b>Material - Weight (lbs) EPS / PS</b>	0.42 lbs
<b>Material - Weight (g) PE</b>	60 g
<b>Material - Weight (lbs) PE</b>	0.13 lbs
<b>Packaging notes</b>	printed user documentation is bleached in chlorine free process

**Warranty**

<b>Warranty period</b>	3 years (depending on country)
<b>Warranty type</b>	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>

**Product Related Services - the perfect extension**

<b>Recommended Service</b>	9x5, Onsite Response Time: Next Business Day
<b>Spare Parts availability</b>	5 years after end of product life 5 years
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

## Recommended Accessories

**Display P27-8 TS Pro**

If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P27-8 TS Pro Display is the perfect choice. The display provides outstanding picture performance thanks to cutting-edge panel technology and 3.7 Mio pixels. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and USB support during standby.

Order Code:  
S26361-K1594-V160



**Display B34-9 UE**

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ Click manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1642-V140

**Blue LED Mouse GL9000**

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:  
S26381-K438-L100

**SpaceMouse™ Pro**

Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:  
S26381-K459-L100

**Keyboard KB900**

The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4\*\* (\*\*:  
Country specific variation)

## More information

### Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS W550 Long Lifecycle, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about the FUJITSU Workstation CELSIUS W550 Long Lifecycle, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/fts/CELSIUS](http://www.fujitsu.com/fts/CELSIUS)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2019-01-18 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH