

Data Sheet

FUJITSU Storage CELVIN® NAS QR806 Storage

Powerful 4-Drive NAS Solution

The FUJITSU Storage CELVIN® NAS QR806 is the ideal solution for file sharing, end to end backup options and SAN (Storage Area Network) integration for SMB customers - enabling centralized data management at a reasonable price. It has dual power supplies for superior reliability with up to 24 TB of storage capacity and is designed to be rack mounted right alongside other networked enterprise equipment.

Business Server Features

- Rack mountable
- Four hot swappable business critical or NAS drives
- VMWare®/Citrix®/HyperV™ Capable
- Redundant power supplies and cooling
- High performance through 10Gbit Ethernet

Reliability

- Service-friendly cabinet
- 3-years spare part supply
- Country-specific warranty
- Top-up services are available



CELVIN® NAS QR806

Technical specifications

	Linux embedded system Firmware based on 4.3.3 or higher Processor:64-Bit Quad-Core AMD® G-Series 2.0GHz Memory: 4 GB DDR3L RAM, one free slot, max up to 16GB 512 MB Flash on DOM FAN:2x quiet cooling fan (4 cm) Formfactor: Rackmount 1U
Hard disk capacity	Up to 4 x 2.5-inch or 3.5-inch SATA I/II/SATA 6Gb/s HDD or SSD up to 24 TB raw capacity, consult HDD compatibility list NAS HDD: ready for 24x7 use; Business Critical HDD: tailored for 24x7 reliability
System controls	Power button, One-touch copy button, Reset Button

Interfaces

USB 2.0 total	3
USB 3.1 Gen1 (USB 3.0) total	2
LAN / Ethernet	Rear side: x4 Gigabit RJ-45 Ethernet port (always on) Rear side: x1 10GbE PCI-E SFP+ NIC, no transceiver included

Functional Description

Networking	<p>TCP/IP (IPv4 /IPv6 dual stack), multi IP setting, LACP, Port trunking /NIC teaming: Balance-rr (Round-Robin), Active Backup, Balance XOR, Broadcast, IEEE 802.3ad, Balance-tlb (Adaptive, Transmit Load Balancing), Balance-alb (Adaptive Load Balancing)</p> <p>DHCP client, DHCP server including PXE boot CIFS/SMB(1.0,2.0,2.1,3.0 selectable), SAMBA 4, AFP/Netatalk3.3, NFS v3, HTTP, HTTPS, FTP,SFTP(admin), DDNS, NTP, Telnet, SSH, iSCSI, SNMP,WebDAV,SMSC Gigabit w/ Jumbo Frame, Bonjour</p> <p>iSCSI target (with multi-LUNs per target), Up to 256 LUNs/targets combined iSCSI LUN online expansion LUN mapping / LUN masking Online LUN capacity expansion SCSI Primary Commands -3 (SPC-3) support / persistent reservation MC/S (multiple TCP connections / session) support to reach iSCSI target MPIO (multipath input output) for load balancing and failover iSCSI LUN Backup, One-time-Snapshot and Restore iSCSI initiator for virtual disks (max 8 disks); stack chaining master Virtual disk support for EXT3/ EXT4/ NTFS/ FAT32/ HFS+ iSCSI Connection and Management by Fujitsu Finder (Windows)</p> <p>Support for VMware VSphere (ESXi 5.x) via NFS and iSCSI (VMware VAAI for iSCSI and VAAI for NAS) Windows Server 2008 support (Hyper-V & failover clustering) Windows Server 2012 R2 Hyper-V; Windows Server 2016 ODX support Citrix XenServer (6.2)</p> <p>VLAN 802.1Q USB WiFi-Adapter support IEEE 802.11b/g/n/ac WEP, WPA-personal (AES/TKIP), WPA2-personal (AES) Connection to wireless network or Ad Hoc network</p>
-------------------	--

Functional Description

Backup Management	<ul style="list-style-type: none"> Client backup software Time machine backup (OS X Lion support) 3rd party backup software support Encrypted block-level remote replication (instant, scheduled backup management); synchronization mode/Rsync Real-time remote replication (RTRR protocol) for real-time backup of server & client, 3 sync modes, filter, policy definition, SSL protected Backup to Cloud Backup to (encryptable) USB storage devices LUN backup and restore LUN point-in-time snapshot (1x) Snapshot: Volume/LUN snapshots <ul style="list-style-type: none"> Cloning of snapshots, snapshot vault, snapshot replica, snapshot agent for WINDOWS VSS /VMware
File System Management	<ul style="list-style-type: none"> Network share management '(max. 512 shares) Share folder level ACL support Unicode support Journaling file system Web File Manager <ul style="list-style-type: none"> File management by Web-browser File and folder search Direct file viewing via Google Docs support (pdf,tif/tiff,ppt,doc,xls,pptx,docx,xlsx,svg,odt) Create and send download links for public file sharing (time expiration, password protected)
Disk Management	<ul style="list-style-type: none"> Flexible volume / LUN with thin provisioning and space reclaim Storage pools and storage pool online expansion SSD read-only/read-write cache Disk usage status management; HDD S.M.A.R.T.; Bad blocks scan RAID 0/1/5/5+HS/10/6, JBOD Online RAID capacity expansion; online RAID-level migration RAID recovery, Bitmap support ISO mounting (max 256) via Web File Manager
User Management	<ul style="list-style-type: none"> User quota management Microsoft Active Directory (AD) & Domain Controller support LDAP server, LDAP client Domain users login via CIFS/SMB, AFP, FTP, and File Station User account management (max. 4096users) User group management (max. 512 groups) Shared folders (max. 512) Concurrent connections (max. 256) Support batch creating users User Import/ Export for Multiple CELVIN NAS Deployment Subfolder Permission (File/Directory ACL) Microsoft Networking (Samba) Host Access Control (Domain/IP)
Radius Server	<ul style="list-style-type: none"> Support for 802.1x security authentication: PAP , EAP-TLS/PAP, EAP-TTLS/PAP (WPA-Enterprise, WPA2-Enterprise) max. 10 RADIUS clients, max. 4096 users
VPN Server	<ul style="list-style-type: none"> OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption; 15 clients each
System Tools	<ul style="list-style-type: none"> E-mail alert (SMTP authentication); SMS alert notification Disk usage alert HDD standby mode Automatic power on after power loss Schedule power on/ off System firmware upgrade Wake-on-LAN Smart fan setting Back up, restore, reset system settings Configurable management port Remote login by Telnet connection USB, SNMP(v2, v3) UPS support Network recycle bin
Event Logs	<ul style="list-style-type: none"> Complete system logs (file level): system events management, connection logs, current connection of on-line users Centralized monitoring / syslog server (TCP / UDP) Manually and advanced log filtering via wizard

Functional Description

Multilingual (Online) Support	English, German, Czech, Danish, Spanish, French, Italian, Norwegian, Polish, Russian, Finish, Swedish, Dutch, Turkish, Greek, Hungarian, Portuguese (Brazil), Romanian, Japanese, Korean, Thai, Chinese (Traditional & Simplified)
FTP Server	FTP remote access (max. 256 concurrent connections) FTP with SSL/ TLS (explicit) mode FTP bandwidth control and connection control Passive FTP port range control FXP and Unicode support TFTP server (PXE boot) SFTP (admin only)
Printer Server	USB printer network sharing (Windows / Mac) 3 printers maximum Internet printing protocol, printer management, Apple Bonjour printing
Web Server	Built-in editable php.ini, SQLite and MySQL Web-based management via phpMyAdmin Max. 32 virtual hosts
MySQL Server	MySQL database server
Security	Network access protection with autoblocking (SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP) Policy based automatic IP blocking and IP filter Encrypted access (HTTPS, FTP with SSL/TLS(explicit),SSH/SFTP, RSync over SSH, CIFS host access control for shared folders ClamAV antivirus protection FIPS 140-2 validated AES 256-bit volume based data encryption Importable SSL certificates OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption Radius Server Instant alert via E-mail, SMS, Instant Messaging
Surveillance Station	Includes 4 free camera licenses, up to 40 camera channels via additional license purchase Instant playback to check recent events Online editing to edit cameras during live view Visual aid by e-map Playback and speed control using the shuttle bar Video preview on playback timeline Intelligent video analytics (IVA) for advanced video searching Surveillance Station via App Center
Application center	Diverse applications downloadable via App center Fujitsu NAS Explorer, Fujitsu NAS Manager for Android / iOS Fujitsu Finder, Qsync, Qget, Netbak Replicator standard software

Supported Operating Systems and Browsers

Supported operating systems	Windows 10 Windows 8.1 Windows 8 Windows 7 Mac OS X Linux UNIX Windows® Server 2016 Windows® Server 2012 R2 Windows® Server 2012 Windows® Server 2008 R2 Windows® Server 2003
Browser Support	Internet Explorer 10+ / Edge / Mozilla Firefox 8+ / Apple Safari 4+ / Google Chrome

Supported formats

Supported file system	EXT4 (internal/external HDD) EXT3 (external HDD) NTFS (external HDD) FAT32 (external HDD) HFS+ (external HDD)
------------------------------	---

Electrical values

Power consumption	HDD-Sleep mode: 44,9W (with 10GbE NIC) Operation: 65,62W (with 10GbE NIC)
Power supply input	Internal swappable power supply module 2x250W 50-60Hz Input: 100-240V AC / 5A

Compliance

Europe	CE
USA/Canada	FCC Class A
Saudi Arabia	SASO
Compliance notes	* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Dimensions / Weight / Environmental

Dimensions (W x D x H)	439 x 499 x 44 mm
Weight	Net weight: 7.6 kg, Gross weight: 11.6 kg; Package incl. System w/o HDD
Operating ambient temperature	0 - 40 °C
Operating relative humidity	20 - 85 % (relative humidity), wet bulb 27° C
Acoustic noise level	Sound pressure (LpAm) :36.4 dB(A) Refer to ISO 7779

Package content

CELVIN® NAS QR806; Power Cord, LAN cable, Key for tray lock, trays, Quick Start Guide
Please note: Rail kits are not included in the package.

Order code

S26341-F103-L212	EAN: 4051554629083	Single Tray with 2 TB NAS Hard Disk Drive
S26341-F103-L213	EAN: 4051554629090	Single Tray with 3 TB NAS Hard Disk Drive
S26341-F103-L214	EAN: 4053026594257	Single Tray with 4 TB NAS Hard Disk Drive
S26341-F103-L216	EAN: 4053026871037	Single Tray with 6 TB NAS Hard Disk Drive
S26341-F105-L4	EAN: 4057185592000	CELVIN RAM 4GB DDR3L SO-1600
S26341-F107-L806	EAN: 4057185651387	w/trays, w/o HDD, EU
S26341-F107-L842	EAN: 4057185651424	4x2TB NAS HDD, EU
S26341-F107-L843	EAN: 4057185651462	4x3TB NAS HDD, EU
S26341-F107-L844	EAN: 4057185651509	4x4TB NAS HDD, EU
S26341-F107-L846	EAN: 4057185651547	4x6TB NAS HDD, EU
S26341-F107-L853	EAN: 4057185649506	4x3TB NAS HDD, INT
S26341-F107-L856	EAN: 4057185649513	4x6TB NAS HDD, INT
S26341-F107-L892	EAN: 4057185651585	4x2TB BC HDD, EU
S26341-F107-L893	EAN: 4057185651622	4x3TB BC HDD, EU

Warranty

Warranty period	2 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Recommended Service	2/3 years, 9x5, Onsite Response Time: Next Business Day or Second Business Day
Spare Parts availability	3 years
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Storage CELVIN® NAS QR806, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Storage CELVIN® NAS QR806, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2019-10-01 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH