

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO A525-L

Combines Essential Performance with Longevity

The FUJITSU ESPRIMO A525-L is an individually configurable Desktop for standard office applications or usage in the educational sector. This compact and reliable PC features simple manageability and ease of use. Productivity is enhanced by its fanless design and you can enjoy a tidy workplace thanks to the optional VESA mount. The FUJITSU ESPRIMO A525-L is designed for a long lifecycle, which combined with high energy efficiency, results in low TCO.

Lifecycle

Hardware continuity for long-lasting project requirements

- Managed lifecycle up to 24 months

Increased productivity

Quiet system for a pleasant working environment

- Fanless cooling

Energy efficiency

Saves energy and reduces CO2 emissions

- Integrated system concept with high-level power-saving components

System management

The perfect answer to offload your IT administrators

- DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation - even remotely and after hours

Backpack solution

Enjoy a tidy desk

- The FUJITSU ESPRIMO A525-L can be mounted behind a display



Components

| | |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating systems | |
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional (available through downgrade rights from Windows 10 Pro) |
| Operating system compatible | Windows 8.1 Pro (available through downgrade rights from Windows 10 Pro) openSUSE Linux |
| Memory modules | |
| | 4 GB (1 module(s) 4 GB) DDR3, 1,600 MHz, PC3-12800, SO DIMM 8 GB (1 module(s) 8 GB) DDR3, 1,600 MHz, PC3-12800, SO DIMM |
| Hard disk drives (internal) | |
| | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch* SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch, SED HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch* |
| Hard disk notes | Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive) |
| Graphics | |
| | DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable |
| Interface add on cards/components (optional) | |
| | Internal speaker Intel® Dual Band Wireless-AC 7260 2nd LAN/Power-over-Ethernet module |

Base unit

| | |
|--------------------------------------|------------------------------------------------------------------------------------------------------|
| Base unit | ESPRIMO A525-L |
| Mainboard | |
| Mainboard type | D3313 |
| Formfactor | miniITX |
| Processor socket | embedded |
| Processor type support | AMD GX-217GA (dual core processor; 1.65 GHz) AMD GX-222GC (dual core processor; 2.2 GHz) |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 8 GB |
| Memory slots | 1 SO DIMM (DDR3, 1600 MHz) |
| Memory frequency | 1,600 MHz |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111G |
| Integrated WLAN | 1 (optional with Bluetooth together) |
| BIOS version | AMI Aptio 4.6 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Audio type | On board |

Mainboard

| | |
|----------------|----------------------------------------------------------------------------|
| Audio codec | Realtek ALC671 |
| Audio features | Internal speaker supports audio playback (optional), High Definition Audio |

I/O controller on board

| | |
|----------------------|------------------------------------------------------------------|
| Serial ATA total | 2 (1x mSATA, 1x SATA) |
| thereof SATA III | 2 |
| Controller functions | Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI |

Interfaces

| | |
|------------------------------|------------------------------------------|
| Audio: line-in | 1 |
| Audio: line-out | 1 |
| Front audio: microphone | 1 |
| Front audio: headphone | 1 |
| USB 2.0 total | 4 |
| USB 3.1 Gen1 (USB 3.0) total | 2 |
| USB front | 2x 3.0 |
| USB rear | 4x 2.0 |
| VGA | 1 (via optional DVI to VGA adapter) |
| DisplayPort | 1 |
| DVI | 1 (DVI-I) |
| Serial (RS-232) | 1 (9pin, 16 byte FIFO, 16550 compatible) |
| Mouse / Keyboard (PS/2) | 2 |
| Ethernet (RJ-45) | 1 |

Input device / components

| | |
|--------------------------|----------------------------------------------------|
| Input devices (optional) | Keyboard Mouse KBPC PX ECO Mouse M440 ECO |
|--------------------------|----------------------------------------------------|

Drive bays

| | |
|------------------------|---|
| Drive bays total | 1 |
| 2.5-inch internal bays | 1 |

Slots**Graphics**

| | |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Graphics brand name | AMD Radeon™ HD 8280E (in combination with AMD G-Series GX-217GA) |
| TFT resolution (VGA) | 1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel |
| TFT resolution (DVI) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel |

Graphics

| | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel (@30Hz) |
| Graphics features | Dual display support DirectX® 11.1 Shader Model 5 Open CL® 1.2 OpenGL® 4.1 HDCP support DisplayPort interface supports Ver. 1.2 incl. Multi-Stream |
| Graphics notes | Tested resolutions, depending on display type additional resolutions and frequencies possible Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz |

Electrical values

| | |
|-------------------------------------------|--------------------------|
| Rated voltage range | 100 V - 240 V (AC Input) |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 100 V - 240 V (AC Input) |
| Operating line frequency range | 50 Hz - 60 Hz |
| Max. output of single power supply | 40 W |

Power consumption

| | |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power consumption note | See white paper Energy Consumption |
| Link to Energy White Paper | http://docs.ts.fujitsu.com/dl.aspx?id=575b7359-854a-4222-9820-097afea72dac |

Heat dissipation

| | |
|-------------------------------|------------------------------------|
| Heat dissipation notes | See white paper Energy Consumption |
|-------------------------------|------------------------------------|

Dimensions / Weight / Environmental

| | |
|--------------------------------------|---------------------------------------------------|
| Dimensions (W x D x H) | 53 x 179 x 250 mm 2.1 x 7.1 x 9.8 inch |
| Operating position | Vertical / horizontal |
| Weight | 1,3 kg |
| Weight (lbs) | 2.9 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C |
| Operating relative humidity | 5 - 85 % (relative humidity) |

Compliance

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | ESPRIMO A525-L |
| Model | TCS-D3313B |
| Germany | TÜV GS |
| Europe | CE |
| USA/Canada | FCC Class B cCSAus |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) EPEAT® Gold (dedicated regions) ENERGY STAR® 6.0 (dedicated regions) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

Additional Software

| | |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional software (preinstalled) | Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) |

Manageability

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | Inventory Management BIOS Management Driver Management Security Management Alarm Management |
| Supported standards | DMI PXE WMI |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Security

| | |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Physical Security | Kensington Lock support |
| System and BIOS Security | Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces Optional: Trusted platform module (TPM 1.2) |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) |

Miscellaneous

| | |
|--|-------------------------------------------------|
| | Keyboard on (Special Fujitsu keyboard required) |
|--|-------------------------------------------------|

Packaging information

| | |
|------------------------|-----------------------------------------------------------------|
| Packaging notes | printed user documentation is bleached in chlorine free process |
|------------------------|-----------------------------------------------------------------|

Warranty

| | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Warranty period | 1 year |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |

Product Support Services - the perfect extension

| | |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Recommended Service | 9x5, Onsite Response Time: Next Business Day-duplicate |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

Recommended Accessories

Universal Monitor Stand



Save desk space without compromising performance or productivity with the Universal Monitor Stand that brings together a FUJITSU Desktop ESPRIMO Q mini PC or FUJITSU Thin Client FUTRO and a VESA compatible FUJITSU Display. For optimum ergonomics the height and tilt angle of the display can be adjusted, helping you to stay productive and comfortable, whilst hassle-free installation of the devices on the stand makes the life of your IT department easier.

Order Code:
S26361-F2601-L700

Keyboard KB900



The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO A525-L, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO A525-L, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH
Website: www.fujitsu.com/fts
2017-09-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH