

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO D956/E90+

Combines High Efficiency with Manageability

The FUJITSU ESPRIMO D956/E90+ Desktops provide highest manageability, performance and expandability. Its low noise design supports a pleasant working environment, and the 90% efficient power supply will reduce your energy bills. With its innovative Low Power Active Mode feature you are ready for instant communication in the modern office. The use of a common software load within the product series ensures perfect infrastructure compatibility. On retirement, the Fujitsu distinctive EraseDisk function securely wipes your data.

Quiet

Pleasant working environment due to an extremely quiet system

- Innovative hardware design and optimized cooling concept ensures silent operations

Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced your bill

- Innovative Low Power Active Mode and highly-efficient integrated power-supply

Energy efficiency and high performance

Low power consumption combined with high levels of performance

- 6th generation Intel® Core™ processor family, a switched monitor outlet and a power supply with 90% efficiency

System management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor) and DeskView manageability suite

Green technology

Another example of the Fujitsu commitment to environmental protection and sustainability

- Halogen-free printed circuit board of mainboard, sophisticated product concept for the entire lifecycle



Components

Processor	Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, **
	Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, **
	Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, **
	Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **
	Intel® Pentium® processor G4500 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 530) **
	Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **
	Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510) **
	Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) Intel® Smart Response Technology supported by Intel® Core™ i3, i5 and i7 processors **6th generation Intel® processor
Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional (available through downgrade rights from Windows 10 Pro)
Operating system compatible	Windows 8.1 Pro (available through downgrade rights from Windows 10 Pro) openSUSE Linux
Memory modules	
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
Hard disk drives (internal)	
	SSD PCIe, 1024 GB M.2 NVMe Highend module
	SSD PCIe, 512 GB M.2 NVMe Highend module
	SSD PCIe, 256 GB M.2 NVMe Highend module
	SSD SATA, 512 GB, M.2 module
	SSD SATA, 256 GB, M.2 module
	SSD SATA, 128 GB, M.2 module
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)

Graphics	VGA Extension Card
	NVIDIA® NVS™315 LP, 1 GB
	NVIDIA® GeForce® GTX 745 2 GB LP, 2 GB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DVI-I to VGA Adapter
	DP to DVI-D (single link) Adapter Cable
Drives (optional)	AMD® Radeon R7 340, 2 GB
	BD Triple Writer SATA ultra slim (tray)
	DVD Super Multi ultra slim (tray)
Interface add on cards/components (optional)	MultiCard Reader 24in1 USB 2.0 3.5"
	WLAN 802.11ac (2x2) PCIe x1 LP and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)
	WLAN 802.11ac (2x2) PCIe x1 LP (dedicated regions only)
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
Dual serial card PCIe x1	

Base unit

Base unit	ESPRIMO D956/E90+
Mainboard	
Mainboard type	D3432
Formfactor	proprietary
Chipset	Intel® Q170
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,133 MHz
Memory notes	Dual channel support For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS version	AMI Aptio V UEFI Specification 2.4
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	5
thereof SATA III	5
thereof eSATA	2

I/O controller on board

Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10
----------------------	---

Interfaces

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.1 Gen1 (USB 3.0) total	6
USB front	2x USB 2.0; 2x USB 3.0
USB rear	2x USB 2.0; 4x USB 3.0
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	1 ; optional: 2nd serial port (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	--

Drive bays

3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	5,25" bay: for slim optical disc drive only; internal 3.5" bay: 1x 3.5" drive (screwless) or 1x 2.5" drive (screws) or optional via adapter for 1x or 2x 2.5" drives (screws); external 3.5" bay: optional as internal 3.5" bay (screws)
M.2-2280	1 x on mainboard (for PCIe or SATA SSD modules)

Slots

PCI-Express 3.0 x16	1 x (174 mm / 6.85 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (174 mm / 6.85 inch) Low profile
PCI-Express x1	2 x (174 mm / 6.85 inch) Low profile

Graphics on board

Graphics brand name	Intel® HD Graphics 510, Intel® HD Graphics 530
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel

Graphics on board

TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 84% / 90% / 92% / 91%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=e8a363d3-a208-4673-b54a-2b833cee25b9

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 6700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level LwAd (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.4 B / 20 dB(A) Bystander; 24 dB(A) Operator position
Standard noise operation mode: HDD load	3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position

Noise emission

Standard noise operation mode: Idle mode	3.2 B / 18 dB(A) Bystander; 19 dB(A) Operator position
Standard noise operation mode: ODD load	4.4 B / 30 dB(A) Bystander; 35 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.2 B / 18 dB(A) Bystander; 19 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level L _{wad} (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.4 B = 34 dB (A)
Blue angel noise operation mode: Idle mode	3.3 B = 33 dB (A)
Blue angel noise operation mode: ODD load	4.5 B = 45 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	332 x 338 x 89 mm 12.68 x 13.31 x 3.51 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	8 kg
Weight (lbs)	17.64 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO D956/E90+
Model	DTF
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)
China	CCC (planned)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 11.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)

Security

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional)

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Thermal management
Low Power Active Mode
Extended lifetime

Serviceability

EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information

Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1180 g
Material - Weight (lbs) Carton	2.6 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g

Packaging information

Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Related Services - the perfect extension	
Recommended Service	X - 9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Mouse M440 ECO

Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:
S26381-K450-L200

SOUNDSYSTEM DS E2000 Air

The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

UC&C USB Value Headset

The FUJITSU UC&C USB Value Headset is a lightweight bi-aural full-size stereo headset with high wearing comfort. This Lync-tested USB-Headset has an appropriate Inline-Controller which supports easy call management. A noise cancelling microphone facilitates undisturbing clear phone calls.

Order Code:
S26391-F7139-L20

Keyboard KBPC PX ECO

Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**: country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D956/E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO D956/E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-01-11 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH