Fujitsu recommends Windows 8 Pro.

Data Sheet Fujitsu ESPRIMO E700 E85+ Desktop PC

Your Desktop PC Without Any Compromises

Fujitsu ESPRIMO E700 PCs bring you highly expandable technology for your challenging business applications. The use of identical components within the product family ensures perfect infrastructure compatibility and simplifies rollout. A 86%-efficient power supply will ensure environmental compliance for years to come. Intel® Standard Manageability keeps administration costs to a minimum. Plus, EraseDisk ensures secure system retirement.

Small form factor PC

- Flexible desktop solution whatever the space required
- Less than 13 liters volume, can be positioned vertically and horizontally

Energy Efficiency

- Low power consumption and low costs, without any loss in performance
- Sophistacted technology, low energy-consuming processors, up to 86% efficient power supply and enhanced power management settings

Green technology

- Fujitsu's contribution to environmental protection for the continued existence of our planet
- Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle

Quiet

- Pleasant working environment due to an extremely quiet system
- Innovative hardware design, optimized cooling concept ensures silent operations

Serviceability

- Easy to extend and optimal user-friendliness without any additional tools
- Easy access to all replaceable and expandable components







FUJITSU

Components

Processor	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000)		
10(230)	Intel® Core™ i3-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)		
	Intel [®] Pentium [®] processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel [®] HD Graphics)		
Operating systems			
Operating system	Windows® 7 Home Basic (EM) 32-bit		
	Windows [®] 7 Home Premium 64-bit		
	Windows® 7 Professional 32-bit		
	Windows® 7 Professional 64-bit		
Operating system compatible	openSUSE Linux		
	Windows Vista®		
	Windows® XP		
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via		
	http://support.ts.fujitsu.com		
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM		
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM		
Hard disk drives (internal)	SSD SATA III, 256 GB, 2.5-inch		
	SSD SATA III, 128 GB, 2.5-inch		
	SSD SATA II, 128 GB, 2.5-inch, FDE		
	mSATA, 16 GB, Flash drive		
	mSATA, 8 GB, Flash drive		
	mSATA, 4 GB, Flash drive		
	mSATA, 2 GB, Flash drive		
	mSATA, 1 GB, Flash drive		
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch		
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical		
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch		
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch		
	HDD SATA II, 7200 rpm, 320 GB, 2.5-inch		
	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch		
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery		
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, 512 MB		
	NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB		
	NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB		
	LFH59/ 2x DVI-I adapter cable		
	LFH59/ 2x DP adapter cable		
	DP to DVI-D (single link) Adapter Cable		
	2nd NVIDIA® Quadro® NVS 300 LP, 512 MB		
Drives (optional)	BD Triple Writer SATA slim (tray)		
	DVD-ROM		
	DVD Super Multi		
	MCR 24in1 & USB 3.0 front con., 3.5"		
	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch		
	MultiCard Reader 24in1 USB 2.0 3.5"		

Interface add on cards/components (optional)					
	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only)				
	Parallel Interface				
	Gigabit Ethernet PCle x1, DS				
	eSATA Interface				
	Dual serial card PCIe x1, powered				
	Dual serial card PCIe x1, powered				
Base unit	ESPRIMO E700 E85+				
Mainboard					
Mainboard type	D3061				
Formfactor	μΑΤΧ				
Chipset	Intel® Q65				
Processor socket	LGA 1155				
Processor quantity maximum	1				
Memory slots	4 DIMM (DDR3)				
Supported capacity RAM (max.)	32 GB				
Memory frequency	1333 MHz				
Memory notes	Dual channel support.				
	For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be				
	the same.				
	> 16 GB support with future memory modules				
LAN	10/100/1000 MBit/s Intel® 82579 V				
BIOS version	AMI Aptio 4.6				
BIOS features	BIOS Flash EPROM update by software				
	Recovery BIOS				
	Unified Extensible Firmware Interface (UEFI)				
Audio codec	Conexant CX20642				
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound				
I/O controller on board					
Serial ATA total	5				
thereof SATA III	1				
thereof eSATA	2 (optional)				
Controller functions	Serial ATA II (3 Gbit)				
	Serial ATA III (6 Gbit)				
	NCQ AHCI				
	AHU				
Interfaces					
Audio: line-in	1				
Audio: line-in / microphone	1				
Audio: line-out	1				
Front audio: microphone	1				
Front audio: headphone	1				
USB 2.0 total	14				
USB 3.0 total	optional				
USB front	4				
	8				
USB rear					
USB internal	2				
USB internal	2				
USB internal VGA	2 1 (via DVI to VGA adapter, part of shipment)				

Interfaces						
Mouse / Keyboard (PS/2)	2					
Ethernet (RJ-45)	1					
Parallel	1 (optional) (25pin with EPP and ECP)					
eSATA	1 (optional)					
Interface Module notes	Anytime USB charge functionality					
Input device / components						
input device / components	Optical USB tilt wheel mouse					
Input devices (optional)	Optical USB/PS2 tilt wheel mouse					
input derices (optional)	KBPC PX ECO					
	Mouse M440 ECO					
Drive bays						
Drive bays total	3					
3.5-inch internal bays	1					
3.5-inch external bays	1					
5.25-inch external bays	1					
Drive bay notes	optional external bay as internal 3,5"					
Slots						
PCI-Express 2.0 x16	1 x (200 mm / 7.87 inch) Low profile					
PCI-Express 2.0 x4 (mech. x16)	1 x (200 mm / 7.87 inch) Low profile					
PCI-Express x1	1 x (200 mm / 7.87 mm) Low profile					
PCI (32-bit / 33 MHz)	1 x (174 mm / 6.85 inch) Low profile					
Slots optional configuration	or 2x PCI full high via Riser					
Graphics on board						
Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)					
Shared video memory	up to 1759 MB					
TFT resolution (VGA)	1024 x 768 pixel					
	1280 x 1024 pixel 1360 x 768 pixel					
	1440 x 900 pixel					
	1600 x 900 pixel					
	1600 x 1200 pixel					
	1680 x 1050 pixel					
	1920 x 1080 pixel					
	1920 x 1200 pixel					
TFT resolution (DVI)	1360 x 768 pixel					
	1440 x 900 pixel					
	1600 x 900 pixel					
	1680 x 1050 pixel					
	1920 x 1080 pixel					
TET recelution (DisplayDest)	1920 x 1200 pixel					
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel					
	1600 x 900 pixel					
	1680 x 1050 pixel					
	1920 x 1080 pixel					
	1920 x 1200 pixel					
	2560 x 1440 pixel					
	2560 x 1600 pixel					
Graphics features	Dual display support					
	DirectX 10.1					
	HDCP support					
	OpenGL® 2.1					
	For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)					

Graphics on board	Tested recolutions, depending on display type additional resolutions and fragmentics preside		
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system		
	Resolution (color depth up to 32 Bit/pixel)		
	For TFT we recommend using 60Hz		
lectrical values			
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85%		
	0-Watt mode with hard-off switch		
Rated voltage range	100 V - 240 V		
Rated frequency range	50 Hz - 60 Hz		
Dperating voltage range	90 V - 264 V		
Derating line frequency range	47 Hz - 63 Hz		
Nax. output of single power supply	280 W		
Power factor correction/active power	active		
Monitor outlet	No		
Power consumption	Sao white paper Energy Concumption		
Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch		
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=99f7e49f-c7c3-45f0-8928-6f6092900926		
Heat dissipation			
Heat dissipation notes	See white paper Energy Consumption		
Noise for standard configuration (HDD,	ODD)		
Noise emission	According to ISO9296		
Related Processors for noise	Intel [®] Core™ i5 2400		
loise Operation mode 1: ODD load	4.0 B/ 27 dB(A)		
Blue angel requirement)			
Noise Operation mode 2: HDD load	3.5 B/ 20 dB(A)		
Blue angel requirement)			
Noise Operation mode 3: CPU 90% load	3.6 B/ 21 dB(A)		
Blue angel requirement)			
Noise Operation mode 4: High load	3.6 B/ 21 dB(A)		
Noise Operation mode 5: Office	3.5 B/ 20 dB(A)		
applications 2.0 dlo modo (Rluo Apgol requirement)	2 5 / 20 dp(A)		
dle mode (Blue Angel requirement) Noise notes / description	3.5 / 20 dB(A)		
יטוצי ווטנייט י מפארווףנוטוו	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position		
) Dimensions / Weight / Environmental			
Dimensions (W x D x H)	340 x 382 x 98 mm		
. ,	13.39 x 15.04 x 3.86 inch		
)perating position	horizontal / vertical (optional, feet needed)		
Veight	10 kg		
Veight (lbs)	22.05 lbs		
Veight notes	Actual weight may vary depending on configuration		
)perating ambient temperature	10 - 35°C (50 - 95°F)		
ompliance			
Product	ESPRIMO E700		
Nodel	DT8-3061		
Germany	D18-3061 TÜV GS		
Europe	CE		
-urohe	CE Nordic Swan		
USA/Canada	FCC Class B		
	cCSAus		

Compliance			
Compliance Global	RoHS (Restriction of hazardous substances)		
	WEEE (Waste electrical and electronic equipment)		
	Microsoft Operating Systems (HCT / HCL entry / WHQL)		
	ENERGY STAR®		
	EPEAT® Gold (dedicated regions)		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/		
Additional Software			
Additional software (preinstalled)	Nero Essentials S (burning software)		
	Fujitsu Recovery (Hard Disk Based Recovery)		
	Norton Internet Security (incl. Firewall) 60 days version		
	Don't forget Office.		
Additional software (optional)	Recovery DVD for Windows®		
	Drivers & Utilities DVD (DUDVD)		
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not		
	supported under Windows XP if the system runs on Intel onboard graphics)		
Miscellaneous			
	Keyboard on (Special Fujitsu keyboard required)		
	Thermal management		
	Extended lifetime		
Compatibility (references)			
	DMI 2.0		
	PC 2001		
	WMI 1.5		
	USB 2.0		
	SMBIOS		
Manageability			
Manageability technology	DeskUpdate Driver management		
	PXE 2.1 Boot code		
	Wake up from S5 (off mode)		
	Intrusion switch (optional) Intel® Standard Manageability		
	WoL (Wake on LAN)		
Manageability software	DeskView Client		
Manageability software	Deskview Chent DeskView Instant BIOS Management		
	Deskview instant bios Management DeskView Integration for Symantec Management Platform		
DeskView components	Inventory Management		
F	BIOS Management		
	Driver Management		
	Security Management		
	Alarm Management		
Manageability link	http://ts.fujitsu.com/manageability		
Security			
System protection	Kensington Lock support		
	Eye for padlock		
	Optional: Integrated cabinet lock		
Audit proof protection	EraseDisk (optional)		
	Boot sector virus protection		
	Write protect option for the Flash EPROM		
	Embedded security (TPM 1.2)		
	Control of all USB interfaces		
	External USB ports can be disabled separately		
	Control of external interfaces		

Converting .				
Security				
Access protection	User and supervisor BIOS password			
	Hard disk password			
	Optional: Access protection via external SmartCard reader			
	Optional: Access protection via internal SmartCard reader			
Serviceability				
	EasyFix			
	EasyChange for HDD			
	EasyChange for optical drives			
Packaging information				
Packaging dimension (mm)	467 x 265 x 540 mm			
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch			
Max. quantity / pallet	28			
Material - Weight (g) Carton	1140 g			
Material - Weight (lbs) Carton	2.51 lbs			
Material - Weight (g) EPS / PS	180 g			
Material - Weight (lbs) EPS / PS	0.4 lbs			
Material - Weight (g) PE	60 g			
Material - Weight (lbs) PE	0.13 lbs			
Packaging notes	printed user documentation is bleached in chlorine free process			
Warranty				
Standard Warranty	1 year			
Service level	Bring-In / On-Site Service (depending on country)			
Maintenance and Support Services - I	he perfect extension			
Recommended Service	5x9, Response Time: Next Business Day			
Spare Parts availability	5 years			
Service Weblink	http://www.fujitsu.com/fts/services/support/index.html			

Recommended Accessories

Wireless Keyboard Set LX900	0	The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.	S26381-K564-L4**(**: Country specific variation)
Keyboard KBPC PX ECO		Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.	S26381-K341-L1** (**: country specific variation)
SOUNDSYSTEM DS E2000 Air		The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
WebCam 130 HD2		With the most advanced HD (High Definition / 720p) recording feature and widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.	Order Code: S26391-F7136-L5

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use yourOpersonal computer for Voice over IP (VoIP) in stereo audio quality. ThisSpremium headset is designed to provide superb audio quality and comfortfor the telephony, internet chat, speech recognition, video conferencing andmultimedia applications.S

Order Code: S26391-F7139-L5

CELVIN[®] Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a Order Code: standard USB-interface for easy Plug & Play use with a notebook or PC. It is also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO E700 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E700 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/ about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2012-11-06 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their

own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions