

DATASHEET

FUJITSU ESPRIMO E7935 E85+ DESKTOP PC

YOUR DESKTOP WITHOUT COMPROMISES

ESPRIMO E7935 E85+

The ESPRIMO E7935 E85+ can be positioned vertically or horizontally - the ideal choice for any desk. Equipped with state-of-the-art Intel® technology, especially with regard to system management, this PC, made of environmentally-conscious material, operates reliably and quietly. It also has a power supply with up to 87% efficiency which significantly helps to protect the environment and reduce your costs. Why compromise between a good conscience and top-quality equipment when you can have both at the same time?



SMALL FORM FACTOR PC

Flexible desktop solution whatever the space required

- Less than 13 litres volume, can be positioned vertically and horizontally

ENVIRONMENTALLY COMPATIBLE PRODUCT

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free mainboard, sophisticated product concept for the entire lifecycle



SILENT OPERATION

Innovative hardware design, optimized cooling concept

- Pleasant working environment due to an extremely quiet system

SYSTEM MANAGEMENT



Easy system administration for complex IT infrastructure

- Intel® vPro™ technology

ENERGY SAVING

Low power consumption and low costs, without any loss in performance

- State-of-the-art technology, low energy-consuming processors, up to 87% efficient power supply and enhanced power management settings



COMPONENTS

PROCESSOR

Intel® Core™2 Quad processor Q9650 (4C/4T, 3.0 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9550 (4C/4T, 2.83 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9505 (4C/4T, 2.83 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9400 (4C/4T, 2.66 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Quad processor Q8300 (4C/4T, 2.5 GHz, 4 MB, 1333 MHz)
Intel® Core™2 Duo processor E8600 (2C/2T, 3.33 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8500 (2C/2T, 3.16 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8400 (2C/2T, 3.0 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E7600 (2C/2T, 3.06 GHz, 3 MB, 1066 MHz)
Intel® Core™2 Duo processor E7500 (2C/2T, 2.93 GHz, 3 MB, 1066 MHz)
Intel® Pentium® processor E6300 (2C/2T, 2.8 GHz, 2 MB, 1066 MHz)
Intel® Pentium® processor E5400 (2C/2T, 2.7 GHz, 2 MB, 800 MHz)
Intel® Pentium® processor E5200 (2C/2T, 2.5 GHz, 2 MB, 800 MHz)
Intel® Celeron® processor E3200 (2C/2T, 2.4 GHz, 1 MB, 800 MHz)
Intel® Celeron® processor 450 (1C/1T, 2.2 GHz, 512 KB, 800 MHz)

MEMORY MODULES

1 GB (1 module(s) 1 GB) DDR2, 800 MHz, PC2-6400, DIMM
2 GB (1 module(s) 2 GB) DDR2, 800 MHz, PC2-6400, DIMM
4 GB (1 module(s) 4 GB) DDR2, 800 MHz, PC2-6400, DIMM

HARD DISK DRIVES (INTERNAL)

SSD SATA, 128 GB, 2.5-inch
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.

Hard disk notes

Supporting NCQ and 3 GBit

GRAPHICS ADD ON CARDS (OPTIONAL)

Dual DVI Adapter
DVI Adapter
NVIDIA® Geforce® 9300GE display port low profile, 512 MB
NVIDIA® Geforce® 9300GE low profile, 256 MB
NVIDIA® Geforce® 9300GE low profile, 512 MB
NVIDIA® Geforce® 9500GS low profile, 512 MB
NVIDIA® Quadro NVS 290 low profile, 256 MB

MODULAR BAY OPTIONS

1.44 MB Floppy
Blu-ray Disc Triple Writer, SATA I
DVD-ROM, SATA I
DVD Super Multi, SATA I
MultiCard Reader 20in1, 3,5-Inch, USB 2.0

INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)

WLAN III, 802.11g/Draft-n (Windows only)
WLAN II, 802.11g, 54Mbps (Windows only)
Parallel Interface
Modem adapter kit (EU)
Modem 56k incl. RJ11 modem cable
Gigabit Ethernet PCIe x1
FireWire PCI-Card IEEE1394
eSATA Interface
Dual serial card PCI LP

Base unit	ESPRIMO E7935 E85+
MAINBOARD	
Mainboard type	D2828
Formfactor	proprietary
Chipset	Intel® Q45
Processor socket	LGA 775
Processor quantity maximum	1
System bus (FSB / HT / QPI)	up to 1333 MHz
Memory slots	DIMM (DDR2)
Supported capacity RAM (max.)	16 GB
Memory frequency	800 MHz
Memory notes	With future modules. Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1000 MBit/s Intel® 82567 LM
BIOS version	Phoenix 6.0
BIOS features	BIOS Flash EPROM update by software Recovery BIOS
Audio codec	Realtek ALC663
Audio features	Internal speaker supports audio playback, High Definition audio
I/O CONTROLLER ON BOARD	
Serial ATA total	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II NCQ and 3 GBit AHCI Raid 1/0
INTERFACES	
Audio: line-in	1
Audio: line-out	1
USB 2.0 total	12
USB front	2
USB rear	6
USB internal	4
VGA	1
DVI	optional
Serial (RS-232)	2 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	optional (25pin with EPP and ECP)
INPUT DEVICE / COMPONENTS	
	Optical USB tilt wheel mouse Optional: Optical USB/PS2 tilt wheel mouse
DRIVE BAYS	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
SLOTS	
PCI-Express 2.0 x16	1 x (210 mm) low profile
PCI-Express x4 (mech. x8)	1 x (210 mm) low profile
PCI (32-bit / 33 MHz)	2 x (190 mm) low profile

SLOTS	
Slots optional configuration	or 1x PCI Express x16 low profile (190mm) and via Riser 2 x PCI full height (174 / 210 mm)
GRAPHICS ON BOARD	
Graphics brand name	Intel® GMA 4500
Shared video memory	up to 256 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
Graphics features	DirectX 10
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
ELECTRICAL VALUES	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 84% / 87% / 85%) 0-Watt mode with hard-off switch
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of power supply	250 W
Power factor correction/active power	active
Monitor outlet	No
POWER CONSUMPTION	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=84deb1f1-9e16-46b5-803a-72b350ee565c
HEAT DISSIPATION	
Heat dissipation notes	See white paper Energy Consumption
NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	4.5 B / 30 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.5 B / 19 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.6 B / 20 dB(A)
Noise Operation mode 4: High load	3.8 B / 22 dB(A)
Noise Operation mode 5: Office applications	3.6 B / 20 dB(A)
Idle mode (Blue Angel requirement)	3.4 B / 18 dB(A)
Noise notes / description	A weighted sound power level L _{wad} (in B) / workplace related A-weighted sound pressure level L _{pAm} (in dB(A)), Bystander position
DIMENSIONS / WEIGHT / ENVIRONMENTAL	
Dimensions (W x D x H)	340 x 380 x 100 mm

DIMENSIONS / WEIGHT / ENVIRONMENTAL

Operating position	Vertical / horizontal (no feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C

COMPLIANCE

Product	ESPRIMO E7935
Model	DT7-2824
Germany	GS optional
Europe	CE Nordic Swan in progress
USA/Canada	FCC Class B UL cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

OPERATING SYSTEM

Operating system optional preinstalled	Microsoft® Windows® 7 Home Premium Microsoft® Windows® 7 Professional Microsoft® Windows Vista® Home Basic Microsoft® Windows Vista® Home Premium Microsoft® Windows Vista® Business 32-bit Microsoft® Windows Vista® Business 64-bit TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	Linux
Operating system notes	All Windows Vista® and Windows® 7 versions are Office 2007 ready.

ADDITIONAL SOFTWARE

Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive)

	Keyboard on (Fujitsu keyboard required) Thermal management
--	---

Spare part availability	5 years
--------------------------------	---------

COMPATIBILITY (REFERENCES)

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0
--	--

MANAGEABILITY

Manageability features	ASF 2.0 (Alert Standard Format) DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) PXE 2.1 Boot code BootP Boot Code including Bootmanage Administrator Software (tested) Wake up from S5 (off mode) Intrusion switch (optional) iAMT 5.0
Manageability type	DeskView 10.x client management including:

MANAGEABILITY

DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Advanced alerts (ASF implementation) Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
--------------------------	--

Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu
---------------------------	--

SECURITY

Physical security	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
--------------------------	---

System security	Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) - Infineon Control of all USB interfaces External USB ports can be disabled separately Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of external interfaces
------------------------	---

User security	User and supervisor BIOS password SystemLock 2 BIOS SmartCard Security Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader
----------------------	---

SERVICEABILITY

FlexySlot
EasyFix
EasyChange for HDD
EasyChange for optical drives

PACKAGING INFORMATION

Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (g) EPS / PS	230 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

WARRANTY**MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION**

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO E7935 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO E7935 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/ESPRIMO>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2010-02-01 CE-EN
