

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

Data Sheet

Fujitsu ESPRIMO E7936 E-Star5 Desktop PC

Your desktop without compromises

The ESPRIMO E7936 E-Star5 can be positioned vertically or horizontally - the ideal choice for any desk. Equipped with state-of-the-art Intel® technology, especially with regard to system management, this PC, made of environmentally-conscious material, operates reliably and quietly. Furthermore, this device is equipped with an efficient power supply (up to 87%) that already meets today's ENERGY STAR® criteria. Why compromise between a good conscience and top-quality equipment when you can have both at the same time?



Small form factor PC

Flexible desktop solution whatever the space required

- Less than 13 litres volume, can be positioned vertically and horizontally

Environmentally compatible product

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free mainboard, sophisticated product concept for the entire lifecycle

Silent operation

Innovative hardware design, optimized cooling concept

- Pleasant working environment due to an extremely quiet system



System management


Easy system administration for complex IT infrastructure

- Intel® vPro™ technology

ENERGY STAR®

Low power consumption and low costs, without any loss in performance

- Power supply with up to 87% efficiency and enhanced power management settings



Components

Processor	Intel® Core™2 Quad processor Q9550 (4 Cores / 4 Threads, 2.83 GHz, 12 MB, 1333 MHz) Intel® Core™2 Quad processor Q9505 (4 Cores / 4 Threads, 2.83 GHz, 6 MB, 1333 MHz) Intel® Core™2 Quad processor Q8300 (4 Cores / 4 Threads, 2.5 GHz, 4 MB, 1333 MHz) Intel® Core™2 Duo processor E8600 (2 Cores / 2 Threads, 3.33 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E8500 (2 Cores / 2 Threads, 3.16 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E8400 (2 Cores / 2 Threads, 3.0 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E7600 (2 Cores / 2 Threads, 3.06 GHz, 3 MB, 1066 MHz) Intel® Core™2 Duo processor E7500 (2 Cores / 2 Threads, 2.93 GHz, 3 MB, 1066 MHz) Intel® Pentium® processor E6600 (2 Cores / 2 Threads, 3.06 GHz, 2 MB, 1066 MHz) Intel® Pentium® processor E5800 (2 Cores / 2 Threads, 3.2 GHz, 2 MB, 800 MHz) Intel® Celeron® processor E3400 (2 Cores / 2 Threads, 2.6 GHz, 1 MB, 800 MHz)
Operating system	
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Buy Microsoft® Office 2010 to use the full-featured Office software on this PC. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	1 GB (1 module(s) 1 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
Hard disk drives (internal)	SSD SATA, 128 GB, 2.5-inch SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
Hard disk notes	Supporting NCQ and 3 GBit
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 290 low profile, 256 MB NVIDIA® GeForce® GT 420 NVIDIA® GeForce® 405 display port low profile, 512 MB DP to DVI-D (single link) Adapter Cable
Drives (optional)	1.44 MB Floppy Blu-ray Disc™ Triple Writer DVD-ROM DVD Super Multi MultiCard Reader 20in1, USB 2.0, 3.5-Inch MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch

**Interface add on cards/components
(optional)**

USB 3.0 PCIe x1
Parallel Interface
FireWire PCI-Card IEEE1394
eSATA Interface
Dual serial card PCI LP

Base unit ESPRIMO E7936 E-Star5

Mainboard

Mainboard type D3028
Formfactor proprietary
Chipset Intel® Q45
Processor socket LGA 775
Processor quantity maximum 1
System bus (FSB / HT / QPI) up to 1333 MHz
Memory slots 4 DIMM (DDR3)
Supported capacity RAM (max.) 16 GB
Memory frequency 1066 MHz
Memory notes Dual channel support.
For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN 10/100/1000 MBit/s Intel® 82567 LM
BIOS version Phoenix 6.0
BIOS features BIOS Flash EPROM update by software
Recovery BIOS
Audio codec Realtek ALC663
Audio features Internal speaker supports audio playback, High Definition audio

I/O controller on board

Serial ATA total 4
thereof eSATA 2 (optional)
Controller functions Serial ATA II
NCQ and 3 GBit
AHCI
Raid 1/0

Interfaces

Audio: line-in 1
Audio: line-out 1
Front audio: microphone 1
Front audio: headphone 1
USB 2.0 total 12
USB front 2
USB rear 6
USB internal 4
VGA 1
DisplayPort 1 (optional)
DVI 1 (optional)
Serial (RS-232) 2 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2) 2
Ethernet (RJ-45) 1
Parallel 1 (optional) (25pin with EPP and ECP)
Interface Module notes Anytime USB charge functionality

Input device / components

Optical USB tilt wheel mouse

Input device / components

Input devices (optional)	Optical USB/PS2 tilt wheel mouse
--------------------------	----------------------------------

Drive bays

Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"

Slots

PCI-Express 2.0 x16	1 x (210 mm) Low profile
PCI-Express x4 (mech. x8)	1 x (210 mm) Low profile
PCI (32-bit / 33 MHz)	2 x (190 mm) Low profile
Slots optional configuration	or 1x PCI Express x16 low profile (190mm) and via Riser 2 x PCI full height (174 / 210 mm)

Graphics on board

Graphics brand name	Intel® GMA 4500
---------------------	-----------------

Shared video memory	up to 1759 MB
---------------------	---------------

Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
--	-----------

Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
---	-----------

Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
---	-----------

TFT resolution (VGA)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel

TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel

TFT resolution (DisplayPort)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
	2560 x 1440 pixel
	2560 x 1600 pixel

Graphics features	DirectX 10
	HDCP support
	OpenGL® 2.0

Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 84% / 87% / 85%)
-----------------------	---

Rated voltage range	100 V - 240 V
---------------------	---------------

Rated frequency range	50 Hz - 60 Hz
-----------------------	---------------

Operating voltage range	90 V - 264 V
-------------------------	--------------

Operating line frequency range	47 Hz - 63 Hz
--------------------------------	---------------

Electrical values

Max. output of single power supply	250 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=a146abbb-e146-4056-8cb2-96fc71de8b71

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise for standard configuration (HDD, ODD, FDD)

Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	4.5 B / 30 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.5 B / 20 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.6 B / 20 dB(A)
Noise Operation mode 4: High load	3.8 B / 20 dB(A)
Noise Operation mode 5: Office applications	3.6 B / 20 dB(A)
Idle mode (Blue Angel requirement)	3.4 B / 20 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	340 x 380 x 100 mm
Operating position	Vertical / horizontal (no feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C

Compliance

Product	ESPRIMO E7936
Model	DT7-3028
Germany	Blauer Engel / Blue Angel GS optional
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 EPEAT® Silver (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink Power2Go BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 9 Essentials XL

Miscellaneous

Thermal management
Keyboard on (Special Fujitsu keyboard required)
Extended lifetime

Compatibility (references)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0
SMBIOS

Manageability**Manageability technology**

DeskUpdate Driver management
PXE 2.1 Boot code
Wake up from S5 (off mode)
Intrusion switch (optional)
iAMT 5.0

Manageability software

DeskView 10.x client management including:

DeskView components

On/Offline remote client management
Detailed system inventory management and reports
BIOS Management
Remote power management
System notifications
Advanced alerts (ASF implementation)
Security Remote Control
DeskView Helpdesk Integration
WoL (Wake on LAN)

Manageability link

<http://ts.fujitsu.com/manageability>
<http://www.altiris.com/fujitsu>

Security**System protection**

Kensington Lock support
Eye for padlock
Optional: Integrated cabinet lock

Audit proof protection

Boot sector virus protection
Write protect option for the Flash EPROM
Embedded security (TPM 1.2)
Control of all USB interfaces
External USB ports can be disabled separately
Boot protection for floppy disk / CD drive and write protection for floppy disk drive
Control of external interfaces

Access protection

User and supervisor BIOS password
SystemLock 2 BIOS SmartCard Security
Hard disk password
Optional: Access protection via external SmartCard reader
Optional: Access protection via internal SmartCard reader

Serviceability

FlexySlot
EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information**Packaging dimension**

500x290x540 mm

Max. quantity / pallet

24

Material - Weight (g) Carton

1270 g

Material - Weight (g) EPS / PS

230 g

Material - Weight (g) PE

appr. 60 g

Packaging information

Packaging notes printed user documentation is bleached in chlorine free process

Warranty

Standard Warranty 3 years

Service level Bring-In / On-Site Service (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service 5x9, Response Time: Next Business Day

Spare Parts availability 5 years

Service Weblink <http://ts.fujitsu.com/Supportservice>

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO E7936 E-Star5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E7936 E-Star5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/ESPRIMO>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2011-07-29 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions