

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO P557/E90+

Your Flexible and Economic PC

The FUJITSU ESPRIMO P557/E90+ Desktop provides high-quality computing for your daily office tasks. It supports attractive price points and delivers the continuity needed for daily operations. Your valuable business data is protected by the latest TPM controller and the Erasedisk option. To meet your specific hardware needs it can be either individually configured or customized.

High performance and best price/performance ratio

Powerful and cost-effective microtower

- 7th generation Intel® Core™ processor family

System management

The perfect answer to offload your IT administrators

- DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation – even during remote periods and after hours

Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and functionality tests - all under one roof in Germany

Lifecycle

Hardware continuity for long-lasting project requirements

- Managed lifecycle of up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- 90% energy efficient power supply



Components

Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system compatible	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Windows 7 Professional 64-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) openSUSE Linux (with 6th generation Intel® processors)
Operating system notes	Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see Microsoft Support Lifecycle. Downgrade to Microsoft Windows 7 Professional only available with 6th generation Intel® processor Certified for SUSE Enterprise Desktop Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .
	*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **6th generation Intel® processor
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)

Base unit

Base unit	ESPRIMO P557/E90+
Mainboard	
Mainboard type	D3500
Formfactor	proprietary
Chipset	Intel® H110
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,400 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Realtek RTL8111G
BIOS version	AMI Aptio V UEFI Specification 2.5
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound

I/O controller on board

Serial ATA total	3
thereof SATA III	3
thereof eSATA	1
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.1 Gen1 (USB 3.0) total	4
USB 3.1 Gen2 total	optional via add on card
USB front	2x USB 2.0; 2x USB 3.0; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay
USB rear	2x USB 2.0; 2x USB 3.0
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	--

Drive bays

Drive bays total	5
2.5-inch internal bays	1
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	5,25" bays: one bay in HH format, one bay for slim optical disc drive only
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)

Slots

PCI-Express 3.0 x16	1 x (240 mm / 9.45 inch) Full height
PCI-Express x1	2 x (174mm / 210 mm / 6.85 inch / 8.27 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics 510, Intel® HD Graphics 530, Intel® HD Graphics 610, Intel® HD Graphics 630
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel

Graphics on board

TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Dual display support DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 84% / 90% / 92% / 91%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=fd165ac0-ea00-4154-a747-fdb1e974e91e

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 7700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.7 B / 23 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: HDD load	3.9 B / 24 dB(A) Bystander; 28 dB(A) Operator position

Noise emission

Standard noise operation mode: Idle mode	3.7 B / 23 dB(A) Bystander; 26 dB(A) Operator position
Standard noise operation mode: ODD load	4.5 B / 31 dB(A) Bystander; 38 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.7 B / 23 dB(A) Bystander; 26 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level L _{wad} (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.8 B = 38 dB (A)
Blue angel noise operation mode: Idle mode	3.5 B = 35 dB (A)
Blue angel noise operation mode: ODD load	4.6 B = 46 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	180 x 304 x 375 mm 7.09 x 11.97 x 14.76 inch
Operating position	Vertical
Weight	7 kg
Weight (lbs)	15.50 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO P557/E90+
Model	MI6W
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)
China	CCC (planned) TPM 2.0 for China (optional)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)

Manageability

Security	
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1511) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional)
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required) Thermal management
Serviceability	
	EasyFix EasyChange for single 3.5" HDD (optional) EasyChange for optical drives
Packaging information	
Packaging dimension (mm)	439 x 296 x 499 mm
Packaging dimension (inch)	17.28 x 11.65 x 19.65 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1040 g
Material - Weight (lbs) Carton	2.29 lbs
Material - Weight (g) EPS / PS	165 g
Material - Weight (lbs) EPS / PS	0.36 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process
Warranty	
Warranty period	1 year (for countries in EMEA)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Display B24-9 TS



The FUJITSU Display B24-9 TS is a widescreen display with 1920 x 1080 Full HD resolution with a ultra-thin bezel housing. The monitor has a wide viewing angle that delivers consistent picture quality and DisplayView™ manageability software for further enhancing monitor features with a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1643-V160

Display P24-8 WE Neo



The FUJITSU Display P24-8 WE Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such Presence Sensor, Workplace Lighting Guide that promote the overall ergonomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.

Order Code:
S26361-K1647-V140

Wireless Mouse Touch WI910



The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:
S26381-K465-L100

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P557/E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P557/E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2020-03-25 EM-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH