

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO P557/power

### Your Flexible and Economic PC

The FUJITSU ESPRIMO P557/power Desktop provides high-quality computing for your daily office tasks. It supports attractive price points and delivers the continuity needed for daily operations. Your valuable business data is protected by the latest TPM controller and the Erasedisk option. To meet your specific hardware needs it can be either individually configured or customized.

#### High performance and best price/performance ratio

Powerful and cost-effective microtower

- 7th generation Intel® Core™ processor family

#### System management

The perfect answer to offload your IT administrators

- DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation – even during remote periods and after hours

#### Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and functionality tests - all under one roof in Germany

#### Lifecycle

Hardware continuity for long-lasting project requirements

- Managed lifecycle of up to 12 months

#### Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- Higher output power and 90% energy efficient power supply



# Components

|   |   |
|---|---|
| <b>Processor</b>  | Intel® Core™ i7-7700 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.2 GHz, 8 MB, Intel® HD Graphics 630) *   |
|   | Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, **   |
|   | Intel® Core™ i5-7600 processor (4 Cores / 4 Threads, 3.50 GHz, up to 4.1 GHz, 6 MB, Intel® HD Graphics 630) *   |
|   | Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) *   |
|   | Intel® Core™ i5-7400 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 6 MB, Intel® HD Graphics 630) *   |
|   | Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, **   |
|   | Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, **   |
|   | Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, **   |
|   | Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630)  |
|   | Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **   |
|   | Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **  |
|   | Intel® Pentium® Gold G4560 processor (2 Cores / 4 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 610)  |
|   | Intel® Celeron® processor G3930 (2 Cores / 2 Threads, 2.90 GHz, 2 MB, Intel® HD Graphics 610)   |
|   | Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510) **  |
| *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) |   |
| **6th generation Intel® processor   |   |
| <b>Operating systems</b>  |   |
| <b>Operating system pre-installed</b>   | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home<br>Windows 7 Professional 64-bit pre-installed (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) |
| <b>Operating system compatible</b>  | Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors)<br>openSUSE Linux (with 6th generation Intel® processors)                              |
| <b>Operating system notes</b>   | Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see Microsoft Support Lifecycle.                                 |
| <b>Memory modules</b>   |   |
|   | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM   |
|   | 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM   |
|   | 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM   |
|   | 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM   |
| <b>Hard disk drives (internal)</b>  |   |
|   | SSD PCIe, 1024 GB M.2 NVMe module   |
|   | SSD PCIe, 512 GB M.2 NVMe module  |
|   | SSD PCIe, 256 GB M.2 NVMe module  |
|   | SSD PCIe, 128 GB M.2 NVMe module  |
|   | SSD SATA III, 512 GB, 2.5-inch  |
|   | SSD SATA III, 256 GB, 2.5-inch  |
|   | SSD SATA III, 128 GB, 2.5-inch  |
|   | SSD SATA III, 512 GB, 2.5-inch, SED   |
|   | SSD SATA III, 256 GB, 2.5-inch, SED   |
|   | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical  |
|   | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch   |
|   | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch   |
|   | HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch   |
|   | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch  |

|   |   |
|---|---|
| <b>Hard disk notes</b>                              | Up to 20 GB of HDD space is reserved for system recovery<br>SSHD (Solid State Hard Disk, Hybrid drive)<br>SSD (Solid State Disk)<br>SED (Self-Encrypting Drive)   |
| <b>Graphics</b>                                     | VGA Extension Card<br>NVIDIA® Quadro® P400 , 2 GB<br>NVIDIA® NVS™ 315, 1 GB<br>NVIDIA® GeForce® GTX 745 2 GB FH, 2 GB<br>LFH59/ 2x DVI-I adapter cable<br>LFH59/ 2x DP adapter cable<br>DVI-I to VGA Adapter<br>DP to DVI-D (single link) Adapter Cable<br>AMD® Radeon RX 460, 4 GB<br>AMD® Radeon R7 340, 2 GB |
| <b>Drives (optional)</b>                            | BD Triple Writer SATA ultra slim (tray)<br>DVD-ROM<br>DVD Super Multi<br>DVD Super Multi ultra slim (tray)<br>MultiCard Reader 24in1 USB 2.0 3.5"   |
| <b>Interface add on cards/components (optional)</b> | WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)<br>WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)<br>Gigabit Ethernet PCIe x1<br>Dual serial card PCIe x1   |

## Base unit

|                                      |  |
|--------------------------------------|--|
| <b>Base unit</b>                     | ESPRIMO P557/power   |
| <b>Mainboard</b>                     |  |
| <b>Mainboard type</b>                | D3500  |
| <b>Formfactor</b>                    | proprietary  |
| <b>Chipset</b>                       | Intel® H110  |
| <b>Processor socket</b>              | LGA 1151   |
| <b>Processor quantity maximum</b>    | 1  |
| <b>Supported capacity RAM (max.)</b> | 32 GB  |
| <b>Memory slots</b>                  | 2 DIMM (DDR4)  |
| <b>Memory frequency</b>              | 2,400 MHz  |
| <b>Memory notes</b>                  | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.        |
| <b>LAN</b>                           | 10/100/1,000 MBit/s Realtek RTL8111G   |
| <b>BIOS version</b>                  | AMI Aptio V<br>UEFI Specification 2.5  |
| <b>BIOS features</b>                 | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)<br>CSM (Compatibility Support Module) |
| <b>Audio type</b>                    | On board   |
| <b>Audio codec</b>                   | Realtek ALC671   |
| <b>Audio features</b>                | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound   |

**I/O controller on board**

|                      |  |
|----------------------|--|
| Serial ATA total     | 3                                      |
| thereof SATA III     | 3                                      |
| thereof eSATA        | 1                                      |
| Controller functions | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI |

**Interfaces**

|                              |  |
|------------------------------|--|
| Audio: line-in               | 1  |
| Audio: line-out              | 1  |
| Front audio: microphone      | 1  |
| Front audio: headphone       | 1  |
| USB 2.0 total                | 6  |
| USB 3.1 Gen1 (USB 3.0) total | 4  |
| USB 3.1 Gen2 total           | optional via add on card   |
| USB front                    | 2x USB 2.0; 2x USB 3.0; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay |
| USB rear                     | 2x USB 2.0; 2x USB 3.0   |
| USB internal                 | 2x USB 2.0   |
| VGA                          | optional: via adapter card   |
| DisplayPort                  | 1  |
| DVI                          | 1 (DVI-D)  |
| Mouse / Keyboard (PS/2)      | 2  |
| Ethernet (RJ-45)             | 1  |
| eSATA                        | 1 (optional)   |
| Interface Module notes       | Anytime USB charge functionality   |

**Input device / components**

|                          |  |
|--------------------------|--|
| Input devices (optional) | Keyboard<br>Mouse<br>KBPC PX ECO<br>Mouse M440 ECO |
|--------------------------|--|

**Drive bays**

|                         |  |
|-------------------------|--|
| Drive bays total        | 5  |
| 2.5-inch internal bays  | 1  |
| 3.5-inch internal bays  | 1  |
| 3.5-inch external bays  | 1  |
| 5.25-inch external bays | 2  |
| Drive bay notes         | 5,25" bays: one bay in HH format, one bay for slim optical disc drive only |
| M.2-2280                | 1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)                |

**Slots**

|                     |  |
|---------------------|--|
| PCI-Express 3.0 x16 | 1 x (240 mm / 9.45 inch) Full height                     |
| PCI-Express x1      | 2 x (174mm / 210 mm / 6.85 inch / 8.27 inch) Full height |

**Graphics on board**

|                      |  |
|----------------------|--|
| Graphics brand name  | Intel® HD Graphics 510, Intel® HD Graphics 530, Intel® HD Graphics 610, Intel® HD Graphics 630   |
| Shared video memory  | up to 1,782 MB   |
| TFT resolution (VGA) | 1,024 x 768 pixel<br>1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,600 x 1,200 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel |

**Graphics on board**

|                                     |   |
|-------------------------------------|---|
| <b>TFT resolution (DVI)</b>         | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel   |
| <b>TFT resolution (DisplayPort)</b> | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel<br>2,560 x 1,440 pixel<br>2,560 x 1,600 pixel<br>3,440 x 1,440 pixel<br>3,840 x 2,160 pixel<br>4,096 x 2,304 pixel  |
| <b>Graphics features</b>            | Dual display support<br>DirectX® 12<br>HDCP support<br>OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)<br>OpenGL® 4.4<br>One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter<br>For multi monitoring mode, graphics card and integrated graphics run in parallel<br>DisplayPort interface supports Ver. 1.2 incl. Multi-Stream<br>DVI-D interface supports audio output for HDMI monitors |
| <b>Graphics notes</b>               | up to 1 GB dedicated video memory (main memory owned and locked for graphics use)<br>Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size and operating system<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz  |

**Electrical values**

|   |  |
|---|--|
| <b>Power efficiency note</b>                | power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 83% / 89% / 91% / 90% |
| <b>Rated voltage range</b>                  | 100 V - 240 V  |
| <b>Rated frequency range</b>                | 50 Hz - 60 Hz  |
| <b>Operating voltage range</b>              | 90 V - 264 V   |
| <b>Operating line frequency range</b>       | 47 Hz - 63 Hz  |
| <b>Max. output of single power supply</b>   | 400 W  |
| <b>Power factor correction/active power</b> | active   |
| <b>Power supply output</b>                  | 1 graphics power rail (6pin connector)   |
| <b>Monitor outlet</b>                       | No   |

**Power consumption**

|                                   |   |
|-----------------------------------|---|
| <b>Power consumption note</b>     | See white paper Energy Consumption  |
| <b>Link to Energy White Paper</b> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=86389870-a666-4ca7-987f-828a14cc3f9f">http://docs.ts.fujitsu.com/dl.aspx?id=86389870-a666-4ca7-987f-828a14cc3f9f</a> |

**Heat dissipation**

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>Heat dissipation notes</b> | See white paper Energy Consumption |
|-------------------------------|------------------------------------|

**Noise emission**

|  |  |
|--|--|
| <b>Related Processors for noise</b>                | Intel® Core™ i7 7700   |
| <b>Standard noise emission</b>                     | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   |
| <b>Standard noise notes / description</b>          | A-weighted sound power level LwAd (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| <b>Standard noise operation mode: CPU 50% load</b> | 3.7 B / 23 dB(A) Bystander; 25 dB(A) Operator position   |

**Noise emission**

|  |   |
|--|---|
| Standard noise operation mode: HDD load                | 3.9 B / 24 dB(A) Bystander; 28 dB(A) Operator position              |
| Standard noise operation mode: Idle mode               | 3.7 B / 23 dB(A) Bystander; 26 dB(A) Operator position              |
| Standard noise operation mode: ODD load                | 4.5 B / 31 dB(A) Bystander; 38 dB(A) Operator position              |
| Standard noise operation mode: Office applications 2.0 | 3.7 B / 23 dB(A) Bystander; 26 dB(A) Operator position              |
| Blue angel noise emission according certification      | According to ISO 7779:2010, ECMA-74 for max. possible configuration |
| Blue angel noise notes / description                   | A-weighted sound power level L <sub>wad</sub> (in B); 1B = 10dB     |
| Blue angel noise operation mode: HDD load              | 3.8 B = 38 dB (A)   |
| Blue angel noise operation mode: Idle mode             | 3.5 B = 35 dB (A)   |
| Blue angel noise operation mode: ODD load              | 4.6 B = 46 dB (A)   |

**Dimensions / Weight / Environmental**

|                               |   |
|-------------------------------|---|
| Dimensions (W x D x H)        | 180 x 304 x 375 mm<br>7.09 x 11.97 x 14.76 inch   |
| Operating position            | Vertical  |
| Weight                        | 7 kg  |
| Weight (lbs)                  | 15.50 lbs   |
| Weight notes                  | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F)                           |
| Operating relative humidity   | 5 - 85 % (relative humidity)                      |

**Compliance**

|                 |   |
|-----------------|---|
| Product         | ESPRIMO P557/power  |
| Model           | MI6W  |
| Germany         | TÜV GS  |
| Europe          | CE  |
| USA/Canada      | FCC Class B<br>cCSAus   |
| Global          | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>ENERGY STAR® 6.1 (dedicated regions)<br>EPEAT® Gold (dedicated regions) |
| China           | CCC (planned)<br>TPM 2.0 for China (optional)   |
| Compliance link | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |

**Additional Software**

|                                    |   |
|------------------------------------|---|
| Additional software (preinstalled) | Adobe® Reader® (pdf reader)<br>McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version)<br>Microsoft Office (buy license to activate the pre-installed Microsoft Office) |
| Additional software (optional)     | Recovery DVD for Windows®<br>Drivers & Utilities DVD (DUDVD)<br>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)<br>CyberLink PowerDVD DVD (playback software for DVD)<br>Nero Essentials XL         |

**Manageability**

|                                 |  |
|---------------------------------|--|
| <b>Manageability technology</b> | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode)<br>Intrusion switch (optional)<br>WoL (Wake on LAN)  |
| <b>Manageability software</b>   | DeskView Client<br>DeskView Instant BIOS Management  |
| <b>DeskView components</b>      | BIOS Management incl. Security<br>Inventory Management<br>Driver Management<br>Alarm Management  |
| <b>Supported standards</b>      | DMI (Desktop Management Interface)<br>SMBIOS (System Management BIOS)<br>PXE (Preboot Execution Environment)<br>WMI (Windows Management Instrumentation)<br>WBEM (Web Based Enterprise Management)<br>CIM (Common Information Model) |

**Security**

|                                 |  |
|---------------------------------|--|
| <b>Physical Security</b>        | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional)<br>Cable Cover (optional; covers and secures the ports and cables on rear side)   |
| <b>System and BIOS Security</b> | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1511)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces |
| <b>User Security</b>            | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  |
| <b>Workplace Embedded Tools</b> | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server (optional)<br>Easy PC Protection (optional)  |

**Miscellaneous**

Keyboard on (Special Fujitsu keyboard required)  
Thermal management

**Serviceability**

EasyFix  
EasyChange for one HDD  
EasyChange for optical drives

**Packaging information**

|   |                            |
|---|----------------------------|
| <b>Packaging dimension (mm)</b>         | 439 x 296 x 499 mm         |
| <b>Packaging dimension (inch)</b>       | 17.28 x 11.65 x 19.65 inch |
| <b>Max. quantity / pallet</b>           | 24                         |
| <b>Material - Weight (g) Carton</b>     | 1040 g                     |
| <b>Material - Weight (lbs) Carton</b>   | 2.29 lbs                   |
| <b>Material - Weight (g) EPS / PS</b>   | 165 g                      |
| <b>Material - Weight (lbs) EPS / PS</b> | 0.36 lbs                   |
| <b>Material - Weight (g) PE</b>         | 60 g                       |
| <b>Material - Weight (lbs) PE</b>       | 0.13 lbs                   |




**Packaging information**

|                        |   |
|------------------------|---|
| <b>Packaging notes</b> | If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process |
|------------------------|---|

**Warranty**

|   |  |
|---|--|
| <b>Warranty period</b>                                  | 1 year (for countries in EMEA)   |
| <b>Warranty type</b>                                    | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations) |
| <b>Warranty Terms &amp; Conditions</b>                  | <a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>                          |
| <b>Product Related Services - the perfect extension</b> |  |
| <b>Recommended Service</b>                              | - 9x5, Onsite Response Time: Next Business Day   |
| <b>Spare Parts availability</b>                         | 5 years after end of product life  |
| <b>Service Weblink</b>                                  | <a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>                |

## Recommended Accessories

|                                    |   |  |  |
|------------------------------------|---|--|--|
|                                    |   |  | Order Code:<br>BDL:BFS-B24-8-TE                      |
| <b>Display B24-8 TE Pro</b>        |   | The FUJITSU Display B24-8 TE Pro is made for intensive office work. With visual and mechanical ergonomics this marble-grey display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity. | Order Code:<br>S26361-K1577-V140                     |
| <b>Wireless Mouse Touch WI910</b>  |  | The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.   | Order Code:<br>S26381-K465-L100                      |
| <b>Wireless Keyboard Set LX901</b> |  | The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption.  | S26381-K565-L4** (**:<br>Country specific variation) |



## More information

### Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P557/power, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about FUJITSU Desktop ESPRIMO P557/power, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

© 2017 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2018-07-04 EM-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2017 Fujitsu Technology Solutions GmbH