

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO P757/E94+

### Excellent Performance, Expandability and Efficiency

The FUJITSU ESPRIMO P757/E94+ Desktop provides high expandability and solid performance for your challenging business applications. The use of a common software load within the product series ensures perfect infrastructure compatibility and simplifies roll outs. Its 94%-efficient power supply will ensure environmental compliance for years to come. With its innovative Low Power Active Mode feature you are ready for instant communication in the modern office. Intel® Standard Manageability keeps administration costs low. Finally, EraseDisk ensures secure system retirement.

#### Quiet

Pleasant working environment due to an extremely quiet system

- Innovative hardware design, optimized cooling concept ensures silent operations

#### Always Available Office PC - stay connected and save power

Reduce power consumption and costs without sacrificing performance

- Latest technology, switched monitor outlet, low energy-consuming processors and enhanced power management settings

#### Best energy efficiency coupled with high performance

Low power consumption combined with high levels of performance

- 7th generation Intel® Core™ processor family, a switched monitor outlet and a power supply with 94% efficiency

#### Green technology

Another example of the Fujitsu commitment to environmental protection and sustainability

- Halogen-free printed circuit board of mainboard, sophisticated product concept for the entire lifecycle

#### Serviceability

Easy to extend and optimal user-friendliness without any additional tools

- Easy access to all replaceable and expandable components



# Components

| <b>Operating systems</b>              |  |
|---------------------------------------|--|
| <b>Operating system pre-installed</b> | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home  |
| <b>Operating system compatible</b>    | Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors)<br>Windows 7 Professional 64-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors)   |
| <b>Operating system notes</b>         | Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see Microsoft Support Lifecycle.<br>Downgrade to Microsoft Windows 7 Professional only available with 6th generation Intel® processor<br>Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> . |
| <b>Processor</b>                      |  |
|                                       | Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, **  |
|                                       | Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) *  |
|                                       | Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, **  |
|                                       | Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630)   |
|                                       | Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **  |
|                                       | *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)  |
|                                       | **6th generation Intel® processor  |
| <b>Memory modules</b>                 |  |
|                                       | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM  |
|                                       | 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM  |
|                                       | 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM  |
|                                       | 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM  |
| <b>Hard disk drives (internal)</b>    |  |
|                                       | SSD PCIe, 1024 GB M.2 NVMe Highend module  |
|                                       | SSD PCIe, 512 GB M.2 NVMe Highend module   |
|                                       | SSD PCIe, 256 GB M.2 NVMe Highend module   |
|                                       | SSD PCIe, 1024 GB M.2 NVMe module  |
|                                       | SSD PCIe, 512 GB M.2 NVMe module   |
|                                       | SSD PCIe, 256 GB M.2 NVMe module   |
|                                       | SSD PCIe, 128 GB M.2 NVMe module   |
|                                       | SSD SATA, 512 GB, M.2 module   |
|                                       | SSD SATA, 256 GB, M.2 module   |
|                                       | SSD SATA, 128 GB, M.2 module   |
|                                       | SSD SATA III, 512 GB, 2.5-inch   |
|                                       | SSD SATA III, 256 GB, 2.5-inch   |
|                                       | SSD SATA III, 128 GB, 2.5-inch   |
|                                       | SSD SATA III, 512 GB, 2.5-inch, SED  |
|                                       | SSD SATA III, 256 GB, 2.5-inch, SED  |
|                                       | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical   |
|                                       | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch  |
|                                       | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch  |
|                                       | HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch  |
|                                       | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch   |

|   |  |
|---|--|
| <b>Hard disk notes</b>                              | Up to 20 GB of HDD space is reserved for system recovery<br>SSHD (Solid State Hard Disk, Hybrid drive)<br>SSD (Solid State Disk)<br>SED (Self-Encrypting Drive)  |
| <b>Graphics</b>                                     | VGA Extension Card<br>NVIDIA® Quadro® P400 , 2 GB<br>DVI-I to VGA Adapter<br>DP to DVI-D (single link) Adapter Cable<br>AMD® Radeon R7 340, 2 GB   |
| <b>Drives (optional)</b>                            | BD Triple Writer SATA ultra slim (tray)<br>DVD-ROM<br>DVD Super Multi<br>DVD Super Multi ultra slim (tray)<br>MultiCard Reader 24in1 USB 2.0 3.5"  |
| <b>Interface add on cards/components (optional)</b> | WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)<br>WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)<br>Parallel Interface<br>eSATA Interface<br>Dual serial card PCIe x1 |

## Base unit

|                                      |  |
|--------------------------------------|--|
| <b>Base unit</b>                     | ESPRIMO P757/E94+  |
| <b>Mainboard</b>                     |  |
| <b>Mainboard type</b>                | D3501  |
| <b>Formfactor</b>                    | proprietary  |
| <b>Chipset</b>                       | Intel® Q250  |
| <b>Processor socket</b>              | LGA 1151   |
| <b>Processor quantity maximum</b>    | 1  |
| <b>Supported capacity RAM (max.)</b> | 64 GB  |
| <b>Memory slots</b>                  | 4 DIMM (DDR4)  |
| <b>Memory frequency</b>              | 2,400 MHz  |
| <b>Memory notes</b>                  | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.<br>DDR4 2,400 MHz will be clocked with 2,133 MHz in combination with 6th generation Intel® processor |
| <b>LAN</b>                           | 10/100/1,000 MBit/s Intel® I219V   |
| <b>BIOS version</b>                  | AMI Aptio V<br>UEFI Specification 2.5  |
| <b>BIOS features</b>                 | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)<br>CSM (Compatibility Support Module)   |
| <b>Audio type</b>                    | On board   |
| <b>Audio codec</b>                   | Realtek ALC671   |
| <b>Audio features</b>                | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound   |
| <b>I/O controller on board</b>       |  |
| <b>Serial ATA total</b>              | 5  |
| <b>thereof SATA III</b>              | 5  |

**I/O controller on board**

|                      |  |
|----------------------|--|
| thereof eSATA        | 2                                      |
| Controller functions | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI |

**Interfaces**

|                              |  |
|------------------------------|--|
| Audio: line-in               | 1  |
| Audio: line-out              | 1  |
| Front audio: microphone      | 1  |
| Front audio: headphone       | 1  |
| USB 2.0 total                | 5  |
| USB 3.1 Gen1 (USB 3.0) total | 7  |
| USB 3.1 Gen2 total           | optional via add on card   |
| USB front                    | 2x USB 2.0; 2x USB 3.0; 1x USB 3.1 Type C (Gen1); optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay |
| USB rear                     | 2x USB 2.0; 4x USB 3.0; optional: 1x USB 3.1 Type C (Gen2) via add on card   |
| USB internal                 | 1x USB 2.0   |
| VGA                          | optional: via adapter card   |
| DisplayPort                  | 2  |
| DVI                          | 1 (DVI-D)  |
| Serial (RS-232)              | optional: first and 2nd serial port (9pin, 16 byte FIFO, 16550 compatible)   |
| Mouse / Keyboard (PS/2)      | 2  |
| Ethernet (RJ-45)             | 1  |
| Parallel                     | 1 (optional) (25pin with EPP and ECP)  |
| eSATA                        | 1 (optional)   |
| Interface Module notes       | Anytime USB charge functionality, USB Typ C connector supports up to 15W   |

**Input device / components**

|                          |   |
|--------------------------|---|
| Input devices (optional) | Keyboard<br>Mouse<br>KBPC PX ECO<br>Mouse M440 ECO  |
| Drive bays total         | 6   |
| 2.5-inch internal bays   | 1   |
| 3.5-inch internal bays   | 2   |
| 3.5-inch external bays   | 1   |
| 5.25-inch external bays  | 2   |
| Drive bay notes          | 5,25" bays: one bay in HH format, one bay for slim optical disc drive only;<br>internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless).<br>drive cage for external 3.5" bay and internal 2.5" bay: optional |
| M.2-2280                 | 1 x on mainboard (for PCIe or SATA SSD modules)   |

**Slots**

|                                |  |
|--------------------------------|--|
| PCI-Express 3.0 x16            | 1 x (240 mm / 9.45 inch) Full height                     |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (210 mm / 8.27 inch) Full height                     |
| PCI-Express x1                 | 2 x (174mm / 210 mm / 6.85 inch / 8.27 inch) Full height |

**Graphics on board**

|                     |  |
|---------------------|--|
| Graphics brand name | Intel® HD Graphics 510, Intel® HD Graphics 530, Intel® HD Graphics 610, Intel® HD Graphics 630 |
| Shared video memory | up to 1,782 MB   |

**Graphics on board**

|                                     |   |
|-------------------------------------|---|
| <b>TFT resolution (VGA)</b>         | 1,024 x 768 pixel<br>1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,600 x 1,200 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel  |
| <b>TFT resolution (DVI)</b>         | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel   |
| <b>TFT resolution (DisplayPort)</b> | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel<br>2,560 x 1,440 pixel<br>2,560 x 1,600 pixel<br>3,440 x 1,440 pixel<br>3,840 x 2,160 pixel<br>4,096 x 2,304 pixel  |
| <b>Graphics features</b>            | Support for up to three independent displays<br>DirectX® 12<br>HDCP support<br>OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)<br>OpenGL® 4.4<br>One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter<br>For multi monitoring mode, graphics card and integrated graphics run in parallel<br>DisplayPort interface supports Ver. 1.2 incl. Multi-Stream<br>DVI-D interface supports audio output for HDMI monitors |
| <b>Graphics notes</b>               | up to 1 GB dedicated video memory (main memory owned and locked for graphics use)<br>Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size and operating system<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz  |

**Electrical values**

|   |  |
|---|--|
| <b>Power efficiency note</b>                | power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 86% / 90% / 94% / 93% |
| <b>Rated voltage range</b>                  | 100 V - 240 V  |
| <b>Rated frequency range</b>                | 50 Hz - 60 Hz  |
| <b>Operating voltage range</b>              | 90 V - 264 V   |
| <b>Operating line frequency range</b>       | 47 Hz - 63 Hz  |
| <b>Max. output of single power supply</b>   | 280 W  |
| <b>Power factor correction/active power</b> | active   |
| <b>Monitor outlet</b>                       | Switched   |

**Power consumption**

|                                   |   |
|-----------------------------------|---|
| <b>Power consumption note</b>     | See white paper Energy Consumption  |
| <b>Link to Energy White Paper</b> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=6897af28-0a61-4918-a9df-66328510db2d">http://docs.ts.fujitsu.com/dl.aspx?id=6897af28-0a61-4918-a9df-66328510db2d</a> |

**Heat dissipation**

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>Heat dissipation notes</b> | See white paper Energy Consumption |
|-------------------------------|------------------------------------|

**Noise emission**

|                                     |                      |
|-------------------------------------|----------------------|
| <b>Related Processors for noise</b> | Intel® Core™ i7 7700 |
|-------------------------------------|----------------------|

**Noise emission**

|   |  |
|---|--|
| <b>Standard noise emission</b>                                | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   |
| <b>Standard noise notes / description</b>                     | A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)) |
| <b>Standard noise operation mode: CPU 50% load</b>            | 3.5"-HDD: 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   |
| <b>Standard noise operation mode: HDD load</b>                | 3.5"-HDD: 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position   |
| <b>Standard noise operation mode: Idle mode</b>               | 3.5"-HDD: 3.3 B / 20 dB(A) Bystander; 20 dB(A) Operator position   |
| <b>Standard noise operation mode: ODD load</b>                | 3.5"-HDD: 4.6 B / 32 dB(A) Bystander; 38 dB(A) Operator position   |
| <b>Standard noise operation mode: Office applications 2.0</b> | 3.5"-HDD: 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   |
| <b>Blue angel noise emission according certification</b>      | According to ISO 7779:2010, ECMA-74<br>for max. possible configuration   |
| <b>Blue angel noise notes / description</b>                   | A-weighted sound power level L <sub>wad</sub> (in B); 1B = 10dB  |
| <b>Blue angel noise operation mode: HDD load</b>              | 3.6 B = 36 dB (A)  |
| <b>Blue angel noise operation mode: Idle mode</b>             | 3.3 B = 33 dB (A)  |
| <b>Blue angel noise operation mode: ODD load</b>              | 4.5 B = 45 dB (A)  |

**Dimensions / Weight / Environmental**

|                                      |   |
|--------------------------------------|---|
| <b>Dimensions (W x D x H)</b>        | 180 x 304 x 375 mm<br>7.09 x 11.97 x 14.76 inch   |
| <b>Operating position</b>            | Vertical  |
| <b>Weight</b>                        | 7 kg  |
| <b>Weight (lbs)</b>                  | 15.50 lbs   |
| <b>Weight notes</b>                  | Actual weight may vary depending on configuration |
| <b>Operating ambient temperature</b> | 10 - 35 °C (50 - 95 °F)                           |
| <b>Operating relative humidity</b>   | 5 - 85 % (relative humidity)                      |

**Compliance**

|                        |   |
|------------------------|---|
| <b>Product</b>         | ESPRIMO P757/E94+   |
| <b>Model</b>           | MI6W  |
| <b>Germany</b>         | TÜV GS  |
| <b>Europe</b>          | CE  |
| <b>USA/Canada</b>      | FCC Class B<br>cCSAus   |
| <b>Global</b>          | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>ENERGY STAR® 6.1 (dedicated regions)<br>EPEAT® Gold (dedicated regions) |
| <b>China</b>           | CCC (depending on configuration)<br>CEL (Chinese energy label)<br>TPM 2.0 for China (optional)  |
| <b>Compliance link</b> | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |

**Additional Software**

|   |  |
|---|--|
| <b>Additional software (preinstalled)</b> | Adobe® Reader® (pdf reader)<br>McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)<br>Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
|---|--|

**Additional Software**

|                                       |   |
|---------------------------------------|---|
| <b>Additional software (optional)</b> | Recovery DVD for Windows®<br>Drivers & Utilities DVD (DUDVD)<br>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)<br>CyberLink PowerDVD DVD (playback software for DVD)<br>Nero Essentials XL<br>Microsoft® Office Professional 2019<br>Microsoft® Office Home and Business 2019<br>(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |
|---------------------------------------|---|

**Manageability**

|                                 |  |
|---------------------------------|--|
| <b>Manageability technology</b> | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode)<br>Intrusion switch (optional)<br>WoL (Wake on LAN)<br>Intel® Standard Manageability (depending on processor)  |
| <b>Manageability software</b>   | DeskView Client<br>DeskView Instant BIOS Management  |
| <b>DeskView components</b>      | BIOS Management incl. Security<br>Inventory Management<br>Driver Management<br>Alarm Management  |
| <b>Supported standards</b>      | DMI (Desktop Management Interface)<br>SMBIOS (System Management BIOS)<br>PXE (Preboot Execution Environment)<br>WMI (Windows Management Instrumentation)<br>WBEM (Web Based Enterprise Management)<br>CIM (Common Information Model) |

**Security**

|                                 |  |
|---------------------------------|--|
| <b>Physical Security</b>        | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional)<br>Cable Cover (optional; covers and secures the ports and cables on rear side)   |
| <b>System and BIOS Security</b> | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1511)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces |
| <b>User Security</b>            | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  |
| <b>Workplace Embedded Tools</b> | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server (optional)<br>Easy PC Protection (optional)  |

**Miscellaneous**

Keyboard on (Special Fujitsu keyboard required)  
Thermal management  
Low Power Active Mode  
Extended lifetime

**Serviceability**

EasyFix  
EasyChange for HDD  
EasyChange for optical drives

**Packaging information**

|                                  |   |
|----------------------------------|---|
| Packaging dimension (mm)         | 439 x 296 x 499 mm  |
| Packaging dimension (inch)       | 17.28 x 11.65 x 19.65 inch  |
| Max. quantity / pallet           | 24  |
| Material - Weight (g) Carton     | 1040 g  |
| Material - Weight (lbs) Carton   | 2.29 lbs  |
| Material - Weight (g) EPS / PS   | 165 g   |
| Material - Weight (lbs) EPS / PS | 0.36 lbs  |
| Material - Weight (g) PE         | 60 g  |
| Material - Weight (lbs) PE       | 0.13 lbs  |
| Packaging notes                  | If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process |

**Warranty**

|   |  |
|---|--|
| Warranty period   | 1 year (for countries in EMEA)   |
| Warranty type   | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions                             | <a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>                          |
| <b>Product Support Services - the perfect extension</b> |  |
| Recommended Service                                     | 9x5, Onsite Response Time: Next Business Day   |
| Spare Parts availability                                | 5 years after end of product life<br>5 years   |
| Service Weblink   | <a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>                |

## Recommended Accessories

**Display B34-9 UE**

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1642-V140

**Display P24-8 WE Neo**

The FUJITSU Display P24-8 WE Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such Presence Sensor, Workplace Lighting Guide that promote the overall ergonomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.

Order Code:  
S26361-K1647-V140

**Wireless Mouse Touch WI910**

The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:  
S26381-K465-L100



## More information

### Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P757/E94+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about FUJITSU Desktop ESPRIMO P757/E94+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2019-03-25 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH