

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO P958/power

Extremely powerful desktop PC with superior expandability

The FUJITSU ESPRIMO P958/power Desktop provides high manageability and performance. Its low noise design supports a pleasant working environment, and the high-performance power supply satisfies the needs of your most demanding office applications. With tool-less access to components, front connectors and four full-height slots for additional graphics cards, ESPRIMO P958/power ensures excellent serviceability, ease of use and expandability. Based on German production standards and green IT technology, it uses halogen-free materials showcasing Fujitsu's commitment to environmental protection and sustainability. Its innovative Low Power Active Mode feature facilitates instant communication capabilities in your workplace. On retirement, the Fujitsu distinctive EraseDisk function securely wipes your data.

Expandability

Scale up with ESPRIMO efficiency

- 400W PSU and additional graphics cards allow customization for special use cases and future business needs

Excellent Performance and Energy Efficiency

Best-in-class regarding low power consumption combined with new levels of performance

- 8th generation Intel® Core™ processor family and a highly efficient power supply

Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and energy-efficient integrated power supply

Superior system management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor) and DeskView manageability suite

Robust Security

Designed to protect data and hardware components against manipulation and theft

- Cable cover with lock option at the back to protect ports, cables and components from theft.
- Embedded Trusted Platform Module (TPM), Fujitsu Workplace Protect software with full disk encryption and system-level passwords. EraseDisk software and SmartCard are available as options



Components

Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system notes	Certified for SUSE Enterprise Desktop (pending) Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .
Processor	
	Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i7-8700K processor (6 Cores / 12 Threads, 3.70 GHz, up to 4.7 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)
	Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Memory modules	
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM
Hard disk drives (internal)	
	SSD PCIe, 1024 GB M.2 NVMe Highend module
	SSD PCIe, 512 GB M.2 NVMe Highend module
	SSD PCIe, 256 GB M.2 NVMe Highend module
	RAID1 Bundle 2x512GB M.2 NVMe Highend
	RAID1 Bundle 2x256GB M.2 NVMe Highend
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 1024 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD SATA III, 1024 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	Intel Optane Memory (16 GB)
Hard disk notes	
	SSD (Solid State Disk)
	SED (Self-Encrypting Drive)
Graphics	
	VGA Extension Card
	NVIDIA® Quadro® P400 , 2 GB
	NVIDIA® GeForce® RTX 2080 Mini, 8 GB
	NVIDIA® GeForce® GTX 1050 Ti, 4 GB
	DP to DVI-D (single link) Adapter Cable
	AMD® Radeon R7 340, 2 GB

Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD-ROM
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	Parallel Interface
	M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only)
	Gigabit Ethernet PCIe x1
	eSATA Interface
	Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO P958/power
Mainboard	
Mainboard type	D3602
Formfactor	proprietary
Chipset	Intel® Q370
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,666 MHz
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Intel® I219LM
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	5
thereof SATA III	5
thereof eSATA	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10
Interfaces	
Audio: line-in	1

Interfaces

Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	5
USB 3.1 Gen1 (USB 3.0) total	3
USB 3.1 Gen2 total	4 and 2 optional via add on card
USB front	2x USB 2.0; 2x USB 3.1 (gen2), 1x USB 3.1 (gen2) Type C; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay
USB rear	2x USB 2.0; 3x USB 3.1 (Gen1); 1x USB 3.1 (Gen2); optional: additional 1x USB 3.1 Type C (Gen2) via add on card
USB internal	1x USB 2.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	optional: serial port (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality, USB Typ C connector supports up to 15W

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	--

Drive bays

Drive bays total	6
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	5,25" bays: one bay in HH format, one bay for slim optical disc drive only; internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless). drive cage for external 3.5" bay and internal 2.5" bay: optional
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s; supports Intel® Optane™ technology)

Slots

PCI-Express 3.0 x1	2 x (174 mm / 6.85 inch)
PCI-Express 3.0 x4 (mech. x16)	1 x (210 mm / 8.27 inch)
PCI-Express 3.0 x16	1 x (240 mm / 9.45 inch) Full height
M.2-2230	on mainboard for WLAN module

Graphics on board

Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel

Graphics on board

TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output and higher resolutions up to 4096 x 2160 pixel (at 30Hz refresh rate) if connected to the HDMI interface of a display via suitable adapter cables (not included)
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 83% / 89% / 91% / 90%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	400 W
Power factor correction/active power	active
Power supply output	1 graphics power rail (6pin connector)
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=4e37eb2c-34b6-498c-bb7b-c236885a15d4

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 8700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level LwAd (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.5"-HDD: 3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position

Noise emission

Standard noise operation mode: HDD load	3.5"-HDD: 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position
Standard noise operation mode: Idle mode	3.5"-HDD: 3.2 B / 19 dB(A) Bystander; 20 dB(A) Operator position
Standard noise operation mode: ODD load	3.5"-HDD: 4.6 B / 32 dB(A) Bystander; 38 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.5"-HDD: 3.3 B / 19 dB(A) Bystander; 21 dB(A) Operator position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	180 x 304 x 375 mm 7.09 x 11.97 x 14.76 inch
Operating position	Vertical
Weight	7 kg
Weight (lbs)	15.50 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO P958/power
Model	MI6W
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cTUVus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 7.1 EPEAT® Gold (dedicated regions)
China	CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 12.0 (depending on processor)
---------------------------------	---

Manageability

Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	http://www.fujitsu.com/fts/manageability

Security

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Windows 10, v. 1809 "Credential Guard Ready and Device Guard Capable" requires 8 GB or more system RAM and SSD PCIe NVME Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Keyboard on with one key (KBPX Eco, KB521)
Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards
Keyboard on with any key (USB)
Thermal management
Low Power Active Mode

Serviceability

EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information

Packaging dimension (mm)	439 x 296 x 499 mm
Packaging dimension (inch)	17.28 x 11.65 x 19.65 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1040 g
Material - Weight (lbs) Carton	2.29 lbs
Material - Weight (g) EPS / PS	165 g
Material - Weight (lbs) EPS / PS	0.36 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs




Packaging information

Packaging notes	If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process
------------------------	---

Warranty

Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display P27-8 TS UHD		The FUJITSU Display P27-8 TS UHD has a 3840 x 2160 Ultra HD resolution ships with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a 178°/178° wide viewing angle that delivers consistent picture quality, a 100% sRGB color space, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.	Order Code: S26361-K1610-V160
Display B34-9 UE		The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ software and a range of connectivity options ideal for medium- and large-sized businesses.	Order Code: S26381-K1642-V140
Wireless Mouse Touch WI910		The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.	Order Code: S26381-K465-L100
Keyboard KB950 Phone		The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.	S26381-F950-L4** (**: Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P958/power, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P958/power, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2019-03-25 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH