

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO Q957/MRE

Meeting Room Edition

Today's business world needs smarter meeting spaces – conference rooms that guarantee that meetings can start on time and that can seamlessly and wirelessly connect all employees from any location. With a FUJITSU ESPRIMO Q957/MRE mini PC in the conference room and the Intel® Unite™ application running on devices, meetings always get off to a good start. Participants can easily view and interact with content in real time, and colleagues sitting side by side can even share screens wirelessly long after the meeting is over.



Easy-to-Use collaboration solution

Employees can meet and work together more productively

- Transform existing conference rooms into smart, connected places to meet

Enhanced usability

Eliminates dongles, cables, and meeting delays via the integrated solution

- Fewer wires but faster meetings

Seamless collaboration

Wireless collaboration starts here

- All participants can see and interact with content in real time

Safer meetings

Intel® Unite™ powers secure, connected meeting spaces

- Protect meeting access with a secure, alternating PIN code

Lower Total Cost of Ownership

Make the most out of your existing IT investments

- Utilizing the power of Intel® vPro™ technology



Components

Operating systems	
Operating system pre-installed	Windows 10 Pro
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com .
	Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) **6th generation Intel® processor
Memory modules	
	4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,400 MHz, SO DIMM
	8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,400 MHz, SO DIMM
	16 GB (1 module(s) 16 GB) DDR4, non-ECC, 2,400 MHz, SO DIMM
Hard disk drives (internal)	
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
	SSD SATA, 512 GB, M.2 module
	SSD SATA, 256 GB, M.2 module
	SSD SATA, 128 GB, M.2 module
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
Hard disk notes	
	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	
	DP to DVI-D (single link) Adapter Cable
Drives (optional)	
	BD Triple Writer SATA ultra slim (tray)
	DVD Super Multi ultra slim (tray)

Base unit

Base unit	ESPRIMO Q957/MRE
Mainboard	
Mainboard type	D3513
Formfactor	proprietary
Chipset	Intel® Q270
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,400 MHz

Mainboard

Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same DDR4 2,400 MHz will be clocked with 2,133 MHz in combination with 6th generation Intel® processor
LAN	10/100/1,000 MBit/s Intel® I219LM
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio V UEFI Specification 2.5
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio

I/O controller on board

Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	2
USB 3.1 Gen1 (USB 3.0) total	7
USB front	2x USB 3.0 and 1x USB 3.1 Type-C (Gen1)
USB rear	2x USB 2.0 and 4x USB 3.0
VGA	optional: via external active adapter cable
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	1 9pin, 16 byte FIFO, 16550 compatible
Mouse / Keyboard (PS/2)	0/1 optional (with PC on/off function on Pin6)
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
---------------------------------	--

Drive bays

Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim tray for 5.25"; M.2-2280 for SSD
M.2-2280	1 x 1 on mainboard (for PCIe or SATA SSD modules)

Slots

M.2-2230	on mainboard for WLAN module
-----------------	------------------------------

Graphics

Graphics brand name	Intel® HD Graphics 530, Intel® HD Graphics 630
Shared video memory	up to 1,782 MB

Graphics

TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 2 Watt/ 10% / 20% / 50% / 100% load) : > 85%/ 90% / 90% / 92% / 92%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	65 W (integrated in system)
Power factor correction/active power	No (meets input harmonic current according EN61000-3-2)

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=84543802-fb10-464e-a406-9d28984f7652

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 7700T
Standard noise emission	According to ISO 7779:2010, ECMA-74 2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level L _{wad} (in B) / Workplace related A-weighted sound pressure level L _{pAm} (in dB(A))
Standard noise operation mode: CPU 50% load	3.4 B / 22 dB(A) Bystander; 24 dB(A) Operator position
Standard noise operation mode: HDD load	3.1 B / 17 dB(A) Bystander; 18 dB(A) Operator position

Noise emission

Standard noise operation mode: Idle mode	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position
Standard noise operation mode: ODD load	4.4 B / 31 dB(A) Bystander; 35 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level L _{wad} (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.5 B = 35 dB (A)
Blue angel noise operation mode: Idle mode	3.1 B = 31 dB (A)
Blue angel noise operation mode: ODD load	4.4 B = 44 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	186 x 191 x 59 mm 7.32 x 7.49 x 2.30 inch
Operating position	Vertical / horizontal (no feet needed)
VESA mount	integrated (100 mm & 75 mm), applicable for selected monitors only, additional mounting kit for specific monitors optional
Weight	1.6 kg
Weight (lbs)	3.53 lbs
Weight notes	Weight may vary depending on actual configuration (without ODD)
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO Q957
Model	MPC3
Germany	GS (planned)
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions) TCO Certified Desktop
China	CCC (planned) China RoHS
Compliance notes	This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	<p>Intel® Unite™ Hub (supported languages: EN, FR, IT, DE, ES) Adobe® Reader® (pdf reader) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)</p> <p>Important Notice (Intel® Unite™): The Fujitsu Intel® Unite™ Hardware Appliance is preconfigured for the use of the Intel® Unite™ Software Solution. The Intel® Unite™ Software is shipped by Fujitsu and provided free of charge together with the Hardware Appliance. However the Intel® Unite™ Software LICENSE is NOT part of the Fujitsu Deliverables and any and all use of the Intel® Unite™ Software, is subject to the acceptance of the Intel® Unite™ End User License Agreement to be agreed directly between Customer and Intel. Fujitsu takes no part in the licensing and therefore to the maximum extent possible, expressly disclaims and excludes any and all warranty and liability in connection with the Intel® Unite™ product and its use, except for cases where Fujitsu's own misrepresentation, intentional or gross negligent actions or omissions should give cause for such liability or where liability of Fujitsu is mandatory under applicable law.</p>
---	---

Additional software (included as a CD/DVD)	Intel® Unite™ Software DVD (supported languages: EN, FR, IT, DE, ES)
---	--

Manageability




Manageability technology	<p>DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 11.6 (depending on processor)</p>
Manageability software	<p>DeskView Client DeskView Instant BIOS Management</p>
DeskView components	<p>BIOS Management incl. Security Inventory Management Driver Management Alarm Management</p>
Supported standards	<p>DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)</p>

Security

Physical Security	<p>Kensington Lock support Intrusion switch (optional) Eye for padlock Housing Lock Spring (to use with Kensington lock), (optional)</p>
System and BIOS Security	<p>Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1511) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces</p>
User Security	<p>User and supervisor BIOS password Hard disk password Access protection via internal SmartCard reader (optional) Access protection via external SmartCard reader (optional) Embedded PalmSecure® sensor (optional) Workplace Protect (secure authentication solution)</p>
Workplace Embedded Tools	<p>Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional)</p>

Security	
Security notes	Choose people over passwords. Protect your business with PalmSecure technology #http://choosepeopleoverpasswords.global.fujitsu.com/#High accuracy: PalmSecure™ has a proven false rejection rate of 0.01 percent and a false acceptance rate of less than 0.00001 percent. No other system in the world can match this performance.#Hygienic and non-invasive: Contactless scanner#Easy to use: Scanning is intuitive and people feel no mental resistance to it.
Miscellaneous	
	GPJ:Q0956MRE0001IN, supported countries by country kit Euro-cable (INT): http://docs.ts.fujitsu.com/dl.aspx?id=708ebe77-6c80-45e8-9584-bf8e98103d64
Packaging information	
Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Warranty	
Warranty period	3 years (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Universal Monitor Stand		Save desk space without compromising performance or productivity with the Universal Monitor Stand that brings together a FUJITSU Desktop ESPRIMO Q mini PC or FUJITSU Thin Client FUTRO and a VESA compatible FUJITSU Display. For optimum ergonomics the height and tilt angle of the display can be adjusted, helping you to stay productive and comfortable, whilst hassle-free installation of the devices on the stand makes the life of your IT department easier.	Order Code: S26361-F2601-L700
Display P27-8 TS Pro		If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P27-8 TS Pro Display is the perfect choice. The display provides outstanding picture performance thanks to cutting-edge panel technology and 3.7 Mio pixels. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and USB support during standby.	Order Code: S26361-K1594-V160
Display XL55-1 TOUCH		The FUJITSU Display XL55-1 TOUCH is a Full HD display with an interactive panel that supports up to 10 touch points for maximum collaboration during meetings. The display has powerful built-in speakers, a range of interfaces for easy connectivity and maximum flexibility and anti-glare screen for a distraction free viewing experience.	Order Code: S26361-K1632-V160

Blue LED Mouse GL9000

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:
S26381-K438-L100

Keyboard KB950 Phone

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO Q957/MRE, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO Q957/MRE, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2019-03-25 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH