

# Data Sheet

## Fujitsu Thin Client FUTRO S940

### Future-ready Flexible Thin Client

The FUTRO S940 is a future-ready, flexible Thin Client device with an optimal mix of industry leading OS and Thin Client device management consoles, ISV protocols and highly flexible hardware options helping you provide secure computing and full productivity options for your employees for creating the workplace of the future.

#### eLux® RP 6 Thin Client OS and Scout Enterprise Management Suite® 15

Enables you to save on costs upfront and keep your IT infrastructure secure and up-to-date with continuous security patch releases

- Unicon offers a flexible licensing model that includes the eLux OS and Scout Enterprise Management Suite with long term support for the latest updates

#### Enterprise-grade Security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

- Centralized administration and granular access controls coupled with built-in BIOS Security, Write Filter Protection and Kensington lock support

#### Full productivity

Enables your workforce to be more productive with UC&C and multiple display options and multiple connectivity options that can get work done faster and more efficiently

- UC&C ready with multi-monitor support for up to four 4K displays and ideal mix of modern (Type-C) and legacy interfaces

#### Investment Protection

Helps you run your Thin Clients on the latest and most secure versions of the eLux RP and Scout Enterprise Management Suite

- Scout Subscription helps provide perpetual updates and upgrades to eLux RP 6 and Scout Enterprise Management Suite 15

#### Lean IT ready

Helps you modernize your workspaces by promoting a Lean IT, clean desk and ergonomic approach without compromising on performance

- Small footprint, Fanless design, Power-over-Ethernet (PoE) option and optimal Performance-to-Power ratio



# Technical details Components

<b>Storage notes</b>	<p>Important Notice for M.2 Module Use: Predefined by NAND-Flash-Technology the device only supports a defined maximum number of Terabytes written.</p> <p>Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section "restricted warranty" in our warranty book.</p> <p>Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be deactivated again at any time.</p> <p>*Terabytes written (TBW) calculated based on JESD-218 SSD Client workload</p> <p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p>
<b>Base unit</b>	FUTRO S940
<b>Operating system and software (Linux)</b>	
<b>Operating system</b>	eLux® RP
<b>Notes</b>	eLux® is a hardware-independent operating system for cloud computing environments. eLux ensures hardware independence and migration ability. An existing license can simply be transferred via Scout Enterprise whenever the hardware is upgraded. New updates and upgrades are always built modular – only the changed parts (delta) of the software are transferred to the device and implemented into the existing installation. Software updates and upgrades are available around the clock at myelux.com.
<b>Functions</b>	eLux® RP 6 Citrix Receiver VMware® Horizon Client Updates and optional software packages are available at <a href="http://www.myelux.com">www.myelux.com</a>
<b>Manageability</b>	Scout Enterprise, flash memory management, embedded operating system update and system monitoring, managing devices by location, group or user, individual operating system composition with ELIAS (eLux and Scout Enterprise Management Suite license required)
<b>Operating system and software (Windows 10 IoT)</b>	
<b>Operating system</b>	Windows® 10 IoT Enterprise 2019 LTSC Windows® 10 IoT Enterprise 2016 LTSC
<b>Notes</b>	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .
<b>Functions</b>	Internet Explorer Citrix Receiver VMware® Horizon Client
<b>Mainboard</b>	
<b>Mainboard type</b>	D3543-A1
<b>Formfactor</b>	miniITX
<b>Processor</b>	Intel® Pentium® Silver J5005 (Quad Core, 1.5 GHz, up to 2.8 GHz, Intel® UHD Graphics 605) (, )
<b>Memory slots</b>	2 SO DIMM (DDR4, 2400 MHz)
<b>Supported capacity RAM (max.)</b>	16 GB
<b>LAN</b>	Built-in 10/100/1,000 MBit/s Realtek RTL8111G
<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
<b>Audio type</b>	On board
<b>Audio codec</b>	Realtek ALC671
<b>Interfaces</b>	
<b>Audio: line-in</b>	1
<b>Audio: line-out</b>	1
<b>Front audio: microphone</b>	1
<b>Front audio: headphone</b>	1

**Interfaces**

USB 2.0 total	4 rear
USB 3.1 Gen1 (USB 3.0) total	2 front + 1x Type-C rear as option
USB front	2
USB rear	4 + 1 (optional)
USB internal	1 pin header (2x USB 2.0)
DisplayPort	2x DP1.2a
Serial (RS-232)	2
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1x as option
Kensington Lock support	1

**Graphics on board**

Graphics brand name	Intel® UHD Graphics 605
Graphics color depth	32 bit colors
Shared video memory	up to 1.5 GB
TFT resolution (DisplayPort)	up to 4,096 x 2,160 @ 60 Hz
Graphics features	DirectX® 12 OpenGL® 4.4 Open CL® 1.2 OpenGL® ES 3.1 Vulkan™
Graphics notes	Graphics resolution and features depending on operating system and management solution. Three displays up to 2560 x 1440 pixels are supported via Daisy Chain (display 1 at DisplayPort 1, display 2 at DisplayPort 2, display 3 via Daisy Chain at display 1 or 2).

**Electrical values**

Power consumption long idle	10 W
Power consumption sleep mode power	1.14 W (WoL enabled)
Power consumption off mode power	0.2 W (WoL disabled)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	100 V - 240 V (AC Input)
Operating line frequency range	50 Hz - 60 Hz

**Dimensions / Weight / Environmental**

Dimension with stand (W x D x H)	90 x 193 x 261 mm
Dimensions (W x D x H)	52 x 193 x 250 mm
Dimension notes	Dimensions with WiFi w/o stand (W x D x H): 58 x 193 x 250 mm
Operating position	Vertical / horizontal
Weight	1048 g
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C
Operating relative humidity	5 - 85 % (relative humidity)

**Compliance**

Product	FUTRO S940
Model	TCS
Germany	GS
Europe	CE
USA/Canada	FCC part 15B (Class B) and part 15C/E (depending on wireless configuration)
Global	EPEAT® Bronze (dedicated regions) ENERGY STAR® 8.0 compliant
India	BIS
Russia	EAC
China	CCC

**Compliance**

Australia/New Zealand	RCM
Compliance notes	Energy Star compliance may vary depending on actual configuration Product Name maybe followed by suffixes
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

**Security**

Physical Security	Kensington Lock support Intrusion switch
System and BIOS Security	Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password
User Security	Access protection via internal SmartCard reader (optional)


**Warranty**

Warranty period	2 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a> free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

**Product Support - the perfect extension**

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>
Service Weblink	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

## Recommended Accessories

VESA Subadapter Velcro® strap for Fujitsu FUTRO Thin Clients	To mount the FUTRO system at rear side of the monitor. Contents: Subadapter, screws, bolts. Please check the compatibility of the monitor.	Order Code: S26361-F2601-L200
eLux® RP & Scout Enterprise Management Suite®	 Scout Enterprise Management Suite® ensures scalability, high availability and enabling the management of an unlimited number of Thin Clients and PCs with eLux® OS or Windows operating systems. eLux OS is an open, hardware agnostic operating system designed for cloud end points such as Thin Clients with a modular design, offering easy licensing options and migration alternatives.	Order Code: S26361-F2727-L801

# More information

## Fujitsu products, solutions & services

In addition to Fujitsu Thin Client FUTRO S940, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu Thin Client FUTRO S940, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/FUTRO](http://www.fujitsu.com/emeia/FUTRO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2020 Fujitsu Technology Solutions GmbH

## Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.