FUJITSU

Data Sheet
Fujitsu STYLISTIC Q7311

Tablet Mobility Meets Notebook Productivity

The FUJITSU Tablet STYLISTIC Q7311 is a highly durable and secure 2-in-1 detachable that meets the demands of today's mobile professionals. Its 33.8 cm (13.3-inch) FHD anti-glare display comes with pen and touch support. The latest 11th generation Intel® Core™ i7 vPro® processor technology and Intel® Thunderbolt™ 4 ensure excellent performance, even when you're on the go.

Combined tablet mobility and notebook productivity in one device - whereever you are
The robust IP42 compliant housing with reinforced corners and port caps protects your device from damages, even outside the office.
- Highly durable IP42 compliant housing with reinforced corners
- Port caps that protect the interfaces like the new Intel® Thunderbolt™ 4 from water spills
- Optional backlit keyboard dock with LAN and charging port
- Optional TPU cover for more robustness
- Always connected and instantly ready

Convenience at work
Sign documents legally secure. The pen is automatically charged within seconds when stored in its pen garage, that protects it also from being lost. Ready whenever you need it.
- 33.8 cm (13.3-inch) Full HD anti-glare touch display
- Supporting pen with 4K pressure levels
- Pen garage with inductive charging function

Lean, agile and secure
More freedom to work safely from anywhere at anytime without compromises in security and data protection – integrated IR Cam with Windows Hello support, fingerprint sensor and Smartcard reader protect your device like a mansion.
- Weight starting at 800 grams, the device offers you ultimate portability
- Fingerprint sensor & IR Camera supporting Windows Hello
- Smartcard reader
- Kensington lock support
- Up to 10 hours battery runtime
- Intel® Iris® Xe Graphics

Components

Base unit	STYLISTIC Q7311
Operating systems	
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see aka.ms/windows11-spec).
Operating system notes	Internet connectivity Windows 10 Support: After the end of the product life Fujitsu will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com.
Processor	Intel® Core™ i7-1185G7 processor (4 Cores / 8 Threads)
	Intel® Core™ i5-1145G7 processor (4 Cores / 8 Threads)
	Intel® Core™ i5-1135G7 processor (4 Cores / 8 Threads) *
	* Processor only for retail, SMB, education and government
Hard disk drives (internal)	SSD PCIe, SSD 512GB Value PCIe G3 M.2 FDE, SED
	SSD PCIe, SSD 512GB MS PCIe G3 M.2 FDE, SED
	SSD PCIe, SSD 256GB Value PCIe G3 M.2 FDE, SED
	SSD PCIe, SSD 1TB Value PCIe G3 M.2 FDE, SED
	SSD PCIe, SSD 1TB MS PCIe G3 M.2 FDE, SED
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery
Interface add on cards/components (optional)	
4G/ LTE (optional)	(Downlink speed up to 300 Mbit/s, Uplink speed up to 150 Mbit/s)
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1,080 pixel, Anti-glare touchscreen, 400 cd/m², 1500:1
Multimedia	
Camera	Front: HD Cam (0.9MP) with LED Front: IR Cam (0.9MP) supporting Windows Hello with LED Rear: 5M with LED

Base unit

Base unit	STYLISTIC Q7311
General system information	
Chipset	Integrated in CPU
Supported capacity RAM (min.)	8 GB
Supported capacity RAM (max.)	16 GB
Memory notes	8 GB onboard or 16 GB onboard Dual channel support LPDDR4x (4,266 MHz)
LAN notes	Virtual MAC address. LAN connector via optional keyboard docking, cradle or optional USB to LAN adapter.
Integrated WLAN	Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1

General system information

BIOS version	UEFI Specification 2.7
BIOS features	InsydeH2O BIOS
Audio type	On board
Audio codec	Realtek ALC255
Audio features	2x digital array microphones, 2x built-in speakers (stereo)
Waterproof / Spillproof	IP42
Disinfectable	no
MIL-STD tested	Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.

Display

Diagonal Size	33.8 cm (13.3-inch)
Display Technology	IPS
Display type	Anti-glare touchscreen
Display Resolution type	FHD
Brightness - typical	400 cd/m^2
Contrast - typical	1500:1
Viewing angle (h/v) - typical	178°/178°
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing) Integrated ambient light sensor for automatic backlight adjustment to the working environment. Toughened glass
Sensors	Ambient Light Sensor Compass Gyroscope Proximity
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen
Pen	AES 4k pressure level Pen garage inductive charging
Ambient light sensor	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight

Graphics

Base unit	STYLISTIC Q7311
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz
Graphics brand name	Intel® Iris® Xe Graphics (with Dual channel memory)
Graphics features	4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator

Interfaces

DC-in	1
Audio: line-out / headphone	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2x digital array microphones
USB 2.0 total	1
USB 3.2 Gen1 (5 Gbps) total	1 x Type-A
USB 4.0 Gen3 (20 Gbps) total	1 x Type-C Intel® Thunderbolt™ 4 (with Power Delivery functionality)
USB Type-C	1 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W)
HDMI	1 v1.4
Ethernet (RJ-45)	-

Interfaces

Memory card slots	1 (USH-I) SD 3.0 Standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB
SmartCard slot	optional
SIM card slot	1 (Nano-SIM, only for models with integrated 4G/LTE module)
Interface Module notes	LAN and VGA available via conversion cable.
Docking connector for Port Replicator	1 (Cradle)
Kensington Lock support	1

Port Replicator interfaces (optional)

	USB Type-C PR	Cradle
DC-in	1 (19V/90W required)	1 (19V)
Power on switch	1	---
Audio: line-in	---	1
Audio: line-in / line-out	1	---
Audio: line-out	---	1
Audio: comments	Combo jack for headset usage	---
USB 3.2 Gen1 (5 Gbps) total	---	3
DisplayPort	1x V1.2	1
VGA	1x	1
HDMI text	1x	---
Interface Notes	3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input	---
Kensington Lock support	no	1
Ethernet (RJ-45)	1	1 (10/100/1000)
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.	---

Wireless technologies

Antennas	2x dual band for WLAN, 2x for LTE, Bluetooth shared with WLAN
Bluetooth	V5.1
Integrated WLAN	Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1
WLAN encryption	WPA/WPA2/WPA3 (Wi-Fi Protected Access)
WLAN notes	Import and usage according to country-specific regulations.
Integrated WWAN	LTE Sierra Wireless EM7421 (Cat.7) - UMTS, LTE
WWAN notes	Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE)
GPS	Embedded in 4G module if configured with WWAN

Power supply

AC adapter	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C
Notes	65W AC Adapter for usage with system/ min. 90W AC Adapter for usage with Cradle
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	Li-Ion battery 3-cell, 38 Wh
Battery features	Quick Charge: 80% in 1h
Runtime 1st battery	10 h

Power supply

Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.

Dimensions / Weight / Environmental

Dimensions (W x D x H)	315 x 200.9 x 10.5 mm
	12.4 x 0.79 x 0.42 inch
Weight	from 0.800 kg slate only, weight of keyboard docking from 0.465 kg
Weight (lbs)	from 1.75 lbs slate only, weight of keyboard docking from 1.25 lbs
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)
Product	STYLISTIC Q7311
Germany	GS
Europe	CE CB
Global	TCO Certified 8.0 EPEAT® Silver (dedicated regions), depending on configuration Microsoft Operating Systems (HCT / HCL entry / WHQL) MIL-STD-810H tested RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Russia	EAC
China	CCC
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

|	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)

Manageability

Security

Physical Security	Kensington Lock support
System and BIOS Security	Absolute Persistence® technology capable BIOS EraseDisk Trusted Platform Module (TPM 2.0)
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Smartcard reader (optional) SystemLock BIOS SmartCard security AuthConductor Client Basic (secure authentication solution)

Packaging information

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Product Support - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/

Recommended Accessories

Thunderbolt™ 4 Port Replicator		First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	Order Code: FPCPR401BP
USB Type-C Port Replicator 2		Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	Order Code: S26391-F3327-L100
STYLISTIC Q7311, Q7310 and STYLISTIC Q5010 Family Cradle		Flexibility, expandability, desktop replacement, investment protection – to name just a few benefits of Fujitsu's docking options.	Order Code: S26391-F3397-L100
USB Type-C AC Adapter		Recharge your notebook or tablet at work, at home or on the road with this USB Type-C power source easily.	Order Code: S26391-F3326-L502
LAN Conversion Cable (USB to LAN) for STYLISTIC Q		The FUJITSU USB Type-A to LAN Conversion Cable enables you to connect your compatible STYLISTIC Tablet to a wired network connection. GBit-LAN via USB conversion cable is limited to 480 Mbit/s due to USB 2.0 specification. (Picture similar to product)	Order Code: S26391-F3398-L840
Tablet Stand for STYLISTIC Q devices		The tablet stand is designed for STYLISTIC devices like latest STYLISTIC Q7312 and can be used universally. Fits for STYLISTIC Q5 and Q7 and the Type-C as well as the Thunderbolt ™ 4 port replicator can be fixed on the stand.	Order Code: FPCSK769BP
AES Pen		Take your creativity to the next level, with the most natural pen experience with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen. The pen fits in the device's integrated pen garage.	Order Code: S26391-F3389-L500

Car Adapter USB-C-QC	One Car Adapter fits all. Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrand-independent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung charge.	Order Code: S26391-F2613-L630
CANVAS HANSEN 14	The PLEVIER CANVAS HANSEN 14 leather and canvas case is a compact and classic carrier for on the go. Available for notebooks up to 14 inches with two compartments and two accessory sections, protection for your device ensured. A subtle design canvas and nappa leather shade.	Order Code: S26391-F1193-L67
Bumper Case Kit	The protective bump case kit is designed to prevent damages to your STYLISTIC Q7. Openings of the cover allow you to access all ports and buttons whilst the hand strap on the back of the case gives you a firm grip while working with your tablet outside the office. The integrated stand solution enhances your productivity.	Order Code: S26391-F3396-L200
Folio Cover STYLISTIC Q7311/ Q7310	The Folio Cover for the STYLISTIC Q7311 and Q7310 is a thin, tailored protective sleeve for your Fujitsu tablet. It keeps the device safe from damage on the go, and brings a touch of style to your daily work. It can even be used as a stand if you need to display a presentation or watch a clip and fits even the device is connected to its keyboard dock. Inclination stand style 120 to 150 degree	Order Code: S26391-F3509-L100
Wireless Mouse WI860 BTC	The Wireless Mouse WI860 BTC can be paired with up to 3 different clients, 2x Bluetooth and 1x wireless USB Type-C dongle. With the blue optical sensor, it works on nearly all surfaces with an 3-step adjustable DPI selector (800/1600/2400). The mouse charges wirelessly through Qi or by USB Type-C cable. A utility button on the side is programmable. The default functions are optimized for Teams calls.	Order Code: S26381-K474-L100
		Order Code: FPCKG453BP

More information

In addition to Fujitsu STYLISTIC Q7311, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu STYLISTIC Q7311, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com

Disclaimer

Contact

Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: www.fujitsu.com/[country]
2023-08-02 CE-EN