

Data Sheet

FUJITSU Accessories USB Port Replicator PR09

Connectivity

High-End Smart Connectivity

The new FUJITSU USB Port Replicator PR09 is the perfect solution for shared desk environments within a hyperconnected world. It connects your mobile system to your main peripherals with a single USB plug. This Port Replicator is equipped with the most powerful DisplayLink chipset supporting high performance video streaming with Dualhead-DisplayPort.

Highest data throughput is guaranteed due to an USB Type-C based Gen2 Hub-Controller enabling up to 10Gbit/s data streaming. The newest version of USB Power Delivery chipset (PD3.0) provides powerful charging during your workday.



Main Features

- Dualhead high-end graphics up to 4k
- Singlehead up to 5k
- Gigabit-LAN integrated
- USB Type-C upstream
- USB Power Delivery (PD3.0)
- Multiport USB 3.1 Gen1 DFP hub
- Multiport USB 3.1 Gen2 DFP hub
- SPDIF digital audio 2.0

Highlights

- Developed for shared multi-vendor system workplaces
- System independent investment protection (TCO)
- Future proof & backwards compatible (e.g. to USB-A systems)
- Easy IT integration (PXE / MAC spoofing support)
- Fast one-cable connection for data and power
- Global country certifications
- Appealing design ID workplace device

Reliability

- Highest availability
- Experience out of huge installed base of Fujitsu USB Port Replicators

USB Port Replicator PR09

Technical specifications

| | | |
|--------------------|---|----------------|
| Required interface | USB Type-C | |
| LED | On/Off switch | (blue) |
| | USB Power Delivery | (amber) |
| | USB connection | (green) |
| | LAN traffic, rear side | (green/yellow) |
| Color | Black | |
| Driver information | Fujitsu certified driver: http://support.ts.fujitsu.com/download DisplayLink driver: http://www.displaylink.com/downloads/windows *Please note: drivers also available for MAC OS, Ubuntu, Chrome OS, Android (no Fujitsu support) Microsoft Windows Updates: available | |

Refresh rate

| | |
|---|--|
| Supported refresh rate (32 bit color depth) | 1x up to 5120 x 2880 @ 60 Hz 2x up to 4096 x 2160 @ 60 Hz |
|---|--|

Interfaces

| | |
|---------------------------|---|
| Ethernet (RJ-45) | 1 Gigabit LAN (based on Realtek RTL8211F) |
| Power on switch | 1 (default: Off) |
| Power supply | 1 AC/DC Power Adapter 120W (package content) |
| DC-in | 20V |
| USB upstream | via USB Type-C cable (1m) |
| USB Type-C (UFP) | 1 w/ USB PD (60W) |
| USB Type-C 3.1 Gen2 (DFP) | 3 thereof 1x BC1.2 w/ 10.5W |
| USB Type-C cable | 1 (5A Gen2) (package content) |
| USB Type-A 3.1 Gen1 (DFP) | 4 |
| DisplayPort | 2 (DP1.2a as Dualmode DP++) |
| Audio | 1 SPDIF (2.0) |
| Notes | Several adapters available: http://www.fujitsu.com/de/products/computing/peripheral/accessories/connectivity |
| Kensington Lock support | yes |

System requirements

| | |
|-----------------------------|---|
| Required interface | USB Type-C |
| System requirements | For office and productivity: Intel Core i3 2+GHz / Intel Core M / AMD Trinity or better USB 3.1 Gen 2 recommended 40MB of free storage space |
| Supported operating systems | Windows® |

Special features

| | |
|--------------------|------------------------------|
| USB power delivery | ver 3.0 |
| DisplayLink | "Plug and Display" certified |
| USB upstream | via USB Type-C cable (1m) |

Electrical values

| | |
|---------------------|---|
| Power consumption | Maximum usage: 120W Average office usage: 82W Without USB PD: 3 W DC Off: 0,07 W |
| Power supply input | 100-240V AC 50-60Hz |
| Power supply output | 20V DC at 6A |

Compliance

| | |
|--------|----|
| Europe | CE |
|--------|----|

Compliance

| | |
|-----------------------|---|
| Switzerland | ENV |
| Russia | EAC |
| USA/Canada | FCC Class B ICES-003 Class B cTUVus UL/cUL |
| Japan | JEITA VCCI PSE (AC-Adapter) JISC |
| South Korea | KC |
| Singapore | S-Mark |
| China | CCC (AC-Adapter) |
| Australia/New Zealand | RCM |
| Taiwan | BSMI |
| Saudi Arabia | SASO |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

Dimensions / Weight / Environmental

| | |
|-------------------------------|----------------------------|
| Miscellaneous | MAC address show |
| Dimensions (W x D x H) | 200 x 97.6 x 29 mm |
| Weight | 340 g (device only) |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Storage ambient temperature | 5 - 45 °C (41 - 113 °F) |
| Operating relative humidity | 10 - 85 % (non condensing) |

Package content

USB Port Replicator PR09
AC/DC Adapter 20V, 120W
EU-power cord, 1,8m
USB Type-C cable, 1m
Quick Start Guide
Service Desk & Warranty Informations
Safety Notes
Informationcard for driver download

Order code

S26391-F6007-L500 EAN: 4057185642316

Warranty

| | |
|-----------------------------|---|
| Warranty period | 3 years |
| Warranty type | Bring-In / Send-In Service (depending on country) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

More information

Fujitsu products, solutions & services

In addition to FUJITSU Accessory USB Port Replicator PR09, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Accessory USB Port Replicator PR09, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2019-02-21 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH