

Data Sheet

Fujitsu Accessory USB Type-C Port Replicator 2

Turning your Fujitsu device into a perfect workplace

Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA.

You also can charge your external USB devices without the need of any additional charger.



Features

- Power delivery charging your Mobile Client
- DisplayPort / HDMI / VGA
- On/off button with resume support for dedicated Fujitsu clients
- USB Type-C and USB Type-A interfaces
- PXE boot
- MAPT (MAC address path through)
- WoL (Wake on LAN)
- Supporting from 9th generation dedicated LIFEBOOK and STYLISTIC devices

Usability

- Instant access to your input devices, LAN and all peripherals via one USB plug
- Keep your peripherals plugged-in when needing your mobile device elsewhere than your desk

USB Type-C Port Replicator 2

Technical specifications

Color	Black
Interfaces	
Power on switch	Power on and off for dedicated Fujitsu products (does not support LIFEBOOK A and CELSIUS H Mobile WS)
DC-in	1 (19 V/90 W required)
USB Type-C (to Devices)	1x USB-C 3.2 Gen1 - 15W 1x Type-C - Up to 60 W (PD v.2.0-1.1) power output to client or 4.5 W input
USB Type-A	3x Type-A 3.2 Gen1 - 5 V / 0.9 A, 4.5 W
USB Type-C cable	1 Length: 1 m
DisplayPort	1x V1.2 resolution up to 4,096 x 2,160@24 Hz / 3,840 x 2,160@30 Hz depending on system for 1 external display up to 1,920 x 1,080@60 Hz for 2 external displays (with 1,920 x 1,080@60 Hz connected HDMI or VGA) up to 1,600 x 900@60 Hz or 1,280 x 1,024@60 Hz for 3 external displays connected to DP, HDMI and VGA in parallel - all 3 external displays with same resolution, no internal display possible in addition
HDMI	1 resolution up to 4,096 x 2,160@24 Hz / 3,840 x 2,160@30 Hz depending on system for 1 external display up to 1,920 x 1,080@60 Hz for 2 external displays (with 1,920x1,080@60 Hz connected DP or VGA) up to 1,600 x 900@60 Hz or 1,280 x 1,024@60 Hz (with 3 external displays connected to DP, HDMI and VGA in parallel - all 3 external displays with same resolution, no internal display possible in addition).
VGA	1 resolution up to 1,920 x 1,200@60 Hz depending on system for 1 external display up to 1,920 x 1,080@60 Hz for 2 external displays (with 1,920 x 1,080@60 Hz connected HDMI or DP) up to 1,600 x 900@60 Hz or 1,280 x 1,024@60 Hz (with 3 external displays connected to DP, HDMI and VGA in parallel - all 3 external displays with same resolution, no internal display possible in addition).
Audio: line-in / microphone	1 Combo jack for headset usage for mic and headphone
Ethernet (RJ-45)	1 x (10/100/1000) WoL from S3 state WoL from S4 / S5 / G3 depending on Fujitsu mobile client Launch of PXE for dedicated FJ mobile clients Set the MAC address by the user MAPT from 9th gen
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.

Compliance

Europe	CE
USA/Canada	FCC Class B
Japan	VCCI JATE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Dimensions / Weight / Environmental

Dimensions (W x D x H)	219 x 75 x 22.9 (front) - 26 (back) mm
Cable length	100 cm
Weight	334 g

Package content

Type-C Port Replicator
including 90 W 3-pin AC adapter
including Type-C cable 100 cm
w/o AC cable

Order code

S26391-F3327-L100 EAN: 4063872104913

Warranty

Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to Fujitsu Accessory USB Type-C Port Replicator 2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Accessory USB Type-C Port Replicator 2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2024-04-06 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu Technology Solutions GmbH