

Datasheet

Brocade G620 Switch

HIGHLIGHTS

- Provides high scalability in an ultra-dense, 1U, 64-port switch to support high-density server virtualization, cloud architectures, and flash-based storage environments
- Increases performance for demanding workloads across 32 Gbps links and shatters application performance barriers with up to 100 million IOPS
- Enables “pay-as-you-grow” scalability— with 24 to 64 ports—for on-demand flexibility
- Provides proactive, non-intrusive, realtime monitoring and alerting of storage IO health and performance with IO Insight, the industry’s first integrated network sensors
- Leverages IO Insight intelligence to identify issues and understand key performance, health, and utilization trends, ensuring consistent performance
- Increases resiliency by automatically discovering and recovering from device or network errors
- Leverages Brocade Fabric Vision technology to simplify administration, quickly resolve problems, increase uptime, and reduce costs
- Simplifies troubleshooting with realtime and historical visibility in a single dashboard

Ultra-dense, Highly Scalable, Easy-to-Use Enterprise-Class Storage Networking Switch

Today’s mission-critical storage environments require greater consistency, predictability, and performance to keep pace with growing business demands. Faced with explosive data growth, data centers need more IO capacity to accommodate the massive amounts of data, applications, and workloads. In addition to this surge in data, collective expectations for availability continue to rise. Users expect applications to be available and accessible from anywhere, at any time, on any device.

To meet these dynamic and growing business demands, organizations need to deploy and scale up applications quickly. As a result, many are moving to higher Virtual Machine (VM) densities to enable rapid deployment of new applications and deploying flash storage to help those applications scale to support thousands of users. To increase agility, reduce expenses, and realize the full benefits of these architectures, organizations need the network to deliver the performance required by today’s server and storage environments.

In addition, storage networks are becoming increasingly important to application performance, which means that they also must become easier to administer and manage. By treating the network as a strategic part of a highly virtualized environment, organizations can increase optimization and efficiency even as they rapidly scale their environments.

The Brocade G620 Switch meets the demands of hyper-scale virtualization, larger cloud infrastructures, and growing flash-based storage environments by delivering market-leading Gen 6 Fibre Channel technology and capabilities. It provides a high-density building block for increased scalability, designed to support growth, demanding workloads, and data center consolidation in small to large-scale enterprise infrastructures. Delivering unmatched 32/128 Gbps performance, industry-leading port density, and integrated network sensors, the Brocade G620 accelerates data access, adapts to evolving requirements, and drives always-on business.



Features and benefits

GEN 6 FIBRE CHANNEL

Brocade Gen 6 Fibre Channel is the purpose-built network infrastructure for mission-critical storage, delivering breakthrough performance, increased scalability, and operational stability. The Brocade G620 Switch with Gen 6 Fibre Channel, Brocade Fabric Vision technology, and IO Insight delivers unmatched 32/128 Gbps performance, industry-leading port density, and integrated network sensors. These next-generation storage networking technologies and capabilities enable the Brocade G620 to accelerate data access, adapt to evolving requirements, and drive always-on business operations for hyper-scale virtualization, larger cloud infrastructures, and growing flash-based storage environments.

The Brocade G620 is built for maximum flexibility, scalability, and ease of use. Organizations can scale from 24 to 64 ports with 48 SFP+ and 4 Q-Flex ports, all in an efficient 1U package. In addition, a simplified deployment process and a point-and-click user interface make the Brocade G620 easy to use. With the Brocade G620, organizations gain the best of both worlds: high-performance access to industry-leading storage technology and “pay-as-you-grow” scalability to support an evolving storage environment.

Maximize Performance for Application and Solid State Storage Architectures

Faced with unpredictable virtualized workloads and growing flash storage environments, organizations need to ensure that the network does not become the bottleneck. The Brocade G620 delivers increased performance for growing and dynamic workloads through a combination of market-leading throughput and low latency across 32 Gbps and 128 Gbps links. With Gen 6 ASIC technology providing up to 566 million frames switched per second, the Brocade G620 Switch shatters application performance barriers with up to 100 million IOPS to meet the demands of flash-based storage workloads. At the same time, port-to-port latency is minimized to 700 nanoseconds through the use of cut-through switching at 32 Gbps. With 48 SFP+ ports and 4 Q-Flex ports, each providing four 32 Gbps connections, the Brocade G620 can scale up to 64 device ports for an aggregate throughput of 2 Tbps. Moreover, each Q-Flex port is capable of 128 Gbps parallel Fibre Channel for device or ISL connectivity, enabling administrators to consolidate and simplify cabling infrastructure. Administrators can achieve optimal bandwidth utilization, high availability, and load balancing by combining up to eight ISLs in a 256 Gbps framed-based trunk. This can be achieved through eight individual 32 Gbps SFP+ ports or two 4 × 32 Gbps QSFP ports. Moreover, exchange-based Dynamic Path Selection (DPS) optimizes fabric-wide performance and load balancing by automatically routing data to the most efficient, available path in the fabric. This augments Brocade ISL Trunking to provide more effective load balancing in certain configurations.

Simplify Scalability and Management Complexity

The Brocade G620 features up to 64 Fibre Channel ports in an efficiently designed 1U form factor, delivering industry-leading port density and space utilization for simplified scalability and data center consolidation. With this high-density design, organizations can pack more into a single data center with a smaller footprint, reducing costs and management complexity.

Designed for maximum flexibility and value, this enterprise-class switch offers “pay-as-you-grow” scalability with Ports on Demand (PoD) capability. Organizations can quickly, easily, and cost-effectively scale from 24 to 64 ports with a combination of 12-port SFP+ PoD and 16-port Q-Flex PoD. Each of the 48 SFP+ ports supports 4, 8, 16, and 32 Gbps Fibre Channel speeds, while each of the 4 Q-Flex ports is capable of supporting 4 × 32 Gbps, or 128 Gbps, Fibre Channel speeds. In addition, Q-Flex ports are designed to support QSFP optics to deliver 4 to 1 cable consolidation (combining four cables into one cable per port).

Brocade G620 ports are available for device port or ISL port connectivity. As such, Q-Flex ports can be used as ISLs to provide simple build-out of fabrics, with more switching bandwidth. In addition, flexible, high-speed 32 Gbps and 16 Gbps optics allow organizations to deploy bandwidth on demand to meet growing data center needs. With its flexible PoD capability, the Brocade G620 provides excellent overall value and the agility needed to deliver rapid deployments to meet user demands and support higher growth.

Along with providing best-in-class scalability, the Brocade G620 simplifies end-to-end network management by automating monitoring and diagnostics through Brocade Fabric Vision™ technology. The switch is easy to deploy with the Brocade EZSwitchSetup wizard and provides validation prior to deployment with the ClearLink Diagnostic Ports (D_Ports) feature. For maximum flexibility, the switch also features dual airflow direction options to support the latest hot aisle/cold aisle configurations.

Gain Control and Insight to Quickly Identify Problems and Meet Critical SLAs

The Brocade G620, with Gen 6 Fibre Channel technology and integrated network sensors, helps organizations achieve greater control and insight to quickly identify root cause at the storage tier, reducing time to resolution so critical Service Level Agreements (SLAs) can be met. The IO Insight capability non-intrusively gathers IO statistics, which can be used within an intuitive, policy-based monitoring and alerting suite to configure thresholds and alarms. In-band device latency and IOPS monitoring detects degraded storage performance, allowing administrators to proactively optimize performance and availability to ensure maximum performance. Additional features include:

- Provides proactive, non-intrusive, real-time monitoring and alerting with visibility into storage IO health and performance
- Monitors individual host or storage devices to gain deeper insight into the performance of the network to maintain SLA compliance
- Obtains IO latency and IOPS metrics for a storage device in order to diagnose IO operational issues

Forward Error Correction (FEC) capabilities further increase resiliency by automatically detecting and recovering network transmission errors. To ensure predictable performance prior to deployment, organizations can validate infrastructure with ClearLink Diagnostics and Flow Generator features, and baseline storage performance using IO Insight.

Simplified Management and Robust Network Analytics

Brocade Fabric Vision technology provides a breakthrough hardware and software solution that helps simplify monitoring, maximize network availability, and dramatically reduce costs. Featuring innovative monitoring, management, and diagnostic capabilities, Fabric Vision technology enables administrators to avoid problems before they impact operations, helping their organizations meet SLAs. Fabric Vision technology includes:

- **IO Insight**
Proactively and non-intrusively monitors storage device IO performance and behavior through integrated network sensors at the storage tier, providing deep insight into problems and ensuring service levels.
- **Monitoring and Alerting Policy Suite (MAPS):**
Leverages prebuilt, rule-policy-based templates within MAPS to simplify fabric-wide threshold configuration, monitoring, and alerting. Administrators can configure the entire fabric (or multiple fabrics) at one time using common rules and policies, or customize policies for specific ports or switch elements. In addition, administrators can include IO Insight metrics in MAPS policies to be notified of performance degradation.
- **Fabric Performance Impact (FPI) Monitoring:**
Leverages predefined MAPS policies to automatically detect and alert administrators to different latency severity levels, and to identify slow drain devices that could impact network performance. This feature identifies various latency severity levels, pinpointing exactly which devices are causing or are impacted by a bottlenecked port, and quarantines slow drain devices automatically to prevent buffer credit starvation.
- **Dashboards:**
Provides integrated dashboards that display an overall SAN health view, along with details on out-of-range conditions, to help administrators easily identify trends and quickly pinpoint issues occurring on a switch or in a fabric.
- **Configuration and Operational Monitoring Policy Automation Services Suite (COMPASS):**
Simplifies deployment, safeguards consistency, and increases operational efficiencies of larger environments with automated switch and fabric configuration services. Administrators can configure a template or adopt an existing configuration to seamlessly deploy a configuration across the fabric. In addition, they can ensure settings do not drift over time with COMPASS configuration and policy violation monitoring within Brocade Network Advisor dashboards.
- **Brocade ClearLink Diagnostics:**
Ensures optical and signal integrity for Fibre Channel optics and cables, simplifying deployment and support of high-performance fabrics. ClearLink Diagnostic Port (D_Port) is an advanced capability of Fibre Channel platforms.
- **Flow Vision:**
Enables administrators to identify, monitor, and analyze specific application flows in order to simplify troubleshooting, maximize performance, avoid congestion, and optimize resources. Flow Vision includes:

- **Flow Monitor:**
Provides comprehensive visibility, automatically learns, and non-disruptively monitors flow performance. Administrators can monitor all flows from a specific host to multiple targets or LUNs, from multiple hosts to a specific target/LUN, or across a specific ISL. Additionally, they can perform LUN level monitoring of specific frame types to identify resource contention or congestion that is impacting application performance. With IO Insight capability, administrators can monitor first IO response time, IO completion time, number of pending IOs, and IOPS metrics for a flow from a specific host to a target or LUN.
- **Flow Learning:**
Enables administrators to non-disruptively discover all flows that go to or come from a specific host port or a storage port, or traverse ISLs/IFLs or FCIP tunnels to monitor fabric-wide application performance. In addition, administrators can discover top and bottom bandwidth consuming devices and manage capacity planning.
- **Flow Generator:**
Provides a built-in traffic generator for pretesting and validating the data center infrastructure for robustness—including route verification and integrity of optics, cables, ports, back-end connections, and ISLs—before deploying applications.
- **Flow Mirroring:**
Provides the ability to non-disruptively create copies of specific application and data flows or frame types that can be captured for in-depth analysis.
- **Forward Error Correction (FEC):**
Enables recovery from bit errors in device connections and ISLs, enhancing transmission reliability and performance.
- **Credit Loss Recovery:**
Helps overcome performance degradation and congestion due to buffer credit loss.

BROCADE FABRIC VISION TECHNOLOGY

Brocade Fabric Vision technology with IO Insight, an extension of Gen 6 Fibre Channel, provides unprecedented insight and visibility across the storage network with powerful integrated monitoring, management, and diagnostic tools that enable organizations to:

- **Simplify monitoring:**
 - Deploy more than 20 years of storage networking best practices with a single click
 - Leverage visibility into storage IO health and performance with key latency and performance metrics to maintain SLA compliance
 - Gain comprehensive visibility into the fabric using browser-accessible dashboards with drill-down capabilities

- **Increase operational stability:**
 - Avoid 50 percent of common network problems with proactive monitoring
 - Identify hot spots and automatically mitigate network problems—before they impact application performance
 - Identify IOs that deviate from expected behavior to facilitate fault isolation and troubleshooting
- **Dramatically reduce costs:**
 - Eliminate nearly 50 percent of maintenance costs through automated testing and diagnostic tools
 - Save up to millions of dollars on CapEx costs by eliminating the need for expensive third-party tools through integrated network sensors, monitoring, and diagnostics
 - Tune device configurations with integrated IO metrics to optimize storage performance and increase ROI

Brocade Network Advisor

Brocade Network Advisor simplifies Gen 6 Fibre Channel management and helps organizations proactively diagnose and resolve issues to maximize uptime, increase operational efficiency, and reduce costs. The wizard-driven interface dramatically reduces deployment and configuration times by allowing fabrics, switches, and ports to be managed as groups. Customizable dashboards graphically display performance and health indicators out of the box, including all data captured using Brocade Fabric Vision technology. To accelerate troubleshooting, administrators can use dashboard playback to quickly review past events and identify problems in the fabric. Dashboards and reports also can be configured to show only the most relevant data, enabling administrators to more efficiently prioritize their actions and maintain network performance.

A Building Block for Virtualized, Private Cloud Storage

The Brocade G620 provides a critical building block for today's highly virtualized and cloud environments. It both simplifies server virtualization and meets the high-throughput demands of Solid State Disks (SSDs). The Brocade G620 also supports multitenancy in cloud environments through Virtual Fabrics, Quality of Service (QoS), and fabric-based zoning features. In addition, it provides efficient link utilization with up to 64 Gbps of in-flight data compression over ISLs. Organizations can have up to four ports at 16 Gbps of in-flight data compression per Brocade G620 Switch. Furthermore, internal fault-tolerant and enterprise-class RAS features help minimize downtime to support mission-critical cloud environments.

Brocade Access Gateway Mode

The Brocade G620 can be deployed as a full-fabric switch or as a Brocade Access Gateway, which simplifies fabric topologies and heterogeneous fabric connectivity (the default mode setting is a switch). Brocade Access Gateway mode utilizes N_Port ID Virtualization (NPIV) switch standards to present physical and virtual servers directly to the core of SAN fabrics. This makes it transparent to the SAN fabric, greatly reducing management of the network edge. The Brocade G620 in Brocade Access Gateway mode can connect servers to NPIV-enabled Brocade B-Series, or other SAN fabrics.

Organizations can easily enable Brocade Access Gateway mode via Brocade Network Advisor or a CLI. Key benefits of Brocade Access Gateway mode include:

- Improved scalability for large or rapidly growing server and virtual server environments
- Reduced management of the network edge, since Brocade Access Gateway does not have a domain identity and appears transparent to the core fabric
- Support for heterogeneous SAN configurations without reduced functionality for server connectivity

Maximizing Investments

To help optimize technology investments, Fujitsu offer complete solutions that include professional services, technical support, and education.

Technical details

BROCADE G620 Specifications

System Architecture

Fiber Channel ports	<p>Switch mode (default): Minimum of 24 ports and maximum of 64 ports configuration. Port numbers above minimum are enabled through 12-port SFP+ increments via Ports on Demand (PoD) licenses and through one 4-port QSFP PoD, providing 16-port increments through a Q-Flex license; E_Ports, F_Ports, D_Ports, EX_Ports.</p> <p>Brocade Access Gateway default port mapping: 40 SFP+ F_Ports, 8 SFP+ N_Ports</p>
Scalability	Full-fabric architecture with a maximum of 239 switches
Certified maximum	6,000 active nodes; 56 switches, 19 hops in Brocade Fabric OS® fabrics; larger fabrics certified as required
Performance	Fibre Channel: 4.25 Gbps line speed, full duplex; 8.5 Gbps line speed, full duplex; 14.025 Gbps line speed, full duplex; 28.05 Gbps, full duplex; 112.2 Gbps, full duplex; auto-sensing of 4, 8, 16, 32 Gbps port speeds and capable of supporting 128 Gbps speeds;
ISL trunking	Frame-based trunking with up to eight 32 Gbps SFP+ ports per ISL trunk or up to two 128 Gbps QSFP ports per ISL trunk. Exchange-based load balancing across ISLs with DPS included in Brocade Fabric OS.
Aggregate bandwidth	2 Tbps
Maximum fabric latency	Latency for locally switched ports is 700 ns; compression is 1 μ s per node
Maximum frame size	2,112-byte payload
Frame buffers	15,360 dynamically allocated
Classes of service	Class 2, Class 3, Class F (inter-switch frames)
Port types	D_Port (ClearLink Diagnostic Port), E_Port, EX_Port, F_Port, AE_Port; optional port-type control Brocade Access Gateway mode: F_Port and NPIV-enabled N_Port
Data traffic types	Fabric switches supporting unicast
Media types	128 Gbps: Brocade G620 requires Brocade hot-pluggable QSFP, MPO connector; 128 Gbps SWL 32 Gbps: Brocade G620 requires Brocade hot-pluggable SFP+, LC connector; 32 Gbps SWL 16 Gbps: Brocade G620 requires Brocade hot-pluggable SFP+, LC connector; 16 Gbps SWL Fibre Channel distance subject to fiber-optic cable and port speed.
Fabric services	Monitoring and Alerting Policy Suite (MAPS); Flow Vision; Brocade Adaptive Networking (Ingress Rate Limiting, Traffic Isolation, QoS); Fabric Performance Impact (FPI) monitoring; Slow Drain Device Quarantine (SDDQ); Brocade Advanced Zoning (default zoning, port/WWN zoning, broadcast zoning, peer zoning, target-driven zoning); Dynamic Fabric Provisioning (DFP); Dynamic Path Selection (DPS); Brocade Extended Fabrics; Enhanced BB Credit Recovery; FDMI; Frame Redirection; Frame-based Trunking; FSPF; Integrated Routing; IPoFC; Brocade ISL Trunking; Management Server; NPIV; Time Server; Registered State Change Notification (RSCN); Reliable Commit Service (RCS); Simple Name Server (SNS); Virtual Fabrics (Logical Switch, Logical Fabric); Read Diagnostics Parameter (RDP)

Note: Some fabric services do not apply or are unavailable in Brocade Access Gateway mode.

BROCADE G620 Specifications(Continued)

Management

Supported management software	HTTP, SNMP v1/v3 (FE MIB, FC Management MIB), SSH; Auditing, Syslog; NTP v3; Brocade Advanced Web Tools; Brocade Network Advisor SAN Enterprise or Brocade Network Advisor SAN Professional/Professional Plus; EZSwitch; Command Line Interface (CLI); SMI-S compliant; REST API; Administrative Domains; trial licenses for add-on capabilities
Security	DH-CHAP (between switches and end devices), FCAP switch authentication; HTTPS, IPsec, IP filtering, LDAP with IPv6, OpenLDAP, Port Binding, RADIUS, TACACS+, user-defined Role-Based Access Control (RBAC), Secure Copy (SCP), Secure RPC, Secure Syslog, SFTP, SSH v2, SSL, Switch Binding, Trusted Switch
Management access	10/100/1000 Mbps Ethernet (RJ-45), in-band over Fibre Channel, serial port (RJ-45)
Diagnostics	ClearLink optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/distance; flow mirroring; built-in flow generator; POST and embedded online/offline diagnostics, including environmental monitoring, FCping and Pathinfo (FC traceroute), frame viewer, non-disruptive daemon restart, optics health monitoring, power monitoring, RAStace logging, and Rolling Reboot Detection (RRD)

Mechanical

Enclosure	Back-to-front airflow; non-port-side intake; power from back, 1U
Size	Width: 440 mm (17.32 in.)
	Height: 43.9 mm (1.73 in.)
	Depth: 355.6 mm (14 in.)
System weight	7.71 kg (17 lb) with two power supply FRUs, without transceivers

Environmental

Operating environment	Temperature: 0°C to 40°C/32°F to 104°F Humidity: 10% to 85% (non-condensing)
Non-operating environment	Temperature: -25°C to 70°C/-13°F to 158°F Humidity: 10% to 90% (non-condensing)
Operating altitude	Up to 3,000 m (9,842 ft)
Storage altitude	Up to 12 km (39,370 ft)
Shock	Operating: Up to 20 G, 6 ms half-sine
	Non-operating: Half-sine, 33 G 11 ms, 3/eg axis
Vibration	Operating: 0.5 g sine, 0.4 grms random, 5 to 500 Hz
	Non-operating: 2.0 g sine, 1.1 grms random, 5 to 500 Hz
Airflow	64 ports at 716 BTU/hr

Power

Power supply	Dual, hot-swappable redundant power supplies with integrated system cooling fans
AC input	90 V to 264 V ~3.5 A
AC input line frequency	47 Hz to 63 Hz
AC power consumption	204 W with all 64 ports populated with 48×32 Gbps SFP+ SWL optics and 4× (4×32 Gbps) QSFP SWL optics 85 W for empty chassis with no optics

More information

Fujitsu platform solutions

In addition to Brocade G620 Switch, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing products

www.fujitsu.com/global/services/computing/

- PRIMERGY: Industry standard server
- SPARC Enterprise: UNIX server
- PRIMEQUEST: Mission-critical IA server
- ETERNUS: Storage system

Software

www.fujitsu.com/software/

- Interstage: Application infrastructure software
- Systemwalker: System management software

More information

Learn more about Brocade G620 Switch, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.
www.fujitsu.com/eternus/

Copyright

© Copyright 2016 Fujitsu Limited. Fujitsu, the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Limited
Website: www.fujitsu.com/eternus/
2016-10-03 AP-EN