Fujitsu recommends Windows 8 Pro.



Data Sheet Fujitsu CELSIUS H720 Workstation

Workstation Power on-the-Go

If you're a mobile worker looking for a customizable workstation and enhanced productivity, Fujitsu's CELSIUS H720 is the ideal device. This high-quality 39.6 cm (15.6-inch) workstation with comprehensive ISV certifications combines powerful performance with multiple connectivity options for effective mobile working. The modular bay provides individual expandability. Comprehensive protection against physical damage and security threats complete a reliable package.

Workstation performance

Higher productivity thanks to mobile workstation performance

■ 3rd generation Intel® Core™ i7 & i5 processors with vPro™ technology or Intel® Core™ i7 Extreme processor. Professional NVIDIA® Quadro® graphics with up to 384 CUDA cores.



Online anywhere, anytime.

■ Optional integrated 4G/LTE, Bluetooth® and WLAN

Full flexibility

Equip your system individually

■ Modular bay option for 2nd hard disk drive, 2nd battery or personal dongles

NVIDIA® Optimus™ Technology

Increased battery runtime

■ Dedicated graphics card is only used when needed

ISV certification

Excellent performance and absolute stability in professional environments

■ Comprehensive certification for workstation applications











Components

Processor	Intel® Core™ i7-3940X	M processor (3.0 GHz, c	ıp to 3.9 GHz, 8 MB)				
	Intel® Core™ i7-3920XM processor (2.9 GHz, up to 3.8 GHz, 8 MB)						
	Intel® Core™ i7-3840QM processor (2.8 GHz, up to 3.8 GHz, 8 MB)						
	Intel® Core™ i7-3820QM processor (2.7 GHz, up to 3.7 GHz, 8 MB) Intel® Core™ i7-3740QM processor (2.7 GHz, up to 3.7 GHz, 6 MB)						
							Intel® Core™ i7-3720QM processor (2.6 GHz, up to 3.6 GHz, 6 MB) Intel® Core™ i7-3630QM processor (2.4 GHz, up to 3.4 GHz, 6 MB)
			•				
	Intel® Core™ i7-3610QM processor (2.3 GHz, up to 3.3 GHz, 6 MB)						
	Intel® Core™ i7-3540M processor (3.0 GHz, up to 3.7 GHz, 4 MB)						
	Intel® Core™ i5-3380M processor (2.9 GHz, up to 3.6 GHz, 3 MB)						
	Intel® Core™ i5-3360M processor (2.8 GHz, up to 3.5 GHz, 3 MB) Intel® Core™ i5-3340M processor (2.7 GHz, up to 3.4 GHz, 3 MB) Intel® Core™ i5-3320M processor (2.6 GHz, up to 3.3 GHz, 3 MB) Intel® Core™ Processor with Intel® Small Business Advantage - Smart Platform for Unmanaged Small Business						
							PIOCESSO
Operating systems							
Operating system	Windows® 7 Professional 64-bit						
	Windows 8						
Operating system compatible	Windows 8 Pro Windows 7 Professional 22 hit						
	Windows® 7 Professional 32-bit Windows® 7 Professional 64-bit						
	Windows 8 / Professional 64-bit Windows 8						
	Windows 8 Pro						
Memory modules	2 GB (1 module(s) 2 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM						
	4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM 8 GB (1 module(s) 8 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM						
Base unit memory	CELSIUS H720 Dual Core K1000M	CELSIUS H720 Dual Core K2000M	CELSIUS H720 Quad Core K1000M	CELSIUS H720 Quad Core K2000M	CELSIUS H720 Quad Core K500M		
Supported capacity RAM (min.)	2 GB		4 GB				
Supported capacity RAM (max.)	16 GB 32 GB						
Memory slots total	2 4						
Memory slot type	SO DIMM (DDR3)						
Hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch						
	SSD SATA III, 256 GB, 2.5-inch						
	SSD SATA III, 128 GB, 2.5-inch, FDE						
	SSD SATA III, 128 GB, 2.5-inch						
	HDD SATA, 7,200 rpm, 640 GB, 2.5-inch, S.M.A.R.T.						
	HDD SATA, 7,200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.						
	HDD SATA, 5,400 rpm, 1000 GB, 2.5-inch, S.M.A.R.T.						
	HDD SATA, 5,400 rpm, 320 GB, 2.5-inch, S.M.A.R.T., FDE						
Hard disk notes	ShockSensor for HDD s	shock protection					
		One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.					
		ay vary, also depending		,			
WLAN (optional)	Intel® (entrino® Adva	nced-N 6205 802.11 a/b	o/a/n				
		ording to country-specif	-				
		Intel® Centrino® Wireless-N 2200 802.11b/g/n					
	Import and usage according to country-specific regulations.						
3G/4G (optional)	Sierra Wireless Gobi 3000 module						
	Sierra Wireless MC771						
		() LTF/HSPA+ module					

Page 2 / 7 www.fujitsu.com/fts/CELSIUS


Bluetooth (optional)	Bluetooth 4.0						
 Display	39.6 cm (15.6-inch), LE	ED backlight, (HD+), An	ti-glare display, magnes	ium, 1,600 x 900 pixel,	300:1, 220 cd/m²		
	39.6 cm (15.6-inch), LED backlight, (HD+), Anti-glare display, magnesium, 1,600 x 900 pixel, 300:1, 220 cd/m ² 39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display, magnesium, 1,920 x 1,080 pixel, 300:1, 220 cd/m ²						
Modular bay options	2nd battery						
	2nd hard disk drive						
	Blu-ray burner						
	DVD-RW Dual Double Layer Super Multi						
	Weight saver						
	CELCIUS 11720 D	CELCUIC LIZZO D	CEL CILIC 11720 0	CELCING LIZZO O	651 CHIC 11720 0 1		
Base unit	CELSIUS H720 Dual Core K1000M	CELSIUS H720 Dual Core K2000M	CELSIUS H720 Quad Core K1000M	CELSIUS H720 Quad Core K2000M	CELSIUS H720 Quad Core K500M		
Chipset	Intel® QM77						
BIOS features	BIOS based on Phoenix SecureCore						
Graphics							
Base unit	CELSIUS H720 Dual Core K1000M	CELSIUS H720 Dual Core K2000M	CELSIUS H720 Quad Core K1000M	CELSIUS H720 Quad Core K2000M	CELSIUS H720 Quad Core K500M		
Max. resolution external display	2,560 x 1,600 pixel via DisplayPort and Dual Link DVI	2,560 x 1,600 pixel via DisplayPort and Dual Link DVI	2,560 x 1,600 pixel via DisplayPort and Dual Link DVI	2,560 x 1,600 pixel via DisplayPort and Dual Link DVI	2,560 x 1,600 pixel via DisplayPort and Dual Link DVI		
Graphics brand name	NVIDIA® Quadro® K1000M	NVIDIA® Quadro® K2000M	NVIDIA® Quadro® K1000M	NVIDIA® Quadro® K2000M	NVIDIA® Quadro® K500M		
Graphics features	DualView	DualView	DualView	DualView	DualView		
Graphics card notes	NVIDIA® Quadro® K1000M: 192 cores	NVIDIA® Quadro® K2000M: 384 cores	NVIDIA® Quadro® K1000M: 192 cores	NVIDIA® Quadro® K2000M: 384 cores	NVIDIA® Quadro® K500M: 192 cores		
Dedicated video memory	2 GB (GDDR3 VRAM)	2 GB (GDDR3 VRAM)	2 GB (GDDR3 VRAM)	2 GB (GDDR3 VRAM)	1 GB (GDDR3 VRAM)		
Interfaces							
DC-in	1						
Audio: in	1						
Audio: out	1						
Internal microphones	2 digital array micropho	ones					
USB 2.0 total	1						
USB 3.0 total	3						
VGA	1						
DisplayPort	1						
Ethernet (RJ-45)	1						
Express card slots	1 (34 mm)						
SmartCard slot	1						
SIM card slot	1						
Multicardreader	1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB)						
eSATA	1	·					
Wired communication							
LAN	10/100/1,000 MBit/s In	tel® 82579 LM					
Keyboard							
,	TouchStick (optional) Touchpad with two mouse buttons and scroll via fingerprint sensor EcoButton LockWorkstation button MobilityCenter Button Fingerprint sensor						
Multimedia							
Audio type	On board						

Page 3 / 7 www.fujitsu.com/fts/CELSIUS

Multimedia			
Audio codec	Realtek ALC269		
Audio features	Stereo speakers, 2 internal microphones		
Power supply			
AC adapter	19 V / 150 W (7.89 A)		
Rated voltage range	100 V - 240 V (AC Input)		
Rated frequency range	50 Hz - 60 Hz		
1st battery	Li-lon battery 6-cell		
Runtime 1st battery	up to 9 hours		
Runtime 1st + 2nd battery	up to 14 hours		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	379.8 x 257.0 x 35.5 mm		
Weight	2.8 kg		
Weight notes	Actual weight may vary depending on configuration		
Operating ambient temperature	5 - 35 ℃		
Operating relative humidity	20 - 80 % (relative humidity, non-condensing)		
Additional Software			
Additional software (preinstalled) Additional software (optional) Manageability Manageability technology	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Fujitsu Display Manager EasyGuide online user documentation Power Saving Utility ShockSensor Utility SmartAccess Fujitsu Plugfree Network (network management utility) Intel® SBA (manageability suite for local administration) DTS® Sound Enhance Software Fujitsu Application Button Utility Fujitsu DeskUpdate (Driver and Utility tool) Microsoft Office (buy license to activate the pre-installed Microsoft Office) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) iAMT Intel® Active Manageability Technology v8.0 (not activated, not set up)		
Manageability software	Intel® vPro™ technology WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management		
DeskView components	DeskView Integration for Symantec Management Platform Inventory Management BIOS Management Driver Management Security Management Alarm Management		
Supported standards	WMI PXE BootP (made4you)		
Manageability link	http://www.fujitsu.com/fts/solutions/high-tech/dynamic-infrastructure/solutions/workplace/manageability/feature-finder.html		
Security			
Physical Security	Kensington Lock support		

Page 4 / 7 www.fujitsu.com/fts/CELSIUS

Socurity							
Security	Advanced Theft Protection						
System and BIOS Security	Computrace® enabled BIOS						
	Optional: Trusted platform module (TPM 1.2)						
	Optional: Irusted platform module (IPM 1.2) Norton Internet Security (incl. Firewall) 90 days version						
User Security	Integrated Fingerprint Sensor						
oser security	Separate SmartCard slot						
	Hard disk password						
	SystemLock BIOS SmartCard security						
	User and supervisor BIOS password						
	Preboot Authentification with SystemLock 3						
Compliance							
Product	CELSIUS H720 CELSIUS H720 CELSIUS H720 CELSIUS H720 CELSIUS H720						
Floduct	Dual Core K1000M Dual Core K2000M Quad Core Quad Core Quad Core K500M						
	K1000M K2000M						
Germany	GS						
Europe	CE						
USA/Canada	cULus						
USA/Callada	FCC Class B part 15C/E + 22 + 24 (depending on wireless configuration)						
Global	RoHS (EU & China)						
diobai	Medical EMC standard IEC60601-1-2 in combination with medical kit						
	ENERGY STAR® 5.0 (depending on configuration)						
	EPEAT® Gold (dedicated regions)						
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates						
Port Replicator interfaces (optional)							
DC-in	1 (19V)						
Power on switch	1						
Audio: headphone	1						
Audio: microphone	1						
USB 3.0 total	4						
DisplayPort	1 (up to 2560 x 1600)						
VGA	1						
DVI	1 (up to 1920 x 1200)						
Ethernet (RJ-45)	1 (10/100/1000)						
Kensington Lock support	1						
eSATA	1						
Notes	Port replicator does not support 0-Watt technology, must use AC Adapter 19V/210W (11,05 A).						
Warranty							
Standard Warranty	3 years (depending on country)						
Service level	Collect & Return Service / Bring-in Service (for countries within region FTS CEMEA&I, for all other countries depending						
Selvice level	on local regulations)						
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty						
Maintenance and Support Services - th							
Spare Parts availability	5 years after end of product life						
Service Weblink	http://www.fujitsu.com/fts/services/support						
DELAICE MEDITIK	пир.пууууладиза.сопппзэстунсэлэйрүөн						



Notebookcheck.com – online, Fujitsu CELSIUS H720, test result: good, Germany, November 2012



PC För Alla, Fujitsu CELSIUS H720, test result: Best in Test (Bäst i test), Sweden - November 2012

Recommended Accessories

PocketSaver



The Fujitsu Kensington PocketSaver with its pocketable design and 1200mm retractable steel cable is the perfect anti-theft solution for when you are on the go. The patented T-bar lock mechanism and the tempered steel cable provide maximum security. The Fujitsu Kensington PocketSaver keeps your device protected wherever you roam.

Order Code: S26391-F6045-L100

Privacy filter



Privacy filters help block the screen view from anyone viewing the computer Order Code: from a side view. 3M's unique microlouver privacy technology allows S26391-F6097-L317 persons directly in front of the computer to see on-screen data clearly

Supreme Case Grand 16



The Supreme Case Grand 16 protects notebooks with up to 16-inch screens. Order Code: A padded notebook compartment with shock-absorbing foam ensures your notebook is well protected. Front and back pockets provide space for office supplies and documents. The leather finish, professional design and carrying comfort make it the ideal business case.

S26391-F119-L770

Wireless Notebook Mouse WI610



The Wireless Notebook Mouse WI610 uses the latest wireless 2.4 GHz technology, and an ultra-high resolution switchable sensor to give you the precision and reliability you need (1000/1500/2000 dpi). Sporting a stylish silver-black finish, the WI610 wireless mouse is well suited to all

Order Code: S26381-K460-L100

SpaceMouse™ Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse[™] Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code: S26381-K459-L100

More information

Fujitsu platform solutions

In addition to Fujitsu CELSIUS H720, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS H720, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2014-01-21 CE-EN All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions