

Data Sheet

FUJITSU Display B24W-6 LED Display

Advanced display: 61 cm (24-inch) widescreen
Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B24W-6 LED combines the best ergonomic and energy saving solutions for intensive office use. The flexible stand with height adjust assures an individual and healthy posture for long-time working sessions. With its impressive screen size it allows working on different documents in parallel or standard CAD applications.

Unique, high efficient energy saving solutions like LED backlight panel, ECO operation mode and ECO standby.

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office.

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt.

Highly flexible connectivity through different interfaces - 4x USB, DisplayPort, HDCP (via DVI-D), DVI and Analog.

The abundant screen size of 61 cm (24-inch) provides the professional 16:10 format with 1920 x 1200 pixels for view of 2 x DIN A4 pages side by side.

Representative design with space saving front frame and discretely integrated speakers.

With DisplayView Manageability tools ready for remote inventory gathering and configuration tasks.



Technical details

Special features

4-in-1 Stand, Eco button for Eco mode and 3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage

Ergonomic stand

Stand	4-in-1 Stand
Height adjust range	100 mm
Picture height over desk (min)	50 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	340°

Picture performance

Panel and backlit	TN/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1000:1
Contrast - advanced	20,000,000:1
Response time typical	5 ms
Viewing angle (h/v) - typical	170°/170° CR5:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m ²

Size and resolution

Aspect ratio	16:10
Diagonal Size	61 cm (24-inch)
Resolution (native)	1,920 x 1,200 pixel (recommended)
Resolution (interpolated)	1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	518 x 324 mm
Pixel Pitch	0.270 mm

Frequencies

Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz

Connectivity

DisplayPort	1 x DisplayPort
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 1.5 W
USB downstream	4 x USB 2.0
USB upstream	1 x USB

Ease-of-use menu

Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	9300K, 6500K, sRGB, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Position, OSD-Timeout, Factory recall

Power consumption (typical)

Soft switch off	0.3 W
Power save mode	0.4 W
Operating with EPA settings	22 W
Operating maximum brightness	26 W

Power supply display	integrated
Power notes	without sound, without USB;
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	CE certification according to EC Directive 2004/108/EEC, EN 60950, Nordic Swan, RoHS, WEEE, IT-Eco-Declaration
Model	B24W-6
Germany	GS
Russia	GOST-R
USA/Canada	FCC Class B, cUL
Australia/New Zealand	C-Tick
Japan	VCCI
South Korea	KC
Argentina	TÜV-S
Taiwan	BSMI
China	CCC
Saudi Arabia	SASO
Mexico	cUL
Global	TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70,000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	559 x 65 x 368 mm 22.01 x 2.56 x 14.49 inch
Dimension with stand (W x D x H)	559 x 197 x 395 mm 22.01 x 7.76 x 15.55 inch
Weight (packed)	8.4 kg 18.52 lbs
Weight (unpacked)	6.3 kg 13.89 lbs
Weight (Monitor only)	3.6 kg 7.94 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1427-V140
Country specific order code	BDL:K1427V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1427V140-CHN - with China power cable and CEL, mandatory for China BDL:K1427V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
EAN Code	4051554318802
Warranty	
Standard Warranty	3 years (depending on country)
Service level	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Warranty

Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B24W-6 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B24W-6 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2014-07-04 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions