

# Data Sheet

## FUJITSU Display P24-9 TE

Widescreen 60.5 cm (23.8-inch) Superior Display  
Ideal for future-oriented workplaces that need Shared Desk scenarios

The FUJITSU Display P24-9 TE is a widescreen, ultra-thin bezel display that combines future workplace concepts with advanced ergonomics. The monitor has an intelligent USB Type C hub ideal for a AiO-type use in addition to one cable connectivity for notebooks used by an on-the-move flexible workforce that needs shared workspaces.

23.8-inch monitor with 16:9 aspect ratio and USB Type C interface that enables users to connect their PC using just one cable

DisplayPort Out (Daisy Chain) allows users to connect to two displays easily and without complexity enabling a tidy, shared desk scenario

Smart Power ON and LED function for AiO-type usage that enables you to operate your mini PC and Display with one switch and status indicator on display front

5-in-1 stand base with integrated cable guide that enables users to adjust height, tilt, swivel and rotate monitor display as per their comfort

Ultra-thin bezel housing on three sides for multi-monitoring scenarios and integrated speakers and cable guide for a clean desk experience

Environmental-friendly LED technology with highly efficient energy saving functions like ECO Operation mode and ECO standby helping you save on costs

DisplayView™ Software enables you to configure your monitor for remote management, administrative tasks and much more



# Technical details

## Special features

Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU PC e.g. ESPRIMO G), DICOM Greyscale Standard Display Function compatible gamma preset, Eco button for Eco mode and 4-colored status LED, Presence sensor with PC security solution, In-Plane Switching (IPS) technology, Color accuracy average DeltaE<2, Auto Brightness Control (ABC), Workplace Lighting Guide, DisplayView™ Software, 5-in-1 Stand, Cable guide, 24/7 usage, Integrated speakers

## Ergonomic stand

Stand	5-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	45 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	345°

## Picture performance

Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m <sup>2</sup>

## Size and resolution

Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm

## Frequencies

Horizontal	30 - 82 kHz
Vertical	48 - 76 Hz

## Connectivity

DisplayPort	1 x DisplayPort, 1 x DisplayPort Out (Daisy Chain)
HDMI	1 x HDMI
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2 W
USB downstream	4x USB 3.2 Superspeed 5Gbit (1x Type C and 1x Type A on side, 2x Type A on bottom)
USB upstream	1 x USB Type C with alternate mode for video data and power delivery up to 65W

## Ease-of-use menu

Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level, ACR
Mode	sRGB, Office, Photo, Video, Low Blue Light, Custom, D-Mode
Color	5000K, 6500K, 7500K, Native, RGB Adjust
OSD	Language, OSD-Timeout, OSD rotation

<b>Image adjust</b>	Clock, Phase, H-Position, V-Position, Expansion, Sharpness
<b>Audio</b>	Mute, Volume, Analog, Digital
<b>Information</b>	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status, ABC Status
<b>Advanced settings</b>	Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall

**Power consumption (typical, w/o sound)**

<b>Soft switch off</b>	0.23 W
<b>Power save mode</b>	0.38 W
<b>Operating with EPA settings</b>	14.29 W
<b>Total Energy Consumption (ETEC)</b>	45.97 kWh/year
<b>Power supply</b>	external
<b>Power notes</b>	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0

**Electrical values**

<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Protection class</b>	1

**Compliance**

<b>Model</b>	P24-9T
<b>Global</b>	TCO Certified Displays 8.0, ENERGY STAR® 8.0, EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I)
<b>Europe</b>	Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration
<b>Australia/New Zealand</b>	RCM
<b>Germany</b>	TÜV GS
<b>Russia</b>	EAC
<b>Singapore</b>	S-Mark
<b>South Korea</b>	KC, E-Standby
<b>Taiwan</b>	BSMI
<b>USA/Canada</b>	FCC Class B, cTUVus
<b>Compliance notes</b>	Certifications are still in progress
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

**Dimensions / Weight / Environmental**

<b>Dimension without stand (W x D x H)</b>	540.3 x 63.1 x 325.6 mm 21.27 x 2.48 x 12.82 inch
<b>Dimension with stand (W x D x H)</b>	540.3 x 229.3 x 347 mm 21.27 inch x 9.03 x 13.65 inch
<b>Weight (unpacked)</b>	5.3 kg 11.7 lbs
<b>Weight (Monitor only)</b>	3.3 kg 7.3 lbs
<b>Operating ambient temperature</b>	5 - 35 °C (41 - 95 °F)
<b>Operating relative humidity</b>	10 - 85 % (non condensing)

**Miscellaneous**

<b>Miscellaneous</b>	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
<b>Color</b>	Marble grey

**Package content**

<b>Display delivered accessories</b>	DisplayPort data cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m USB cable 1m (USB-C to USB-C) External power adapter Quickstart flyer Safety notes
--------------------------------------	--

<b>Display delivered accessories notes</b>	Power cable with IEC-60320-C5 (Mickey Mouse) 3-pin connector on power adapter side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for Presence Sensor PC security solution External power adapter and power cable in black color
<b>Packaging dimension (mm)</b>	
<b>Weight (packed)</b>	7.2 kg
<b>Weight (packed) (lbs)</b>	15.8 lbs
<b>Order information</b>	
<b>Order Code</b>	S26361-K1646-V141
<b>EAN Code</b>	4059595615010
<b>Country specific order code</b>	BDL:K1646V141-UK - with UK power cable, mandatory for Arabian countries BDL:K1646V141-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
<b>Accessories information</b>	Further helpful options: Stands and Mounting kits: <a href="http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html">http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html</a> Available Adapters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf</a>
<b>Warranty</b>	
<b>Warranty period</b>	3 years (depending on country)
<b>Warranty type</b>	Collect & Return Service (depending on country specific requirements)
<b>Warranty Terms &amp; Conditions</b>	<a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>
<b>Spare Parts availability</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Display P24-9 TE, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Display P24-9 TE, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/products/computing/peripheral/displays](http://www.fujitsu.com/emeia/products/computing/peripheral/displays)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2020 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

## CONTACT

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2020-05-25 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2020 Fujitsu Technology Solutions GmbH