

# Data Sheet

## FUJITSU Display P27-8 TE Pro

Widescreen Performance Display 68.5 cm (27 inch)  
Advanced sensor for workplace security and user comfort

The FUJITSU Display P27-8 TE Pro has a 2560 x 1440 QHD resolution and comes with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a wide viewing angle that delivers consistent picture quality, a 100% sRGB color space coverage, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.


High performance QHD resolution monitor with IPS technology that delivers consistent clarity from any perspective

Thin bezel housing that gives you maximum display area ideal for multi-monitor installations

Front sensor on the display frame helps users activate human-centric features such as Auto Brightness, Presence sensing using DisplayView IT Suite software

Pre-calibrated for color ( $\Delta E \leq 2$ ) and grey scale calibration as per Digital Imaging and Communications in Medicine (DICOM) Standards

Best choice for multi monitor environments due to DisplayPort 1.2 and DisplayPort output for daisy chaining. Bidirectional 90° rotation with Auto Pivot sensor.



# Technical details

## Special features

Presence sensor with PC security solution, In-Plane Switching (IPS) technology, DICOM Greyscale Standard Display Function compatible gamma preset, Color accuracy average DeltaE<2, Eco button, 4-in-1 Stand, Auto Brightness Control (ABC), Workplace Lighting Guide, Auto Pivot, Always available USB (in operating and standby mode), DisplayView™ IT Suite, 24/7 usage, Cable guide, Integrated speakers

## Ergonomic stand

Stand	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	50 mm
Rotation to portrait	90° clockwise and counterclockwise, Auto Pivot sensor
Tilt angle	-5° / +35°
Swivel angle	340°

## Picture performance

Panel and backlight	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	3H hard coating, Anti-glare
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (8-bit)
High color gamut - typical	77% NTSC (CIE 1931) / 100% sRGB color space
Brightness - typical	350 cd/m <sup>2</sup>

## Size and resolution

Aspect ratio	16:9
Diagonal Size	68.5 cm (27-inch)
Resolution (native)	2,560 x 1,440 pixel
Resolution (interpolated)	1,920 x 1,200 pixel, 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	597 x 336 mm
Pixel Pitch	0.233 mm

## Frequencies

Horizontal	30 - 100 kHz
Vertical	48 - 76 Hz
Frequencies - bandwidth	360 MHz (DisplayPort)

## Connectivity

DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
DVI	1 x DualLink DVI
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 2 W
USB downstream	4 x USB 3.1 Gen1
USB upstream	1 x USB 3.1 Gen1

## Ease-of-use menu

Notes	6 sensor keys on front side
Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese traditional, Chinese simply
Brightness / Contrast	Brightness, Contrast, Black level, Auto level, Auto Brightness, ACR, Lighting Guide
Mode	D-Mode, sRGB, Office, Photo, Video, Low Blue Light, Custom
Color	5000K, 6500K, 7500K, Native, RGB Adjust

OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Expansion, Saturation, Sharpness
Audio	Mute, Volume
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status, ABC Status
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall
<b>Power consumption (typical)</b>	
Soft switch off	0.2 W
Power save mode	0.3 W
Operating with EPA settings	18 W
Total Energy Consumption (Etec)	56.75 kWh/year
Operating maximum brightness	36 W
Power supply	integrated
Power notes	Speakers off, USB not connected Etec and EPA refer to ENERGY STAR® 7.0
<b>Electrical values</b>	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
<b>Compliance</b>	
Europe	Energy Efficiency Class: A, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration
Model	P27-8T
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Australia/New Zealand	RCM
Japan	VCCI
South Korea	KC#E-Standby
Singapore	S-Mark
Taiwan	BSMI
China	CCC
Saudi Arabia	SASO
Global	TCO Certified Displays 7.0, ENERGY STAR® 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified, TÜV Low Blue Light Certified
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
<b>Dimensions / Weight / Environmental</b>	
Dimension without stand (W x D x H)	613 x 57 x 364 mm
	24.13 x 2.24 x 14.33 inch
Dimension with stand (W x D x H)	613 x 227 x 396 mm
	24.13 x 8.94 x 15.59 inch
Weight (packed)	9.87 kg
	21.76 lbs
Weight (unpacked)	7.61 kg
	16.78 lbs
Weight (Monitor only)	3.02 kg
	6.66 lbs
Operating ambient temperature	5 - 35 °C
<b>Miscellaneous</b>	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey

**Package content**

<b>Display delivered accessories</b>	DisplayPort data cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
<b>Display delivered accessories notes</b>	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution

**Order information**

<b>Order Code</b>	S26361-K1609-V140
<b>EAN Code</b>	4057185779036
<b>Country specific order code</b>	BDL:K1609V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1609V140-CHN - with China power cable and CEL, mandatory for China BDL:K1609V140-ID - with Import label, mandatory for Indonesia (on demand) BDL:K1609V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed BDL:K1609V140-IND - with India power cable and BIS certificate, mandatory for India
<b>Accessories information</b>	Further helpful options: Stands and Mounting kits: <a href="http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html">http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html</a> Available Adapters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf</a>

**Warranty**

<b>Warranty period</b>	3 years (depending on country)
<b>Warranty type</b>	Collect & Return Service (depending on country specific requirements)
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Spare Parts availability</b>	5 years after end of product life 5 years
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Display P27-8 TE Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Display P27-8 TE Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/fts/displays>

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2018 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2018-12-18 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2018 Fujitsu Technology Solutions GmbH