

# Data Sheet

## FUJITSU Storage ETERNUS AF650 S2 All-Flash Array

Storage Unchained!



### ETERNUS AF Storage

FUJITSU Storage ETERNUS AF is an incredibly fast and flexible all-flash storage system for the next generation data center. At an affordable price point, it makes flash the new normal for all tier-1 applications in enterprise IT. Response times are ultra-low – in fact, they set performance records. The ETERNUS AF is also built to be smart, with easily-configurable automated quality of service to ensure each app gets the performance it needs, plus flexible deduplication and compression that can be turned on when required – and off when not. It keeps data safe as houses, with full-fledged DR with mirroring and automated transparent failover.

### ETERNUS AF650 S2

The Fujitsu All-Flash Storage system ETERNUS AF650 S2 delivers leading storage performance and automated quality of service management enabling a maximum of system utilization and contributing to a fast ROI. It is the perfect solution when consolidating data of large-scale databases, business-critical applications and business analytics / big data – all into one all-flash system. Extensive high-availability and disaster recovery capabilities make ETERNUS AF650 an ideal storage system for any kind of business data.



# Features & Benefits

Main Features	Benefits
Based on ETERNUS DX standard architecture	<ul style="list-style-type: none"> <li>■ Performance optimized design</li> <li>■ Proven and mature technology</li> <li>■ System availability of 99.9999%</li> <li>■ Common management across all-flash and hybrid ETERNUS storage systems</li> </ul>
Flexible and flash optimized storage	<ul style="list-style-type: none"> <li>■ Ultra-low response times for all applications</li> <li>■ Massive increase of IOPS</li> <li>■ No complicated tuning measures required</li> <li>■ Scalable in capacity and connectivity</li> </ul>
Selective use of deduplication / compression	<ul style="list-style-type: none"> <li>■ Decide on volume label whether to use it or not</li> <li>■ Cost reduction for flash</li> <li>■ Increased lifespan of flash</li> </ul>
Automated Quality-of-Service	<ul style="list-style-type: none"> <li>■ Control of applications priorities according to business needs.</li> <li>■ Automation of monitoring and adjustment</li> <li>■ Minimization of admin efforts</li> <li>■ Guaranteed service levels</li> </ul>
Storage Cluster Option/Transparent failover	<ul style="list-style-type: none"> <li>■ Avoid planned or unplanned downtimes</li> <li>■ Enjoy 100% data insurance and non-stop operations</li> </ul>
<b>Convincing access performance and latency</b> <ul style="list-style-type: none"> <li>■ Random access performance: Up to 810.000 IOPS (4 KB Blocks)</li> <li>■ Sequential access performance: Max. 23 GB/s (128 KB Blocks)</li> <li>■ Latency: Less than 1 ms (4 KB Blocks)</li> </ul>	<ul style="list-style-type: none"> <li>■ Sufficient performance for all applications requiring high data rates and low response times</li> </ul>

# Technical details

## General system information

ETERNUS AF650 S2	
No. of controllers	2
No. of host interfaces	32ports [FC(16Gbit/s)], 16ports [FC(32Gbit/s), iSCSI(10Gbit/s)]
Maximum System Memory	512
Maximum Disk Drives	192
Max. no. of drive enclosures	8
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6
Host Interfaces	Fibre Channel (16 Gbit/s, 32Gbit/s) iSCSI (10 Gbit/s)
Max. no. of hosts	4,096
Maximum Storage Capacity	2,949 TB
Drive Type	2.5-inch, SSD (15.36TB / 7.68TB / 3.84 TB / 1.92 TB / 960GB / 400 GB) 2.5-inch, SSD (self-encrypting) (3.84 TB/1.92 TB)
Drive interface	Serial Attached SCSI (12 Gbit/s)
Back-end disk connectivity	4 pairs of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)
Max. no. of LUNs	12,288
No. of snapshots - max.	8,192
Max. no. of copy generations	512
Deduplication	for block
Compression	for block

## Performance

Latency	Write 60 $\mu$ s, Read 160 $\mu$ s (Minimum)
Sequential access performance	2,560,000 IOPS (100 % Read, 4 KB Blocks)
Random access performance	810,000 IOPS (100 % Read, 4 KB Blocks)

## Performance management

Automated Storage Tiering	Yes
Quality of Service	Yes
Automated QoS	Yes
Wide striping	Yes
Note	Automation options can be activated via ETERNUS SF Software

## Continuity management

Storage Cluster	Yes
Remote Copy functionality	Synchronous and asynchronous
Note	Options can be activated via ETERNUS SF Software

## Information security management

Data confidentiality	Self-Encrypting Disk, Controller based Encryption, HTTPS (SSL), One Time Password, RADIUS, SSH
Data integrity	Cache Protection, Data Block Guard, Disk Drive Patrol

## Availability management

Non-disruptive maintenance	Dedicated Hot Spare, Global Hot Spare
Non-disruptive firmware upgrade	Yes
Redundancy	RAID Controller, Power supply, Fan
Hot part replacement	Yes

## Capacity management

Thin Provisioning	Yes
RAID migration	Yes

**Capacity management**

LUN online expansion w/o interruption	Yes
Reporting function	Yes
Hot part expansion	Yes

**Management**

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.6
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF
Remote Support	Event notification (E-mail / SNMP / Syslog), Remote maintenance

**Supported OS for ETERNUS SF**

Operation Management Server	Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Microsoft Windows Server 2008, 2008 R2 Solaris® 11 (11/11 or later) Solaris® 10 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Red Hat® Enterprise Linux® 5 VMware® vSphere® 6.0, 6.5 VMware® vSphere® 5/ 5.1/ 5.5 Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V Microsoft Windows Server 2008 Hyper-V, 2008 R2 Hyper-V Hyper-V 2.0
Operation Management Client	Internet Explorer® 9, 10, 11 FireFox® ESR 17, 24, 31, 38, 45, 52 Microsoft Edge® 25 Chrome® 60 Chrome® 47, 50 (Android®) Safari 8, 9 (iOS)

<b>Supported configurations</b>	<b>All major host operating systems, servers and business applications</b> Detailed support matrix: <a href="http://www.fujitsu.com/global/support/products/computing/storage/all-flash-array/supported-configurations/">http://www.fujitsu.com/global/support/products/computing/storage/all-flash-array/supported-configurations/</a>
---------------------------------	---

**Installation specification**

19" rackmount	Yes	
Service Area	Front: 850 mm (33.5 inch) or more Rear: 850 mm (33.5 inch) or more	
Power voltage	AC 100 - 120 V / AC 200 - 240 V	
Power frequency	50 / 60 Hz	
Power supply efficiency	92 % (80 PLUS gold)	
Maximum Power Consumption	AC 100 - 120 V: 4,260W (4,350VA)	
Maximum Power Consumption	AC 200 - 240 V: 4,370W (4,460VA)	
Power phase	Single	
Dimensions (W x D x H)	ETERNUS AF650 S2	2.5-inch Drive Enclosure
	482 x 805 x 133 mm 19 x 31.7 x 5.2 inch 3 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U
Weight	54 kg (119 lb)	35 kg (77 lb)
Maximum Power Consumption (AC 100 - 120 V)	820W (830VA)	430W (440VA)
Maximum Power Consumption (AC 200 - 240 V)	930W (940VA)	430W (440VA)

**Environment**

Maximum Heat Generation	AC 100 - 120 V: 15,800: kJ/h AC 200 - 240 V: 16,200: kJ/h
-------------------------	--

**Environment**

Temperature (not operating)	0 - 50 °C	
Humidity (operating)	20 - 80 % (relative humidity, non-condensing)	
Humidity (not operating)	8 - 80 % (relative humidity, non-condensing)	
Altitude	3,000 m (10,000 ft.)	
Sound pressure (LpAm)	54dB(A)	
Sound power (LWAd; 1B = 10dB)	7.2B	
Noise notes	Measured with single enclosure according to ISO 7779 and declared according to ISO 9296	
Operating environment	Site Planning Guide	
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=dcd40f02-7a1d-4ed9-9c4f-705c8ff67ea9">http://docs.ts.fujitsu.com/dl.aspx?id=dcd40f02-7a1d-4ed9-9c4f-705c8ff67ea9</a>	
Type	ETERNUS AF650 S2	2.5-inch Drive Enclosure
Maximum Heat Generation (AC 100 - 120 V)	3000 kJ/h	1600 kJ/h
Maximum Heat Generation (AC 200 - 240 V)	3400 kJ/h	1600 kJ/h

**Compliance**

Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1	
Electromagnetic Compatibility	CNS 13438, FCC Part-15 Subpart B Class A, ICES 003 Class A, EN55032, VCCI Class A, AS/NZS CISPR 32 class A	
Electromagnetic Immunity	EN 55024	
CE certification	2014/30/EU, 2014/35/EU, 2011/65/EU	
Approvals	CB, CE, C-Tick, FCC, EAC, GS, VCCI	
Environmental compliance	RoHS compliant, WEEE compliant	
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.	
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	

**Warranty**

Warranty period	3 years	
Warranty type	Onsite warranty	
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/support">www.fujitsu.com/support</a>	

**Product Related Services - the perfect extension**

Support Pack Options	- Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)	
Recommended Service	- 24x7, Onsite Response Time: 4h	
Service Lifecycle	5 years after end of product life	
Service Weblink	<a href="http://www.fujitsu.com/support">http://www.fujitsu.com/support</a>	

### Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS AF650 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ETERNUS AF650 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2018 FUJITSU LIMITED

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

---

#### Contact

FUJITSU LIMITED  
Website: [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)  
2018-10-11 WW-EN