

Data Sheet

FUJITSU Storage ETERNUS AF650 S3 All-Flash Array

Storage Unchained



ETERNUS AF Storage

FUJITSU Storage ETERNUS AF series are incredibly fast and flexible all-flash storage systems for the next-generation data center. At an affordable price point, it makes flash the new normal for all tier-1 applications in enterprise IT. Response times are ultra-low – in fact, they set performance records. The ETERNUS AF is also built to be smart, with easily configurable automated quality of service to ensure each app gets the performance it needs, plus flexible deduplication and compression that can be turned on when required – and off when not. It keeps data safe with full-fledged DR with mirroring and automated transparent failover.

ETERNUS AF650 S3

The Fujitsu Storage ETERNUS AF650 S3 delivers leading storage performance and automated quality of service management, enabling a maximum of system utilization and contributing to a fast ROI. It is the perfect solution when consolidating data of large-scale databases, business-critical applications and business analytics / big data – all into one all-flash system. Extensive high-availability and disaster recovery capabilities make ETERNUS AF650 an ideal storage system for any business data.



Features & Benefits

Main Features	Benefits
Based on ETERNUS DX standard architecture	<ul style="list-style-type: none"> ■ Performance optimized design ■ Proven and mature technology ■ System availability of 99.9999% ■ Common management across all-flash and hybrid ETERNUS storage systems
Flexible and flash optimized storage	<ul style="list-style-type: none"> ■ Ultra-low response times for all applications ■ Massive increase of IOPS ■ No complicated tuning measures required ■ Scalable in capacity and connectivity
Selective use of deduplication / compression	<ul style="list-style-type: none"> ■ Decide on volume label whether to use it or not ■ Cost reduction for flash ■ Increased lifespan of flash
Automated Quality-of-Service	<ul style="list-style-type: none"> ■ Control of applications priorities according to business needs. ■ Automation of monitoring and adjustment ■ Minimization of admin efforts ■ Guaranteed service levels
Storage Cluster Option/Transparent failover	<ul style="list-style-type: none"> ■ Avoid planned or unplanned downtimes ■ Enjoy 100% data insurance and non-stop operations
Convincing access performance and latency <ul style="list-style-type: none"> ■ Random access performance: Up to 920,000 IOPS (8 KB Blocks) ■ Sequential access performance: Max. 22 GB/s (128 KB Blocks) ■ Latency: Less than 1 ms (4 KB Blocks) 	<ul style="list-style-type: none"> ■ Sufficient performance for all applications requiring high data rates and low response times

Technical details

General system information

		ETERNUS AF650 S3
No. of controllers		2
No. of host interfaces		4-32 ports [FC(32Gbit/s,16Gbit/s)], 4-16 ports [iSCSI(10Gbit/s,1Gbit/s)]
Maximum System Memory		1,536 GB
Maximum Disk Drives		1,056
Max. no. of drive enclosures		43
Supported RAID levels		0, 1, 1+0, 5, 5+0, 6
Host Interfaces		Fibre Channel (16 Gbit/s, 32Gbit/s) iSCSI (10Gbit/s [10GBASE-SR, 10GBASE-CR])
Mixed host interfaces		Yes
Max. no. of hosts		4,096
Maximum Storage Capacity		32,440 TB
Drive Type		2.5-inch, SSD (30.72TB / 15.36TB / 7.68TB / 3.84TB / 1.92TB / 960GB) 2.5-inch, SSD (FIPS) (7.68TB / 3.84TB / 1.92TB)
Drive interface		Serial Attached SCSI (12 Gbit/s)
Back-end disk connectivity		4 pairs of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)
Max. no. of RAID groups per system		528
Max. no. of LUNs per RAID group		128
Max. no. of LUNs		12,288
Max. LUN capacity		128 TB
Max. no. of copy generations		512
Deduplication		Yes
Compression		Yes, Yes

Performance

Latency		140µsec (Read), 60µsec (Write)
Sequential access performance		22,000 MB/s (128KB Read) 11,000 MB/s (128KB Write)
Random access performance		920,000 IOPS (8KB Read) 670,000 IOPS (8KB Write)

Performance management

Automated Storage Tiering		Yes
Quality of Service		Yes

Continuity management

Storage Cluster		Yes
Remote Copy functionality		Synchronous and asynchronous

Information security management

Data confidentiality		HTTPS (SSL), SSH, CHAP, Bidirectional CHAP
Data integrity		Data Block Guard, Data Encryption, Cache Protection, Disk Drive Patrol, Global Hot Spare, Dedicated Hot Spare, Copy back less, Drive shield, Fast Recovery

Availability management

Non-disruptive firmware upgrade		Yes
Hot part replacement		Yes

Capacity management

Thin Provisioning	Yes	
RAID migration	Yes	
Hot part expansion	Yes	

Management

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.4
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF

Supported OS for ETERNUS SF

Operation Management Server	Microsoft® Windows Server® 2019 Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Solaris® 11 (11/11 or later) Solaris® 10 (except ETERNUS SF Express) Red Hat Enterprise Linux 8 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Oracle Linux 6 VMware® vSphere® 6.0, 6.5, 6.7 Microsoft Windows Server 2019 Hyper-V Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V
Operation Management Client	Microsoft Internet Explorer 10, 11 Firefox ESR 60, ESR 68 Microsoft Edge 25, 42, 44 Google Chrome 60, 75 Chrome® 47, 50 (Android®) Safari 8, 9 (iOS)
Note	See the ETERNUS SF datasheet for further options

Installation specification

19" rackmount	Yes	
Power voltage	AC 100 - 120 V / AC 200 - 240 V	
Power frequency	50 / 60 Hz	
Maximum Power Consumption	AC 100 - 120 V: 19,380W (19,820VA)	
Maximum Power Consumption	AC 200 - 240 V: 19,830W (20,280VA)	
Power phase	Single	
Dimensions (W x D x H)	ETERNUS AF650 S3	2.5-inch Drive Enclosure
	482 x 805 x 133 mm 19 x 31.7 x 5.2 inch 3 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U
	Weight	54 kg (119 lb) 35 kg (77 lb)

Environment

Maximum Heat Generation	AC 100 - 120 V: 72,010: kJ/h AC 200 - 240 V: 73,630: kJ/h
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0

Compliance

Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, TP TC 004/2011, CNS14336
Electromagnetic Compatibility	FCC Part-15 Subpart B Class A, ICES-003 Class A, EN 55022 (2010), +AI, VCCI Class A, AS/NZS CISPR 22 Class A, CNS13438 (C6357) Class A, KN22
Electromagnetic Immunity	EN 55024
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Warranty

Warranty period	3 years
Warranty type	Onsite warranty

Warranty

Warranty Terms & Conditions www.fujitsu.com/warranty

Product Support Services - the perfect extension

Support Pack Options Available in major business areas:
9x5, Next Business Day Onsite Response Time
9x5, 4h Onsite Response Time (depending on country)
24x7, 4h Onsite Response Time (depending on country)

Recommended Service 24x7, Onsite Response Time: 4h

Service Lifecycle 5 years after end of product life

Service Weblink www.fujitsu.com/services/product-services

Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS AF650 S3, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS AF650 S3, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



**Green
Policy
Innovation**

Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED
Website: www.fujitsu.com/eternus
2019-12-03 WW-EN