

Data Sheet

FUJITSU Storage ETERNUS CS800 S7

Data Protection Appliance: Backup to Disk with Deduplication



ETERNUS CS Data Protection Appliances

Data protection appliances from Fujitsu simplify and consolidate backup and archive infrastructures. Fujitsu specializes in mapping the right technology for individual needs depending on your business size. Our appliances offer advanced capabilities such as deduplication and replication, thus mitigating risk and minimizing downtime.

ETERNUS CS800 S7

FUJITSU Storage ETERNUS CS800 is a turnkey, easy to operate data protection appliance providing leading data deduplication technology which reduces required disk capacity by up to 95%. By combining deduplication with replication it enables backup and restore across IT sites with low network bandwidth requirements and allows collecting remote backups to a central site. By supporting all major backup suites it is a perfect consolidation platform for data copies. Deep integration capabilities for VEEAM and Veritas OST functions enable a tight integration into backup processes including additional copies on tape whilst reducing the investment in additional hardware. Easy scalability results in investment protection for environments with high data growth.



Features & Benefits

Main Features	Benefits
High capacity and performance while reducing costs	<ul style="list-style-type: none">■ Maximum disk performance for better data protection■ Highest scalability from 8 up to 640 TB■ Data deduplication technology reduces disk requirements■ Pay-as-you-grow with easy scalability
Improved and automated disaster recovery	<ul style="list-style-type: none">■ Remote replication with reduced network bandwidth■ 1:2 replication and cloud hosted disaster recovery■ Reduced media handling and easy administration■ Integrated Path to Tape Option■ Optimized integration with Veeam and Veritas OST
Integration into Business-centric Data-centers	<ul style="list-style-type: none">■ Turnkey solution for easy and economical deployment■ Standard NAS or VTL interface for easy implementation■ Ready to realize cloud concepts for backup services

Technical details

General system information

Base unit	Entry	Flex	Scale
Performance (max. SPEED mode)	up to 13.4 TB/h	up to 13.4 TB/h	up to 22.0 TB/h
Performance (max.)	up to 8.4 TB/h	up to 8.8 TB/h	up to 13.9 TB/h
Performance Notes	Actual performance figures depend on user data and user environment		
Capacity (logical)	up to 1.2 PB	up to 6 PB	up to 20 PB
Capacity (net usable)	8 TB - 24 TB	16 TB - 280 TB	16 TB - 640 TB
Ethernet Ports (fixed)	5 x 1 GbE 2 x 10 Base-T GbE	5 x 1 GbE 2 x 10 Base-T GbE	1 x 1 GbE 2 x 10 Base-T GbE

Ethernet Connectivity (optional)

Base unit	Entry/Flex	Scale
Ethernet Ports	2 x 10 Gbps SFP+	4 x 10 Gbps SFP+ 8 x 1 Gbps
NAS - supported protocols	CIFS, NFS	
NAS Shares (max.)		

Fibre Channel Connectivity (optional)

Base unit	Entry	Flex	Scale
Fibre Channel Ports	2 x 16 GbFC	2 x 16 GbFC	4 x 16 GbFC
Partitions (max.)	64	64	64
Virtual Tape Cartridges (per partition)	61,000	61,000	61,000
Virtual Tape Drives (max.)	80	256	256
Tape Drive Emulations	DLT7000, LTO-1, LTO-2, LTO-3, LTO-4, LTO-5, SDLT 320, SDLT 600, SLT-S4		
Libraries Emulations	Quantum Scalar 24, Scalar 100, Scalar i2000, Scalar i500, Scalar i6000		
Notes	<p>"The following options are available: 8 x 1 Gb Ethernet, 4 x 10 Gb Ethernet, 4 x 16 GbFC / 8 GbFC depending on country One of these 3 options has to be selected; Max. 2 of these 3 options can be combined. Combination of 1GbE and 10GbE is not possible"</p>		

Supported environments - excerpt

Supported backup and archiving software for open systems	Atempo (Time Navigator) Commvault Software Computer Associates (BrightStor ARCserve Backup) Dell EMC (NetWorker) HP (DataProtector) IBM (Spectrum Protect) Quest (NetVault, vRanger) Veritas (Backup Exec, NetBackup) Veeam (Backup & Replication) SEP sesam - support on special request
	For additional information or applications not listed please contact your Fujitsu sales representative

Installation specification

19" rackmount	Yes		
Dimension (W x D x H) - standard	482.6 x 770 x 2U - 18U (1U = 44,45mm)		
Height Unit Maximum	24 U		
Weight	25kg - 305 kg		
Power voltage	AC 200 - 240 V		
Power frequency	50 / 60 Hz		
Power phase	Dual		
Base unit	Entry	Flex	Scale

Dimensions (W x D x H)	482.6 x 770 x 88.9 mm 19 x 30.3 x 3.5 inch 2 U	482.6 x 770 x 355.6 mm 19 x 30.3 x 14 inch 8 U	482.6 x 770 x 800.1 mm 19 x 30.3 x 31.5 inch 18 U
Weight	25 kg (55 lb)	up to 130 kg (NaN lb)	up to 305 kg (NaN lb)
Maximum Power Consumption (AC 200 - 240 V)	290W	1190 W	2700 W
Heat generation	1044 kJ/h	4284 kJ/h	9720 kJ/h
Environment			
Temperature (not operating)	15 - 35 °C		
Humidity (operating)	20 - 80 % (relative humidity, non-condensing)		
Humidity (not operating)	20 - 80 % (relative humidity, non-condensing)		
Altitude	3,000 m (10,000 ft.)		
Sound pressure (LpAm)	45 - 55 dB(A)		
Sound power (LWAd; 1B = 10dB)	6.6		
Noise notes	Noise emissions and operation modes depend on system configuration.		
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)		
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe		
Warranty			
Warranty period	1 year		
Warranty type	Onsite warranty		
Warranty Terms & Conditions	www.fujitsu.com/warranty		
Product Support Services - the perfect extension			
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time		
Service Lifecycle	5 years after end of product life		
Service Weblink	www.fujitsu.com/services/product-services		
Compliance			
Product safety	CSA-C22.2 No. 60950-1, GOST-R, UL 60950-1, EN 60950-1, IEC 60950-1		
Electromagnetic Compatibility	CNS 13438, FCC Part-15 Class A, ICES 003 Class A, BSMI Class A, C-Tick, AS/NZ CISPR 22 Class A, EN 55022 Class A, VCCI Class A		
Electromagnetic Immunity	EN 55024		
CE certification	2014/35/EU, 2014/30/EU, 2011/65/EU, 2009/125/EC		
Approvals	CE, EAC, GS, FCC, RoHS, WEEE		
Environmental compliance	RoHS compliant, WEEE compliant		
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		

Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS CS800 S7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS CS800 S7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.