

Data Sheet

ETERNUS CS8000

Central Backup and Archive Storage

Strengthen data resiliency with highest SLA and reduce TCO up to 60% in hybrid IT

ETERNUS CS Data Protection Appliances

Data protection appliances and solutions from Fujitsu ensure data protection and 'always-on' availability across your hybrid cloud estate. Fujitsu's comprehensive range of backup and archiving solutions safeguard the right data service levels for the complete data lifecycle with the right protection and at optimized cost. The appliances protect sensitive data from threat, corruption, or loss addressing end-to-end operational security and data availability concerns from on-premises through to the cloud. The speedy recovery after downtime or ransomware attacks provides 24/7 business continuity, ensures highest data resiliency, and enhance your business agility.

The solutions comply with security, data, and industry regulations and transform your hybrid cloud into a genuine enabler for digital business growth, efficiency, and continuity.

ETERNUS CS8000

Based on a long-lasting user-driven development, the ETERNUS CS8000 is the most reliable central repository for backup, archive, second tier and object data. The appliance consolidates data from mainframe and open system environments and can help to reduce the TCO in complex hybrid IT environments by up to 60%.

Data is automatically managed between different storage tiers, including SSD, disk, and tape technology as well as different performance and availability levels. To strengthen the data resiliency the solution creates an airgap with offline backup to tape. Designed to flexibly fulfill various data protection service levels, the ETERNUS CS8000 provides automated 24/7 operation, comprehensive high availability with near-zero downtime and disaster recovery capabilities. Unique scalability in capacity and performance makes it a viable solution, that enables continuous cost savings.



Features & Benefits

Main Features	Benefits
<p>Flexible, modular architecture with pooling of resources</p> <ul style="list-style-type: none"> ■ Infrastructure virtualization for the whole backup and archive storage environment, including second tier and object data ■ Consolidates mainframe and open system infrastructures 	<ul style="list-style-type: none"> ■ TCO reductions in complex hybrid IT environments by up to 60% ■ Flexibility to allocate resources as required ■ Reduces floor space, power, and cooling and helps driving sustainability transformation
<p>Intelligent automation with self-healing mechanism</p> <ul style="list-style-type: none"> ■ ILM on SSD, disk, and tape technology ■ Managing multiple local and remote copies ■ Long-lasting, user-driven development for optimization 	<ul style="list-style-type: none"> ■ Flexibility regarding capacity, performance and costs ■ Ensures highest and most reliable service levels and data resiliency ■ Reduces administrator workload and optimizes processes
<p>High performance appliance with unique scalability</p> <ul style="list-style-type: none"> ■ Storage capacity from 19 TB up to 350 PB (net usable) on disk ■ Manage exabytes of data on tape ■ Backup and recovery performance of up to 150 TB/h ■ Decoupled technology lifecycles and automated data migration 	<ul style="list-style-type: none"> ■ Long-term investment protection ■ On-demand scalability to adapt to unpredictable requirements on capacity and performance ■ Faster innovations to leverage latest technology
<p>Split-site solution with cache-mirror for highest demands</p> <ul style="list-style-type: none"> ■ Physical separation (up to 100 km) of one logical system ■ Automated continuation even in case of complete site failure 	<ul style="list-style-type: none"> ■ Provides maximum protection for mission critical data ■ Ensures highest data resiliency with near-zero downtime and near-zero data loss

Models and architecture

ETERNUS CS8000 architecture

- Four different basic architectures are available: the branch-office model CS8050, the scale-up model CS8200, the scale-out-single-site model CS8400 and the scale-out-split-site model CS8800.

CS8050 - the branch-office model

- The CS8050 VTL system is applied in branch offices to replicate data to a central ETERNUS CS8000 model in the main data center. This 2U systems has all the features of a larger ETERNUS CS8000 appliance with regards to backup to disk requirements. To strengthen the data resiliency CS8050 VTL creates an airgap with offline backup to tape.
- Archiving is becoming more and more an integral part of any modern, intelligent data protection strategy. The CS8050 NAS system is a reliable, cost-efficient storage appliance dedicated for archive and second-tier file storage. The solution features replication, integrated backup and SoftWORM capabilities to ensure business efficiency, continuity and to fulfill compliance regulations.

CS8200 - the scale-up model

- This model is available either as a VTL system for backup purposes, or as a NAS system for archive and second-tier storage purposes. The main components are a pair of front-end nodes to receive the data and a scalable RAID system.
- With a VTL system, the data is first stored to disk. Optional, thanks to tape automation functions, data can be copied to an attached tape library. For disaster recovery scenarios, data can be copied to a remote tape library or replicated to a second ETERNUS CS8000 system. CS8200 can consolidate data from mainframe and open system environments.
- With a NAS system, data can be received via NFS, CIFS and Object interfaces. Optional WORM functionality enables long-term storage for compliant archive purposes. For disaster recovery scenarios, data can be replicated to a second ETERNUS CS8000. Furthermore, an integrated snapshot-based backup is available. This snapshot data can also be replicated to a second ETERNUS CS8000 system.

CS8400 - the scale-out-single-site model

- Backup, archive, second tier and object data from mainframe and open system environments can be consolidated in a single CS8400. Optional CS8400 can also be provided as a VTL-only system or as a NAS-only system.
- All the functions for the CS8200 VTL system are also available for the CS8400 VTL subsystem; the functions of the CS8200 NAS system are available for the CS8400 NAS subsystem.
- In contrast to the scale-up model the CS8400 provides a scale-out approach. It is scalable in capacity as well as in performance. Several front-end nodes, back-end nodes or RAID systems can be easily added. All components are redundantly connected, thus providing a single, high-available real scale-out system without any single point of failure.
- CS8400 supports the cache-mirror feature to increase the availability level for the data itself by enabling the synchronous mirroring of data within the internal RAID systems.
- With the CS8400 NAS subsystem an automated HSM (Hierarchical Storage Management) function is available as an option, using tape automation functionality to copy data to attached tape libraries. WORM tape is supported for compliant archive requirements in addition to the WORM functionality on disk level.

CS8800 - the scale-out-split-site model

- All the features, functions and architecture highlights specified for the CS8400 model are also available for the CS8800 model.
- CS8800 also offers a split-site function. One logical ETERNUS CS8800 system can be deployed over two geographically separated sites. The internal ETERNUS CS8800 infrastructure is thus extended to a second site – still representing one single system thanks to the cache-mirror feature. Data can be written to or read from both sites. The system internal automatic failover ensures that data remains available even if a complete site is affected by a disaster. Combined with the highly automated tape integration, the result is a system with no single point of failure which provides the highest levels of data availability and resiliency.

Technical details

General system information

Model	CS8050	CS8200	CS8400	CS8800
Type	Branch-office System	Scale-up System	Scale-out-single-site System	Scale-out-split-site System
Host connectivity options	VTL or NAS and Object	VTL or NAS and Object	VTL, NAS, Object	VTL, NAS, Object
Hardware platform	S17	S17	S17	S17
Software version	V9.1	V9.1	V9.1	V9.1
RAID capacity	40 TB - 96 TB	19 TB - 20 PB	19 TB - 350 PB	38 TB - 350 PB
Note	Capacity value calculated using Base10 (i.e. 1TB = 1,000,000,000,000 bytes). The model CS8050 VTL provides a fix capacity of 40 TB, the CS8050 NAS a fix capacity of 96 TB.			

VTL Subsystem

Sustained Performance (max.)	1.4 TB/h	30 TB/h	150 TB/h	150 TB/h
VTL Front-end Ports	4 FC 32 GB	4 to 8 FC 32 Gb / FICON 32 Gb	4 to 84 FC 32 Gb / FICON 32 Gb	4 to 84 FC 32 Gb / FICON 32 Gb
Virtual Tape Drives	max. 32	32 to 64	32 to 5,208	32 to 5,208
Virtual Tape Volumes (max.)	20,000	300,000	3,000,000	3,000,000
VTL Back-end Port Options	4 FC 32 Gb	4 to 8 FC 32Gb	4 to 84 FC 32 Gb	4 to 84 FC 32 Gb
Physical Tape Volumes (max.)	500	50,000	50,000	50,000
Performance Note	To the extent that specific performance specifications for the product are indicated in the product data sheet, these are usually also dependent on the specific use and workload of the product and may therefore not be reached equally in all application situations. Such performance specifications thus do not represent a specifically agreed characteristic or feature of the product, but only serves as an orientation. The responsibility for a sufficient sizing of the overall system functionality lies solely with the user.			

NAS Subsystem

Supported protocols	NFS CIFS	NFS CIFS	NFS CIFS	NFS CIFS
NAS Front-end Ports	2 to 4 x 1 GbE or 2 to 4 x 25 GbE	4 to 8 x 1 GbE or 2 to 8 x 25 GbE	4 to 84 x 1 GbE or 2 to 84 x 25 GbE	4 to 84 x 1 GbE or 2 to 84 x 25 GbE
Number of Inodes (per file system)	200 Million	2 Billion	2 Billion	2 Billion
NAS Back-end Port Options	- (no HSM)	- (no HSM)	2 to 8 active FC 32 Gb 2 to 8 passive FC 32 Gb	2 to 8 active FC 32 Gb 2 to 8 passive FC 32 Gb
Note	If more NAS Front-end Ports are needed, a Special Release Request is required Maximum number of Inodes per file system (Depending if special service such as HSM, VRB or File Protection is applied). Ask for project specific configuration for more details.			

Object (COSS) Subsystem

Supported protocols	S3	S3	S3	S3
Storage Classes	Standard			
Number of Objects per Account	200 Million	2 Billion	2 Billion	2 Billion
Bucket Policies	Object Locking Object Versioning			
Note	COSS = Cloud Object Storage Service			

Physical Tape Support

Physical Tape Drives (max.)	8	32	135	135
Physical Tape Libraries supported (max.)	1	10	10	10

Supported environments - excerpt

Host interoperability	Fujitsu (BS2000/OSD, MSP, XSP, VME (ICL)) IBM (z/OS, OS/390, i5/OS, z/VM, z/VSE) Bull (GCOS 8) Open Systems (AIX, HP-UX, Solaris, SUSE LINUX, Red Hat LINUX, z/Linux, Windows, NDMP Backup (NetApp, EMC)) No IBM mainframe support with CS8050 model For additional information or operating systems not listed please contact your Fujitsu sales representative			
-----------------------	---	--	--	--

Supported environments - excerpt

Supported backup and archiving software for open systems	Atempo (Time Navigator) Ceyoniq nscale 7 Commvault Software Dell NetWorker IBM (Storage Protect, prev. Tivoli Storage Manager) Micro Focus (Data Protector) (former "HP Data Protector") OpenText™ Archive Center SEP sesam Veeam (Backup & Replication) Veritas (Backup Exec, NetBackup, EnterpriseVault) For additional information or applications not listed please contact your Fujitsu sales representative
Supported physical tape libraries	Fujitsu (ETERNUS LT Family) Quantum (Scalar iSeries) Oracle (SL Series) IBM (TS4500) Spectra Logic (Spectra T50, T120, T950) For additional information or tape libraries not listed please contact your Fujitsu sales representative
Supported physical tape drives	IBM (Jaguar 3592 / TS1120 / TS1130 / TS1140 / TS1150) Oracle (T9840, T9940, T10000) LTO Ultrium (Gen 3, Gen 4, Gen 5, Gen 6, Gen 7, Gen 8, Gen 9) For additional information or tape drives not listed please contact your Fujitsu sales representative

Installation specification

Model	CS8050	CS8200	CS8400	CS8800
19" rackmount	Yes			
No. of racks	0	1-3	1-35	2-36
Dimension - per rack (W x D x H)	445 x 700 x 87 mm 17.5 x 27.6 x 3.4 inch	800 x 1200 x 2000 mm 31.5 x 47.2 x 78.7 inch		
Height Unit standard	2 U	42 U		
Power voltage	Industry: 1, 2 or 3 phases of 230 V / US: 2 supplies of 208 V (phase to phase)			
Power frequency	50 / 60 Hz			
Maximum Power Consumption	Industry: 1, 2 or 3 phases of 230 V: 305 W	Industry: 1, 2 or 3 phases of 230 V: 10,160 W	Industry: 1, 2 or 3 phases of 230 V: 152,520 W	
Maximum Power Consumption	US: 2 supplies of 208 V (phase to phase): 305 W	US: 2 supplies of 208 V (phase to phase): 10,160 W	US: 2 supplies of 208 V (phase to phase): 152,520 W	
Power phase	Single, Dual or Triple			
Fuse protection	Industry: 16 A per phase (fuses not coupled) US: 20 A per phase (fuses not coupled) To be cared about by the customer			
Power Connector Options	2 x IEC 320 10A KG	2 x CEE 3x16A (3 phases red plug) 2-6 CEE 1x16A (1 phase blue plug) 2-6 L6-30 (US: 2 phases 208V)		
Notes	Power Connection Options: Default is 2 x CEE 3x16A (best power redundancy, which is highly recommended). Each configuration will be analyzed in SysARC and the internal power distribution will be set for maximum power redundancy. A mix inside a Rack is not allowed. Each rack can be individually configured.			

Installation specification for a typical configuration

Model	CS8050	CS8200	CS8400	CS8800
Weight	30 kg	450 kg	554 kg	981 kg
Power consumption (standby)	230 W	2,060 W	2,714 W	5,128 W
Power consumption (under load)	305 W	2,360 W	3,400 W	6,440 W
Heat generation	1,098 kJ/h / 1,041 BTU/h	8,496 kJ/h / 8,053 BTU/h	12,240 kJ/h / 11,601 BTU/h	23,184 kJ/h / 21,974 BTU/h
Notes	Weight, power consumption and heat generation are stated for a typical system configuration! Due to high scalability, detailed values are calculated and available through the configuration tool Webarchitect.			

Environment

Room air conditioned	Recommended, at 20° C (68° F)
Floor air supply	No

Environment				
Temperature (not operating)	-20 - 40 °C	-20 - 40 °C	-20 - 40 °C	-20 - 40 °C
Temperature (operating)	Long term at 20° C (68° F), max. 2 hours at minimum 15° C or maximum of 35° C (59 to 95° F)			
Humidity (operating)	Long Term at appr. 50 % RH; tolerances at 30 to 70 % RH (relative humidity, non-condensing)			
Humidity (not operating)	30 - 70 % (relative humidity, non-condensing)			
Altitude	3,000 m (10,000 ft.)			
Sound pressure (dB/A)	<60			
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)			
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe			
Warranty				
Manufacturer warranty period	2 years			
Warranty type	Onsite warranty			
Warranty Terms & Conditions	www.fujitsu.com/warranty			
Product Support - the perfect extension				
Recommended Service	- Reactive and proactive Service			
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/			
Service Weblink	www.fujitsu.com/services/product-services			
Compliance				
Product safety	CE, NRTL (UL/CSA/TÜV)			
Electromagnetic Compatibility	CE, FCC Class A			
Electromagnetic Immunity	CE			
CE certification	Self Declaration			
Approvals	CE, UKCA, CB, NRTL, FCC, VCCI, RCM			
Environmental compliance	RoHS compliant, WEEE compliant			
Compliance notes	There is general compliance with the safety/EMC requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.			
Compliance link	https://sp.ts.fujitsu.com/sites/certificates			
Notes				
Compatibility	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.			
Security	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fsas Technologies Inc. as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.			
Continuity management	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.			
Software	Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.			

Fsas Technologies products, solutions & services

In addition to ETERNUS CS8000, Fsas Technologies provides a range of platform solutions. They combine reliable Fsas Technologies products with the best in services, know-how and worldwide partnerships.

Fsas Technologies Portfolio

Built on industry standards, Fsas Technologies offers a full portfolio of datacenter hardware, software and related services. This allows customers to select alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Data Center Solutions
<https://www.fsastech.com/en-eu/>

More information

Learn more about ETERNUS CS8000, please contact your Fsas Technologies sales representative or Business partner, or visit our website.

<https://www.fujitsu.com/global/products/computing/storage/data-protection/cs8000/index.html>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
Copyright Fsas Technologies 2025

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.
Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fsas Technologies
Email: storage-marketing@fujitsu.com
Website: www.fujitsu.com/eternus
2025-04-24 WW-EN