

Data Sheet

FUJITSU Storage ETERNUS DX200 S5 Disk System

The all-in-one storage system for SMBs or subsidiaries



ETERNUS DX - Business-centric Storage

FUJITSU Storage ETERNUS DX series are the ideal hybrid storage for on-premise storage of business-critical data in data centers, branch offices and self-operated IT of SMBs, something every business can afford, with integrated and powerful features for business growth, efficiency and continuity. Latest capacity and performance optimization capabilities contribute to overall business efficiency, outstanding data-safe technologies and all-inclusive encryption guarantee uncompromised business continuity.

ETERNUS DX200 S5

The scalable and unified Fujitsu Storage ETERNUS DX200 S5 delivers enterprise-class functionality to small and medium-sized companies and subsidiaries with an excellent price/performance ratio. It is the perfect solution when consolidating data for server virtualization, e-mail, databases and business applications as well as centralized file services. Simple, intuitive system management, highly flexible connectivity and the option of field upgrades to higher system classes significantly reduce operational and migration costs. The ETERNUS DX family architecture lets customers benefit from software options such as - thin provisioning, automatic storage tiering, transparent failover and quality of service management even in the entry-level class. All of which contribute to better business support and guarantees continuity and efficiency in daily operations.



Features & Benefits

Main Features	Benefits
Maximum utilization and consolidation	<ul style="list-style-type: none">■ Comprehensive scalability ready for future needs■ Outstanding benchmark results with ultra-low latency■ Unified SAN and NAS access drive system utilization improving ROI■ Flexible combination of flash and disk media for a broader scope of deployments■ ETERNUS SF Express management suite included at no extra cost
Business Continuity around the clock	<ul style="list-style-type: none">■ Replication and Storage Cluster to avoid planned or unplanned downtimes■ Transparent failover for 100% data insurance and non-stop operations■ Intelligent snapshot functionality for backup■ System availability of 99.9999%
Automated Quality-of-Service	<ul style="list-style-type: none">■ Control of applications priorities according to business needs.■ Automation of monitoring and adjustment■ Minimization of admin efforts■ Guaranteed service levels
Selective use of deduplication / compression	<ul style="list-style-type: none">■ Decide on application label which option fits best■ Don't compromise applications with performance SLA's■ Capacity savings in hybrid configurations

Technical details

General system information

	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure
No. of controllers		1/2
No. of host interfaces	4-16 ports [FC(16Gbit/s)], 8/16 ports [Ethernet(1Gbit/s)], 4/8 ports [FC(32Gbit/s), iSCSI(10Gbit/s, 1Gbit/s), SAS (12Gbit/s)]	
Maximum System Memory	128 GB	
Extreme Cache Pool	1.6 TB	
Maximum Disk Drives	264	
Max. no. of drive enclosures	10	
Note	10 with 2.5" or 3.5" DE, 4 with HD-DE or mixture of DEs up to Max no. Drives	
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6	
Host Interfaces	Fibre Channel (16 Gbit/s, 32Gbit/s) iSCSI (10 Gbit/s [10GBase-SR, 10GBase-CR, 10GBase-T], 1 Gbit/s) SAS (12Gbit/s) Ethernet (10 Gbit/s, 1 Gbit/s)	
Mixed host interfaces	Yes	
Max. no. of hosts	1,024	
Supported NAS protocols	CIFS (SMB 3.0), CIFS (SMB 2.0), NFSv4, NFSv3, NFSv2, FTP, FXP	
Maximum Storage Capacity HDD	3,696 TB	
Maximum Storage Capacity SSD	8.110 TB	
Drive Type	2.5-inch, SAS, 15,000 rpm (900 GB* / 600 GB* / 300 GB*) 2.5-inch, SAS, 10,000 rpm (2.4 TB / 1.8 TB / 1.2 TB / 600 GB / 300 GB*) 2.5-inch, SAS (FIPS), 10,000rpm (1.2TB) 2.5-inch, SSD (30.72TB / 15.36TB / 7.68TB / 3.84TB / 1.92TB / 960GB / 800GB) 2.5-inch, SSD (FIPS) (7.68TB / 3.84TB / 1.92TB) 3.5-inch, Nearline SAS, 7,200 rpm (14TB / 12TB / 10TB / 8TB / 6TB / 4TB) 3.5-inch, Nearline SAS (FIPS), 7,200 rpm (12TB / 8TB / 4TB) 3.5-inch, SSD (7.68TB / 3.84TB / 1.92TB / 960GB / 800GB) 3.5-inch, SSD (self-encrypting) (3.84 TB/1.92 TB) HDDE, Nearline SAS, 7,200 rpm (14TB / 12TB / 8TB / 4TB) HDDE, Nearline SAS (FIPS), 7,200 rpm (12TB / 8 TB / 4TB)	
Note	*For EMEIA only available on special request	
Max. no. of SSDs	unlimited	
Mixed 2.5 inch/ 3.5 inch drive enclosures	Yes	
Drive interface	Serial Attached SCSI (12 Gbit/s)	
Back-end disk connectivity	1 pair of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)	
Max. no. of RAID groups per system	132	
Max. no. of LUNs per RAID group	128	
Max. no. of LUNs	8,192	
Max. LUN capacity	128 TB	
Max. no. of copy generations	512	
Deduplication	for block	
Compression	for block	

Performance

Latency	140µsec (Read), 60µsec (Write)
Sequential access performance	11,000 MB/s (128KB Read) 4,400 MB/s (128KB Write)
Random access performance	530,000 IOPS (8KB Read) 230,000 IOPS (8KB Write)

Performance management	
Automated Storage Tiering	Yes
Quality of Service	Yes
Note	Automation options can be activated via ETERNUS SF Software
Continuity management	
Storage Cluster	Yes
Remote Copy functionality	Synchronous and asynchronous
Information security management	
Data confidentiality	HTTPS (SSL), SSH, CHAP, Bidirectional CHAP
Data integrity	Data Block Guard, Data Encryption, Cache Protection, Disk Drive Patrol, Global Hot Spare, Dedicated Hot Spare, Copy back less, Drive shield, Fast Recovery
Availability management	
Non-disruptive firmware upgrade	Yes
Hot part replacement	Yes
Capacity management	
Thin Provisioning	Yes
RAID migration	Yes
Reporting function	Yes
Hot part expansion	Yes
Management	
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF
Supported OS for ETERNUS SF	
Operation Management Server	Microsoft® Windows Server® 2019 Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Solaris® 11 (11/11 or later) Solaris® 10 (except ETERNUS SF Express) Red Hat Enterprise Linux 8 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Oracle Linux 6 VMware® vSphere® 6.0, 6.5, 6.7 Microsoft Windows Server 2019 Hyper-V Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V
Operation Management Client	Microsoft Internet Explorer 10, 11 Firefox ESR 60, ESR 68 Microsoft Edge 25, 42, 44 Google Chrome 60, 75 Chrome® 47, 50 (Android®) Safari 8, 9 (iOS)
Note	See the ETERNUS SF datasheet for further options
Supported configurations	All major host operating systems, servers and business applications Detailed support matrix: www.fujitsu.com/global/support/products/computing/storage/disk/supported-configurations
Installation specification	
19" rackmount	Yes
Power voltage	AC 100 - 120 V / AC 200 - 240 V
Power frequency	50 / 60 Hz
Maximum Power Consumption	AC 100 - 120 V: 6,630W {6,760VA}
Maximum Power Consumption	AC 200 - 240 V: 6,630W (6,760VA)
Power phase	Single

	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure	2.5-inch Drive Enclosure	3.5-inch Drive Enclosure	High-Density Drive Enclosure
Dimensions (W x D x H)	482 x 645 x 88 mm 19 x 25.4 x 3.5 inch 2 U	482 x 670 x 88 mm 19 x 26.4 x 3.5 inch 2 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U	482 x 560 x 88 mm 19 x 22 x 3.5 inch 2 U	482 x 980 x 176 mm 19 x 38.6 x 6.9 inch 4 U
Weight	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)	100 kg (220 lb)
Environment					
Maximum Heat Generation	AC 100 - 120 V: 24,390: kJ/h AC 200 - 240 V: 24,390: kJ/h				
Humidity (operating)	20 - 80 %				
Operating environment	FTS 04230 - Guideline for Data Center (installation specification)				
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0				
Compliance					
Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, TP TC 004/2011, CNS14336				
Electromagnetic Compatibility	FCC Part-15 Class A, ICES-003 Class A, EN 55022 (2010), +AI, VCCI Class A, AS/NZS CISPR 22 Class A, CNS13438 (C6357) Class A, KN22				
Electromagnetic Immunity	EN 55024				
Environmental compliance	RoHS compliant, WEEE compliant				
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.				
Compliance link	https://sp.ts.fujitsu.com/sites/certificates				
Warranty					
Warranty period	3 years				
Warranty type	Onsite warranty				
Warranty Terms & Conditions	www.fujitsu.com/warranty				
Product Support Services - the perfect extension					
Support Pack Options	Available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)				
Recommended Service	24x7, Onsite Response Time: 4h				
Service Lifecycle	5 years after end of product life				
Service Weblink	www.fujitsu.com/services/product-services				

Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS DX200 S5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS DX200 S5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2020 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED
Website: www.fujitsu.com/eternus
2020-02-05 WW-EN