

Data Sheet

FUJITSU Storage ETERNUS DX60 S4 Hybrid System

The Economy Storage System for SMBs



ETERNUS DX - Business-centric Storage

FUJITSU Storage ETERNUS DX S4 is the perfect hybrid storage for SMB, something every business can afford, with integrated and powerful features for business growth, efficiency and continuity. Latest capacity and performance optimization capabilities contribute to comprehensive business efficiency. Outstanding data-safe technologies and all-inclusive encryption guarantee uncompromised business continuity

ETERNUS DX60 S4

Delivering reliable operation at an affordable price makes ETERNUS DX60 S4 an ideal disk storage system for small and medium-sized IT environments.

Management software, included at no extra cost, reduces administration effort and provides functionality to ensure data protection. Flexible support for different network connections and disk types enables choice in cost and performance optimization.

Designed for smaller environments it provides remarkable scalability in storage capacity offering good headroom for future growth. Thus makes it the perfect storage solution for consolidation of distributed data and for smaller server virtualization projects.



Features & Benefits

Main Features	Benefits
Reliable operation at an affordable price	<ul style="list-style-type: none">■ Best-in-class price/performance ratio■ Rich data safety functionality■ Enterprise feature set
Free-of-charge ETERNUS SF Express Storage Management	<ul style="list-style-type: none">■ Single point administration■ Easy and efficient operation■ No extra cost for software package
Ideal for small and medium-sized IT environments	<ul style="list-style-type: none">■ Easy to install, configure, operate and maintain■ Perfect fit for storage consolidation & virtualization■ Serves the need of medium capacity requirements and predictable growth rates

Technical details

General system information

	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure
No. of controllers		1/2
No. of host interfaces	2/4 ports [FC(16Gbit/s, 8Gbit/s), iSCSI(10Gbit/s, 1Gbit/s), SAS(12Gbit/s)]	
Maximum System Memory	8GB	
Maximum Disk Drives	96	
Max. no. of drive enclosures	3	
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6	
Host Interfaces	Fibre Channel (16Gbit/s, 8Gbit/s) iSCSI (10 Gbit/s [10GBase-T], 1 Gbit/s) SAS (12Gbit/s)	
Max. no. of hosts	128	
Maximum Storage Capacity HDD	576 TB	
Maximum Storage Capacity SSD	31 TB	
Drive Type	2.5-inch, SAS, 15,000 rpm (900 GB / 600 GB / 300 GB*) 2.5-inch, SAS, 10,000 rpm (2.4 TB / 1.8 TB / 1.2 TB / 900 GB* / 600 GB / 300 GB*) 2.5-inch, Nearline SAS, 7,200 rpm (2 TB / 1 TB) 3.5-inch, SAS, 10,000 rpm (2.4TB / 1.8 TB / 1.2 TB / 900 GB*) 3.5-inch, Nearline SAS, 7,200 rpm (12 TB / 10 TB / 8 TB / 6 TB / 4 TB / 2 TB) 2.5-inch, SSD (3.84 TB / 1.92 TB / 960GB / 400 GB) 3.5-inch, SSD (400GB)	

Note 2.5-inch drives are available only for 2.5-inch drive enclosures and 3.5-inch drives are available only for 3.5-inch drive enclosures.
2.5-inch 2TB, 3.5-inch 6TB/8TB/10TB Nearline SAS and 1.8TB SAS drives are Advanced Format drives.
* Not Available in EMEA region

Mixed 2.5 inch/ 3.5 inch drive enclosures	Yes
Drive interface	Serial Attached SCSI (6 Gbit/s)
Max. no. of LUNs	1,024
Max. LUN capacity	128 TB
No. of snapshots - max.	1,024
Max. no. of copy generations	512
Eco-mode	Yes

Performance management

Wide striping	Yes
---------------	-----

Information security management

Data confidentiality	HTTPS (SSL), One Time Password, RADIUS, SSH
Data integrity	Cache Protection, Data Block Guard, Disk Drive Patrol

Availability management

Fast Recovery	Yes
Non-disruptive maintenance	Dedicated Hot Spare, Global Hot Spare
Non-disruptive firmware upgrade	Yes
Hot part replacement	Yes

Capacity management

Thin Provisioning	Yes
RAID migration	Yes
LUN online expansion w/o interruption	Yes
Reporting function	Yes
Hot part expansion	Yes

Management

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.6
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF
Remote Support	Event notification (E-mail / SNMP / Syslog), Remote maintenance

Supported OS for ETERNUS SF Express

Operation Management Server	Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Microsoft Windows Server 2008, 2008 R2 Solaris® 11 (11/11 or later) Solaris® 10 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Red Hat® Enterprise Linux® 5 VMware® vSphere® 6.0, 6.5 VMware® vSphere® 5/ 5.1/ 5.5 Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V Microsoft Windows Server 2008 Hyper-V, 2008 R2 Hyper-V Hyper-V 2.0
Operation Management Client	Internet Explorer® 9, 10, 11 FireFox® ESR 17, 24, 31, 38, 45, 52 Microsoft Edge® 25 Safari 8, 9 (iOS) Chrome® 60 Chrome® 47, 50 (Android®)

Supported configurations**All major host operating systems, servers and business applications**

Detailed support matrix:

www.fujitsu.com/global/support/products/computing/storage/disk/supported-configurations**Installation specification**

19" rackmount	Yes			
Service Area	Front: 850 mm (33.5 inch) or more Rear: 850 mm (33.5 inch) or more			
Power voltage	AC 100 - 120 V / AC 200 - 240 V			
Power frequency	50 / 60 Hz			
Power supply efficiency	92 % (80 PLUS gold)			
Maximum Power Consumption	AC 100 - 120 V: 1,900 W (1,940 VA)			
Maximum Power Consumption	AC 200 - 240 V: 1,890 W (1,930 VA)			
Power phase	Single			
	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure	2.5-inch Drive Enclosure	3.5-inch Drive Enclosure
Dimensions (W x D x H)	482 x 645 x 88 mm 19 x 25.4 x 3.5 inch 2 U	482 x 670 x 88 mm 19 x 26.4 x 3.5 inch 2 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U	482 x 560 x 88 mm 19 x 22 x 3.5 inch 2 U
Weight	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)
Maximum Power Consumption (AC 100 - 120 V)	610W (620VA)	530W (540VA)	430W (440VA)	340W (350VA)
Maximum Power Consumption (AC 200 - 240 V)	600W (610VA)	530W (540VA)	430W (440VA)	340W (350VA)

Environment

Maximum Heat Generation	AC 100 - 120 V: 7,000: kJ/h AC 200 - 240 V: 7,000: kJ/h
Temperature (not operating)	0 - 50 °C
Humidity (operating)	20 - 80 % (relative humidity, non-condensing)
Humidity (not operating)	8 - 80 % (relative humidity, non-condensing)
Altitude	3,000 m (10,000 ft.)

Environment

Sound pressure (LpAm)	49dB(A)
Sound power (LWAd; 1B = 10dB)	6.7B
Noise notes	Measured with single enclosure according to ISO 7779 and declared according to ISO 9296
Operating environment	Site Planning Guide
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=d1f9f172-a1cc-4f5c-8136-cd764fb08b8c

Compliance

Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1
Electromagnetic Compatibility	CNS 13438, FCC Part-15 Subpart B Class A, ICES 003 Class A, EN55032, VCCI Class A, AS/NZS CISPR 32 class A
Electromagnetic Immunity	EN 55024
CE certification	2014/30/EU, 2014/35/EU, 2011/65/EU
Approvals	CB, CE, C-Tick, FCC, EAC, GS, VCCI
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Warranty

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/support

Product Related Services - the perfect extension

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	5 years after end of product life
Service Weblink	www.fujitsu.com/services/product-services

Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS DX60 S4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS DX60 S4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED
Website: www.fujitsu.com/eternus
2018-12-18 WW-EN