

# Data Sheet

## FUJITSU Storage ETERNUS DX60 S4 Hybrid System

The Economy Storage System for SMBs



### ETERNUS DX - Business-centric Storage

FUJITSU Storage ETERNUS DX S4 is the perfect hybrid storage for SMB, something every business can afford, with integrated and powerful features for business growth, efficiency and continuity. Latest capacity and performance optimization capabilities contribute to comprehensive business efficiency. Outstanding data-safe technologies and all-inclusive encryption guarantee uncompromised business continuity

### ETERNUS DX60 S4

Delivering reliable operation at an affordable price makes ETERNUS DX60 S4 an ideal disk storage system for small and medium-sized IT environments.

Management software, included at no extra cost, reduces administration effort and provides functionality to ensure data protection. Flexible support for different network connections and disk types enables choice in cost and performance optimization.

Designed for smaller environments it provides remarkable scalability in storage capacity offering good headroom for future growth. Thus makes it the perfect storage solution for consolidation of distributed data and for smaller server virtualization projects.



# Features & Benefits

Main Features	Benefits
Reliable operation at an affordable price	<ul style="list-style-type: none"><li>■ Best-in-class price/performance ratio</li><li>■ Rich data safety functionality</li><li>■ Enterprise feature set</li></ul>
Free-of-charge ETERNUS SF Express Storage Management	<ul style="list-style-type: none"><li>■ Single point administration</li><li>■ Easy and efficient operation</li><li>■ No extra cost for software package</li></ul>
Ideal for small and medium-sized IT environments	<ul style="list-style-type: none"><li>■ Easy to install, configure, operate and maintain</li><li>■ Perfect fit for storage consolidation &amp; virtualization</li><li>■ Serves the need of medium capacity requirements and predictable growth rates</li></ul>

# Technical details

## General system information

	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure
No. of controllers		1/2
No. of host interfaces	2/4 ports [FC(16Gbit/s, 8Gbit/s), iSCSI(10Gbit/s, 1Gbit/s), SAS(12Gbit/s)]	
Maximum System Memory	8GB	
Maximum Disk Drives	96	
Max. no. of drive enclosures	3	
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6	
Host Interfaces	Fibre Channel (16Gbit/s, 8Gbit/s) iSCSI (10 Gbit/s [10GBase-T], 1 Gbit/s) SAS (12Gbit/s)	
Max. no. of hosts	128	
Maximum Storage Capacity HDD	672 TB	
Maximum Storage Capacity SSD	31 TB	
Drive Type	2.5-inch, SAS, 15,000 rpm (900 GB / 600 GB / 300 GB*) 2.5-inch, SAS, 10,000 rpm (2.4 TB / 1.8 TB / 1.2 TB / 900 GB* / 600 GB / 300 GB*) 2.5-inch, Nearline SAS, 7,200 rpm (2 TB / 1 TB) 3.5-inch, SAS, 10,000 rpm (2.4TB / 1.8 TB / 1.2 TB / 900 GB*) 3.5-inch, Nearline SAS, 7,200 rpm (14 TB / 12 TB / 10 TB / 8 TB / 6 TB / 4 TB / 2 TB) 2.5-inch, SSD (3.84 TB / 1.92 TB / 960GB / 400 GB) 3.5-inch, SSD (400GB)	
Note	2.5-inch drives are available only for 2.5-inch drive enclosures and 3.5-inch drives are available only for 3.5-inch drive enclosures. 2 TB (2.5-inch) / 6 TB / 8 TB / 10 TB / 12 TB / 14TB Nearline SAS and 1.8 TB / 2.4 TB SAS drives are Advanced Format drives * Not Available in EMEA region	
Mixed 2.5 inch / 3.5 inch drive enclosures	Yes	
Drive interface	Serial Attached SCSI (6 Gbit/s)	
Max. no. of LUNs	1,024	
Max. LUN capacity	128 TB	
No. of snapshots - max.	1,024	
Max. no. of copy generations	512	
Eco-mode	Yes	
<b>Performance management</b>		
Wide striping	Yes	
<b>Information security management</b>		
Data confidentiality	HTTPS (SSL), One Time Password, RADIUS, SSH	
Data integrity	Cache Protection, Data Block Guard, Disk Drive Patrol	
<b>Availability management</b>		
Fast Recovery	Yes	
Non-disruptive maintenance	Dedicated Hot Spare, Global Hot Spare	
Non-disruptive firmware upgrade	Yes	
Hot part replacement	Yes	
<b>Capacity management</b>		
Thin Provisioning	Yes	
RAID migration	Yes	
LUN online expansion w/o interruption	Yes	
Reporting function	Yes	
Hot part expansion	Yes	

**Management**

<b>Interfaces</b>	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
<b>Supported protocols</b>	SNMP (version1, 2C, 3), SMI-S 1.6
<b>Administration</b>	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF
<b>Remote Support</b>	Event notification (E-mail / SNMP / Syslog), Remote maintenance

**Supported OS for ETERNUS SF Express**

<b>Operation Management Server</b>	Microsoft® Windows Server® 2019 Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Microsoft Windows Server 2008, 2008 R2 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Red Hat® Enterprise Linux® 5 Oracle Linux 6 VMware® vSphere® 6.0, 6.5, 6.7 VMware® vSphere® 5/ 5.1/ 5.5 Microsoft Windows Server 2019 Hyper-V Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V Microsoft Windows Server 2008 Hyper-V, 2008 R2 Hyper-V Hyper-V 2.0
<b>Operation Management Client</b>	Internet Explorer® 9, 10, 11 FireFox® ESR 17, 24, 31, 38, 45, 52, 60 Microsoft Edge® 25, 42 Safari 8, 9 (iOS) Chrome® 60 Chrome® 47, 50 (Android®)

**Supported configurations****All major host operating systems, servers and business applications**

Detailed support matrix:

[www.fujitsu.com/global/support/products/computing/storage/disk/supported-configurations](http://www.fujitsu.com/global/support/products/computing/storage/disk/supported-configurations)**Installation specification**

<b>19" rackmount</b>	Yes			
<b>Service Area</b>	Front: 850 mm (33.5 inch) or more Rear: 850 mm (33.5 inch) or more			
<b>Power voltage</b>	AC 100 - 120 V / AC 200 - 240 V			
<b>Power frequency</b>	50 / 60 Hz			
<b>Power supply efficiency</b>	92 % (80 PLUS gold)			
<b>Maximum Power Consumption</b>	AC 100 - 120 V: 1,900 W (1,940 VA)			
<b>Maximum Power Consumption</b>	AC 200 - 240 V: 1,890 W (1,930 VA)			
<b>Power phase</b>	Single			
	2.5-inch Controller Enclosure	3.5-inch Controller Enclosure	2.5-inch Drive Enclosure	3.5-inch Drive Enclosure
<b>Dimensions (W x D x H)</b>	482 x 645 x 88 mm 19 x 25.4 x 3.5 inch 2 U	482 x 670 x 88 mm 19 x 26.4 x 3.5 inch 2 U	482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U	482 x 560 x 88 mm 19 x 22 x 3.5 inch 2 U
<b>Weight</b>	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)	35 kg (77 lb)
<b>Maximum Power Consumption (AC 100 - 120 V)</b>	610W (620VA)	530W (540VA)	430W (440VA)	340W (350VA)
<b>Maximum Power Consumption (AC 200 - 240 V)</b>	600W (610VA)	530W (540VA)	430W (440VA)	340W (350VA)

**Environment**

<b>Maximum Heat Generation</b>	AC 100 - 120 V: 7,000: kJ/h AC 200 - 240 V: 7,000: kJ/h
<b>Temperature (not operating)</b>	0 - 50 °C
<b>Humidity (operating)</b>	20 - 80 % (relative humidity, non-condensing)
<b>Humidity (not operating)</b>	8 - 80 % (relative humidity, non-condensing)

**Environment**

Altitude	3,000 m (10,000 ft.)
Sound pressure (LpAm)	49dB(A)
Sound power (LWAd; 1B = 10dB)	6.7B
Noise notes	Measured with single enclosure according to ISO 7779 and declared according to ISO 9296
Operating environment	Site Planning Guide
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d1f9f172-a1cc-4f5c-8136-cd764fb08b8c">http://docs.ts.fujitsu.com/dl.aspx?id=d1f9f172-a1cc-4f5c-8136-cd764fb08b8c</a>

**Compliance**

Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1
Electromagnetic Compatibility	CNS 13438, FCC Part-15 Subpart B Class A, ICES 003 Class A, EN55032, VCCI Class A, AS/NZS CISPR 32 class A
Electromagnetic Immunity	EN 55024
CE certification	2014/30/EU, 2014/35/EU, 2011/65/EU
Approvals	CB, CE, C-Tick, FCC, EAC, GS, VCCI
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

**Warranty**

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">www.fujitsu.com/warranty</a>

**Product Support Services - the perfect extension**

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/services/product-services">www.fujitsu.com/services/product-services</a>

### Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS DX60 S4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ETERNUS DX60 S4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

FUJITSU LIMITED  
Website: [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)  
2019-08-01 WW-EN