

# Data Sheet

## ETERNUS HX2200

### Hybrid Storage System

#### ETERNUS HX

FUJITSU Storage ETERNUS HX series is a collection of unified and massively scale-out hybrid storage systems, designed to enable your digital transformation by offering superior flexibility, continuous availability and seamless cloud-connected data management in Hybrid IT environments. ETERNUS HX series storage systems accelerate your applications while seamlessly managing your data on the edge, core and the cloud to keep your data available, protected and secure.

#### ETERNUS HX2200

Fujitsu Storage ETERNUS HX2200 unified hybrid storage is optimized for small to medium-sized enterprises and distributed sites of larger organizations that require simple deployment and operations. In a small 2U footprint it can massively scale up to over 2PB and scale-out to 24PB. ETERNUS HX storage systems are optimized for easy deployment and operations and offer unified storage across block and file workloads. They have the versatility to keep up with ever-changing business needs while delivering superior performance and scalability for diverse workloads. ETERNUS HX Hybrid storage systems offer excellent flexibility to handle future growth and cloud integration, while also improving the storage efficiency and reliability of IT operations by delivering integrated data protection and security to safeguard your data.



# Features & Benefits

Main Features	Benefits
Flexible and future-proof storage	<ul style="list-style-type: none"><li>■ Achieve flexible combination of flash and disk media for diverse workloads, easy management of file and block data on a single system, scale capacity and performance non-disruptively and also seamlessly cluster different ETERNUS AX and ETERNUS HX systems.</li></ul>
Seamless cloud-connected data management	<ul style="list-style-type: none"><li>■ Consolidate data management across on-premise storage and cloud in Hybrid IT Infrastructures, along with effortless integration with multiple public clouds – AWS, Microsoft Azure and Google Cloud.</li></ul>
Accelerate business applications	<ul style="list-style-type: none"><li>■ Speed up your critical applications with NVMe cache and increase data throughput for business-critical applications</li></ul>
Continuous availability without compromise	<ul style="list-style-type: none"><li>■ Best-in-class integrated and application-consistent data protection software to prevent data loss and accelerate recovery with space-efficient snapshots, synchronous and asynchronous replication.</li></ul>
Maximize storage efficiency	<ul style="list-style-type: none"><li>■ Innovative data reduction technologies help minimize storage footprint with proven efficiency technologies such as inline deduplication, compression, compaction, and thin provisioning. Efficiently meet SLAs in hybrid IT environments with secure multitenancy and adaptive quality of service (QoS). Simplify and speed up day-to-day storage management with ONTAP System Manager and optimize your storage infrastructure with predictive analytics using Active IQ.</li></ul>

# Technical details

## General system information

	Base
No. of controllers	NAS:2-24 (HA Pair x12) SAN:2-12 (HA Pair x6)
No. of host interfaces	8 Port [FC (8, 16Gbit/s)] 8 Port [FCoE (10Gbit/s)] 8 Port [iSCSI (1, 10Gbit/s)] 8 Port [iSCSI (10GBase-T)] 8 Port [Ether (1, 10Gbit/s)] 8 Port [Ether (1, 10GBase-T)]
Maximum System Memory (HA pair)	64 GB
Flash Cache	2TB/HA Pair
Max. Disk Drives NAS (HA pairx12)	1,728
Max. Disk Drives SAN (HA pairx6)	864
Max. Disk Drives (HA pair)	144
Max. no. of LUNs (HA Pair)	16,384
Max. no. of LUNs (SAN)	98,304
Supported RAID levels	4, 6, TEC
Host Interfaces	FC (8, 16Gbit/s) FCoE (10Gbit/s) iSCSI (1, 10Gbit/s, 10GBASE-T) Ethernet (1, 10Gbit/s, 1, 10GBASE-T)
Mixed host interfaces	Yes
Max. no. of hosts	2048
Maximum Storage Capacity (HA Pair)	2,753.4 TB
Drive Type	2.5-inch, SAS, 10krpm (1.8TB / 1.2TB) 2.5-inch, SAS (FIPS), 10krpm (1.8TB) 2.5-inch, SSD (15.3TB / 7.6TB / 3.8TB / 960GB) 2.5-inch, SSD (FIPS) (3.8TB ) 3.5-inch, Nearline SAS, 7.2krpm (22TB / 16TB / 10TB / 4TB) 3.5-inch, Nearline SAS (FIPS), 7.2krpm (10TB) 3.5-inch, SSD (3.8TB / 960GB) HDDE, Nearline SAS, 7.2krpm (22TB / 16TB / 10TB / 4TB) HDDE, Nearline SAS (FIPS), 7.2krpm (10TB) HDDE, SSD (960GB)
Mixed 2.5 inch/ 3.5 inch drive enclosures	Yes
Drive interface	12G SAS(MiniSAS HD)
Back-end disk connectivity	4/HA pair
Max. no. of RAID groups per system (HA Pair)	48
Max. no. of RAID groups per system (SAN)	288
Max. no. of RAID groups per system (NAS)	576
Max. no. of LUNs per RAID group	16,384
Max. LUN capacity	16 TB
Max. no. of copy generations	1,023
Deduplication	Yes
Compression	Yes
Compaction	Yes

**Performance management**

Quality of Service	Yes
--------------------	-----

**Continuity management**

Metro cluster	Yes
---------------	-----

Remote Copy functionality	Synchronous and asynchronous
---------------------------	------------------------------

Note	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.
------	---

**Information security management**

Data confidentiality	HTTPS (SSL), SSH, iSCSI (CHAP, Bidirectional CHAP)
----------------------	--

Data integrity	Rebuild, Cache Protection (Backup method, Backup data, Backup retention time: No limit), Data Encryption (Software Encryption, Storage Encryption, Self encryption disk), Disk Patrol, Data Block Guard, HDD Shield, CheckSum: BCS/AZCS, Pool Diagnosis (CLI Only)
----------------	--

Note	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fsas Technologies Inc. as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
------	--

**Availability management**

Non-disruptive firmware upgrade	Yes
---------------------------------	-----

Hot part replacement	Yes
----------------------	-----

**Capacity management**

Thin Provisioning	Yes
-------------------	-----

Reporting function	Yes (capacity, health, performance, and protection relationships)
--------------------	---

Hot part expansion	Yes
--------------------	-----

Non-disruptive firmware upgrade	Yes
---------------------------------	-----

**Management**

Interfaces	1Gb Ethernet
------------	--------------

Supported protocols	SNMP v1/v2c/v3, REST, SMI-S
---------------------	-----------------------------

Administration	ONTAP System manager (GUI: Graphical user interface), CLI (Command Line Interface), REST API, Active IQ Unified Manager, SnapCenter
----------------	---

**Supported OS for Management software**

Operation Management Client	Google Chrome 65.0 Microsoft Internet Explorer 11.0 Mozilla Firefox 59.0
-----------------------------	--

**Installation specification**

19" rackmount	Yes
---------------	-----

Power voltage	AC200-240V/AC100V-120V (DE460C Support only AC200V-240V)
---------------	--

Power frequency	50 / 60 Hz
-----------------	------------

Maximum Power Consumption	AC200-240V/AC100V-120V (DE460C Support only AC200V-240V): Controller Shelf: 615W 2U-Drive Shelf: - DS212C: 338W - DS224C: 396W HD-Drive Shelf: - DS460C: 1541W
---------------------------	---

Power phase	Single
-------------	--------

	Base	DS212C	DS224C	DS460C
Dimensions (W x D x H)	480 x 483 x 85 mm 18.9 x 19 x 3.3 inch 2 U	480 x 505 x 87 mm 18.9 x 19.9 x 3.4 inch 2 U	480 x 484 x 85 mm 18.9 x 19.1 x 3.3 inch 2 U	486 x 922 x 176 mm 19.1 x 36.3 x 6.9 inch 4 U

Weight	27.6 kg (61 lb)	28.7 kg (63 lb)	24.4 kg (54 lb)	112 kg (247 lb)
Note	Numbers do not include Rack Mount Kits. Rack Mount Kits increase the weight by 4 kg.			
<b>Environment</b>				
Maximum Heat Generation	AC200-240V/AC100V-120V (DE460C Support only AC200V-240V): 13309: kJ/h			
Temperature (operating)	5 - 40 °C			
Humidity (operating)	8 - 85 %			
<b>Compliance</b>				
Product safety	IEC 60950-1, IEC 62368-1, EN 62368-1, ANSI/UL 62368-1, 2nd Ed, CAN/CSA C22.2 No. 62368-1-14, CNS 14336-1, TP TC 004			
Electromagnetic Compatibility	EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, FCC Part-15 Subpart B Class A, ICES-003 Class A, VCCI Class A, JIS C 61000-3-2, CNS 13438, AS/NZS CISPR 32 class A, TP TC 020, KN32 Class A, KN35			
Electromagnetic Immunity	EN 55035			
Environmental compliance	RoHS compliant, WEEE compliant			
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>			
<b>Warranty</b>				
Manufacturer warranty period	3 years			
Warranty type	Onsite warranty			
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">www.fujitsu.com/warranty</a>			
<b>Product Support - the perfect extension</b>				
Service Lifecycle	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>			
Service Weblink	<a href="http://www.fujitsu.com/services/product-services">www.fujitsu.com/services/product-services</a>			

### Fujitsu products, solutions & services

In addition to ETERNUS HX2200, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/](http://www.fujitsu.com/global/products/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about ETERNUS HX2200, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2024 Fujitsu Limited

### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Limited

Website: [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

2025-02-05 JP-EN