

Data Sheet

FUJITSU PLAN EP QL41132 2X 10G SFP+

Dual-port 10Gbit/s PCIe 3.0 Network Interface Card

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.



PLAN EP QL41132 2X 10G SFP+

The Fujitsu PLAN EP QL41132 2X 10G SFP+ PCIe adapter is based on Marvell's® FastLinQ™ QL41132 HLCU Dual Port RDMA Ethernet Network Interface Adapter. This intelligent Ethernet Network adapter uses Marvell's eighth generation technology to deliver true 10Gb per second (10Gbps) Ethernet performance per port. Integrated, advanced networking eliminates I/O bottlenecks and conserves CPU cycles.

Compared to other 10GbE solutions, NPAR technology unique to this adapter provides switch-independent network partitioning. Fujitsu PLAN EP QL41132 Dual-Port 10GbE Network Interface Adapters deliver advanced Ethernet solutions designed for FUJITSU Server PRIMERGY systems with general purpose operating systems.

Main Features	Benefits
<ul style="list-style-type: none"> Industry's most powerful 10G Ethernet network adapter with both iWARP and RoCE RDMA 	<ul style="list-style-type: none"> This Marvell(TM) FastLinQ(R) RDMA Ethernet Network Adapter PLAN EP QL41132 HLCU delivers much better price and performance versus its predecessor PLAN EP OCe14102. SFP+, 10G DAC connectivity options are supported with either SFP+ optical transceivers for optical fibers, or 10G Twinax DAC (Direct Attached Copper) cables. Supports 10 Gbps line rate with 40G/4x10G Splitter DAC cables. Boosts host CPU efficiency with hardware offloads for GRE, NVGRE, and VXLAN tunnels. NPAR is unique to this adapter and allows network partitioning, successor to the UMC feature known from PLAN EP OCe14102 adapters.
<ul style="list-style-type: none"> Universal RDMA— iWARP and RoCE Remote Direct Memory Access 	<ul style="list-style-type: none"> Delivers choice and flexibility with concurrent support for RoCE v2 and iWARP technologies. Recommended as a discrete PCIe adapter for scale-up of Fujitsu's default DynamicLoM iWARP adapter capabilities.
<ul style="list-style-type: none"> Intelligent Hardware Offload Adapter with iSCSI - iBFT. 	<ul style="list-style-type: none"> Increase VM density and accelerate multitenant networks with full offload for tunneling protocols. iSCSI Boot will be commercially supported once the server UEFI is implemented.
<ul style="list-style-type: none"> NPAR and General Purpose Operating System Support 	<ul style="list-style-type: none"> Enables provisioning of 10GbE ports for greater deployment flexibility through switch-independent NIC partitioning, Microsoft Windows Server, VMware ESXi, SLES, and RHEL. Certified, and Microsoft Standard and Premium Qualifiers for SDDC included as well.
<ul style="list-style-type: none"> Designed for UEFI 	<ul style="list-style-type: none"> Works best on UEFI (Unified Extensible Firmware Interface) PRIMERGY and PRIMEQUEST servers, which is default on the PRIMERGY M4 generation. Supports legacy boot as well, however Fujitsu's ServerView Update Tools and iRMC network inventory are not supported on legacy.

Technical details

Technical details

Controller Silicon	Marvell(R) FastLinQ(TM) QL41132 10G Dual-Port Gigabit Ethernet Controller
Controller type	Ethernet Ctrl.
Connector type	SFP+
Operating system pre-installed	Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of ports	2
Number of Connectors	2
Number of external ports	2
Data transfer rate(s)	10 Gbit/s; 1 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 3.0 x8
Bus type	PCIe 3.0
Bus transfer rate	8GT/s
Bus width	x8

Technical details

Network protocol and standards compatibility	IEEE 802.1q VLAN IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.1Qbb Priority Flow Control (PFC) IEEE 802.3x Flow Control IPv4, IPv6 and mixed IPv4/IPv6 network protocols
HW Virtualization	SR-IOV: up to 240 virtual functions, 120 per port, NPAR: up to 16 physical functions, 8 per port
Interrupt Levels	MSI-X
WoL	No
Virtualization	Server Virtualization - Windows Server 2016 Hyper-V Virtual Machine Queue (VMQ) and Virtual Machine Multi-Queue (VMMQ) - SR-IOV Network Virtualization Offload - VXLAN - NVGRE
Teaming	Windows Server 2016 Teaming Driver
Flow Control	IEEE 802.3-2012 and Ethernet flow control
Additional features	Microsoft SDDC PREMIUM and STANDARD Logo Qualifiers for e.g., Storage Spaces Direct
Offloading	- TCP Stateless Offloads (include checksum, TSO, TSS, RSS, and RSC) - TX/RX IP, TCP & UDP checksum offload (IPv4, IPv6) capabilities
Data transfer rate up to	10 Gbit/s

Order code	Product Name	Height of bracket	Number of ports	Related product
MC-0JXF41	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Low Profile (LP)	2	PRIMEQUEST Server
MC-0JXF42	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Full Height (FH)	2	PRIMEQUEST Server
MCX0JXF41	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Low Profile (LP)#Full Height (FH)	2	PRIMEQUEST Server
S26361-F4069-E202	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Low Profile (LP)	2	PRIMERGY Server
S26361-F4069-E2	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Full Height (FH)	2	PRIMERGY Server
S26361-F4069-L502	Cavium FastLinQ® QL41132HLCU Intelligent Ethernet Adapter 10G SFP+ Dual-Port	Low Profile (LP)#Full Height (FH)	2	PRIMERGY Server

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F3986-E3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10Km
S26361-F3986-E5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3989-E600	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m or 5m
S26361-F3989-L102	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m
S26361-F3989-L105	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 5m
S26361-F3989-L110	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 10m

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
Description optional cable	10Gbit/s optical transceiver module for MMF (S26361-F3986-E3, -L3 and MC-0JXE51, MCX0JXE51):		
	- OM1 (Multi Mode Fiber 62.5/125µm, 200 MHz*km) up to 33m		
	- OM2 (Multi Mode Fiber 50.0/125µm, 500 MHz*km) up to 82m		
	- OM3 (Multi Mode Fiber 50.0/125µm, 2000 MHz*km) up to 300m		
	- OM4 (Multi Mode Fiber 50.0/125µm, 4700 MHz*km) up to 400m		
	10Gbit/s optical transceiver module for SMF (S26361-F3986-E4, -L4):		
	- OS1 (Single Mode Fiber 9µm) up to 10kn:		
	10Gbit/s active twinax cable:		
	- Amphenol 2m, 5m, 10m (S26361-F3989-L102, -L105, -L110)		
	- Brocade 1m, 3m, 5m (S26361-F3873-L501, -L503, -L505)		
	- Cisco 7m, 10m (S26361-F4571-E107, -L107, -E110, -L110)		
	10Gbit/s passive twinax cable:		
	- Cisco 1m, 3m, 5m (S26361-F4571-E101, -L101, -E103, -L103, -E105, -L105)		

Environment

Power consumption	Dual Port SFP+ 10GBase-SR typ. 16 W, max. 18 W Dual Port SFP+ 10GBase-LR typ. 16 W, max. 18 W Dual Port SFP+ 10G Twinax typ. 16 W, max. 18 W
Temperature (operating)	0 - 55 °C
Storage temperature	-40 - 65 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP QL41132 2X 10G SFP+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PLAN EP QL41132 2X 10G SFP+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited
Website: www.fujitsu.com/primergy
2019-08-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED