



# Data Sheet

## FUJITSU PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28

Dual-port 25 Gbit PCIe 3.0

---

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

### **PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28**

The Fujitsu PLAN EP XXV710-DA2 SFP28 Server Adapter is the most flexible and scalable Ethernet adapter for the current demanding data center environments from Intel.

This adapter family addresses the demanding needs of today's generation agile data center by providing unmatched features for both server and network virtualization, flexibility for LAN networks and proven, reliable performance. The PLAN EP XXV710-DA2 SFP28 adapter delivers superior performance with a throughput 100Gb/s, in a PCI Express 3.0 slot.

Main Features	Benefits
<ul style="list-style-type: none"> <li>■ Intel® XXV710-DA2 SFP28 Dual-Port 25/10 GbE Network Adapter</li> <li>■ A Complete, Unified Networking Solution</li> <li>■ Data, Storage, Management - DCB</li> <li>■ Server Virtualization and VMDq</li> <li>■ SR-IOV for Direct Assignment</li> <li>■ Network Virtualization</li> </ul>	<ul style="list-style-type: none"> <li>■ Industry-leading, cost-- and energy-efficient design delivers superior performance with a theoretical throughput of 100 Gb/s (50 Gb/s Tx; 50Gb/s Rx) bidirectional throughput, in a PCI Express v3.0 x8 slot.</li> <li>■ Converging data and storage onto one fabric eliminates the need for multiple adapters, cables and switches.</li> <li>■ A key capability that makes all this possible is traffic class separation provided by Data Center Bridging (DCB) – providing a one-wire solution with virtual pipes for the different classes of traffic.</li> <li>■ The host-based virtualization technologies supported by Intel VT include VMDq for Emulated Path: Adapter-based Queue sorting enabling efficient hyper-visor-based switching.</li> <li>■ Adapter-based isolation and switching for various virtual station instances enabling optimal CPU usage in virtualized environments.</li> <li>■ VXLAN, NVGRE, GENEVE, NSH Offloads. These stateless offloads preserve application performance for overlay networks. With these offloads it is possible to distribute network traffic across CPU cores.</li> </ul>

## Technical details

### Technical details

Controller Silicon	Intel® XXV710-DA2 25 Gigabit Ethernet Controller
Controller type	Ethernet Ctrl.
Connector type	SFP28
Operating system pre-installed	Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.
Released drivers list link	<a href="http://support.ts.fujitsu.com/Download/Index.asp">http://support.ts.fujitsu.com/Download/Index.asp</a>
Number of ports	2
Data transfer rate(s)	1 Gbit/s; 10 Gbit/s; 25 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 3.0 x8
Bus transfer rate	8GT/s
LEDs	LINK (solid) and ACTIVITY (blinking) LINK SPEED (green = 10Gbps; yellow = 1Gbps)
Network protocol and standards compatibility	IPv4, IPv6 and mixed IPv4/IPv6 network protocols IEEE 802.1p Class of Service IEEE 802.1q VLAN IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.3ae 10Gbit Ethernet IEEE 802.3x Flow Control IEEE 802.1as Timing and Synchronization IEEE 1588 Precision Time Protocol IEEE 802.3az Energy Efficient Ethernet (EEE) SFF 8431 SFP+
Interrupt Levels	MSI-X; INTA; MSI

## Technical details

<b>Virtualization</b>	Server Virtualization <ul style="list-style-type: none"> <li>- VMDq (up to 256 maximum VMDq VMs supported)</li> <li>- SR-IOV ready (64 virtual function per port)</li> <li>- VEPA: IEEE 802.1Qbg support for Virtual Ethernet Port Aggregator</li> </ul> Network Virtualization <ul style="list-style-type: none"> <li>- VXLAN, NVGRE, GENEVE</li> <li>- VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags</li> </ul>
<b>Teaming</b>	by OS driver
<b>Remote boot support</b>	PXE 2.0
<b>iSCSI support</b>	Yes
<b>Offloading</b>	<ul style="list-style-type: none"> <li>- TCP Stateless Offloads (include checksum, TSO, VMDq and RSS)</li> <li>- TX/RX IP, SCTP, TCP &amp; UDP checksum offload (IPv4, IPv6) capabilities</li> <li>- iSCSI Host Initiator</li> <li>- Flow Classification (Trafficking data flows across multiple consumers and connections)</li> </ul>
<b>Data transfer rate up to</b>	10 Gbit/s

Order code	Product Name	Height of bracket	Number of ports	Related product
S26361-F4055-E202	Intel XXV710-DA2 25GbE Dual-Port SFP28 PCIe	Low Profile (LP)	2	PRIMERGY Server
S26361-F4055-E2	Intel XXV710-DA2 25GbE Dual-Port SFP28 PCIe	Full Height (FH)	2	PRIMERGY Server
S26361-F4055-L502	Intel XXV710-DA2 25GbE Dual-Port SFP28 PCIe	Low Profile (LP)#Full Height (FH)	2	PRIMERGY Server

## Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F4055-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4055-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F3986-E3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-E5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3989-E600	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m or 5m
S26361-F3989-L102	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m
S26361-F3989-L105	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 5m
S26361-F3989-L110	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 10m
Description optional cable	10Gbit/s transceiver module for MMF (S26361-F3986-E3 / -L3 and MC-0JXE51 / MCX0JXE51): <ul style="list-style-type: none"> <li>- OM1 (Multi Mode Fiber 62.5/125µm, 200 MHz*km) up to 33m</li> <li>- OM2 (Multi Mode Fiber 50.0/125µm, 500 MHz*km) up to 82m</li> <li>- OM3 (Multi Mode Fiber 50.0/125µm, 2000 MHz*km) up to 300m</li> <li>- OM4 (Multi Mode Fiber 50.0/125µm, 4700 MHz*km) up to 400m</li> </ul> 10Gbit/s transceiver module for SMF (S26361-F3986-E4 / -L4): <ul style="list-style-type: none"> <li>- OS1 (Single Mode Fiber 9µm) up to 10km</li> </ul>		

## Environment

<b>Power consumption</b>	typ. 4.5 W, max. 5.1 W
<b>Power consumption</b>	
<b>Temperature (operating)</b>	0 - 55 °C
<b>Storage temperature</b>	-40 - 70 °C

---

**Compliance**

---

<b>Compliance notes</b>	According to the corresponding system
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

---

# More information

## Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 , Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Server PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 , please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/primergy](http://www.fujitsu.com/primergy)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Limited  
Website: [www.fujitsu.com/primergy](http://www.fujitsu.com/primergy)  
2019-04-27 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED