

Data Sheet

FUJITSU Analog and Digital KVM console switches

The console switches (Keyboard Video Mouse = KVM) from Fujitsu Technology Solutions are vital in the operation of cluster configurations and server farms in data centers. They offer a cost-optimized, platform and software-independent solution for rack system integration. Both PS/2 and USB interfaces from servers are supported, resulting in possible mixed configurations with different Fujitsu servers in one rack.

Analog and Digital KVM console switches

The console switches provide a solution positioned between simple mechanical and high-end digital console switches for rack integration. A maximum of 16 servers can be operated in a rack, locally or with one console in an IP connection (10/100/1000 Mbit/s) depending on the switch model. Cascaded switches up to 256 servers are even possible.

They are also DDC2B compatible. The console switches are primarily designed for integration into 19-inch racks. They round off the 19-inch technology portfolio of Fujitsu servers and are indispensable for the operation of cluster configurations and server farms in data centers. The cost benefits (cutting back on monitors and keyboards that are otherwise needed) are obvious.

8- and 16-port switch for system consoles that

can be configured to provide connections for up to one local user for analog switches. For one, remote user plus one local user for 16-port digital switches. End-to-end CAT5e/6 connections, firmware flash-upgradability and keep-alive function are provided. Advanced on-screen management for configuration/server selection, client-based GUI for remote access and improved graphics. Virtual Media (VM) and LDAP support for Digital KVM switches. Password protection and remote access secured by SSL encryption.



Main Features	Benefits
Flexible access <ul style="list-style-type: none"> Access via remote IP or locally 	<ul style="list-style-type: none"> More flexible access: one local console for Analog KVM or one local and one remote consoles (via IP) for Digital KVM
Simplified management <ul style="list-style-type: none"> Advanced on-screen management for configuration and server selection 	<ul style="list-style-type: none"> Direct access for administrators or rack users via local console
Access protection <ul style="list-style-type: none"> Access protection 	<ul style="list-style-type: none"> LDAP support for Digital KVM; Password protection and various levels of access control; Remote access secured by encryption
Connectivity <ul style="list-style-type: none"> USB 2.0, CAT5e/6, RJ-45 	<ul style="list-style-type: none"> Multi-platform compliant: USB 2.0, CAT5e/6, RJ-45

Technical details

Technical details

	Analog KVM	Digital KVM
Installation format		Rack-optimized,1U
Console connections	One local console	One remote-console via TCP/IP (10/100/1000MBit/s auto-sense), One local console
Supported displays	Monitor: VGA, SVGA (XGA, XGA-II with adapter) Monitor: Wide Screen support (WXGA) Local port: up to 1600 x 1200 @60Hz	
Supported keyboards	USB, RC25	
Supported mouse systems	USB, RC25	
Server selection	By Advanced On-Screen Management (OSD)	By Advanced On-Board WEB-Interface (OBWI)
Configuration	By Advanced On-Screen Management (OSD)	By Advanced On-Board WEB-Interface (OBWI)
OSD languages	English, German, Russian, French, Spanish, Japanese, Chinese	
Remote access	On-Board WEB-Interface (OBWI)	
KVM client software	Linux, Windows	
Browser support (OBWI)	Firefox, Chrome, IE	
Client software languages	English, German, Russian, French, Spanish, Japanese, Chinese	
Virtual media support	All with PRIMERGY servers supported USB devices. Only in connection with KVM adapter cable - USB VM.	
Released server for virtual media via USB	Servers BIOS has to support "Composite USB2.0" in boot phase.	
Color coding	VGA according to PC99	
Dimensions (W x D x H)	424 x 238 x 42.5 mm	424 x 238 x 42.5mm
Weight	2,4 kg without cable	2.6 kg without cable
Rated voltage range	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	
Active power (max. configuration)	21 W	16 W

Accessories

Cabling	Cabling hints
	UTP CAT5e/6 cable (RJ45): 2m, 5m and 10m, as well as customized length for ex works installation KVM adapter USB cable
Cascading	Cascading hints
	All Analog KVM switches have Chain IN/OUT ports. The cascading protocol runs via this Chain IN/OUT port and the "master" and "slave" switch are automatically detected and integrated. KVM Cable-Daisy Chain needed for cascading Analog KVM switches. Digital KVM should always be selected as the "master" switch. The local console is also connected to this switch. KVM adapter cable-USB needed for cascading Digital KVM switches
	Analog KVM 8port/16port on top Analog KVM 8port/16port Digital KVM 16port on top of Analog KVM 8port/16port

Order code	Product Name	Server ports	Remote ports	Local ports
S26361-F5644-E108	KVM0108A	8	0	1
S26361-F5644-E116	KVM0116A	16	0	1
S26361-F5644-E196	KVM0116A integration RC25	16	0	1
S26361-F5644-E198	KVM0108A integration RC25	8	0	1
S26361-F5644-E25	RC25 TFT drawer kit			
S26361-F5644-E501	KVM-USB, adapter USB, VGA			
S26361-F5644-E502	KVM-USBVM			
S26361-F5644-E503	AP5263 KVM Daisy-Chain Cable			
S26361-K1612-V116	KVM1116Q	16	1	1+1 cascading

Approvals & Conformity (Standards)

Germany	VDE
Europe	CE EN
USA/Canada	CSAc/us FCC Class A AULc/us ULc/Canada
Global	CB
Japan	VCCI
Russia	EAC
South Korea	KC
Australia/New Zealand	RCM
Taiwan	BSMI
Vietnam	ICT
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu Server Analog and Digital KVM console switches, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Server Analog and Digital KVM console switches, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2022 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu LIMITED

Website: www.fujitsu.com
2022-12-02 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2022 Fujitsu LIMITED