

Data Sheet

FUJITSU PRIMECENTER M1 19-inch Racks

19-inch Industry Standard Rack Systems

easy service and simple maintenance.

PRIMECENTER M1 19-inch Racks

The Fujitsu PRIMECENTER M1 19-inch Racks are the basis for rack configurations, such as server, storage systems as well as operating controls, such as consoles, switches, power distribution units (PDUs) and uninterruptible power supplies (UPS). As the PRIMECENTER M1 19-inch Racks are based on the industry standards EIA310-D, DIN41494 and IEC 297, they can accommodate commercial products that match such standards. The racks can be extended horizontally and fit into the existing IT scenario.

The PRIMECENTER M1 Racks come as asymmetric and symmetric 700 mm wide versions in 24 and 42 height units as well as symmetric 600 mm wide versions in 16, 24 and 42 height units.

The symmetric racks offer up to 4 vertical 19-inch slots on left and right front side which can be used for switches or to guide cables from front to rear. The asymmetric racks provide up to 6 vertical 19-inch slots on left front side and space for the patented sideways Fujitsu cable management in the rear. 80% degree of perforation (approximate) and excellent cable management to optimize air flow for cooling and high heat dissipation. The design of the PRIMECENTER M1 Racks ensures



Main Features	Benefits
<ul style="list-style-type: none"> ■ 19-inch standard rack technology 	<ul style="list-style-type: none"> ■ To install Fujitsu Technology Solutions rack servers, storage products and components as well as products from other manufacturers.
<ul style="list-style-type: none"> ■ Optimized rack structures 	<ul style="list-style-type: none"> ■ Different rack frames for efficient server, switch, power and cable installation with best possible airflow.
<ul style="list-style-type: none"> ■ Design 	<ul style="list-style-type: none"> ■ Asymmetric rack structure with perfect lateral cable management (700 mm width) or symmetric rack structures (600 mm or 700 mm width)
<ul style="list-style-type: none"> ■ Capacity ■ Ease of service 	<ul style="list-style-type: none"> ■ as ■ One wing design front door and two wing rear door, tool less removable. ■ Retractable anti-tilt protection. ■ Optional factory installation with cabling and final tests.
<ul style="list-style-type: none"> ■ Access protection 	<ul style="list-style-type: none"> ■ Front-, rear doors and side panels are lockable.

Technical details

Base unit	Order code	Dimensions (W x D x H)	Vertical Slots	Transport Dimensions (W x D x H)	Max. pay load / dynamic load	Net weight
PCR M1 724S (24 U symmetrical)	S26361-K827-V220	700mm x 1050mm x 1203mm	2	800mm x 1200mm x 1350mm (approx.)	540 kg / 650 kg	89 kg
PCR M1 742S (42 U symmetrical)	S26361-K827-V240	700mm x 1050mm x 2003mm	4	800mm x 1200mm x 2150mm (approx.)	878 kg / 1000 kg	122 kg
PCR M1 624S (24 U symmetrical)	S26361-K827-V320	600mm x 1050mm x 1203mm		700mm x 1200mm x 1350mm (approx.)	540 kg / 650kg	82 kg
PCR M1 642S (42 U symmetrical)	S26361-K827-V340	600mm x 1050mm x 2003mm		700mm x 1200mm x 2150mm (approx.)	888 kg / 1000 kg	112 kg

Rack Infrastructure

Variants	Asymmetrical design 700 mm, 24+4 U and 42+6 U, for patented cable management Symmetrical design 700 mm, 24+2 U and 42+4 U with standard rack design Symmetrical design 600 mm, 16 U, 24 U and 42 U with space optimized rack design		
Capacity	16 heights units with up to 20 kg load per horizontal height unit, maximum weight up to 400 kg.	24 height units plus up to 4 vertical height units (depth of up to 300 mm incl. cable space). Up to 20 kg load per horizontal, 3.5 kg per vertical height unit, maximum weight up to 650 kg.	42 height units plus up to 6 vertical height units (depth of up to 300 mm incl. cable space). Up to 20 kg load per horizontal, 3.5 kg per vertical height unit, maximum weight up to 1000 kg.
Doors	One-piece front door and two-piece rear door with high percentage of holes (approx. 80%) for improved server cooling. Ergonomic door handles		
Front door	One-piece design front door with ergonomic handle bar, right or left hand mounting possible.		
Rear door	Twin doors to optimize needed service space One door with cable entry		

Internal depth

19-inch clearance	450.5 mm +1 mm/-0 mm		
Front/rear 19-inch level	740 mm		
Space for cabling	Up to 100 mm on front side Up to 180 mm on rear side		
Cable management and service	Optimized cable routing solutions. Cabling openings in the floor group and in the rear door.		
Maximum load	Up to 10000 N stationary on leveling feets, 200 N per U 10000 N dynamic load (movable on castors)		
Permitted total weight	Up to 10000 N / 1000 kg for 42U racks		
Shipment	Optionally ex works, fully mounted and tested including cabling. Shipment including 4 heavy-duty castors and 4 adjusting feet on a shock-absorbing pallet.		
Top cover	Two break out entries for external cabling		
Security			
Protection class	DIN (EN60529) IP20		
Security functions	Lockable front, rear door and side panels, optional antitilt protection.		
Rack accessories	Optional available: rack mounting kits; cable management solutions; networking components, I/O switches, mounting kits, accessory kits, shelves, electrical connections, monitoring (rack console, KVM switches), uninterruptible power supply (UPS), power distribution units (PDU)		

Environment

Environmental compliance	Operation:	Class 3K3*, 3M2, 3S2
	Transport:	Class 2K2, 2M2, 2M1
Environmental compliance note	*Possibly restricted by rack components	

Compliance

Germany	GS
Europe	EN

Compliance

USA/Canada	UL/CSA
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronical equipment)
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMECENTER M1 19-inch Racks, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMECENTER M1 19-inch Racks, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/Primergy>

Fujitsu green policy innovation

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner