

Data Sheet

FUJITSU PCI BOX

Designed for high availability and performance - I/O expansion for PRIMEQUEST 2x00E servers

The PRIMEQUEST PCIe Expansion System provides a high-performance and low latency solution for expanding PCIe slots outside PRIMEQUEST systems. Designed for high availability and performance, PRIMEQUEST PCI BOX is an I/O expansion option for applications demanding high I/O scalability in mission-critical systems. It can be seamlessly integrated into mission-critical systems.

PCI BOX

Thanks to the high availability of PRIMEQUEST, the PCI Box can be seamlessly integrated into mission-critical servers. Most of the components such as PSU, fan, and PCI Express cards can be redundant and hot swappable.

The PRIMEQUEST PCI Box expands the I/O slots of PRIMEQUEST servers. Up to 12 PCI Express slots (two host interfaces of 6 slots each) per I/O Box help to expand I/O throughput while maintaining high availability.



Main Features	Benefits
<ul style="list-style-type: none"> ■ PCI hot-plug (2x 6 full height slots per box) ■ Powersupply redundancy ■ Up to 4 x per PQ2x00E possible 	<ul style="list-style-type: none"> ■ Protects your investment in expensive I/O cards ■ Provides dedicated power for PCI Express cards ■ Expands the PRIMEQUEST 2x00E Modell PCI slot value

Technical details

Slots

PCI-Express 3.0 x8	12 x Full height PCI Hot Plug
--------------------	-------------------------------

Number of fans

Fan configuration	Redundant
-------------------	-----------

Operating buttons

Status LEDs	Power (green)
-------------	---------------

Dimensions / Weight

Rack (W x D x H)	482 x 740 x 175 mm
------------------	--------------------

Height Unit Rack	4 U
------------------	-----

19" rackmount	Yes
---------------	-----

Weight	35 kg (77 lb.)
--------	----------------

Weight notes	Fully assembled Actual weight may vary depending on configuration
--------------	--

Rack integration kit	Rack mount kit attached. For additional Material see PQ2x00E Configuration guides.
----------------------	--

Environment

Operating ambient temperature	0 - 35 °C
-------------------------------	-----------

Operating relative humidity	20 - 80 %
-----------------------------	-----------

Maximum altitude	3000 m
------------------	--------

Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
-----------------------	--

Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
----------------------------	---

Noise emission	The relevant value is included in PRIMEQUEST chassis specification.
----------------	---

Electrical values

Power supply configuration	Up to 2 power supply. Unit equipped with 0 power supplies, redundancy as option.
----------------------------	---

Max. input of single power supply	5.7A
-----------------------------------	------

Hot-plug power supply redundancy	Yes
----------------------------------	-----

Rated voltage range	100 V - 240 V
---------------------	---------------

Rated frequency range	50 Hz - 60 Hz
-----------------------	---------------

Active power (max. configuration)	460 W
-----------------------------------	-------

Apparent power (max. configuration)	485 VA
-------------------------------------	--------

Heat emission (max. configuration)	1656.0 kJ/h (1569.6 BTU/h)
------------------------------------	----------------------------

Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) - planned
--------	---

Germany	GS
---------	----

Europe	CE Class A *
--------	--------------

Japan	VCCI
-------	------

Compliance link	https://sp.ts.fujitsu.com/sites/certificates
-----------------	---

Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
------------------	---

Components

Warranty

Warranty period	3 years
Warranty type	Onsite Service
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Recommended Service	-
Service Lifecycle	5 years after end of product life
Service Weblink	www.fujitsu.com/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PCI BOX, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PCI BOX, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH
Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: [www.fujitsu.com/\[country\]](http://www.fujitsu.com/[country])
2017-10-05 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions