

Data Sheet

Fujitsu PRIMERGY BX Ethernet Switch/IBP 1Gbit/s 36/12

Connects 2 channels of each server blade with any number of external 1 Gbit/s Ethernet networks

PRIMERGY BX Ethernet Switch/IBP 1Gbit/s 36/12

The PRIMERGY Ethernet Switch/IBP 36/12 is an integrated 1 Gbit/s Connection Blade for use in the PRIMERGY BX400 and BX900 chassis. It can be installed in all Connection Blade bays (4x in BX400, 8x in BX900) and provides 36 downlink ports each with 1 Gbit/s to the midplane to connect with the Server Blades. The module contains 12 uplink ports each 1 Gbit/s; Layer 2+ functionalities are supported.

The Intelligent Blade Panel mode combines the advantages of a switch regarding cable and port consolidation with the pass-thru advantage of total (VLAN) transparency without protocol compatibility problems occurring. Server Blade LAN ports may be grouped together with one or more external ports, into independent named port groups. Using the so-called Management VLAN grouping feature, a separate VLAN-based management access can be assigned to each Server Blade.



Features & Benefits

Main Features	Benefits
<p>Independent of external Ethernet switches</p> <ul style="list-style-type: none">■ Integrated switch and Intelligent Blade Panel for PRIMERGY BX400 and BX900 Blade Servers.	<ul style="list-style-type: none">■ Variable usage in one of the up to 8 connection slots on the rear of a system unit.■ Effortless switching between the pure switch and the IBP functionality allows flexible use depending on demands.■ High scalability due to a large number of external connections.■ The IBP mode avoids protocol compatibility problems (e. g. Cisco compatibility) and offers extended functions in comparison to the standard switch mode■ The IBP mode avoids protocol compatibility problems (e. g. Cisco compatibility) and offers extended functions in comparison to the standard switch mode
<p>Flexible and easy to adapt</p> <ul style="list-style-type: none">■ Unites switch and IBP functionality.	
<p>Comprehensive connection options</p> <ul style="list-style-type: none">■ 8 x 1Gbit/s (RJ45) uplink ports + 4 x 1Gbit/s (SFP) uplink ports.	
<p>Compatible and functional</p> <ul style="list-style-type: none">■ When used in IBP mode: Uplink Sets, Port Grouping, Standard Port Group, VLAN Port Group, Service LAN Group, Service VLAN Group.	
<ul style="list-style-type: none">■ When used in IBP mode: Uplink Sets, Port Grouping, Standard Port Group, VLAN Port Group, Service LAN Group, Service VLAN Group.	

Technical details

PRIMERGY BX Ethernet Switch/IBP 1Gbit/s 36/12

Connection type	LAN Connection Blade Layer 2+, 1 Gbit/s Ethernet Switch or Intelligent Blade Panel (IBP)
Supported system units	PRIMERGY BX400 S1, PRIMERGY BX900 S1, PRIMERGY BX900 S2
Max. number per BX unit	4 in PRIMERGY BX400 S1, 8 in PRIMERGY BX900 S1/S2
Supported Server Blades	PRIMERGY BX9xx Server Blade w. 1 Gbit/s LAN on board PRIMERGY BX9xx Server Blade w. 10 Gbit/s LAN on board PRIMERGY BX9xx S3/S4 Server Blades w. 10 Gbit/s CNA on Board PRIMERGY BX25xx Server Blades w. 10Gbit/s CNA on Board
Supported Mezzanine Cards	PRIMERGY BX Eth Mezz Card 1 Gbit/s 4 port PRIMERGY BX Eth Mezz Card 10 Gbit/s 2 port

Interfaces

Down-link ports	36 x 1 Gbit/s Eth
Up-link ports	8 x 1 Gbit/s Eth (RJ45) 4 x 1 Gbit/s Eth (SFP)

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F3986-E1	Ethernet 1 Gbit/s	SFP / 1000BASE-T	RJ45 / up to 100m
S26361-F3986-E2	Ethernet 1 Gbit/s	SFP / MMF (SWL)	LC-style / up to 300m
Interface Module notes	Only Fujitsu certified modules and cables are supported		

Technical specifications

Layer 2 feature	Auto MDI/MDIX on all 10/100/1000BASE-TX ports 10/100/1000BASE-TX ports auto-sensing, auto-negotiation Flow control: - IEEE802.3x for full duplex mode - Back-pressure flow control in half duplex mode Jumbo frames up to 9KB Link Aggregation Port mirror Spanning Tree (not for IBP mode) VLAN IGMP snooping v1/v2/v3 IGMP querier v1/v2 (not for IBP mode) Provide storm control protection Link State (force downlink port down, if uplink port is down) Port backup LLDP
Quality of service	IEEE 802.1p based CoS (Class of Service) IP TOS/Precedence/DSCP based CoS Layer 2/3/4 Access Control Lists (ACLs) Differentiated Service (DiffServ)
Link aggregation	Support of: - up to 6 groups for uplink ports and 18 groups for downlink ports - up to 8 ports per group Supported Link Aggregation features: - IEEE 802.3ad Link Aggregation (LACP) - Cisco EtherChannel (static) - Load balancing with configurable rule (MAC-based and IP-based)
Spanning tree	only for Switch mode IEEE 802.1D (STP) IEEE 802.1W (RSTP) IEEE 802.1S (MSTP) 32 MSTP instances

Technical specifications

Network protocol and standards compatibility for IBP	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3z 1000BASE-SX IEEE 802.3ab 1000BASE-T IEEE 802.3ad LACP IEEE 802.3x Flow Control IEEE 802.1ab LLDP IEEE 802.1p Class of Service
Network protocol and standards compatibility	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3z 1000BASE-SX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3ad LACP IEEE 802.1v Protocol VLAN, Port VLAN IEEE 802.1d Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1s Multiple Spanning Tree Protocol IEEE 802.1q VLAN IEEE 802.1ab LLDP IEEE 802.1p Class of Service
Performance	Bandwidth: 96-Gbps Forwarding modes: Store-and-forward Switch latency: average 8 us for 64-byte frames System memory: 256MB Flash size: 64MB Support up to 8K MAC address entries
Port group feature	only for IBP mode 30 uplink-sets 30 port-groups 30 VLAN-groups 10 service-LAN 128 service-VLAN
VLAN	VLAN features in Switch Mode: IEEE 802.1Q VLAN Up to 1000 VLANs, out of 4K VLAN IDs Port-based VLAN Protocol-based VLAN MAC & IP-Subnet based VLANs GVRP, GARP, GMRP VTP v1/v2 VLAN features in IBP Mode: IEEE 802.1Q VLAN

Technical specifications

Management	<ul style="list-style-type: none"> 1 console interface for MMB internal management Software upload/download via FTP or TFTP Configuration upload/download via FTP or TFTP Dual firmware images Up to 11 configuration files including factory default SSH/SSL/TLS keys download via FTP or TFTP Message/event/error/trap logs BOOTP and DHCP v4/v6 for IP address assignment IPv6 for management IP address DHCP/DHCPv6 Client support Ping function Traceroute function for IPv4 and IPv6 SNTP (Simple Network Time Protocol) version 4 CDP (Cisco Discovery Protocol) version 2 (not for IBP mode) LLDP (Link Layer Discovery Protocol) SSH v1/v2 switch management SSL v3/TLS v1 switch management CLI (Command Line Interface) switch management Support Web switch management SNMP v1, v2c, and v3 switch management Private Enterprise MIB RMON groups 1, 2, 3, and 9 sFlow (RFC 3176)
Security	<ul style="list-style-type: none"> User name and password IP address filter Remote Authentication Dial In User Service (RADIUS) client Terminal Access Controller Access Control System (TACACS+) client Secure Sockets Layer (SSL) version 3 and Transport Layer Security (TLS) version 1 Secure Shell (SSH) version 1 and version 2 IEEE 802.1x port access control Port Security
User interface	<ul style="list-style-type: none"> Command Line Interface (CLI) Web-based management SNMP v1/v2c/v3.
Dimensions / Weight	
Dimensions (W x D x H)	192.6 x 267.9 x 27.9 mm
Weight	1.35 kg
Environmental compliance	
Temperature note	See corresponding PRIMERGY BX System Unit
Electrical values	
Active power (max. configuration)	35 W
Heat emission (max. configuration)	126.0 kJ/h (119.4 BTU/h)
Compliance	
Germany	GS
Europe	CE Class A *
USA/Canada	ULc/us FCC Class A
Global	CB RoHS WEEE
Japan	VCCI:V3 Class A + JIS 61000-3-2
Australia/New Zealand	C-Tick
Taiwan	BSMI

Compliance

Compliance notes

In combination with corresponding PRIMERGY BX system unit
There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
* Warning:
This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Compliance link

<https://sp.ts.fujitsu.com/sites/certificates>

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY BX Ethernet Switch/IBP 1Gbit/s 36/12, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX Ethernet Switch/IBP 1Gbit/s 36/12, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://www.fujitsu.com/fts/products/computing/servers/primergy/blades/connection/cb-pmod-75302.html>

Fujitsu green policy innovation

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU LIMITED

Address: x-xx-x, street, city, state, ZIP code, country

Phone: xx-xxxx-xxxx

Fax : xx-xxxx-xxxx

Email: xxx.xxxxx@xx.fujitsu.com

Website: [http://\[country\].fujitsu.com](http://[country].fujitsu.com)

2019-08-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions