

Data Sheet

Fujitsu PRIMERGY BX InfiniBand Switch 56 Gbit/s 18/18

Top performance for highly-demanding network connections

PRIMERGY BX InfiniBand Switch 56 Gbit/s 18/18

The InfiniBand Switch 56 Gb 18/18 is a double-width Connection Blade that can be used in the Fujitsu PRIMERGY Blade Servers. The Connection Blade offers maximum performance by providing a high bandwidth and at the same time low latency. The hardware requires two horizontal slots at the rear of the blade chassis; up to three of the switches can be used in one housing. The switch with its total of 36 connections provides one of the highest densities in today's switch architectures. The Connection Blade supports Fourteen Data Rate (FDR x4) Infiniband and thus offers a bandwidth of up to 56Gb/s per port. The non-blocking architecture is used to support both adaptable and static routing so as to avoid or reduce any overloading. Combining InfiniBand with the highly-flexible dense capacity of the PRIMERGY BX900 series, Fujitsu enables datacenters to enjoy overall savings, through system consolidation from larger, less powerful server racks, and reduced floor-space requirements.



Features & Benefits

Main Features	Benefits
Efficient performance <ul style="list-style-type: none">■ 18x uplink ports, 18x downlink ports with Fourteen Data Rate (FDR x4) and QSFP connectors	<ul style="list-style-type: none">■ Leading industrial switch platform as regards performance, power consumption and packing density
Best-in-class transfer rates <ul style="list-style-type: none">■ InfiniBand switch architecture with up to 56Gb/s per port	<ul style="list-style-type: none">■ High bandwidth, low latency for compute-intensive applications
Management for constant usage <ul style="list-style-type: none">■ Two internal Ethernet ports (one port for each MMB) for switch management tasks	<ul style="list-style-type: none">■ - Monitoring temperature and power consumption■ - Health check■ - Configuration settings■ - Hot-pluggable
Never overloaded <ul style="list-style-type: none">■ Non-blocking architecture	<ul style="list-style-type: none">■ Automatic and dynamic routing of data traffic to avoid overload

Technical details

PRIMERGY BX InfiniBand Switch 56 Gbit/s 18/18

Connection type	InfiniBand Connection Blade 36-port IB CB 18 ports internal, 18 ports external up to 56Gb per port QSFP connectors for external ports included
Supported system units	PRIMERGY BX400 S1, PRIMERGY BX900 S2
Max. number per BX unit	1 in PRIMERGY BX400 S1, 3 in PRIMERGY BX900 S2
Supported Server Blades	PRIMERGY BX9xx Server Blades w. IB mezzanine card PRIMERGY BX25xx M1 Server Blades w. IB mezzanine card
Supported Mezzanine Cards	PRIMERGY BX IB Mezz Card 56 Gbit/s 2 port

Interfaces

Down-link ports	18 x 56 Gbit/s IB
Up-link ports	18 x 56 Gb (QSFP)

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
------------	-------------	-------------	--------------------------

Technical specifications

Management	Embedded CPU for out-band management Management is done via Command Line Interface (CLI) Features: <ul style="list-style-type: none"> CPU board management FW management Inventory, Status and Statistics Debug tools Logging
-------------------	---

Dimensions / Weight

Dimensions (W x D x H)	387.5 x 266.5 x 28.22 mm
Weight	3.3 kg

Environment

Temperature note	see corresponding PRIMERGY BX System Unit
-------------------------	---

Electrical values

Active power (max. configuration)	150 W
Heat emission (max. configuration)	540.0 kJ/h (511.8 BTU/h)
Electrical value notes	18x QSFP module for uplink ports included

Product	
Germany	GS
Europe	CE Class A *
USA/Canada	ULc/us FCC Class A
Global	CB RoHS WEEE
Japan	VCCI:V3 Class A + JIS 61000-3-2
Taiwan	BSMI

Compliance notes

In combination with corresponding PRIMERGY BX system unit

There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

* Warning:

This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Compliance link

<https://sp.ts.fujitsu.com/sites/certificates>

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY BX InfiniBand Switch 56 Gbit/s 18/18, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX InfiniBand Switch 56 Gbit/s 18/18, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://www.fujitsu.com/fts/products/computing/servers/primergy/blades/connection/cb-pmod-109706.html>

Fujitsu green policy innovation

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright 2017 FUJITSU LIMITED

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU LIMITED

Address: x-xx-x, street, city, state, ZIP code, country

Phone: xx-xxxx-xxxx

Fax : xx-xxxx-xxxx

Email: xxx.xxxxx@xx.fujitsu.com

Website: [http://\[country\].fujitsu.com](http://[country].fujitsu.com)

2019-06-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright 2017 FUJITSU LIMITED