

Data Sheet

FUJITSU Server PRIMERGY BX2580 M2 Blade Server

Feature-rich 2-socket server blade designed for maximum performance

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY BX blade systems are the perfect platform to build a converged infrastructure designed to reduce IT costs, time and efforts. PRIMERGY Blade Servers utilizes a modular architecture and contain in addition to the compute power, all required infrastructure and network components, storage capacity as well as management modules that helps companies to simplify their infrastructure, achieve significant cost reductions and increase flexibility.

PRIMERGY BX2580 M2

Optimized for a broad spectrum of workloads including virtualized workloads, consolidating applications as well as ERP and CRM applications, the PRIMERGY BX2580 M2 provides dense computing features with ultra-large memory capabilities. The server blade delivers improved performance for data centers and remote sites. Based on the latest Intel® Xeon® processor E5-2600 v4 product family, it offers up to 3072 GB of memory (24 DIMM slots) and up to two disk drives. The PRIMERGY BX2580 M2 offers exceptional levels

of flexibility and I/O throughput to run the most demanding applications. The system is equipped with a dual port 10 Gigabit Ethernet, Data Center Bridging (DCB)-capable LAN on motherboard (LOM) that supports NIC, iSCSI, and FCoE and can in addition be configured with two mezzanine cards. The onboard converged network adapter can be partitioned in up to eight physical functions per port that can be dynamically configured. The adapters serve as a common interface for both storage and IP traffic retaining familiar FC and networking software stacks, OS drivers, and management.



Features & Benefits

Main Features	Benefits
<p>Scalability and performance</p> <ul style="list-style-type: none"> ■ Support of up to two processors, 44 cores with up 88 threads, up to 55 MB Last-level Cache (LLC) that maximizes the concurrent execution of multi-threaded applications. ■ Up to 2400 MHz memory speeds in a dual RDIMM configuration to help maximize system performance. ■ Up to 3 TB of memory capacity with 64 GB load-reduced DIMMs, or LRDIMMs. ■ Up to 16 virtual I/O ports with embedded 2x 10 Gbit/s LoM that offers the choice of Ethernet, iSCSI, or Fibre Channel over Ethernet (FCoE) connectivity. <p>Usability and serviceability</p> <ul style="list-style-type: none"> ■ SD-Card connected to iRMC to support e.g. backup and restore functions or embedded lifecycle management (eLCM). ■ Optional Trusted Platform Module (TPM) for safer storage of keys. ■ Tool-less cover removal provides easy access to upgrades and serviceable parts. ■ Status LED's with illuminated icons and Customer Self Service (CSS) concept that enables to identify and replace affected component in case of error scenarios. ■ Automatic Server Reconfiguration and Restart (ASR&R) restarts the system in the event of an error and automatically "hides" the defective system components. ■ Prefailure Detection and Analyzing (PDA) technology analyzes and monitors all components that are critical for system reliability. <p>Energy efficiency</p> <ul style="list-style-type: none"> ■ The Intel Xeon processor E5-2600 v4 product family built on latest 14nm process technology offers significantly better performance over the previous CPU generation. ■ Fujitsu's enhanced power management features provide a range of possibilities that enable the energy consumption of the blade chassis and the individual server blades to be dynamically monitored and influenced. ■ Low-voltage 1.2 V DDR4 memory DIMMs use up to 20% less energy compared to 1.35 V DDR3 DIMMs. 	<ul style="list-style-type: none"> ■ The PRIMERGY BX2580 M2 offers enhanced features that boost performance, improve scalability while reducing costs. ■ Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power of about 20% compared to the previous generation. ■ DDR4 memory enables for higher bandwidth and lower consumption, optimized for data center tasks, enterprise applications but also collaboration & messaging solutions. <ul style="list-style-type: none"> ■ The PRIMERGY BX2580 M2 enhances usability and serviceability to increase system up-time. ■ The comprehensive tools of the Fujitsu ServerView Suite eases the administrators life. ■ Lifecycle investment protection: Updates are very important in a fast-paced world, especially considering cyber crime. <ul style="list-style-type: none"> ■ The PRIMERGY BX2580 M2 increases the efficiency to be able to save energy and reduce operational costs.

Technical details

PRIMERGY BX2580 M2

Mainboard

Mainboard type	D3321
Chipset	Intel® C610
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2600 v4 product family

Processor

Intel® Xeon® processor E5-2699v4 (22C/44T, 2.20 GHz, up to 2.8 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2699Av4 (22C/44T, 2.40 GHz, up to 3.0 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2698v4 (20C/40T, 2.20 GHz, up to 2.7 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2697v4 (18C/36T, 2.30 GHz, up to 2.8 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2697Av4 (16C/32T, 2.60 GHz, up to 3.1 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2695v4 (18C/36T, 2.10 GHz, up to 2.6 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2690v4 (14C/28T, 2.60 GHz, up to 3.2 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2683v4 (16C/32T, 2.10 GHz, up to 2.6 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2680v4 (14C/28T, 2.40 GHz, up to 2.9 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2667v4 (8C/16T, 3.20 GHz, up to 3.5 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2660v4 (14C/28T, 2.00 GHz, up to 2.4 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2650v4 (12C/24T, 2.20 GHz, up to 2.5 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2650Lv4 (14C/28T, 1.70 GHz, up to 2.0 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2643v4 (6C/12T, 3.40 GHz, up to 3.6 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2640v4 (10C/20T, 2.40 GHz, up to 2.6 GHz, 8.0 GT/s)
Intel® Xeon® processor E5-2637v4 (4C/8T, 3.50 GHz, up to 3.6 GHz, 9.6 GT/s)
Intel® Xeon® processor E5-2630v4 (10C/20T, 2.20 GHz, up to 2.4 GHz, 8.0 GT/s)
Intel® Xeon® processor E5-2630Lv4 (10C/20T, 1.80 GHz, up to 2.0 GHz, 8.0 GT/s)
Intel® Xeon® processor E5-2623v4 (4C/8T, 2.60 GHz, up to 2.9 GHz, 8.0 GT/s)
Intel® Xeon® processor E5-2620v4 (8C/16T, 2.10 GHz, up to 2.3 GHz, 8.0 GT/s)
Intel® Xeon® processor E5-2609v4 (8C/8T, 1.70 GHz, 6.4 GT/s)
Intel® Xeon® processor E5-2603v4 (6C/6T, 1.70 GHz, 6.4 GT/s)

Memory slots	24 (4 channels per CPU with 3 slots each)
Memory slot type	DIMM (DDR4)
Memory capacity (min. - max.)	8 GB - 3072 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC Memory Mirroring support Rank sparing memory support

Standard memory modules	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 1Rx4
	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx8
	16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx4
	16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx8
	32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx4
	64 GB (1 module(s) 64 GB) DDR4 3DS, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 4Rx8
	64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-L, LRDIMM, 4Rx4
	128 GB (1 module(s) 128 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-L, LRDIMM, 8Rx4

Interfaces

USB 2.0 ports	4 (4x USB via special cable)
USB 3.0 ports	2 (1x USB at the front side + 1x USB intern)
Graphics (15-pin)	1 x VGA at the front via special cable

Interfaces	
LAN / Ethernet	2 x 10 Gbit/s or 4 x 1 Gbit/s via Midplane to Ethernet Connection Blade
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard LAN port
Serial 1 (9-pin)	
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard LAN port
Onboard or integrated Controller	
SATA Controller	Intel® C610
LAN Controller	Emulex OCI14102 2 x 10 Gbit/s, 2x or 4 x 1 Gbit/s Ethernet depending on installed Connection Blade in 10Gbit/s mode CNA functionality with: - up to 8 physical function per port - optional one storage function (FCoE or iSCSI) with full offload PXE-Boot via LAN from PXE server in all modes FCoE and iSCSI boot in CNA mode PCI-SIG SR-IOV compliant with up to 128 VFs (depending on OS support) Support for VMware NetQueue and Microsoft VMQ optimizes performance for virtualized servers
Remote management controller	Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)
Slots	
PCI-Express 3.0 x8	2 x BX900 Mezzanine card
Drive bays	
Storage drive bays	2 x 1.8-inch SATA SSD
Operating panel	
Operating buttons	On/off switch ID button
Status LEDs	Power (amber / green) System status (orange) LAN connection (green) Identification (blue) CSS (orange)
BIOS	
BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring, Sparing) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support
Eco System	
	BX900: Supported with MMB-FW >=5.50 BX400: Supported with MMB-FW >=6.80

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Hyper-V Server 2016
	Windows Server 2016 Datacenter
	Windows Server 2016 Standard
	Windows Server 2016 Essentials
	Windows Server Datacenter, version 1709
	Hyper-V Server 2012 R2
	Windows Server 2012 R2 Datacenter
	Windows Server 2012 R2 Standard
	Windows Server 2012 R2 Essentials
	Windows Storage Server 2012 R2 Standard
	Hyper-V Server 2012
	Windows Server 2012 Datacenter
	Windows Server 2012 Standard
	Windows Server 2012 Essentials
	Windows Storage Server 2012 Standard
	Hyper-V™ Server 2008 R2
	Windows Server 2008 R2 Datacenter
	Windows Server 2008 R2 Enterprise
	Windows Server 2008 R2 Standard
	VMware vSphere™ 6.5
	VMware vSphere™ 6.7
	VMware vSphere™ 6.0
	VMware vSphere™ 5.5
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
Citrix® XenServer®	
Oracle® Linux 7	
Oracle® Linux 6	
Oracle® VM 3	
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	<ul style="list-style-type: none"> ServerView Suite - Deploy <ul style="list-style-type: none"> Installation Manager Scripting Toolkit ServerView Suite - Control <ul style="list-style-type: none"> Operations Manager incl. PDA and ASR & R Agents and CIM Providers / Agentless Service System Monitor RAID Manager Capacity Management Power Management Storage Support ServerView Suite - Maintain <ul style="list-style-type: none"> Remote Management (iRMC in combination with Intel® Node Manager) Update Management (BIOS, Firmware, Windows Drivers, Agents and CIM Providers) Performance Measurement Asset Management Online Diagnostics ServerView Suite - Integrate <ul style="list-style-type: none"> Integration packs for Microsoft System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM Deployment tools and others
-----------------	--

Server Management

Option	ServerView embedded Lifecycle Management (eLCM) Lifecycle management ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media ServerView Suite - Dynamize Virtual-IO Manager (VIOM) Infrastructure Manager (ISM) Automate device config Mass OS Installation Node Management Health Status Monitoring Capacity Management Power Management Converged View Network & Virtual IO Management Update Management Integrate IT Remote Management Update Management Logging and Auditing Integrate in to Enterprise Management Vendor specific Management Monitor 3rd party platforms
Server Management notes	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.

Dimensions / Weight

Dimensions (W x D x H)	45 x 500 x 210 mm
Weight	7 kg
Weight notes	Actual weight may vary depending on configuration

Environment

Temperature note	In accordance with the corresponding PRIMERGY BX900 System Unit
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe

Electrical values

Active power (max. configuration)	500 W
Heat emission (max. configuration)	1800.0 kJ/h (1706.1 BTU/h)

Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE Class A *
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	In combination with corresponding PRIMERGY BX system unit There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Solid-State-Drive	SSD M.2 SATA, 6 Gb/s, 480 GB, non hot plug, enterprise, 1.4 DDPD (Drive Writes Per Day for 5 years) SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, 1.4 DDPD (Drive Writes Per Day for 5 years)
--------------------------	--

PCIe SSD & SATA DOM SSD	DOM SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years) DOM SATA, 6 Gb/s, 64 GB, non hot plug, enterprise, 0.14 DWPD (Drive Writes Per Day for 5 years)
Mezzanine Cards	Ethernet Mezzanine Card 4 x 1 Gbit/s PCIe x4 Fujitsu CNA Mezzanine Card 2 x 10 Gbit/s PCIe 2.0 x8 Emulex Ethernet Mezzanine Card 2 x 10 Gbit/s PCIe 2.0 x8 Fujitsu Fibre Channel Mezzanine Card 2 x 16 Gbit/s PCIe 3.0 x8 Emulex Fibre Channel Mezzanine Card 2 x 8 Gbit/s PCIe 2.0 x8 Emulex SAS RAID Mezzanine Card 2 x 6 Gbit/s PCIe 2.0 x8 Fujitsu
LAN controller notes	The dual-channel 10 Gbit/s onboard CNA provides either 2x 10 Gbit/s ports, or 4x 1 Gbit/s ports.
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/support
Product Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Spare Parts availability	5 years
Service Lifecycle	5 years after end of product life
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Server PRIMERGY BX2580 M2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://www.fujitsu.com/fts/products/computing/servers/primergy/blades/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2019-08-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED