

Data Sheet

FUJITSU Server PRIMERGY CX2550 M4 Multi-node Server

Cloud/HPC optimized server node for PRIMERGY CX400 M4

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

The PRIMERGY CX multi-node systems are the ideal basis for cloud, hyper-converged and high performance computing solutions. They provide data centers as well as branch offices with massive computing power while at the same time delivering best economics for server density, energy consumption, heat optimization and lower overall operating costs.

PRIMERGY CX2550 M4

The FUJITSU Server PRIMERGY CX2550 M4 is a compact server node enabling highest computing density with up to four independent servers in just 2U (PRIMERGY CX400 M4). As a dual socket server node it features the latest Intel® Xeon® Processor Scalable Family and 16 DIMM slots (up to 2,048 GB DDR4 memory). With its two-storage-drive configuration, the CX2550 M4 is well-suited for mainstream enterprise workloads, cloud and high performance computing scenarios. The server node is prepared for individual future demands by offering further various modular options. In addition to the basic onboard LAN, the node provides additional 2x PCIe Gen3 x16 slots as well

as an optional CPU direct high-speed interconnect (Intel® Omni-Path Architecture) offering low communication latency, low power consumption and a high throughput. The PRIMERGY CX400 M4 enclosure allows nodes and components to share power, cooling and management. It houses hot-plug, redundant power supply units, hot-plug, redundant fan modules and can be equipped with up to 8 storage drives.



Features & Benefits

Main Features	Benefits
<p>Maximize Efficiency</p> <ul style="list-style-type: none"> Four PRIMERGY CX2550 M4 server nodes, each with latest Intel® Xeon® Processor Scalable Family, can be smartly packaged into a condensed 2U rack enclosure. Half-width, two-socket server node for PRIMERGY CX400 M4 chassis enabling highest computing density. Intel® Xeon® Processor Scalable Family with up to 28 cores relying on Intel® UltraPath Interconnect for an increased data rate between the CPUs. Up to 2,048 GB DDR4 memory with 2,666 MHz (16 DIMM slots). <p>Shared infrastructure & easy serviceability</p> <ul style="list-style-type: none"> Server nodes share central cooling, hot-plug and redundant power supply units as well as storage drives within the 2U PRIMERGY CX400 M4 chassis. <p>Enhanced Features for enhanced computing</p> <ul style="list-style-type: none"> Intel® Omni-Path Architecture (Intel® OPA) support. Basic onboard LAN and additional 2x PCIe Gen3 x16 slots for extended requirements. Optional liquid cooling solution helps to further reduce data center cooling costs and density. <p>Simplify Complexity</p> <ul style="list-style-type: none"> Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control. BIOS, firmware and selected software are updated free of charge. iRMC S5 comes with new interactive web UI and conforms to Redfish providing unified API support for heterogeneous environment. 	<ul style="list-style-type: none"> Well suited for mainstream enterprise workloads, cloud and high performance computing scenarios. Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power. Increased multi-tenancy and VM density for cloud application performance and parallelizable workloads. High bandwidth connections for networking and memory performance. Decreased energy consumption and lower investments. Each single server can be serviced without affecting the other nodes in the chassis. Redundancy for shared components provides maximum reliability. Wide range of connectivity options guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure. Helps to reduce data center cooling costs by over 50% and allows for 2.5-5x higher density to realise even ambitious projects. Enable faster IT service by automating and simplifying infrastructure operations across compute, storage and networking with ServerView Infrastructure Software Manager. The comprehensive tools of the Fujitsu ServerView Suite ease the administrator's life. Providing increased security and server administrator productivity, iRMC S5 simplifies server management.

Technical details

PRIMERGY CX2550 M4

Base unit	PRIMERGY CX2550 M4 air cooling	PRIMERGY CX2550 M4 liquid cooling
Housing types	Air-cooled node	Liquid-cooled node
Product Type	Dual Socket 1U Server Node	Dual Socket 1U Server Node

Mainboard

Processor quantity and type	1 - 2 x Intel® Xeon® Processor Scalable Family	
Mainboard type	D 3853	D 3853
Chipset	Intel® C621	Intel® C621

Intel® Xeon® Gold Processor

Intel® Xeon® Gold 5215 (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5215M (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5217 (8C, 3.00 GHz, TLC: 11 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 115 W, AVX Base 2.50 GHz, AVX Turbo 3.00 GHz)
Intel® Xeon® Gold 5218 (16C, 2.30 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5220 (18C, 2.20 GHz, TLC: 24.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
Intel® Xeon® Gold 5222 (4C, 3.80 GHz, TLC: 16.5 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 105 W, AVX Base 3.80 GHz, AVX Turbo 3.80 GHz)
Intel® Xeon® Gold 6230 (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6240 (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6240Y (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6242 (16C, 2.80 GHz, TLC: 22 MB, Turbo: 3.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)
Intel® Xeon® Gold 6244 (8C, 3.60 GHz, TLC: 24.75 MB, Turbo: 4.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 3.00 GHz, AVX Turbo 3.90 GHz)
Intel® Xeon® Gold 6248 (20C, 2.50 GHz, TLC: 27.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 1.90 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6252 (24C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6254 (18C, 3.10 GHz, TLC: 24.75 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 200 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)

Intel® Xeon® Platinum Processor	Intel® Xeon® Platinum 8260 (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz) Intel® Xeon® Platinum 8260M (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz) Intel® Xeon® Platinum 8260Y (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz) Intel® Xeon® Platinum 8268 (24C, 2.90 GHz, TLC: 35.75 MB, Turbo: 3.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.40 GHz, AVX Turbo 3.00 GHz) Intel® Xeon® Platinum 8270 (26C, 2.70 GHz, TLC: 35.75 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz) Intel® Xeon® Platinum 8276 (28C, 2.20 GHz, TLC: 38.5 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.60 GHz) Intel® Xeon® Platinum 8276M (28C, 2.20 GHz, TLC: 38.5 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.60 GHz) Intel® Xeon® Platinum 8280 (28C, 2.70 GHz, TLC: 38.5 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz) Intel® Xeon® Platinum 8280M (28C, 2.70 GHz, TLC: 38.5 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
Memory slots	16 (8 DIMMs per CPU, 6 channels with 2 slots per channel)
Memory capacity (min. - max.)	8 GB - 2048 GB
Memory protection	Advanced ECC SDDC
Memory notes	Performance Mode with identical modules in all six channels (6 modules per bank).
Memory capacity (min. - max.)	8 GB - 2048 GB
Non-volatile memory modules	256 GB (2 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4 512 GB (2 module(s) 256 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 2Rx4
Standard memory modules (for use in combination with non-volatile memory modules)	96 GB (6 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 64 GB (4 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 192 GB (6 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 128 GB (4 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 768 GB (6 module(s) 128 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 384 GB (6 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 256 GB (4 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4
Standard memory modules	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx8 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx8 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4
Upgrade notes	4x in PRIMERGY CX400 M4
Interfaces	
USB 3.0 ports	2 x USB 3.0 (rear) with high density connector
Graphics (15-pin)	1 x VGA (1x rear) with high density connector
LAN / Ethernet (RJ-45)	2 / 1x Gbit/s Ethernet + 1x service LAN Onboard
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard Gbit LAN port
Onboard or integrated Controller	
RAID controller	8 Port RAID 0/1 or RAID 5/6 controller as option
SATA Controller	Intel® C621
LAN Controller	Intel® i210 onboard 10/100/1000 Mbit/s Ethernet
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S5, 512 MB attached memory incl. graphics controller)
Trusted Platform Module (TPM)	optional TPM

Slots (Base unit specific)

PCI-Express 3.0 x16	2 x low profile PCIe 3.0 x16 slots (via riser card)	1 x for low profile
---------------------	---	---------------------

Drive bays

Storage drive bays	up to 2x 2.5-inch (in the PRIMERGY CX400 M4 chassis)
Storage drive bay configuration	up to 2x 2.5" SATA device can be installed in CX400 M4 and 2x M.2 device can be installed in CX2550 M4 node

General system information

Fan configuration	Redundant and hot-plug fans part of CX400 M4 chassis
-------------------	--

Operating panel

Operating buttons	On/off switch ID button
Status LEDs	Power (green) System status (orange) LAN speed (green / yellow) LAN connection (green) Identification (blue)

BIOS

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option IPMI support BIOS settings save and restore Remote iSCSI boot support Remote PXE boot support
---------------	---

Operating Systems and Virtualization Software**Operating system notes**

Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473
-------------------------------	---

Server Management and Infrastructure Management

Standard	<p>Infrastructure Manager (ISM) Essential</p> <ul style="list-style-type: none"> Node Management Health status Monitoring and Control Capacity/Threshold Management Power Management Converged Management Auto Discovery Remote Management Update Management Logging and Auditing <p>ServerView Suite (Control)</p> <ul style="list-style-type: none"> ServerView Operations Manager (incl. PDA and ASR & R) ServerView Agents and CIM provider ServerView Agentless Management ServerView System Monitor SVOM- Event Manager ServerView RAID Manager SVOM- Threshold Manager Power Management (iRMC) Power Monitor (monitoring the Power Consumption) Storage Management (server) with SVOM/SV-RAID <p>ServerView Suite (Maintain)</p> <ul style="list-style-type: none"> iRMC S5 (Remote Management) Performance management (SVOM) Asset Management Primecollect Customer Self Service Online Diagnostics <p>ServerView Suite (Integrate)</p> <ul style="list-style-type: none"> ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM
----------	---

Server Management and Infrastructure Management

Option	Infrastructure Manager (ISM) Automate device configuration Mass OS installation Node Management Health status Monitoring and Control Capacity/Threshold Management Power Management Converged Management Auto Discovery Virtual-I/O Management Network topology Management Remote Management Update Management Logging and Auditing Integrate in to Enterprise Management Vendor specific Management Monitor 3rd party platforms ServerView Suite (Maintain) ServerView eLCM iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media
---------------	---

Dimensions

Dimensions (W x D x H)	174.3 x 580 x 40.5 mm
Weight	4.5 kg
Node size	1 U half wide

Environment

Operating ambient temperature	5 - 35 °C
Operating relative humidity	10 - 85 % (non condensing)
Temperature and humidity notes	Air cooling can support up to 165W CPU
Maximum altitude	3,000 m
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe

Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) IEC 60950
Europe	CE Class A * EN 60950 - 1 EN 50371 EN 55022 EN 61000-3-3 EN 55024
USA/Canada	UL/CSA ICES-003 / NMB-003 Class A
Japan	VCCI Class A
Taiwan	CNS 13436 CNS 13438 class A
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Hard disk drives	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
Solid-State-Drive	SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD M.2 SATA, 6 Gb/s, 256 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years)	
RAID Controller	Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108
Communication, Network	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 (Cavium)
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 (Mellanox)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Mellanox)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
	Ethernet Ctrl. 2 x 40 Gbit/s PCIe 3.0 x16 QSFP (Mellanox)
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
	MPO x 40 Gbit/s ()
Omni Path 1 x PCIe 3.0 x16 (Intel®)	
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty
Product Support Services - the perfect extension	
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years after end of product life
Service Weblink	https://www.fujitsu.com/emeia/support/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Server PRIMERGY CX2550 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PRIMERGY CX2550 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2019-04-27 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED