

# Data Sheet

## Fujitsu PRIMERGY CX2560 M5 Multi-Node Server

Balanced efficiency and expandability for demanding cloud and virtualization scenarios

### PRIMERGY CX2560 M5

The Fujitsu Server PRIMERGY CX2560 M5 delivers the latest generation of powerful processors, large memory capacity and scalable I/O capability that meet virtualization, server consolidation or enterprise application needs. It's a flexible, two-socket half-height/width server node for the PRIMERGY CX400 M4 chassis powered by Intel® Xeon® Scalable processors as well as new 2nd generation processors of the Intel® Xeon® Scalable Family (CLX-R) delivering industry-leading frequencies. Each CX2560 M5 within the enclosure supports up to 2TB of DDR4 memory, making it a perfect candidate for dense virtualization environments. Furthermore, it is possible to use new Intel® Optane™ DC Persistent Memory and to mix them with standard DDR4 modules, resulting in a total capacity of 7,680 GB per server. Unlike traditional DRAM, the new persistent memory modules will offer the unprecedented combination of high-capacity, affordability and persistence. Servers equipped with this new class of memory will be able to adapt and optimize their workloads by moving and maintaining larger amounts of data closer to the processor and minimizing the higher latency of fetching data from system storage. The CX2560 M5 storage options include six 2.5-inch SAS/SATA HDD/SSD drives per node, with additional option of using two M.2 drives or a dual microSD card directly in the system as an internal boot device. The PRIMERGY CX400 M4 chassis supports up to four CX2560 M5 servers.



# Features & Benefits

Main Features	Benefits
<p><b>New efficiency for performance bottlenecks</b></p> <ul style="list-style-type: none"> <li>Wide choice of different types of Intel® Xeon® Scalable processors as well as new 2nd generation Intel® Xeon® Scalable processors. Each processor offers up to 28 cores and up to 56 threads enabling a notably higher performance and efficiency.</li> </ul> <p><b>Increased DDR4 memory bandwidth</b></p> <ul style="list-style-type: none"> <li>Up to 2048 GB DDR4 memory with 16 DIMM slots. The Intel Xeon processors support 6 memory channels per socket (2 slots per channel) with faster memory support of max. 2.933 MT/s.</li> </ul> <p><b>Revolutionizing memory and storage</b></p> <ul style="list-style-type: none"> <li>Intel® Optane™ DC persistent memory is an innovative memory technology that delivers a unique combination of affordable large capacity and persistence (non-volatility).</li> </ul> <p><b>Enhanced features for enhanced computing</b></p> <ul style="list-style-type: none"> <li>Basic Ethernet connection via on-board LAN, DynamicLoM OCP interface cards (4x1 Gbit/s RJ45, 2x 10 Gbit/s RJ45/SFP+ and 4x 10 Gbit/s SFP+ Ethernet) for extended requirements.</li> </ul>	<ul style="list-style-type: none"> <li>Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power. New SKUs of the 2nd generation Intel® Xeon® Scalable processors deliver additional customer value with increased performance and industry leading frequency (up to 3.9 GHz base and up to 44% more processor cache) for the most demanding workloads.</li> <li>Enhanced DDR4 memories enables higher bandwidth and lower consumption. The right choice for any application.</li> <li>Delivered with the next-generation Intel® Xeon® Scalable processor, the Intel® Optane™ DC persistent memory technology will transform critical data workloads – from cloud and databases, to in-memory analytics, and content delivery networks.</li> <li>The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure.</li> </ul>

# Technical details

## PRIMERGY CX2560 M5

Base unit	PRIMERGY CX2560 M5 air cooling
Housing types	Air-cooled node
Product Type	Dual Socket 1U Server Node

## Mainboard

Mainboard type	D 3853
Chipset	Intel® C624
Processor quantity and type	1 - 2 x Intel® Xeon® Bronze 3xxx processor / Intel® Xeon® Silver 4xxx processor / Intel® Xeon® Gold 5xxx processor / Intel® Xeon® Gold 6xxx processor

Mainboard type	D 3854
Chipset	Intel® C624

Intel® Xeon® Bronze Processor	Intel® Xeon® Bronze 3206R (8C, 1.90 GHz, TLC: 11 MB, Turbo: 1.90 GHz, 9.6 GT/s, 2,133 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 1.80 GHz)
-------------------------------	---

Intel® Xeon® Silver Processor	Intel® Xeon® Silver 4208 (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.50 GHz, 9.6 GT/s, 2,400 MHz, 85 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)
	Intel® Xeon® Silver 4210 (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.70 GHz, 9.6 GT/s, 2,400 MHz, 85 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)
	Intel® Xeon® Silver 4214 (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Silver 4214R (12C, 2.40 GHz, TLC: 16.5 MB, Turbo: 3.00 GHz, 9.6 GT/s, 2,400 MHz, 100 W, AVX Base 2.10 GHz, AVX Turbo 2.70 GHz)
	Intel® Xeon® Silver 4214Y (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Silver 4215 (8C, 2.50 GHz, TLC: 11 MB, Turbo: 3.00 GHz, 9.6 GT/s, 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Silver 4216 (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.70 GHz, 9.6 GT/s, 2,400 MHz, 100 W, AVX Base 1.40 GHz, AVX Turbo 2.30 GHz)

<b>Intel® Xeon® Gold Processor</b>	<p>Intel® Xeon® Gold 5215 (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)</p> <p>Intel® Xeon® Gold 5217 (8C, 3.00 GHz, TLC: 11 MB, Turbo: 3.40 GHz, 10.4 GT/s, 2,666 MHz, 115 W, AVX Base 2.50 GHz, AVX Turbo 3.00 GHz)</p> <p>Intel® Xeon® Gold 5218R (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.90 GHz, 10.4 GT/s, 2,666 MHz, 125 W, AVX Base 1.70 GHz, AVX Turbo 2.70 GHz)</p> <p>Intel® Xeon® Gold 5220 (18C, 2.20 GHz, TLC: 24.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)</p> <p>Intel® Xeon® Gold 5222 (4C, 3.80 GHz, TLC: 16.5 MB, Turbo: 3.90 GHz, 10.4 GT/s, 2,933 MHz, 105 W, AVX Base 3.80 GHz, AVX Turbo 3.80 GHz)</p> <p>Intel® Xeon® Gold 6222V (20C, 1.80 GHz, TLC: 27.5 MB, Turbo: 2.40 GHz, 10.4 GT/s, 2,933 MHz, 115 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)</p> <p>Intel® Xeon® Gold 6226 (12C, 2.70 GHz, TLC: 19.25 MB, Turbo: 3.50 GHz, 10.4 GT/s, 2,933 MHz, 125 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)</p> <p>Intel® Xeon® Gold 6226R (16C, 2.90 GHz, TLC: 22 MB, Turbo: 3.60 GHz, 10.4 GT/s, 2,933 MHz, 150 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)</p> <p>Intel® Xeon® Gold 6230 (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, 2,933 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)</p> <p>Intel® Xeon® Gold 6230R (26C, 2.10 GHz, TLC: 35.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, 2,933 MHz, 150 W, AVX Base 1.70 GHz, AVX Turbo 2.70 GHz)</p> <p>Intel® Xeon® Gold 6234 (8C, 3.30 GHz, TLC: 24.75 MB, Turbo: 4.00 GHz, 10.4 GT/s, 2,933 MHz, 130 W, AVX Base 2.8 GHz, AVX Turbo 3.70 GHz)</p> <p>Intel® Xeon® Gold 6238 (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, 2,933 MHz, 140 W, AVX Base 1.70 GHz, AVX Turbo 2.50 GHz)</p> <p>Intel® Xeon® Gold 6242 (16C, 2.80 GHz, TLC: 22 MB, Turbo: 3.50 GHz, 10.4 GT/s, 2,933 MHz, 150 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)</p> <p>Intel® Xeon® Gold 6252 (24C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, 2,933 MHz, 150 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)</p>
Memory slots	16 (8 DIMMs per CPU, 6 channels with 2 slots per channel)
Memory slot type	DIMM (DDR4 / DDR-T for non-volatile memory modules)
Memory capacity (min. - max.)	8 GB - 3.5 TB
Memory protection	Advanced ECC SDDC
Memory notes	<p>Memory Mirroring Mode with identical modules in both channel pairs of a bank (4 or 6 modules per bank) per CPU.</p> <p>Rank Sparing Mode with minimum of 2 modules single ranked (1R) or dual ranked (2R) or 1 module quad ranked (4R) per CPU.</p> <p>2 slots populated with DCPMM modules per CPU</p>
128 GB (1 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4	
256 GB (2 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4	
96 GB (6 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4	
64 GB (4 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4	
192 GB (6 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4	
128 GB (4 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4	
768 GB (6 module(s) 128 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4	
384 GB (6 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4	
256 GB (4 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4	
<b>Standard memory modules</b>	<p>8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx8</p> <p>16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4</p> <p>16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx8</p> <p>32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4</p> <p>64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4</p> <p>64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4</p> <p>128 GB (1 module(s) 128 GB) DDR4 3DS, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 8Rx4</p>
Notes	4x in PRIMERGY CX400 M4

---

**Interfaces**

USB 3.x ports	2 x USB 3.0 (rear) with high density connector
Graphics (15-pin)	1 x VGA (1x rear) with high density connector
LAN / Ethernet (RJ-45)	2 / 1x Gbit/s Ethernet + 1x service LAN Onboard
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard Gbit LAN port

---

**Onboard or integrated Controller**

RAID controller	8 Port RAID 0/1 or RAID 5/6 controller as option
SATA Controller	Intel® C624
LAN Controller	Intel® i210 onboard 10/100/1000 Mbit/s Ethernet
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S5, 512 MB attached memory incl. graphics controller)
Trusted Platform Module (TPM)	optional TPM

---

**Slots (Base unit specific)**

PCI-Express 3.0 x16	2 x low profile PCIe 3.0 x16 slots (via riser card)
---------------------	---

---

**Drive bays**

Storage drive bays	up to 6x 2.5-inch (in the PRIMERGY CX400 M4 chassis)
Storage drive bay configuration	up to 6x 2.5" HDD/SSD devices can be installed in CX400 M4 and 2x M.2 device can be installed in CX2560 M4 node

---

**General system information**

Fan configuration	Redundant and hot-plug fans part of CX400 M4 chassis
-------------------	--

---

**Operating panel**

Operating buttons	On/off switch ID button
Status LEDs	Power (green) System status (orange) LAN speed (green / yellow) LAN connection (green) Identification (blue)

---

**BIOS**

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option IPMI support BIOS settings save and restore Remote iSCSI boot support Remote PXE boot support
---------------	---

## Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Windows Server 2022 Datacenter
	Windows Server 2022 Standard
	Windows Server 2019 Datacenter
	Windows Server 2019 Standard
	Windows Server 2019 Essentials
	Hyper-V Server 2016
	Windows Server 2016 Datacenter
	Windows Server 2016 Standard
	Windows Server 2016 Essentials
	VMware vSphere™ 8.0
	VMware vSphere™ 7.0
	VMware vSphere™ 6.7
	VMware vSphere™ 6.5
	SUSE® Linux Enterprise Server 15
	SUSE® Linux Enterprise Server 12
	Red Hat® Enterprise Linux 8
Red Hat® Enterprise Linux 7	
Oracle® Linux 7	
Oracle® VM 3	
Operating system release link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
Operating system notes	

## Infrastructure and Server Management

### Dimensions

Dimensions (W x D x H)	174.3 x 580 x 40.5 mm
Height Unit Rack	1 U
Weight	4.5 kg
Node size	1 U half wide

### Environment

Operating ambient temperature	5 - 35 °C
Operating relative humidity	10 - 85 % (non condensing)
Temperature and humidity notes	Air cooling can support up to 165W CPU
Maximum altitude	3,000 m
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>

### Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) IEC 60950
Europe	CE Class A * EN 60950 - 1 EN 50371 EN 55022 EN 61000-3-3 EN 55024
USA/Canada	UL/CSA ICES-003 / NMB-003 Class A
Japan	VCCI Class A
Taiwan	CNS 13436 CNS 13438 class A
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

## Compliance

### Compliance notes

There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

\* Warning:  
This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

# Components

## Drives

SSD M.2 SATA, 6 Gb/s, 256 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years)

SSD M.2 SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years)

SSD M.2 SATA, 6 Gb/s, 32 GB, non hot plug, enterprise

## SSD SAS 2.5-inch

SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD

SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD

SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD

SSD SAS, 12 Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD

SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD

SSD SAS, 12 Gb/s, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD

SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD

SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD

SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

## SSD SATA 2.5-inch

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD

SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD

SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD

SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 1.4 DWPD

SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD

SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD

SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD

SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD

SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

HDD 2.5-inch	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
PCIe SSD & SATA DOM SSD	PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
SED	SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
	SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
	SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
SCSI / SAS Controller	Broadcom® PSAS CP503i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
	Broadcom® PSAS CP500e LP SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8
RAID Controller	Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516
	Broadcom® PRAID CP500i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, No FBU support
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
	InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )
	InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )

<STEPTABLE O="PMod\_249895" OT="Product" TT="DS-Server-EU Warranty" VC="INT - eng" VO="stibo.10560277" W="Main"/>

### Warranty

Warranty period	3 years
Warranty type	Onsite warranty
<b>Product Support - the perfect extension</b>	
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>
Service Weblink	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>



# More information

## Fujitsu platform solutions

In addition to Fujitsu PRIMERGY CX2560 M5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY CX2560 M5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/emeia/products/computing/servers/primergy/scale-out/cx2560m5/>

## Fujitsu green policy innovation

## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)

Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

## Contact

FUJITSU LIMITED  
Mies-van-der-Rohe-Straße 8  
80807 München  
Germany  
Website: [www.ts.fujitsu.com](http://www.ts.fujitsu.com)  
2024-04-06 CE-EN