

# Data Sheet

## Fujitsu Server PRIMERGY CX400 M1 Compact and Easy

Scale-Out Smart for HPC, Cloud and Hyper-Converged Computing

---

### PRIMERGY CX400 M1

The Fujitsu Server PRIMERGY CX400 M1 helps to meet the immense challenges now facing companies as well as research and development institutions. The system with only 2 height units contains up to four server nodes, 8 Intel® Xeon® processors and 64 DDR4 memory DIMMs, thus providing the very highest performance and energy efficiency levels. The scale-out system can be perfectly adapted for a wide range of applications thanks to its high degree of modularity. When requirements change, additional server nodes, co-processor cards or hard disks can just be added. In comparison to conventional rack servers the PRIMERGY CX400 M1 wins through thanks to its double server density and low hardware and operating costs. The system is thus an ideal replicable component in order to implement large scale-out solutions.



# Features & Benefits

Main Features	Benefits
<p><b>Condensed 4-in-2U server density</b></p> <ul style="list-style-type: none"> <li>■ The PRIMERGY CX400 M1 features up to 4 half-wide dual socket server nodes plus up to 24 storage drives in a single 2U enclosure.</li> </ul>	<ul style="list-style-type: none"> <li>■ 50% less rack space in comparison with standard rack servers enables to scale-out more smartly. Higher server density results in more performance per rack unit (4 servers, 8 processors, 24 drives and 64 DIMMs in 2U chassis).</li> <li>■ Different types of server nodes allow for best match to particular scale-out solution stacks.</li> <li>■ Latest Intel CPU technology for top performance and lower energy budgets.</li> <li>■ Easy rack-wide team play with already existing datacenter infrastructure lowers overall investment.</li> <li>■ Helps to reduce data center cooling costs by over 50% and allows for 2.5-5x higher data center density.</li> <li>■ Flexibility of drive choice, adaptable to any demand.</li> <li>■ Up to 6 drives can be assigned to a single server node to suit even high storage demands.</li> <li>■ Each single server can be serviced without affecting the other nodes in the chassis.</li> </ul>
<p><b>Server nodes for every scenario</b></p> <ul style="list-style-type: none"> <li>■ Different dual socket server nodes featuring latest Intel® Xeon® processor E5-2600 v4 product family.</li> <li>■ Standard server node, 16 DIMMs (1U).</li> <li>■ Enhanced HPC node with up to two GPGPU or co-processor cards, 16 DIMMs (2U).</li> </ul>	
<p><b>Traditional air cooling or optional liquid cooling</b></p> <ul style="list-style-type: none"> <li>■ The PRIMERGY CX400 M1 complies to conventional datacenter front-to-back airflow and cooling and standard 19" industry rack infrastructure and applications.</li> <li>■ The optional direct-to-chip hot water (40 °C / 105 °F) based Cool-Centra® Liquid Cooling captures between 60-80% of the servers heat.</li> </ul>	
<p><b>Variable local storage</b></p> <ul style="list-style-type: none"> <li>■ Up to 24x 2.5" hot-plug storage drives (HDD, SSD, PCIe) for 4 server nodes.</li> </ul>	
<p><b>Easy serviceability</b></p> <ul style="list-style-type: none"> <li>■ Hot-plug for server nodes, power supplies and disk drives enables enhanced availability and easy serviceability.</li> </ul>	

# Technical details

## PRIMERGY CX400 M1

Base unit	Chassis for CX2550 M1/M2	Chassis for CX2570 M1/M2	HPC optimized chassis for CX2550 M1/M2
Housing types	24x (4 x 6) 2.5-inch	12x (2 x 6) 2.5-inch	8x (4 x 2) 2.5-inch
Storage drive architecture	2.5-inch SAS/SATA	2.5-inch SAS/SATA	2.5-inch SATA

## Enclosure

System unit type	2 U chassis for 19-inch rack
Front bays	Storage drives: 6x 2.5-inch, 12x 2.5-inch or 24x 2.5-inch (HDD, SSD)
Rear bays	4 bays for half wide server trays CX25y0 M1/M2 2 x for PSU
Fan configuration	4 non hot plug fans
Fan notes	System operation also in degraded mode
Power supply configuration	2x hot-plug power supply modules

## Operating panel

Operating buttons	On/off switch ID button
Status LEDs	Identification (blue) Power (green)

## Dimensions / Weight

Rack (W x D x H)	446 x 860.2 x 87.8 mm
Height Unit Rack	2 U
19" rackmount	Yes
Weight	up to 40 kg
Weight notes	Fully assembled Actual weight may vary depending on configuration
Rack integration kit	Included in Rack System

## Electrical values

Max. input of single power supply	2400 W (94% efficiency)
Power supply configuration note	2x PSU in 1+1 redundancy configuration.
Power supply efficiency	94 % (80 PLUS platinum)
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	24.2 A with two PSU (12.1A per PSU)
Electrical value notes	Active power max. value depends on system configuration. For details see System Architect.

## Environment

Operating ambient temperature	5 - 45 °C (41 - 113 °F)
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator. DIN IEC 721-3-3 class 3K2
Operating relative humidity	10 - 85 % (non condensing)
Maximum altitude	3000 m
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Noise emission	According to ISO9296
Sound power (LWAd; 1B = 10dB)	6.5B (idle) / 7.4B (operating)

**Compliance**

<b>Global</b>	CB RoHS (Substance limitations in accordance with global RoHS regulations) - planned WEEE (Waste electrical and electronic equipment) - planned
<b>Germany</b>	GS
<b>Europe</b>	CE Class A *
<b>USA/Canada</b>	ULc/us
<b>Japan</b>	VCCI:V3 Class A + JIS 61000-3-2
<b>Taiwan</b>	CNS 13438 class A
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
<b>Compliance notes</b>	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

**Server Nodes**

<b>Product Model name</b>	PRIMERGY CX2550 M1	PRIMERGY CX2550 M2	PRIMERGY CX2570 M1	PRIMERGY CX2570 M2
<b>Product Type</b>	Dual Socket 1U Server Node	Dual Socket 1U Server Node	Dual Socket 2U Server Node	Dual Socket 2U Server Node
<b>Processor quantity support</b>	2	2	2	2
<b>Number of nodes</b>	4	4	2	2
<b>Memory slots total</b>	16	16	16	16
<b>Supported capacity RAM (max.)</b>	1,024 GB	1,024 GB	1,024 GB	1,024 GB
<b>Number of Storage Drives (max.)</b>	6x 2.5-inch	up to 6x 2.5-inch (in the PRIMERGY CX400 M1 chassis)	6x 2.5-inch	up to 6x 2.5-inch (in the PRIMERGY CX400 M1 chassis)

**Warranty**

<b>Warranty period</b>	3 years
<b>Warranty type</b>	Onsite warranty
<b>Product Related Services - the perfect extension</b>	
<b>Recommended Service</b>	- 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
<b>Service Lifecycle</b>	5 years
<b>Service Weblink</b>	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>

## More information

### Fujitsu platform solutions

In addition to Fujitsu PRIMERGY CX400 M1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu PRIMERGY CX400 M1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/fts/products/computing/servers/primergy/scale-out/cx400m1/>

### Fujitsu green policy innovation

### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

### Contact

FUJITSU LIMITED  
Mies-van-der-Rohe-Straße 8  
80807 München  
Germany  
Website: [www.ts.fujitsu.com](http://www.ts.fujitsu.com)  
2018-11-10 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions