

Data Sheet

FUJITSU Server PRIMERGY CX420 S1 Out-of-the-box Dual Node Cluster Server

High availability for lower expertise and limited budgets

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY CX scale-out systems are built for cloud computing scenarios, high performance computing, service providers and large server farms. They focus on providing large datacenters with massive scale-out x86 server power while at the same time delivering best economics for server density, energy consumption, heat optimization and lower overall operational costs.

PRIMERGY CX420 S1

Maintaining the continuity of your IT services is fundamental to stay in business - and this is also true for small and medium-sized businesses or multi-site organizations.

Fujitsu Server PRIMERGY CX420S1 is a Dual Node cluster server platform, based on Industry Standard Intel Xeon processors, providing continuous uptime for your applications and data. It leverages new High Availability features provided with Microsoft® Windows Server® 2012.

Everything you need is condensed into a 2U rack enclosure comprising two server nodes, up to 12 shared hot-plug storage drives and shared power and cooling, thus lowering capital expenses. Yet it enables flexible configuration of processing power, data capacity and networking options to adopt for various software solution scenarios. Integrated with the Windows Server Management tools, PRIMERGY CX420 S1 is managed as simple as a server, but operates continuously available as a cluster.



Features & Benefits

| Main Features | Benefits |
|---|--|
| <p>Continuous availability with 2 clustered nodes in a 2U chassis</p> <ul style="list-style-type: none"> ■ CX420 densely packs 2 server nodes, shared redundant power & cooling, plus 12 hot-plug storage drives into a highly compact chassis of only 2 height units. New functionalities for continuously available services and protection of storage against a wide range of failure scenarios in Microsoft® Windows Server® 2012 operating systems perfectly combine with CX420 advanced hardware features like onboard node connectivity and shared access to local storage to provide an out-of-the-box foundation for clustered high availability configurations. <p>Shared power and cooling</p> <ul style="list-style-type: none"> ■ CX420 features central cooling fans and 2 commonly shared highly efficient hot-plug power supplies. <p>Full compliance to Microsoft® Windows Server® 2012 certifications</p> <ul style="list-style-type: none"> ■ CX420 and all its components fully comply to the Microsoft® Windows Server® 2012 certifications, making sure that cluster operations such as failover or recovery of applications and data are working reliably. <p>Easy serviceability</p> <ul style="list-style-type: none"> ■ Hot-plug for server nodes, power supplies and disk drives enable enhanced availability and easy serviceability. <p>Highly available shared storage</p> <ul style="list-style-type: none"> ■ Up to twelve hot-plug storage drives for data integrate into the CX420 system, with choice of HDDs or SSDs, using dual ported SAS interfaces. Dynamic pooling of data through Microsoft® Windows Server® 2012 feature "Storage Spaces". | <ul style="list-style-type: none"> ■ Entirely secured continuity of access to applications as well as data, all at an affordable price level, let customers setup their complete solution in an easy and quick manner. CX420 significantly lowers the entrance barriers for high availability of data and applications - no need to invest into expensive SAN storage - designed to operate with only limited expert knowledge - supporting both virtualized and physical server deployments. ■ Shared components pay back in lower costs to buy and lower costs to own. Lower energy budgets for a comparable performance than for standard rack servers. ■ The flexible configuration of server nodes, data capacity and networking options enable various high availability solutions with Windows Server 2012 operating systems, which are covered by our certificates of conformance. ■ Each single server can be serviced without affecting the other nodes in the chassis. ■ Flexibility of drive choice, adaptable to any demand, with full 3-year warranty. ■ Dual ported SAS interfaces enable direct accessibility of drives from both server nodes, thus fast failover from one node to the other is achieved without investing into costly storage network systems. |

Technical details

PRIMERGY CX420 S1

| | |
|----------------------------|-------------------|
| Housing types | 12= 2x 6 3.5-inch |
| Storage drive architecture | 3.5-inch SAS |

Enclosure

| | |
|----------------------------|---|
| System unit type | 2 U chassis for 19-inch rack |
| Front bays | Storage drives: 12x 3.5-inch for 3.5-inch/2.5-inch HDDs |
| Rear bays | 2 bays for half wide server trays CX272 S1 2 x for PSU |
| Fan configuration | 4 non hot plug fans |
| Fan notes | System operation also in degraded mode |
| Power supply configuration | 2x hot-plug power supply modules |

Operating panel

| | |
|-------------------|--|
| Operating buttons | On/off switch ID button |
| Status LEDs | Identification (blue) Power (green) |

Dimensions / Weight

| | |
|----------------------|--|
| Rack (W x D x H) | 447 x 774.7 x 87.3 mm |
| Height Unit Rack | 2 U |
| 19" rackmount | Yes |
| Weight | up to 38 kg plus 2.5 kg for rack rails |
| Weight notes | Fully assembled Actual weight may vary depending on configuration |
| Rack integration kit | Included in Rack System |

Electrical values

| | |
|-------------------------------------|---|
| Max. input of single power supply | 1200 W |
| Power supply configuration note | 2x PSU in 1+1 redundancy configuration. System performance adjusted at 100V, when only one PSU is in operation. |
| Power supply efficiency | 94 % (80 PLUS platinum) |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Rated current max. | 12 A |
| Active power (max. configuration) | 1,200 W |
| Apparent power (max. configuration) | 1,445 VA |
| Heat emission (max. configuration) | 4320.0 kJ/h (4094.6 BTU/h) |
| Electrical value notes | Active power max. value depends on system configuration. For details see System Architect. |

Environment

| | |
|-------------------------------|--|
| Operating ambient temperature | 10 - 35 °C |
| Operating temperature note | DIN IEC 721-3-3 class 3K2 |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Maximum altitude | 3000 m |
| Operating environment | FTS 04230 – Guideline for Data Center (installation specification) |
| Noise emission | Measured according to ISO 7779 and declared according to ISO 9296 |
| Sound power (LWAd; 1B = 10dB) | 6,9B (idle) / 7,4B (operating) |

Compliance

| | |
|--------|--------------------|
| Global | CB RoHS WEEE |
|--------|--------------------|

Compliance

| | |
|-----------------------|---|
| Germany | GS |
| Europe | CE Class A * EN 55022 EN 60950 - 1 EN 50371 EN 61000-3-3 |
| USA/Canada | ULc/us FCC Class A |
| South Korea | KCC (KN22, KN24) |
| Australia/New Zealand | C-Tick |
| Taiwan | CNS 13438 class A |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates |
| Compliance notes | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. |

Cluster Server Nodes

| | |
|---------------------------------|--|
| Product Model name | PRIMERGY CX272 S1 |
| Product Type | Dual Socket 2U Cluster Node |
| Processor quantity support | 2 |
| Number of nodes | 2 |
| Memory slots total | 16 |
| Supported capacity RAM (max.) | 256 GB |
| Number of Storage Drives (max.) | 6x 2.5-inch or 6x 3.5-inch local in CX420 S1 2x 2.5-inch internal in CX272 S1 |

Warranty

| | |
|---|---|
| Warranty period | 3 years |
| Warranty type | Onsite warranty |
| Product Support Services - the perfect extension | |
| Recommended Service | 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner. |
| Service Lifecycle | 5 years |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY CX420 S1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY CX420 S1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
©2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact FUJITSU LIMITED

Website: www.fujitsu.com
2016-08-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
©2016 Fujitsu Technology Solutions GmbH