

Data Sheet

FUJITSU Server PRIMERGY MX130 S2 Micro Server

Micro server for macro results

With limited budgets and resources, small businesses must focus on maximizing productivity at minimum cost. Fujitsu Server PRIMERGY MX Micro Server increase the productivity of small businesses. How? By providing affordable, uncomplicated, reliable server technology on which to centralize their IT services. PRIMERGY MX servers are ultra-compact and whisper quiet, making them perfect for small offices. Their reliability is proven by testing through 5000 boot cycles – far more than other vendors do. The servers also minimize their environmental impact and operating costs through power supplies with a best-in-class energy efficiency of 85%. PRIMERGY MX servers let you focus on your top priority: your customer – not the IT!

PRIMERGY MX130 S2

The Fujitsu Server PRIMERGY MX130 S2 is just what small businesses need. The MX130 S2 is a solid platform on which to base your file, web or print services. It increases your company's potential by offering server reliability, efficiency and great value. The running costs and environmental impact are micro too, thanks to the 85% efficient power supply unit. If you think of servers as complicated, space-eating machines, then think again. The MX130 S2 comes in an ultra-compact chassis which can also be used horizontally. And, best of all, it is so silent you will hardly know it is there. PRIMERGY MX130 S2 – the micro server for macro results.



Features & Benefits

Main Features	Benefits
<ul style="list-style-type: none">■ 24x7 performance, server ECC memory, onboard RAID 0/1/10 and optional Trusted Platform Module (TPM)■ Up to 16 GB DDR3 ECC RAM■ Can integrate up to 4x 3.5-inch HDDs or up to 6x 2.5-inch HDDs■ Ultra-compact form factor with less than 13 liters volume - can be used everywhere in either vertical or horizontal position■ High energy efficiency with 85% efficiency power supply unit (PSU)	<ul style="list-style-type: none">■ Higher data safety and reliability than using PCs with external USB drives or optical media■ Share information by running office server applications■ Flexible and expandable base unit■ Ideal for all environments where space is scarce, e.g. small offices, retail environments or education■ Benefit from Fujitsu's pioneering experience in Green IT - save money and minimize environmental impact

Technical details

PRIMERGY MX130 S2

Mainboard

Mainboard type	D3090
Chipset	AMD 880G
Processor quantity and type	1 x AMD Athlon™ II / AMD Opteron™ 3000 series / AMD FX series

Processor	AMD Athlon™ II XLT V66C (2 Cores, 2.8 GHz, SLC: 2 MB)
------------------	----------------------------------------------------------

Memory slots	4
Memory slot type	DIMM (DDR3) ECC
Memory capacity (min. - max.)	2 GB - 16 GB
Memory protection	ECC
Memory notes	Mix and match possible, with dual channel operation better performance (2 modules with equal capacity necessary). Single channel (1 module) configuration possible.

Memory options	4 GB (1 module(s) 4 GB) DDR3, ECC, 1,333 MHz, PC3-10600, DIMM
-----------------------	---------------------------------------------------------------

Interfaces

USB 2.0 ports	12 (2 x front, 6 x back, 4 x internal)
DVI	1 (Dual link DVI-I), ATI Radeon® HD 4250 (up to 2811MB) on board
Graphics (15-pin)	1 No dedicated 15-pin VGA port available. VGA is available via the supplied DVI to VGA adapter.
Audio: line-in	1
Audio: line-out	1
Audio: microphone	1
Audio: comments	For projects only
Serial connection	1 9pin, 16 byte FIFO, 16550 compatible
Mouse / Keyboard (PS/2)	2
LAN / Ethernet (RJ-45)	1 Gbit/s Ethernet

I/O controller on board

RAID controller	6 port SATA with RAID 0/1/10 for HDDs
SATA Controller	SATA II
LAN Controller	BCM 57780, 10/100/1000 Mbit/s Ethernet, PXE-Boot by LAN via PXE-Server
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

Slots

PCI-Express 2.0 x4	1 x Low profile max. length 180mm
PCI-Express 2.0 x16	1 x Low profile max. length 180mm
PCI-Express x1	1 x Low profile max length 85mm
PCI-slots	1 x Low profile max. length 180mm
Slot Notes	PCI 32/33 MHz, 3.3V/5V

Drive bays

Storage drive bays	3.5-inch non hot-plug SATA
Storage drive bay configuration	Max 4 (2+2) x 3.5-inch (2 x Easy Change, 2 x screw-in) On project request through Fujitsu sales alternatively 2.5-inch configurations possible
Accessible drive bays	1 x 5.25/1.6-inch for slimline ODD and 3.5-inch HDD (internal), or backup devices, or 1.6-inch height ODD, or 3.5-inch HDD (internal) 1 x 5.25/0.5-inch for slimline ODD, or 1 x 3.5-inch HDD (internal)
Notes accessible drives	All possible option described in System Architect.
Number of fans	3
Fan configuration	Front-fan, CPU-fan, PSU-fan
Fan notes	Non hot plug

Operating panel

Operating buttons	On/off switch
Status LEDs	Power (green)

Operating systems

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Server® 2012 R2 Foundation
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
Microsoft® Windows Server® 2008 R2 Standard	
Microsoft® Windows Server® 2008 R2 Foundation	

Operating system release link <http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473>

Operating system notes
 Novell® certification
 Red Hat® certification
 Support of other Linux derivatives on demand

Server Management**Dimensions / Weight**

Floor-stand (W x D x H)	98 x 383 x 340 mm
Dimension notes	Dimensions in vertical position (excluding feet)
Weight	approx. 8 kg
Weight notes	Actual weight may vary depending on configuration

Environmental

Operating ambient temperature	10 - 35 °C
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	According to ISO9296
Sound pressure (LpAm)	20 dB(A) (idle) / 20 dB(A) (operating); may vary according to configuration.
Sound power (LWAd; 1B = 10dB)	3.5B (idle) / 3.5B (operating); may vary according to configuration.
Noise notes	Noise emissions and operation modes depend on system configuration.

Electrical values

Power supply configuration	1
Max. output of single power supply	250 W
Power supply efficiency	85 %
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	3.5 A - 1.5 A (100 V / 240 V)
Active power (max. configuration)	159 W
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Heat emission	572.4 kJ/h (542.5 BTU/h)

Compliance

Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
--------	------------------------------------------------------------------------------------------------------

Compliance

Germany	GS
Europe	CE Class A *
USA/Canada	FCC Class A CSAc/us
Japan	VCCI
Russia	GOST-R
South Korea	KC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Saudi Arabia	SASO
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

Components

Storage drives	HDD SATA, 2000 GB, 7,200 rpm, 3.5-inch, economic HDD SATA, 1000 GB, 7,200 rpm, 3.5-inch, economic HDD SATA, 500 GB, 7,200 rpm, 3.5-inch, economic HDD SATA, 250 GB, 7,200 rpm, 3.5-inch, economic HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, non hot plug, 3.5-inch, business critical HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
Backup Drives	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	DVD-ROM, SATA I DVD Super Multi, SATA I
Communication, Network	Ethernet Ctrl. 1 x 1 Gbit/s () Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 (Fujitsu)
Warranty	
Standard Warranty	1 year
Service level	Onsite Service
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Maintenance and Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	9x5, Onsite Response Time: Next Business Day
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY MX130 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY MX130 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.