

Data Sheet

FUJITSU PCNA EP QL41262 2X 25G SFP28

Dual-port Dual-rate 10/25Gbit/s PCIe 3.0 Network Interface Card

A Converged Network Adapter (CNA) is a Network Adapter that supports both the Ethernet and Fibre Channel standards. It provides connectivity at various transfer rates to Ethernet networks and also connects to Fibre Channel storage area networks (SANs) using Fibre Channel over Ethernet (FCoE) and Data Center Bridging (DCB). The adapter consolidates Ethernet data and FCoE storage traffic, reducing the number of cables and adapters needed for a server. The CNA provides 2 independent physical functions per port which can both be used at the same time for FC and Ethernet. Each port of the device provides separate NIC and HBA functions to the operating system or hypervisor. FC and network traffic are transmitted simultaneously over a common cable to a DCB-enabled FCoE switch which segregates Ethernet and Fibre Channel I/O to the appropriate network.

PCNA EP QL41262 2X 25G SFP28

The Fujitsu PCNA EP QL41262 is based on Marvell's® FastLinQ™ QL41262 HLCU Dual Port RDMA Converged Network Interface Adapter. This intelligent Converged Ethernet Network adapter uses Marvell's eighth generation technology to deliver true 10/25Gb per second (10/25Gbps) Ethernet performance per port. Integrated, advanced networking eliminates I/O bottlenecks and conserves CPU cycles. 25Gb Ethernet (25GbE) enables network bandwidth to be cost-effectively scaled in support of next-generation server and

storage solutions residing in cloud and web-scale data center environments. The 25GbE results in a single-lane connection similar to existing 10GbE technology—but it delivers 2.5 times greater bandwidth.

Compared to 40GbE solutions, 25GbE technology provides superior switch port density by requiring just a single switch lane compared to the 40GbE with four lanes. Fujitsu PCNA EP QL41262 Dual-Port 10/25GbE Network Interface Cards deliver advanced Ethernet solutions designed for Fujitsu Server PRIMERGY systems with general purpose operating systems.



Main Features	Benefits
<ul style="list-style-type: none"> Industry's most powerful converged Ethernet network adapter with iSCSI hardware offload and FCoE capabilities for Fibre Channel over Ethernet 	<ul style="list-style-type: none"> This Marvell(TM) FastLinQ(R) RDMA Ethernet Converged Network Adapter PCNA EP QL41262 HLCU delivers much better price and performance versus its predecessor PCNA EP OCe14102. The adapter is backward compatible with existing 10GbE installations while allowing an upgrade to 25GbE infrastructure. SFP+, SFP28, 10G DAC, 25G DAC connectivity options supported with either SFP+ or SFP28 optical transceivers for optical fibers, or 10G Twinax or 25G DAC (Direct Attached Copper) cables. Supports 25 Gbps line rate with 100G/4x25G Splitter DAC cables. Boosts host CPU efficiency with hardware offloads for GRE, NVGRE, and VXLAN tunnels. NPAR is unique to this adapter and allows network partitioning, successor to the UMC feature known from PCNA EP OCe14102 adapters.
<ul style="list-style-type: none"> Universal RDMA-- iWARP and RoCE Remote Direct Memory Access 	<ul style="list-style-type: none"> Delivers choice and flexibility with concurrent support for RoCE v2 and iWARP technologies. Recommended as a discrete PCIe adapter for scale-up of Fujitsu's default DynamicLoM iWARP adapter capabilities.
<ul style="list-style-type: none"> iSCSI - Intelligent Hardware Offload Adapter 	<ul style="list-style-type: none"> Increase VM density and accelerate multitenant networks with full offload for tunneling protocols. iSCSI Boot with the Ethernet Network Adapters and iSCSI Hardware Offload features of the Converged Ethernet Network Adapter have been released for Microsoft Windows Server, and will be released for Red Hat Enterprise Linux and SuSE Linux. With VMare iSCSI hardware offload is not supported, must use iSCSI iBFT software boot.
<ul style="list-style-type: none"> FCoE - Fibre Channel over Ethernet 	<ul style="list-style-type: none"> This Converged Ethernet Adapter supports FCoE. Configuration works through the adapter driver's user interface, not by means of Fujitsu ServerView. Instead of integration with upper level upgrade/management tools like SVIM, SVUM Fujitsu provides lower level tools like PSPs/ASPs in case of FCoE function. For FCoE support with the Converged Ethernet Network Adapter please submit a release request with a supported server system. Commercial support will be implemented over time, please add your server, network, switches configuration to your request. If your release request is for a supported server system we have the intention not to charge for it.
<ul style="list-style-type: none"> Designed for UEFI. NPAR and General Purpose Operating System Support 	<ul style="list-style-type: none"> Works best on UEFI (Unified Extensible Firmware Interface) PRIMERGY and PRIMEQUEST servers, which is default at the PRIMERGY M5 and M4 generations. Supports legacy boot as well, however Fujitsu's ServerView Update Tools and iRMC network inventory are not supported on legacy. NPAR enables provisioning of 25GbE or 10GbE ports for greater deployment flexibility through switch-independent NIC partitioning. Microsoft Windows Server, VMware ESXi, SLES, and RHEL. Certified, and Microsoft Standard and Premium Qualifiers for SDDC included as well.

Technical details

Technical details

Controller Silicon	Marvell FastLinQ(TM) QL41262 10/25 Dual-Port Gigabit Ethernet Controller
Controller type	Converged Network Adapter
Connector type	SFP28
Operating system pre-installed	Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.

Technical details

Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Network protocol and standards compatibility	IEEE 802.1q VLAN IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.1Qbb Priority Flow Control (PFC) IEEE 802.3x Flow Control IPv4, IPv6 and mixed IPv4/IPv6 network protocols
Number of ports	2
Number of Connectors	2
Number of external ports	2
Data transfer rate(s)	10 Gbit/s / 25 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 3.0 x8
Bus type	PCIe 3.0
Bus transfer rate	8GT/s
Bus width	x8
HW Virtualization	SR-IOV: up to 240 virtual functions, 120 per port, NPAR: up to 16 physical functions, 8 per port
Interrupt Levels	MSI-X
WoL	No
Virtualization	Server Virtualization - Windows Server 2016 Hyper-V Virtual Machine Queue (VMQ) and Virtual Machine Multi-Queue (VMMQ) - SR-IOV Network Virtualization Offload - VXLAN - NVGRE
Teaming	Windows Server 2016 Teaming Driver
Flow Control	IEEE 802.3-2012 and Ethernet flow control
Additional features	Microsoft SDDC PREMIUM and STANDARD Logo Qualifiers for Storage Spaces Direct
Offloading	- TCP Stateless Offloads (include checksum, TSO, TSS, RSS, and RSC) - TX/RX IP, TCP & UDP checksum offload (IPv4, IPv6) capabilities

Order code	Product Name	Height of bracket	Number of ports	Related product
S26361-F4070-E202	Cavium FastLinQ® QL41262HLCU Converged Network Adapter 25G SFP28 Dual-Port	Low Profile (LP)	2	PRIMERGY Server
S26361-F4070-E2	Cavium FastLinQ® QL41262HLCU Converged Network Adapter 25G SFP28 Dual-Port	Full Height (FH)	2	PRIMERGY Server
S26361-F4070-L502	Cavium FastLinQ® QL41262HLCU Converged Network Adapter 25G SFP28 Dual-Port	Low Profile (LP)#Full Height (FH)	2	PRIMERGY Server

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F4055-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4055-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F3986-E3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10Km
S26361-F3986-E5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F3989-E600	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m or 5m
S26361-F3989-L105	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 5m
S26361-F3989-L110	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 10m
Description optional cable	10Gbit/s optical transceiver module for MMF (S26361-F3986-E3, -L3 and MC-0JXE51, MCX0JXE51): - OM1 (Multi Mode Fiber 62.5/125µm, 200 MHz*km) up to 33m - OM2 (Multi Mode Fiber 50.0/125µm, 500 MHz*km) up to 82m - OM3 (Multi Mode Fiber 50.0/125µm, 2000 MHz*km) up to 300m - OM4 (Multi Mode Fiber 50.0/125µm, 4700 MHz*km) up to 400m 10Gbit/s optical transceiver module for SMF (S26361-F3986-E4, -L4): - OS1 (Single Mode Fiber 9µm) up to 10kn: 10Gbit/s active twinax cable: - Amphenol 2m, 5m, 10m (S26361-F3989-L102, -L105, -L110) - Brocade 1m, 3m, 5m (S26361-F3873-L501, -L503, -L505) - Cisco 7m, 10m (S26361-F4571-E107, -L107, -E110, -L110) 10Gbit/s passive twinax cable: - Cisco 1m, 3m, 5m (S26361-F4571-E101, -L101, -E103, -L103, -E105, -L105) 25G Direct Attach Copper DAC - Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable 1m, 2m, 3m (Cisco P/N: QSFP-4SFP25G-CU1M, QSFP-4SFP25G-CU2M, QSFP-4SFP25G-CU3M)		

Environment

Power consumption	Dual Port SFP+ 10GBase-SR typ. 16 W, max. 18 W Dual Port SFP+ 10GBase-LR typ. 16 W, max. 18 W Dual Port SFP+ 10G Twinax typ. 16 W, max. 18 W Dual Port SFP28 25G typ. 16 W, max. 18W Dual Port SFP28 25G DAC typ. 16 W, max. 18 W
Temperature (operating)	0 - 55 °C
Storage temperature	-40 - 65 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PCNA EP QL41262 2X 25G SFP28, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PCNA EP QL41262 2X 25G SFP28, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2019-08-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED