

Data Sheet

PLAN EP MCX4-EN 40GbE QSFP


Dual-port 40Gbit/s PCIe 3.0 Network Interface Card

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

PLAN EP MCX4-EN 40GbE QSFP

The PLAN EP MCX4-EN 40GbE is based on Mellanox's ConnectX®-4 EN (Dual port) Network Interface Card. ConnectX-4 EN Network Controller with 40Gb/s Ethernet connectivity addresses virtualized infrastructure challenges, delivering best-in-class and highest performance to various demanding markets and applications. Providing true hardware-based I/O isolation with unmatched scalability and efficiency, achieving the most cost-effective and flexible solution for Web 2.0, Cloud, data analytics, database, and storage platforms. 40Gb Ethernet (40GbE) enables network bandwidth to be cost-effectively scaled in support of next-generation server and storage solutions residing in Cloud and Web-scale data center environments.

The PLAN EP MCX4-EN 40GbE Network Interface Cards deliver advanced Ethernet solutions designed for Server PRIMERGY and PRIMEQUEST systems with use cases such as SAP HANA® or Microsoft Storage Spaces Direct (S2D).



Features & Benefits

Main Features	Benefits
Scalability across environments <ul style="list-style-type: none"> ■ Designed for PRIMEQUEST Servers and PRIMERGY systems in SAP and all general purpose environments 	<ul style="list-style-type: none"> ■ Delivering highest performance and true hardware-based I/O isolation with unmatched scalability and efficiency for general purpose, SAP HANA®, and Microsoft S2D (Storage Spaces Direct) environments
Flexible OS support <ul style="list-style-type: none"> ■ Microsoft Windows Server 2016 and 2012 R2, Red Hat Enterprise Linux 7, SuSE Linux Enterprise Server 12, VMware ESXi 6.5 Support 	<ul style="list-style-type: none"> ■ Designed and released for qualifying PRIMERGY and PRIMEQUEST servers with multiple OS support
Efficient networking <ul style="list-style-type: none"> ■ RDMA over Converged Ethernet (RoCE) 	<ul style="list-style-type: none"> ■ Delivering low-latency and high-performance Remote Direct Memory Access (RDMA) over Ethernet networks; RoCE provides efficient low-latency RDMA services over Layer 2 and Layer 3 networks
Connectivity <ul style="list-style-type: none"> ■ Connectivity options 	<ul style="list-style-type: none"> ■ Interoperable with 1/10/25/40/50/100Gb Ethernet switches; powered connectors for optical and active cable support
Simplified Management <ul style="list-style-type: none"> ■ ServerView Management and MCTP/PLDMNC-SI Support 	<ul style="list-style-type: none"> ■ ServerView Update Tools and CLP for iRMC Network Inventory are supported for UEFI and in legacy boot. CLP for eIOV is supported for UEFI only. MCTP Base/Control, MCTP over PCIe/VDM, PLDM Monitoring/Control, PLDM FRU, NC-SI over MCTP

Technical details

Technical details

Controller Silicon	Mellanox ConnectX4-EN MCX416A-BCAT Dual-Port 40 Gigabit Ethernet Controller
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of Connectors	2
Number of external ports	2
Auto Negotiation support	Yes
Bus type	PCIe 3.0
Bus transfer rate	8GT/s
Bus width	x16
Network protocol and standards compatibility	IEEE 802.1p Class of Service IEEE 802.1q VLAN IEEE 802.1Qau Congestion Notification IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.1Qbb Priority Flow Control (PFC) IEEE 802.3ad LACP IEEE 802.3ae 10Gbit Ethernet IEEE 802.ap based auto-negotiation and KR startup IEEE 802.3az Energy Efficient Ethernet (EEE) IEEE 802.3ba 40Gbit Ethernet IEEE 802.3x Flow Control IEEE 1588 Precision Time Protocol IPv4, IPv6 and mixed IPv4/IPv6 network protocols
HW Virtualization	SR-IOV: Up to 256 Virtual Functions
Interrupt Levels	MSI-X
WoL	No
Virtualization	Hardware-based I/O Server Virtualization - SR-IOV - Multi-function per port - Address translation and protection - Multiple queues per virtual machine - Enhanced QoS for vNICs - VMware NetQueue support Overlay Networks - Stateless offloads for overlay networks and tunneling protocols - Hardware offload encapsulation and decapsulation of overlay networks Network Virtualization Offload - NVGRE - VXLAN™ CPU Offloads - RDMA over Converged Ethernet (RoCE) - TCP/UDP/IP stateless offload - LSO, LRO, checksum offload - RSS (can be done on encapsulated packet), TSS, HDS, VLAN insertion / stripping, Receive flow steering - Intelligent interrupt coalescence
Offloading	CPU Offloads - RDMA over Converged Ethernet (RoCE) - TCP/UDP/IP stateless offload - LSO, LRO, checksum offload - RSS (can be done on encapsulated packet), TSS, HDS, VLAN insertion / stripping, Receive flow steering - Intelligent interrupt coalescence
Data transfer rate up to	40 Gbit/s

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
MCX0JFEC1	Ethernet 40 Gbit/s	QSFP+ / MMF (SWL)	up to 150m
S26361-F4053-L703	Ethernet 40 Gbit/s	QSFP+ / MMF (SWL)	up to 150m

Environment

Power consumption	Dual-Port QSFP with passive DAC 40G cables: 10.66W Dual-Port QSFP with active AOC 40G cables: 12.16W Dual-Port QSFP with QSFP optical transceivers: 12.16 W
-------------------	---

Temperature (operating)	0 - 55 °C
-------------------------	-----------

Storage temperature	-40 - 65 °C
---------------------	-------------

Compliance

Compliance notes	According to the corresponding system
------------------	---------------------------------------

Compliance link	https://sp.ts.fujitsu.com/sites/certificates
-----------------	---

Notes

Compatibility	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.
---------------	---

Performance	To the extent that specific performance specifications for the product are indicated in the product data sheet, these are usually also dependent on the specific use and workload of the product and may therefore not be reached equally in all application situations. Such performance specifications thus do not represent a specifically agreed characteristic or feature of the product, but only serves as an orientation. The responsibility for a sufficient sizing of the overall system functionality lies solely with the user.
-------------	---

More information

Fsas Technologies products, solutions & services

In addition to PLAN EP MCX4-EN 40GbE QSFP , Fsas Technologies provides a range of platform solutions. They combine reliable Fsas Technologies products with the best in services, know-how and worldwide partnerships.

Fsas Technologies Portfolio
Built on industry standards, Fsas Technologies offers a full portfolio of datacenter hardware, software and related services. This allows customers to select alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Data Center Solutions
www.fujitsu.com/global/products/computing/

More information

Learn more about PLAN EP MCX4-EN 40GbE QSFP , please contact your Fsas Technologies sales representative or Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
Copyright Fsas Technologies 2025

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.