

Data Sheet

FUJITSU RAID Controller SAS 6Gbit/s 1GB (D3116C)

RAID Controller SAS 6Gbit/s 1GB cache based on LSI MegaRAID® for internal storage devices

The RAID concept (Redundant Array of Independent Disks) refers to several independent hard disks which form a large logical drive when switched together.

Redundancy information is calculated from several data blocks (except for RAID 0) and saved distributed to the individual hard disks. Your operating system no longer accesses the individual hard disks, but the array.

The actual objective of the RAID concept is to increase availability and prevent downtimes in the event of a hard disk failure. However, the theoretical security of the RAID concept is only as good as the RAID controller used. Benefit from the Fujitsu RAID controllers where technology, experience and practical implementation all ensure the security that your company needs in the event of an emergency.

RAID Controller SAS 6Gbit/s 1GB (D3116C)

The Fujitsu RAID Controller SAS 6Gbit/s 1GB(D3116C) with 8 ports sets new speed and data security standards for internal storage drives. The RAID stack is based on the LSI MegaRAID® and offers high data throughput, a comprehensive fault tolerance function and user-friendly management options. Moreover, the Controller management is integrated seamlessly into the Fujitsu server management concept. All controller functions are supported by the Fujitsu ServerView RAID Manager. The RAID Controller SAS 6Gbit/s 1GB (D3116C) is designed for backward compatibility with 3Gbit/s

SAS as well as with 6Gbit/s and 3Gbit/s SATA hard drives. Regardless of the drive speed, it delivers significant performance improvements in both read and write applications. Due to the support of 64-bit addressing, a robust set of RAID features and demanding error tolerance functions the controller provides high RAID performance and data availability. Powerful online management service programs (Fujitsu ServerView RAID Manager), which are simple to operate and quick to install, provide the administrator with unparalleled flexibility and access to the arrays. The RAID controller supports all of the important RAID levels including RAID 6 and 60. The optional flash battery backup (FBU) combined with TFM module ensures the integrity of the data stored in the cache on the RAID controller in case of a power outage. In this event, the data will be copied to a non-volatile flash memory (TFM). The FBU provides a low-priced alternative to an uninterruptible power supply (UPS) and, when compared to battery backup units (BBU), enables a long-term, secure store of data and better serviceability. Always select FBU and TFM module in combination.



Main Features	Benefits
<ul style="list-style-type: none"> ■ 6Gbit/s SAS ports PCI Express® 3.0 x8 ■ LSISAS2208 6Gbit/s RAID-on-Chip ■ 1GB 1333MHz DDRIII cache memory ■ Optional Flash Backup Unit (FBU) 	<ul style="list-style-type: none"> ■ Connect up to 32 HDDs and SSDs ■ RAID levels 0, 1, 5 and 6 for more data security ■ RAID spans 10, 50 and 60 for more data security ■ Ensures the integrity in case of power outage ■ Long-term, secure store of data and better serviceability compared to BBU ■ Seamless merging of the RAID management into system management
<ul style="list-style-type: none"> ■ User Management Options 	

Technical details

Technical details

Controller Silicon	RoC (RAID on Chip) LSI SAS2208
Controller type	RAID 5/6 Ctrl.
Operating system pre-installed	Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of ports	8 ports int.
Connector internal	2x SSF-8087
Data transfer rate up to	6 Gbit/s
Bus type	PCIe 3.0
Bus width	x8
RAID Management	ServerView RAID Manager MegaCLI (command-line interface) WebBIOS
Key RAID Data Protection Feature	<ul style="list-style-type: none"> - RAID levels 0, 1, 5 and 6 - RAID spans 10, 50 and 60 - Online Capacity Expansion (OCE) - Online RAID level Migration (RLM) - Auto resume after loss of system power during array rebuild or reconstruction (RLM) - Fast initialization for quick array setup - Single controller multipathing (failover) - Load Balancing - Configurable stripe size up to 1MB - Fast initialisation for quick array setuo - Check consistency for background data integrity - Make Data Consistent (MDC) - Patrol read for media scanning and repairing - Up to 64 logical drives per controller - S.M.A.R.T support - Global and dedicated Hot Spare with Revertible Hot Spare support <ul style="list-style-type: none"> - Automatic rebuild - Enclosure affinity - Enclosure management <ul style="list-style-type: none"> - SES (inband) - SGPIO (outband)
RAID level	0, 1, 10, 5, 50, 6, 60
RAID cache backup unit	Optional FBU
RAID controller notes	(based on LSI SAS2208)
Interface technology	SAS/SATA

Order code	Product Name	Height of bracket	RAID controller cache size	Number of Connectors
MCX0JSR31	RAID Ctrl SAS 6G 1GB (D3116C)	Matching to system	1 GB	2
S26361-F3669-E3	RAID Ctrl SAS 6G 1GB (D3116C)	Matching to system	1 GB	2
S26361-F3669-E4	RAID Ctrl SAS 6G 1GB (D3116C)	Matching to system	1 GB	2
S26361-F3669-L3	RAID Ctrl SAS 6G 1GB (D3116C)	Full Height / Low Profile	1 GB	2
S26361-F3669-L4	RAID Ctrl SAS 6G 1GB (D3116C)	Matching to system	1 GB	2

Order code	Product Name	Notes
S26361-F3669-E125	RAID Ctrl FBU option with 25cm cable	installed - Super-capacitor incl. cable
S26361-F3669-L110	FBU option with 25/55/70 cm cable	loose delivery - Super-capacitor incl. cables for all systems
S26361-F3669-E100	TFM Module for FBU option on D3116	installed - Transportable Flash Module - contains flash memory and control logic for Flash Backup Unit (FBU) – required for FBU option

Order code	Product Name	Notes
S26361-F3669-L100	TFM Module for FBU option on D3116	loose delivery - Transportable Flash Module - contains flash memory and control logic for Flash Backup Unit (FBU) - required for FBU option

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with RAID Controller SAS 6Gbit/s 1GB (D3116C), Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server RAID Controller SAS 6Gbit/s 1GB (D3116C), please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited
Website: www.fujitsu.com/primergy
2019-03-25 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED