

Data Sheet

PRIMERGY TX1320 M5 Tower Server


Ultra-compact advanced technology server to accelerate your business

PRIMERGY portfolio offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. PRIMERGY server systems deliver workload-optimized x86 industry standard servers for any workload and business demand. Since there is no single server solution to meet all these needs, Fujitsu offers a broad server portfolio consisting of expandable tower servers for remote and branch offices, versatile rack-mount servers and density-optimized multi-node servers. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

PRIMERGY TX1320 M5

The unique ultra-compact Fujitsu PRIMERGY Server TX1320 M5 has advanced technology ideal for most industry verticals, small and medium-sized enterprises (SME), space-constrained environments, retail premises or branch offices. The performance-oriented yet cost-effective mono-socket design supports the latest Intel® Xeon® E-2300 product family processors, an affordable Pentium® processor option plus up to 128 GB RAM at 3,200 MT/s to boost performance for appropriately sized standard business workloads, including virtualized ones (such as: file/print, email, ERP/CRM, messaging, centralized data storage) and industry specific applications. Institutions with special legal requirements such as medical, governmental, legal, or financial offices can benefit from the server's secure and robust storage and transmission features. These include up to eight high quality 2.5-inch storage devices (including up to four ultra-fast PCIe SSDs for demanding applications), powerful RAID controllers, graphics and networking options enabled by 4 PCIe expansion slots (4.0/3.0)

together with versatile and affordable backup plus TPM 2.0 capability. High efficiency (96%), 500W redundant power supplies enhance reliability and protect customer investment. This ultra-compact, silent server with an optional dust protection kit and Advanced Thermal Design Technology is designed for deployment flexibility – it can be deployed in offices, on rack shelves, industrial areas and even on desks at temperatures from 5 °C to 45 °C. New generation technologies include M.2 modules for efficient OS installation along with dual microSD capability for VMware ESXi, plus the latest USB 3.2 Gen 2 ports. Furthermore, the TX1320 M5 server features the iRMC S6 and the Fujitsu Infrastructure Manager (ISM) suite, which enable remote server management and centralized IT infrastructure control respectively, hence boosting IT administrator productivity.



Features & Benefits

Main Features	Benefits
<p>ADVANCED TECHNOLOGY TO DRIVE WORKLOADS</p> <ul style="list-style-type: none"> Wide choice of the Intel® Xeon® E-2300 product family processors and an affordable Pentium® option. Up to 128GB DDR4 ECC memory (4x DIMMs at 3,200 MT/s) is supported for high-speed, reliable performance. The server also features 8x hot-plug 2.5-inch storage (SAS/SATA) devices (including up to 4x PCIe SSD), or 2x 3.5-inch storage, plus RDX backup. Powerful SAS 3.0 RAID Controllers with up to 8 GB cache are also available. Redundant (2x1GbE) LAN as standard, plus 25/10 Gb Ethernet controller options round out the networking capabilities. 	<ul style="list-style-type: none"> Powerful mono-socket compute and memory accelerate performance across both individual and virtualized business and industry workloads. Full-featured base units (with 8x 2.5-inch or 2x 3.5-inch storage drives, dual Gigabit LAN standard) to meet diverse SME storage needs.
<p>FLEXIBLE, FUTURE-READY PLATFORM</p> <ul style="list-style-type: none"> Server expandability for investment protection enabled via a range of PCIe expansion slots, with 4x PCIe (4.0/3.0) slots split between 2x PCIe 4.0 x8 and 2x PCIe 3.0 x4. The two PCIe 4.0 x8 slots can even be converted into a single PCIe 4.0 x16 slot. TPM 2.0 support and Fujitsu's secure 3-way lock secure the data. The flexible design also boosts user efficiency for OS installation: it supports 2x M.2 modules, plus dual microSD modules, also offers new 3.2 Gen2 USB ports (a total of 3x 3.2 Gen2, 1x 3.2 Gen1, 4x USB 2.0) to enhance peripheral device connectivity. 	<ul style="list-style-type: none"> Versatile 4x PCIe 4.0/3.0 slots (2x 4.0) to enable upgrades, with advanced options (RAID, networking, and graphics). Secure storage features protect data while M.2, dual microSD devices support flexible software boot and new high data rate USB ports enable the latest peripheral devices.
<p>EFFICIENT AND RELIABLE BY DESIGN</p> <ul style="list-style-type: none"> The TX1320 M5's base units offer cost-optimized standard power supplies (available with both 3.5-inch and 2.5-inch drive base units) or dual power supplies (available with a 2.5-inch drive base unit). The high-efficiency, dual 500W Titanium power supplies (96% efficiency) offer both hot-plug capability and redundancy. 	<ul style="list-style-type: none"> Designed to be good for both the business and the environment. Choose from amongst a 3.5-inch drive base unit with a value-oriented standard power supply, or the 2.5-inch drive base units which offer either a standard power supply or dual, hot-plug 500W power supplies for enhanced reliability and with high energy-efficiency.
<p>DEPLOY ANYWHERE, SERVICE AND MANAGE EASILY</p> <ul style="list-style-type: none"> The server has an ultra-small form factor with silent operation, and Fujitsu's Cool-safe® Advanced Thermal Design technology for an expanded range of operation. It is also designed for enhanced serviceability with easy, fast and comfortable access to critical components, and also has optional a new dust-protection kit. It also fields the comprehensive Fujitsu iRMC S6, and the Infrastructure Manager (ISM) software suite. The iRMC S6 allows powerful remote access capabilities. The free ISM Essential server management suite provides essential monitoring and firmware update of all supported devices, including servers, storage, and network switches, while you can also upgrade to the ISM Advanced, a powerful, fully featured version offering comprehensive infrastructure management capabilities such as support for multiple hardware configurations, physical and virtual network connection indicators and firmware baseline updates. 	<ul style="list-style-type: none"> Ultra-compact, low noise, easy to maintain, with Fujitsu's Cool-safe® technology, and an optional dust-protection kit enabling wide-spread deployment. The server's iRMC S6 and Fujitsu Infrastructure Manager (ISM) software suite enable efficient server remote management and infrastructure control.

Technical details

PRIMERGY TX1320 M5

Base unit	PRIMERGY TX1320 M5 SFF/Red. PSU
Housing types	Ultra-compact form-factor
Storage drive architecture	2.5-inch
Power supply	Hot-plug
Product Type	Mono Socket Tower Server

Mainboard

Mainboard type	D3931
Chipset	Intel® C256
Processor quantity and type	1 x Intel® Xeon® E-2300 processor family / Intel® Pentium® processor

Intel® Xeon® Max Processor

Intel® Xeon® processor E-2314 (4C/4T, 2.80 GHz, TLC: 8 MB, Turbo: 3.50 GHz, 3,200 MHz, 65 W)
Intel® Xeon® processor E-2324G (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: 4.50 GHz, 3,200 MHz, 65 W)
Intel® Xeon® processor E-2334 (4C/8T, 3.40 GHz, TLC: 8 MB, Turbo: 4.60 GHz, 3,200 MHz, 65 W)
Intel® Xeon® processor E-2336 (6C/12T, 2.90 GHz, TLC: 12 MB, Turbo: 4.60 GHz, 3,200 MHz, 65 W)
Intel® Xeon® processor E-2356G (6C/12T, 3.20 GHz, TLC: 12 MB, Turbo: 4.70 GHz, 3,200 MHz, 80 W)
Intel® Xeon® processor E-2374G (4C/8T, 3.70 GHz, TLC: 8 MB, Turbo: 4.70 GHz, 3,200 MHz, 80 W)
Intel® Xeon® processor E-2378 (8C/16T, 2.60 GHz, TLC: 16 MB, Turbo: 4.50 GHz, 3,200 MHz, 65 W)
Intel® Xeon® processor E-2378G (8C/16T, 2.80 GHz, TLC: 16 MB, Turbo: 4.60 GHz, 3,200 MHz, 80 W)
Intel® Xeon® processor E-2386G (6C/12T, 3.50 GHz, TLC: 12 MB, Turbo: 4.70 GHz, 3,200 MHz, 95 W)
Intel® Xeon® processor E-2388G (8C/16T, 3.20 GHz, TLC: 16 MB, Turbo: 4.60 GHz, 3,200 MHz, 95 W)

Processor

Intel® Xeon® processor E-2388G (8C/16T, 3.20 GHz, up to 4.6 GHz, 3,200 MHz)
Intel® Xeon® processor E-2386G (6C/12T, 3.50 GHz, up to 4.7 GHz, 3,200 MHz)
Intel® Xeon® processor E-2378G (8C/16T, 2.80 GHz, up to 4.6 GHz, 3,200 MHz)
Intel® Xeon® processor E-2378 (8C/16T, 2.60 GHz, up to 4.5 GHz, 3,200 MHz)
Intel® Xeon® processor E-2374G (4C/8T, 3.70 GHz, up to 4.9 GHz, 3,200 MHz)
Intel® Xeon® processor E-2356G (6C/12T, 3.20 GHz, up to 4.8 GHz, 3,200 MHz)
Intel® Xeon® processor E-2336 (6C/12T, 2.90 GHz, up to 4.6 GHz, 3,200 MHz)
Intel® Xeon® processor E-2334 (4C/8T, 3.40 GHz, up to 4.6 GHz, 3,200 MHz)
Intel® Xeon® processor E-2324G (4C/4T, 3.10 GHz, up to 4.5 GHz, 3,200 MHz)
Intel® Xeon® processor E-2314 (4C/4T, 2.80 GHz, up to 3.5 GHz, 3,200 MHz)
Intel® Pentium® Gold G6405 (2C/4T, 4.10 GHz, 2,666 MHz)

Memory slots	4
Memory slot type	UDIMM (DDR4)
Memory capacity (min. - max.)	8 GB - 128 GB
Memory protection	ECC
Memory notes	support up to 3200 MT/s. Pentium CPU support up to 2666 MT/s only. Any mix of different memory modules with different order code is not supported.

Interfaces

USB 2.x ports	4 (Rear: 4x USB 2.0)
USB 3.x ports	6 (Front: 1x USB 3.2 Gen2x2(20 Gbps) Type C, 1x USB 3.2 Gen1x1(5 Gbps) / Rear: 2x USB 3.2 Gen2x1(10 Gbps) / Internal: 2x USB 3.2 Gen1x1(5 Gbps))
Graphics (15-pin)	2 (1x Display Port (Integrated processor graphics) / 1x VGA (15-pin) / can be used exclusively)
Serial connection	1 x RS232 (option)
LAN / Ethernet	2
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S6 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port

Onboard or integrated Controller

Serial ATA total	7
------------------	---

Onboard or integrated Controller	
RAID controller	Optionally integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot). All hardware storage controller options are described under Components
SATA controller type notes	Intel® C256, 1x SATA channel for ODD, 2x SATA channel for M.2, 4x SATA channel for HDD/SSD
LAN Controller	Intel® i210 onboard 2 x 1 Gbit/s Ethernet (RJ45)
Trusted Platform Module (TPM)	TPM 2.0 module (option)
Slots	
PCI-Express 4.0 x8	2 x Low profile (2x PCIe 4.0 x8 slots can be switched to 1x PCIe 4.0 x16)
PCI-Express 3.0 x4	2 x Low profile
Slot Notes	PCIe 4.0 slot works as PCIe 3.0 with Pentium CPU.
Drive bays	
Storage drive bays	3.5-inch non hot-plug or 2.5-inch hot-plug SAS/SATA or 2.5-inch NVMe drives
Accessible drive bays	1 x 3.5/1.6-inch for backup devices 1 x 5.25/9.5mm for DVD-RW/Blu-ray
Drive bays	
Storage drive bays	Max. 8x (4x + 4x) x 2.5-inch hot-plug
Accessible drive bays	1 x 3.5/1.6-inch for backup devices 1 x 5.25/0.4-inch for CD-RW/DVD
Number of fans	
Fan configuration	1 standard fan
Fan notes	non redundant / non hot-plug
Operating panel	
Operating buttons	On/off switch NMI button Reset button ID button
Status LEDs	At system front side: Power (DC-On: green / AC-On: white) Global Error Indicator Identification (blue) Hard disks access (green) CSS (orange) At system rear side: Identification (blue) CSS (orange) Global error (orange) LAN connection (green) LAN speed (green / yellow)
Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2022 Essentials Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials VMware vSphere™ 8.0 VMware vSphere™ 7.0 SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473

Operating Systems and Virtualization Software

Operating system notes	Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
------------------------	--

Server Management

DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Server Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Management notes	For further information regarding ISM and ServerView Suite see dedicated data sheets.
Manageability link	http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6

Dimensions / Weight

Floor-stand (W x D x H)	98 x 400 x 340 mm
Dimension notes	without feet
Weight	up to 11.1 kg
Weight notes	Actual weight may vary depending on configuration

Environment

Operating ambient temperature	5 - 45 °C (41 - 113 °F)
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. Please use the Fujitsu WebArchitect (www.fujitsu.com/configurator/public) to get detailed information on the corresponding configurations.
Operating relative humidity	8 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	According to ISO9296
Sound pressure (LpAm)	17 dB(A) (idle)/ 17 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	3.0B (idle)/ 3.0B (operating)
Noise notes	Noise emissions depend on operation modes, system configuration and ambient temperature.

Electrical values

Power supply configuration	1 x standard, 1 x hot-plug, 2 x hot-plug redundant (depending on Model)
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	613 W
Apparent power (max. configuration)	230V : 600VA 100V: 620 VA
Heat emission (max. configuration)	2206.8 kJ/h (2091.6 BTU/h)
Rated current max.	6A (100V) / 2.9A (240V)
Power supply	250W standard, 90% (Gold efficiency), 100-240V, 50 / 60Hz 500W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 500W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz

Compliance

Product	PRIMERGY TX1320 M5
Model	PS1320A
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE
USA/Canada	NRTLc/us FCC Class A ICES-003 / NMB-003 Class A

Compliance	
Japan	VCCI Class A + JIS 61000-3-2 VCCI Class B + JIS 61000-3-2 (only for std. PSU base unit)
Russia	EAC
South Korea	KC
China	CCC
Australia/New Zealand	RCM
Taiwan	BSMI
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Backup Drives	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
SSD SAS 2.5-inch	SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD SSD SAS, 12 Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD SSD SAS, 12 Gb/s, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

SSD SATA 2.5-inch

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

HDD 2.5-inch

HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise

PCIe SSD & SATA DOM SSD

PCIe-SSD SFF, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD
PCIe-SSD SFF, 12.8 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD

SED

SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED

SCSI / SAS Controller

PSAS CP 2100-8i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
Broadcom® PSAS CP503i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8

RAID Controller	<p>pre-configured RAID1 Array for M.2 in PDUAL,</p> <p>Fujitsu PRAID EP680i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3916</p> <p>Fujitsu PRAID EP640i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3908</p> <p>Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516</p> <p>Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516</p> <p>Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516</p> <p>Broadcom® PRAID CP500i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, No FBU support</p>
GPU computing card	<p>NVIDIA® A2, 200GB/s, 16GB GDDR6, N/A, PCIe 4.0 x8</p> <p>-, xxxGB/s, 24GB GDDR6, N/A, PCIe 4.0 x16</p> <p>NVIDIA® T400 4GB, 4 GB, 384 cores, 4GB, N/A, PCIe x16, 3 x miniDP</p>
Notes	
Compatibility	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.
Continuity management	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.
Security	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
Warranty	
Manufacturer warranty period	1 year
Warranty type	Onsite warranty
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Product Support - the perfect extension	
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to PRIMERGY TX1320 M5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/

Software

www.fujitsu.com/software/

More information

Learn more about PRIMERGY TX1320 M5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/global/products/computing/servers/primergy/tower/tx1320m5/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
Fujitsu LIMITED

Website: www.fujitsu.com
2024-08-06 WW-EN